

Python: Operators

Connect with me: [Youtube](#) | [LinkedIn](#) | [WhatsApp Channel](#) | [Web](#) | [Facebook](#) | [Twitter](#)

- [Download PDF](#)
- To access the updated handouts, please click on the following link:
<https://yasirbhutta.github.io/python/docs/operators.html>

Want to Learn Python, Join our WhatsApp Channel 💎:

What is Operators

- Operators in Python are special symbols that perform specific operations on values and variables.
- They are essential for calculations, comparisons, assignments, and logical operations within your code.

Major operator categories

1. Arithmetic Operators:

- Used for performing basic mathematical calculations.
- Operators: `+` (addition), `-` (subtraction), `*` (multiplication), `/` (division), `//` (floor division), `%` (modulo), `**` (exponentiation)

video: [Basic Mathematical Operations with Examples](#)

- Examples:

```
result = 10 + 5 # Addition
difference = 15 - 7 # Subtraction
product = 4 * 6 # Multiplication
quotient = 12 / 3 # Division
integer_quotient = 17 // 4 # Floor division
remainder = 25 % 4 # Modulo
square = 5 ** 2 # Exponentiation
```

2. Comparison Operators:

- Used to compare values and return a Boolean result (True or False).
- Operators: `==` (equal to), `!=` (not equal to), `>` (greater than), `<` (less than), `>=` (greater than or equal to), `<=` (less than or equal to)

video: [How to Use Comparison Operators in Python](#)

Examples:

```
is_equal = 7 == 7 # True
is_greater = 12 > 9 # True
is_less_or_equal = 5 <= 5 # True
```

3. Assignment Operators:

- Used to assign values to variables.
- Operators: =
- Examples:

```
x = 10 # Simple assignment
```

Compound assignment:

A **compound assignment** is a combination of an operator and an assignment that performs an operation on a variable and then assigns the result back to that variable in a single step.

For example, in the code:

```
message += " Welcome!"
```

This is a **compound assignment** using the `+=` operator. Here's what it does:

1. It concatenates (adds) `" Welcome!"` to the existing value of the `message` variable.
2. Then, it assigns the result back to `message`.

In general, the format of compound assignment operators is:

- `+=` : Adds and assigns
- `-=` : Subtracts and assigns
- `*=` : Multiplies and assigns
- `/=` : Divides and assigns
- `%=` : Takes the modulus and assigns

This shorthand avoids writing out the operation in a longer form, such as:

```
message = message + " Welcome!"
```

The `+=` operator helps to keep the code more concise and readable.

Example:

```
x += 5 # Add 5 to x
x *= 2 # Multiply x by 2
```

4. Logical Operators:

- Used to combine Boolean expressions.
- Operators: `and`, `or`, `not`
- Examples:

```
is_valid = (age >= 18) and (has_license == True)
is_allowed = (is_member) or (has_ticket)
```

5. Identity Operators:

- In Python, the `is` operator is used to compare the identities of two objects. It checks whether two references point to the same object in memory, not whether the values of the two objects are equal.
- Operators: `is`, `is not`

Here's a simple example to illustrate the difference between `is` and `==`:

```
a = [1, 2, 3]
b = [1, 2, 3]
c = a

print(a == b) # Output: True, because the lists have the same content
print(a is b) # Output: False, because they are different objects in memory
print(a is c) # Output: True, because both references point to the same object
```

In this example:

- `a == b` is `True` because the values in both lists are the same.
- `a is b` is `False` because they are two different objects in memory, even though their contents are identical.
- `a is c` is `True` because `c` is assigned to the same object as `a`, so they reference the same memory location.

Example 2

```
x = 5
y = 5
result = x is y # True (they refer to the same integer object)
```

Object Caching in Python: Understanding Memory Optimization for Small Integers

- In Python, small integer objects (typically between -5 and 256) are cached to optimize memory usage and performance. This means that if you create multiple variables with the same value within this range, they all point to the same memory location, instead of creating new objects each time.
- This behavior is part of Python's optimization to save memory and improve performance, as small integers are frequently used. [1]

Here's an example to explain the concept:

```
# Assigning variables within the cached range
a = 100
b = 100

# Checking if the IDs are the same
print(id(a)) # Outputs the memory address of 'a'
print(id(b)) # Outputs the memory address of 'b'

# Since both 'a' and 'b' are within the cached range, their IDs are the same
print(a is b) # True, as both refer to the same cached object

# Assigning variables outside the cached range
x = 300
y = 300

# Checking if the IDs are the same
print(id(x)) # Outputs the memory address of 'x'
print(id(y)) # Outputs the memory address of 'y'

# Since 'x' and 'y' are outside the cached range, they are different objects
print(x is y) # False, as 'x' and 'y' refer to different objects
```

Explanation:

1. **Cached Objects:** The values `a` and `b` are both set to `100`, which falls within the default cached range of small integers. As a result, Python uses the same memory location for both, which is why `id(a)` and `id(b)` are the same, and `a is b` returns `True`.
2. **Non-Cached Objects:** The values `x` and `y` are both set to `300`, which is outside the cached range. Therefore, Python creates separate objects for each, and `id(x)` and `id(y)` are different, meaning `x is y` returns `False`.

This caching behavior saves memory for frequently used small integers and makes the comparison of such objects faster.

6. Membership Operators:

- Used to check if a value is present in a sequence (like a list or string).
- Operators: `in`, `not in`
- Examples:

```
numbers = [1, 3, 5, 7]
is_present = 5 in numbers # True
is_missing = 2 not in numbers # True
```

7. Bitwise Operators:

- Used to perform operations on the binary representation of numbers.
- Operators: `&` (bitwise AND), `|` (bitwise OR), `^` (bitwise XOR), `~` (bitwise NOT), `<<` (left shift), `>>` (right shift)
- These are less common in general-purpose programming, but useful in certain domains like low-level programming or cryptography.

`id()` function

In Python, the `id()` function returns the "identity" of an object, which is a unique integer that serves as a constant for the object during its lifetime. The `id` is often the memory address of the object. Here's a simple example:

```
x = 10
print(id(x))

y = "hello"
print(id(y))
```

This code will print the unique identifiers for the variables `x` and `y`. If you have specific objects or variables in mind that you would like to see the `id` for, please let me know!

Python operators examples:

- [Walrus Operator in Python](#)

Key Terms

True/False (Mark T for True and F for False)

Answer Key (True/False):

Multiple Choice (Select the best answer)

1. Arithmetic Operators:

1. What is the output of the following Python code? [Python Quiz #2](#)

```
x = 10
y = 5

x = x + y
y = x - y
x = x - y

print(x, y)
```

- A) 5 0
- B) 5 -5
- C) 10 5
- D) 5 10

Watch this video for answers: <https://youtube.com/shorts/gz4YuXmZvYo?si=VK50ZYFnhv5WljmT>

2. **What is the output of the following expression?** [Python Quiz #12](#)

```
2 ** 3 + 4 // 2 - 1
```

- A) 8
- B) 9
- C) 10
- D) 11

Watch this video for the answer: https://youtube.com/shorts/_cHsABqmmcM

3. **What is the output of the following expression?** [Python Quiz #24](#)

```
x = 10  
y = 5  
print(x % y)
```

- A) 2
- B) 5
- C) 0
- D) 1

Watch this video for the answer: https://youtube.com/shorts/-mPZMfg_uJ8?si=F6Hk4m4C_HVmHZ9A

4. **What is the output of the following code?** [Python Quiz #33](#)

```
print(11 % 3 == (11 - 3 * (11 // 3)))
```

- A) True
- B) False

Watch the video for the answer: <https://youtube.com/shorts/weXLclrx2Ko?si=JIDU0qMLPgYedatJ>

5. **What will be the output of the following code?** [Python Quiz #61]

```
age = 25  
message = "You are " + str(age) + " years old."
```

```
message += " Welcome!"  
print(message)
```

- A) You are 25 years old. Welcome!
- B) You are 25 years old.
- C) You are 25 Welcome!
- D) You are Welcome!

Watch video for the answer: <https://youtu.be/Q2J1EEedb9E>

6. **What is the output of 45 // 7?** [Python Quiz #62]

- A) 5.0
- B) 6
- C) 5
- D) 6.428571428571429

2. Comparison Operators:

7. **What is the output of the following Python code?** [Python Quiz #10](#)

```
x = 5  
y = 10  
  
result = x > 3 or y < 5  
print(result)
```

- A) True
- B) False
- C) SyntaxError
- D) None of these

Watch video for the answer: <https://youtube.com/shorts/FRa0r4UxyXM>

8. **What is the output of the following PYTHON code?** [Python Quiz #82]

```
flag = not (True and False)  
print(flag)
```

- A) True
- B) False
- C) None
- D) Error

3. Assignment Operators: 4. Logical Operators: 5. Identity Operators: 6. Membership Operators: 7. Bitwise Operators:

1. What is the difference between and and or operators in Python?

- A) and returns True if both operands are True and or returns True if either operand is True
- B) and returns True if either operand is True and or returns True if both operands are True
- C) and returns False if both operands are False and or returns False if either operand is False
- D) both A and C are correct

Answer: D

What is the difference between == and = in Python?

a) == is the comparison operator, = is the assignment operator b) == is the assignment operator, = is the comparison operator c) They are the same operator d) There is no difference

Which operator is used to raise a number to a power? a. ** b. ^ c. pow() d. ** and ^ are both correct

What is the result of the expression 3 + 5 * 2 in Python? [Python Quiz #63]

- A) 16
- B) 13
- C) 11
- D) 26

What is the purpose of the % operator in Python? a. Exponential b. Modulus c. Floor Division d. Addition

Which operator adds a value to a variable?

- A) +=
- B) -=
- C) *=
- D) /=

What is the output of x = 10; x //= 3?

- A) 3
- B) 3.33
- C) 3.5
- D) 4

Which operator checks if two values are greater than or equal to each other?

- A) >
- B) <=
- C) >=
- D) <

Which operator returns True if both operands are True?

- A) and
- B) or
- C) not
- D) xor

Which operator checks if a value is present in a sequence? a. in b. not in c. Both in and not in d. None of the above

1. What is the output of the following PYTHON Code? [Python Quiz #83]

```
num = 4
result = num in [1, 3, 4]
print(result)
```

- A) `True`
- B) `False`
- C) `None`
- D) `Error`

3. What will be the output of the following PYTHON Code? [Python Quiz #84]

```
str = 'x'
result = str in 'python'
print(result)
```

- A) True
- B) False
- C) 'x'
- D) Error

Which operator checks if two objects refer to the same memory location?

- A) ==
- B) is
- C) is not
- D) Both is and is not

What will be the output of the following PYTHON Code? [Python Quiz #85]

```
x = [1, 2]; y = x; print(x is y)
```

- A) True
- B) False
- C) [1, 2]
- D) Error

****Which of these operators can be used to perform bitwise operations on integers in Python?**

- A) & | ^ ~ < >
- B) && || ! < >
- C) * / % ** //
- D) + - * /

Answer: a) & | ^ ~ < >

What is the correct way to use the exponentiation operator in Python?

- A) x ^ y
- B) x ** y
- C) pow(x, y)
- D) either b or c

Answer: d) either b or c

In Python, What is the output of this code? [Python Quiz #86]

```
x = 10
y = 5
x = x + y
y = x - y
x = x - y
print(x, y)
```

- A) 10, 5
- B) 5, 10
- C) 15, -5
- D) -5, 15

Answer key (Mutiple Choice):

Fill in the Blanks

Answer Key (Fill in the Blanks):

Exercises

Review Questions

References and Bibliography

[1] "Python memory management," Discussions on Python.org, Apr. 02, 2023.

<https://discuss.python.org/t/python-memory-management/25391> (accessed Jul. 27, 2024).