

Шаг 1. Запуск контейнера с MongoDB

```
C:\Users\Sergei>docker run -d --name sr1 -p 27017:27017 -e MONGO_INITDB_ROOT_USERNAME=admin -e MONGO_INITDB_ROOT_PASSWORD=sixseven mongo:latest
356071d66191af4f97aec8d2c1e1b99d90e92ace6603c2e11f75d97fdd58f18c
```

docker run -d - создаёт и запускает контейнер в фоновом режиме

–name sr1 - имя контейнера

-p 27017:27017 - пробрасывание порта с компьютера в контейнер

-e MONGO_INITDB_ROOT_USERNAME=admin - имя администратора

-e MONGO_INITDB_ROOT_PASSWORD=sixseven - пароль администратора

mongo:latest - запуск самого свежего образа MongoDB

```
C:\Users\Sergei>docker ps
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS
356071d66191   mongo:latest   "docker-entrypoint.s..."  4 seconds ago  Up 4 seconds  0.0.0.0:27017->27017/tcp, [::]:27017->27017/tcp
sr1
```

Шаг 2. Подключение к контейнеру

```
C:\Users\Sergei>docker exec -it sr1 mongosh -u admin -p sixseven
Current Mongosh Log ID: 6alfeaa1f377833a2c9df8a2
Connecting to:      mongodb://<credentials>@127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.8.3
Using MongoDB:      8.2.9
Using Mongosh:      2.8.3

For mongosh info see: https://www.mongodb.com/docs/mongodb-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

-----
The server generated these startup warnings when booting
2026-06-03T08:48:11.435+00:00: Using the XFS filesystem is strongly recommended with the WiredTiger storage engine. See http://dochub.mongodb.org/core/prodnotes-filesystem
2026-06-03T08:48:11.698+00:00: For customers running the current memory allocator, we suggest changing the contents of the following sysfsFile
2026-06-03T08:48:11.698+00:00: For customers running the current memory allocator, we suggest changing the contents of the following sysfsFile
2026-06-03T08:48:11.698+00:00: We suggest setting the contents of sysfsFile to 0.
2026-06-03T08:48:11.698+00:00: vm.max_map_count is too low
2026-06-03T08:48:11.698+00:00: We suggest setting swappiness to 0 or 1, as swapping can cause performance problems.
-----
```

Шаг 3. Создаем базу данных и добавляем в неё запись

```
test> use university
switched to db university
university> db.students.insertOne({ name: 'Ефимов Сергей', age: 19, task: "Задание 1.4"})
{
  acknowledged: true,
  insertedId: ObjectId('6a1feb11f377833a2c9df8a3')
}
university> db.students.find()
[
  {
    _id: ObjectId('6a1feb11f377833a2c9df8a3'),
    name: 'Ефимов Сергей',
    age: 19,
    task: 'Задание 1.4'
  }
]
university> |
```