- Run a container nginx with name my-nginx and attach 2 volumes to the

```
~> docker volume create nginx-html
nginx-html
~> docker volume create nginx-config
nginx-config
~>
```

```
~> docker run -d --name my-nginx \
-v nginx-html:/usr/share/nginx/html \
-v nginx-config:/etc/nginx/conf.d \
nginx
cf4a75e44b75b2120d691c1a7d427530f8f277ba0776712126d2593f2deb1a49
```

Edit the html content

```
~> docker exec -it my-nginx sh
# echo "<h1>Hello from Docker Volume</h1>" > /usr/share/nginx/html/index.html
# exit
```

- Remove the container

```
~> docker stop my-nginx
my-nginx
~> docker rm my-nginx
my-nginx
~>
```

Run a new 2 containers with the following: o Attach the two volumes that were attached to the previous container using volume mount o Map port 80 to port 8080 on you host machine o Access the html files from your browser

```
~> docker run -d --name nginx12 \
-p 8060:80 \
-v nginx-html:/usr/share/nginx/html \
-v nginx-config:/etc/nginx/conf.d \
nginx
59d2cf94f92edfdf2ad7ce2715d7aa5c63e8c668ed0e22c20f4fd833632db771
~> docker run -d --name nginx13 \
-p 8061:80 \
-v nginx-html:/usr/share/nginx/html \
-v nginx-config:/etc/nginx/conf.d \
nginx
62045ef984cde01087325a3e472184f1048d3dd353c6acdc02ce35aa06aacf5b
~>
```

Run a container Nginx with name nginx-bind-mount and attach 2 volumes using bind mount under any paths

```
~> docker run -d --name nginx-bind-mountt \
-p 8090:80 \
nginx
c0805ed850b957414b1ec5e78de57b166ad7a0be46b0df8786c42da546e9c070
~>
```

Remove the container • Run a new container with the following: o Attach the two volumes that were attached to the previous container o Check the old data in the new containers

```
~> mkdir nginx-config
~> nano nginx-html/index.html
```

```
~> mkdir nginx-html
```

```
~> docker run -d --name nginx-bind-mountt \
-p 8090:80 \
nginx
c0805ed850b957414b1ec5e78de57b166ad7a0be46b0df8786c42da546e9c070
~> docker stop nginx-bind-mountt
nginx-bind-mountt
~> docker rm nginx-bind-mountt
nginx-bind-mountt
~> docker run -d --name nginx-bind-mount2 \
-p 8010:80 \
nginx
1c1e84970e2a6f849b1da7c72f4afe9cc39cf3e49127b61196519b8c4b105a24
```

```
~> docker run -d --name nginx-bind-mount4 \
-p 8092:80 \
-v ~/nginx-html:/usr/share/nginx/html \
-v ~/nginx-config:/etc/nginx/conf.d \
nginx
a31224850e4c97a25e6d37487d96f729a39a1aaf6e940805ee9242c7f525edd3
~>
```