

Phase 1 100% PRIVATE S3 BUCKET

Step 1:

Create bucket [info](#)

Buckets are containers for data stored in S3.

General configuration

AWS Region
US East (N. Virginia) us-east-1

Bucket type [info](#)

☒ **General purpose**
Recommended for most use cases and access patterns. General purpose buckets are the original S3 bucket type. They allow a mix of storage classes that redundantly store objects across multiple Availability Zones.

☐ **Directory**
Recommended for low-latency use cases. These buckets use only the S3 Express One Zone storage class, which provides faster processing of data within a single Availability Zone.

Bucket name [info](#)
boutiquemode-tn-website-ys-mbn
Bucket names must be 3 to 63 characters and unique within the global namespace. Bucket names must also begin and end with a letter or number. Valid characters are a-z, 0-9, periods (.), and hyphens (-). [Learn more](#)

Copy settings from existing bucket - optional
Only the bucket settings in the following configuration are copied.

[Choose bucket](#)
Format: s3://bucket/prefix

Object Ownership [info](#)
Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

Object Ownership

☒ **ACLs disabled (recommended)**
All objects in this bucket are owned by this account. Access to this bucket and its objects is specified using only policies.

☐ **ACLs enabled**
Objects in this bucket can be owned by other AWS accounts. Access to this bucket and its objects can be specified using ACLs.

Block Public Access settings for this bucket
Public access is granted to buckets and objects through access control lists (ACLs), bucket policies, access point policies, or all. In order to ensure that public access to this bucket and its objects is blocked, turn on Block all public access. These settings apply only to this bucket and its access points. AWS recommends that you turn on Block all public access, but before applying any of these settings, ensure that your applications will work correctly without public access. If you require some level of public access to this bucket or objects within, you can customize the individual settings below to suit your specific storage use cases. [Learn more](#)

☒ **Block all public access**
Turning this setting on is the same as turning on all four settings below. Each of the following settings are independent of one another.

- ☒ **Block public access to buckets and objects granted through new access control lists (ACLs)**
S3 will block public access permissions applied to newly added buckets or objects, and prevent the creation of new public access ACLs for existing buckets and objects. This setting doesn't change any existing permissions that allow public access to S3 resources using ACLs.
- ☒ **Block public access to buckets and objects granted through any access control lists (ACLs)**
S3 will ignore all ACLs that grant public access to buckets and objects.
- ☒ **Block public access to buckets and objects granted through new public bucket or access point policies**
S3 will block new bucket and access point policies that grant public access to buckets and objects. This setting doesn't change any existing policies that allow public access to S3 resources.
- ☒ **Block public and cross-account access to buckets and objects through any public bucket or access point policies**
S3 will ignore public and cross-account access for buckets or access points with policies that grant public access to buckets and objects.

Step 2: Applying Policies on S3 Bucket

Go to S3 → your bucket → Permissions → Bucket policy → Edit

Policy-01: Force HTTPS only and denies all HTTP access

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ForceHTTPS",
      "Effect": "Deny",
      "Principal": "*",
      "Action": "s3:*",
```

```
"Resource": [  
  "arn:aws:s3:::boutiquemode-tn-website-ys-mbn",  
  "arn:aws:s3:::boutiquemode-tn-website-ys-mbn/*"  
],  
"Condition": {  
  "Bool": {  
    "aws:SecureTransport": "false"  
  }  
}  
}  
]
```



Bucket policy

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket

Bucket ARN

`arn:aws:s3:::boutiquemode-tn-website-ys-mbn`

Policy

```
1 {
2   "Version": "2012-10-17",
3   "Statement": [
4     {
5       "Sid": "ForceHTTPS",
6       "Effect": "Deny",
7       "Principal": "*",
8       "Action": "s3:*",
9       "Resource": [
10        "arn:aws:s3:::boutiquemode-tn-website-ys-mbn",
11        "arn:aws:s3:::boutiquemode-tn-website-ys-mbn/*"
12      ],
13       "Condition": {
14         "Bool": {
15           "aws:SecureTransport": "false"
16         }
17       }
18     }
19   ]
20 }
```

S3 bucket is now:

- Completely private (Block All Public Access = ON)
- Rejects any HTTP request (only HTTPS allowed)

Block public access (bucket settings)

Public access is granted to buckets and objects through access control lists (ACLs), bucket policies, access point policies, or all. In order to ensure that public access to all your S3 buckets and object access points. AWS recommends that you turn on Block all public access, but before applying any of these settings, ensure that your applications will work correctly without public access. If you need individual settings below to suit your specific storage use cases. [Learn more](#)

Block *all* public access

✔ On

► Individual Block Public Access settings for this bucket

Bucket policy

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket policies don't apply to objects owned by other accounts. [Learn more](#)

❗ Public access is blocked because Block Public Access settings are turned on for this bucket

To determine which settings are turned on, check your Block Public Access settings for this bucket. [Learn more about using Amazon S3 Block Public Access](#)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ForceHTTPS",
      "Effect": "Deny",
      "Principal": "*",
      "Action": "s3:*",
      "Resource": [
        "arn:aws:s3:::boutiquemode-tn-website-ys-mbn",
        "arn:aws:s3:::boutiquemode-tn-website-ys-mbn/*"
      ],
      "Condition": {
        "Bool": {
          "aws:SecureTransport": "false"
        }
      }
    }
  ]
}
```

Secure S3 Bucket OK.