


# AEM Author & Publish Setup on Ubuntu EC2

This guide helps you set up Adobe Experience Manager (AEM) Author and Publish instances on a single Ubuntu EC2 instance (t2.medium, 2 vCPU, 4 GB RAM).

## Prerequisites

- AWS EC2 instance with:
  - **OS:** Ubuntu 24.04 LTS
  - **Instance Type:** t2.medium (2 vCPU, 4 GB RAM)
  - **Disk:** 20 GB (minimum)
  - **Ports Open:** 22, 4502, 4503
  - **AEM:** Adobe Experience Manager Quickstart .jar file with `license.properties` is required – not open-source and needs a valid subscription from Adobe.



The screenshot displays the AWS Management Console interface for an EC2 instance. The left sidebar shows the navigation menu with categories like EC2, Images, Elastic Block Store, and Network & Security. The main content area shows the 'Instances' page with a table listing the instance 'AEM-Author & Publish' (ID: i-0ac3b38eb339b8d76) in a 'Running' state. Below the table, the 'Details' tab for this instance is expanded, showing various attributes such as Instance ID, Public IPv4 address, Private IPv4 addresses, Public DNS, Private IP DNS name, Hostname type, Answer private resource DNS name, Auto-assigned IP address, Instance type, VPC ID, and Elastic IP addresses. The instance is located in the 'ap-south-1' availability zone.

Name	Instance ID	Instance state	Instance type	Status check	Alarm status	Availability Zone	Public IPv4 DNS
AEM-Author & Publish	i-0ac3b38eb339b8d76	Running	t2.medium	2/2 checks passed	View alarms +	ap-south-1a	ec2-13-234-53-222

**i-0ac3b38eb339b8d76 (AEM-Author & Publish)**

**Instance summary**

<b>Instance ID</b> i-0ac3b38eb339b8d76	<b>Public IPv4 address</b> 13.234.53.222   open address	<b>Private IPv4 addresses</b> 172.31.46.90
<b>IPv6 address</b> -	<b>Instance state</b> Running	<b>Public DNS</b> ec2-13-234-53-222.ap-south-1.compute.amazonaws.com   open address
<b>Hostname type</b> IP name: ip-172-31-46-90.ap-south-1.compute.internal	<b>Private IP DNS name (IPv4 only)</b> ip-172-31-46-90.ap-south-1.compute.internal	<b>Elastic IP addresses</b> 13.234.53.222 [Public IP]
<b>Answer private resource DNS name</b> IPv4 (A)	<b>Instance type</b> t2.medium	<b>AWS Compute Optimizer finding</b> Opt-in to AWS Compute Optimizer for recommendations.
<b>Auto-assigned IP address</b> -	<b>VPC ID</b> vpc-0883b4f05260f5e3b	

## Connect to EC2

```
ssh -i ~/Downloads/AL2023.pem ubuntu@13.234.53.222
```

```
yaswanth@PWSLTP204:~$ sudo ssh -i Downloads/AL2023.pem ubuntu@13.234.53.222
Welcome to Ubuntu 24.04.2 LTS (GNU/Linux 6.8.0-1031-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Fri Jul 11 06:50:08 UTC 2025

System load:  0.26               Processes:            118
Usage of /:   31.2% of 28.02GB   Users logged in:     0
Memory usage: 46%               IPv4 address for enX0: 172.31.46.90
Swap usage:   0%

 * Ubuntu Pro delivers the most comprehensive open source security and
   compliance features.

   https://ubuntu.com/aws/pro

Expanded Security Maintenance for Applications is not enabled.

12 updates can be applied immediately.
To see these additional updates run: apt list --upgradable

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

Last login: Fri Jul 11 06:48:24 2025 from 103.120.51.124
ubuntu@ip-172-31-46-90:~$
```



## Install Java 11

AEM requires Java 11. Install it using:

```
sudo apt update
sudo apt install openjdk-11-jdk
java -version
```

```
ubuntu@ip-172-31-46-90:~$ java -version
openjdk version "11.0.27" 2025-04-15
OpenJDK Runtime Environment (build 11.0.27+6-post-Ubuntu-0ubuntu124.04)
OpenJDK 64-Bit Server VM (build 11.0.27+6-post-Ubuntu-0ubuntu124.04, mixed mode, sharing)
ubuntu@ip-172-31-46-90:~$
```



## Directory Structure

Place the `.jar` and `license.properties` files provided by your Adobe/IT team as follows:

```
/opt/aem/
├── author/
│   ├── aem-author.jar
│   └── license.properties
└── publish/
    ├── aem-publish.jar
    └── license.properties
```



Both `author` and `publish` can initially contain identical files, but the **run modes** and **ports** differ.

```
ubuntu@ip-172-31-46-90:~$ tree /opt/aem/
/opt/aem/
├── author
│   ├── aem-author.jar
│   └── license.properties
└── publish
    ├── aem-publish.jar
    └── license.properties

3 directories, 4 files
ubuntu@ip-172-31-46-90:~$
```



# First-Time Setup



## Start Author Instance (Port: 4502)

```
cd /opt/aem/author
```

```
java -Xmx1024m -Dsling.run.modes=author -jar aem-author.jar -p 4502
```

- The system prompts for an **admin password**.
- Takes ~5–10 mins to initialize.

```
ubuntu@ip-172-31-46-90:/opt/aem/author$ java -Xmx1024m -Dsling.run.modes=author -jar aem-author.jar -p 4502
Loading quickstart properties: default
Loading quickstart properties: instance
Low-memory action set to fork
Using 64bit VM settings, min.heap=1024MB, min.permgen=256MB, default fork arguments=[-Xmx1024m, -XX:MaxPermSize=256m]
The JVM reports a heap size of 1024 MB, meets our expectation of 1024 MB +/- 20
Setting properties from filename '/opt/aem/author/aem-author.jar'
Setting 'sling.run.modes' to 'author' from system property.
The admin password for this instance hasn't been defined yet.
Please enter the desired admin password:
Please re-enter password:
Verbose option not active, closing stdin and redirecting stdout and stderr
Redirecting stdout to /opt/aem/author/crx-quickstart/logs/stdout.log
Redirecting stderr to /opt/aem/author/crx-quickstart/logs/stderr.log
Press CTRL-C to shutdown the Quickstart server...
WARNING: An illegal reflective access operation has occurred
WARNING: Illegal reflective access by org.apache.felix.framework.ext.ClassPathExtenderFactory$DefaultClassLoaderExtender (file:/opt/aem/author/crx-quickstart/la
unchpad/org.apache.sling.launchpad.base.jar.1752217346194) to method java.net.URLClassLoader.addURL(java.net.URL)
WARNING: Please consider reporting this to the maintainers of org.apache.felix.framework.ext.ClassPathExtenderFactory$DefaultClassLoaderExtender
WARNING: Use --illegal-access=warn to enable warnings of further illegal reflective access operations
WARNING: All illegal access operations will be denied in a future release
█
```

- Output is logged to:
  - `/opt/aem/author/crx-quickstart/logs/stdout.log`
  - `/opt/aem/author/crx-quickstart/logs/stderr.log`

```
ubuntu@ip-172-31-46-90:~$ cat /opt/aem/author/crx-quickstart/logs/stdout.log
Loading quickstart properties: default
Loading quickstart properties: instance
Quickstart startup at Fri Jul 11 07:02:18 UTC 2025
UpgradeUtil.handleInstallAndUpgrade has mode INSTALL
11.07.2025 07:02:26.182 *INFO * [main] Setting sling.home=/opt/aem/author/crx-quickstart (command line)
11.07.2025 07:02:26.183 *INFO * [main] Starting Apache Sling in /opt/aem/author/crx-quickstart
11.07.2025 07:02:26.185 *INFO * [main] Sling Extension Lib Home : /opt/aem/author/crx-quickstart/launchpad/ext
11.07.2025 07:02:26.186 *INFO * [main] Checking launcher JAR in folder /opt/aem/author/crx-quickstart/launchpad
11.07.2025 07:02:26.194 *INFO * [main] Installing new launcher: jar:file:/opt/aem/author/crx-quickstart/app/cq-quickstart-6.5.0-standalone-quickstart.jar!/resources/org.apache.sling.launchpad.base.jar, 6.0.2.2_6_36 (org.apache.sling.launchpad.base.jar.1752217346194)
11.07.2025 07:02:26.196 *INFO * [main] Loading launcher class org.apache.sling.launchpad.base.app.MainDelegate from org.apache.sling.launchpad.base.jar.1752217346194
11.07.2025 07:02:26.196 *INFO * [main] External Libs Home (ext) is null or does not exists.
11.07.2025 07:02:26.204 *INFO * [main] Setting sling.properties=conf/sling.properties
11.07.2025 07:02:26.204 *INFO * [main] Setting sling.home=/opt/aem/author/crx-quickstart
11.07.2025 07:02:26.204 *INFO * [main] Setting sling.launchpad=/opt/aem/author/crx-quickstart/launchpad
11.07.2025 07:02:26.204 *INFO * [main] Setting org.osgi.service.http.port=4502
11.07.2025 07:02:26.204 *INFO * [main] Starting launcher ...
11.07.2025 07:02:26.211 *INFO * [main] HTTP server port: 4502
```

```
11.07.2025 07:47:59.152 *INFO* [pool-4-thread-1] org.apache.sling.serviceusermapper Service [982, [org.apache.sling.serviceusermapping.ServiceUserMapped]] ServiceEvent UNREGISTERING
11.07.2025 07:47:59.152 *INFO* [OsgiInstallerImpl] org.apache.sling.audit.osgi.installer Installed bundle com.adobe.cq.core.wcm.components.core [579] from resource TaskResource(url=jcrinstall:/apps/core/wcm/install/core.wcm.components.core-2.3.2.jar, entity=bundle:com.adobe.cq.core.wcm.components.core, state=INSTALL, attributes=[org.apache.sling.installer.api.tasks.ResourceTransformer=:35:19:, Bundle-SymbolicName=com.adobe.cq.core.wcm.components.core, Bundle-Version=2.3.2], digest=1752219917088)
11.07.2025 07:47:59.161 *INFO* [OsgiInstallerImpl] com.adobe.cq.core.wcm.components.extension.contentfragment.bundle BundleEvent INSTALLED
11.07.2025 07:47:59.162 *INFO* [pool-4-thread-1] org.apache.sling.serviceusermapper Service [989, [org.apache.sling.serviceusermapping.ServiceUserMapped]] ServiceEvent UNREGISTERING
Attempting to load ESAPI.properties via file I/O.
Attempting to load ESAPI.properties as resource file via file I/O.
Not found in 'org.owasp.esapi.resources' directory or file not readable: /opt/aem/author/ESAPI.properties
Not found in SystemResource Directory/resourceDirectory: .esapi/ESAPI.properties
Not found in 'user.home' (/home/ubuntu) directory: /home/ubuntu/esapi/ESAPI.properties
Loading ESAPI.properties via file I/O failed. Exception was: java.io.FileNotFoundException
Attempting to load ESAPI.properties via the classpath.
SUCCESSFULLY LOADED ESAPI.properties via the CLASSPATH from '/' (root)' using class loader for DefaultSecurityConfiguration class!
!
Attempting to load validation.properties via file I/O.
Attempting to load validation.properties as resource file via file I/O.
Not found in 'org.owasp.esapi.resources' directory or file not readable: /opt/aem/author/validation.properties
Not found in SystemResource Directory/resourceDirectory: .esapi/validation.properties
Not found in 'user.home' (/home/ubuntu) directory: /home/ubuntu/esapi/validation.properties
Loading validation.properties via file I/O failed.
Attempting to load validation.properties via the classpath.
SUCCESSFULLY LOADED validation.properties via the CLASSPATH from '/' (root)' using class loader for DefaultSecurityConfiguration class!
█
```

Check logs:

```
tail -f /opt/aem/author/crx-quickstart/logs/stdout.log
```

Once you see **SUCCESSFULLY LOADED**, press **Ctrl + C** to terminate.

## What Happens After Startup?

- A directory `crx-quickstart/` is created.
- Contains binary files, configuration, start/stop scripts, etc.

```
ubuntu@ip-172-31-46-90:~$ ls -l /opt/aem/author/
total 544320
-rw-rw-r-- 1 ubuntu ubuntu 557369047 Jul  1 09:43 aem-author.jar
drwxrwxr-x 11 ubuntu ubuntu    4096 Jul 11 07:07 crx-quickstart
-rw-rw-r-- 1 ubuntu ubuntu    228 Jul  1 09:51 license.properties
ubuntu@ip-172-31-46-90:~$
```

```
ubuntu@ip-172-31-46-90:~$ ll /opt/aem/author/crx-quickstart/
total 92
drwxrwxr-x 11 ubuntu ubuntu  4096 Jul 11 07:07 ./
drwxr-xr-x  3 ubuntu ubuntu  4096 Jul 11 07:02 ../
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:02 app/
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:02 bin/
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:02 conf/
-rw-rw-r--  1 ubuntu ubuntu  7968 Jul 11 07:02 eula-de_DE.html
-rw-rw-r--  1 ubuntu ubuntu  7004 Jul 11 07:02 eula-en_US.html
-rw-rw-r--  1 ubuntu ubuntu  8955 Jul 11 07:02 eula-fr_FR.html
-rw-rw-r--  1 ubuntu ubuntu 14458 Jul 11 07:02 eula-ja_JP.html
drwxrwxr-x  7 ubuntu ubuntu  4096 Jul 11 07:02 launchpad/
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:07 logs/
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:07 metrics/
drwxrwxr-x  6 ubuntu ubuntu  4096 Jul 11 07:02 opt/
-rw-rw-r--  1 ubuntu ubuntu   84 Jul 11 07:02 readme.txt
drwxrwxr-x  6 ubuntu ubuntu  4096 Jul 11 07:02 repository/
drwxrwxr-x  3 ubuntu ubuntu  4096 Jul 11 07:06 threaddumps/
ubuntu@ip-172-31-46-90:~$ ll /opt/aem/author/crx-quickstart/bin/
total 52
drwxrwxr-x  2 ubuntu ubuntu  4096 Jul 11 07:02 ./
drwxrwxr-x 11 ubuntu ubuntu  4096 Jul 11 07:07 ../
-rw-rw-r--  1 ubuntu ubuntu  3118 Jul 11 07:02 GetProcessID.class
-rwxrwxr-x  1 ubuntu ubuntu  2946 Jul 11 07:02 quickstart*
-rw-rw-r--  1 ubuntu ubuntu  3044 Jul 11 07:02 quickstart.bat
-rwxrwxr-x  1 ubuntu ubuntu  4212 Jul 11 07:02 start*
-rw-rw-r--  1 ubuntu ubuntu  4402 Jul 11 07:02 start.bat
-rwxrwxr-x  1 ubuntu ubuntu   380 Jul 11 07:02 status*
```

## Configure Systemd for Author

Create the service file:

```
sudo nano /etc/systemd/system/aem-author.service
```

```
[Unit]
```

```
Description=AEM Author Instance
```

```
After=network.target
```

```
[Service]
```

```
Type=forking
```

```
User=ubuntu
```

```
Group=ubuntu
```

```
WorkingDirectory=/opt/aem/author
```

```
ExecStart=/opt/aem/author/crx-quickstart/bin/start
```

```
ExecStop=/opt/aem/author/crx-quickstart/bin/stop
```

```
PIDFile=/opt/aem/author/crx-quickstart/conf/cq.pid
```

```
SuccessExitStatus=0 143
```

```
Restart=on-failure
```

```
[Install]
```

```
WantedBy=multi-user.target
```

Enable and start the service:

```
sudo systemctl daemon-reexec
```

```
sudo systemctl daemon-reload
```

```
sudo systemctl enable aem-author.service
```

```
sudo systemctl start aem-author.service
```

```
sudo systemctl status aem-author.service
```

```
ubuntu@ip-172-31-46-90:/opt/aem/author$ sudo systemctl daemon-reexec
sudo systemctl daemon-reload
ubuntu@ip-172-31-46-90:/opt/aem/author$ sudo systemctl start aem-author.service
ubuntu@ip-172-31-46-90:/opt/aem/author$ sudo systemctl status aem-author.service
● aem-author.service - AEM Author Instance
   Loaded: loaded (/etc/systemd/system/aem-author.service; enabled; preset: enabled)
   Active: active (running) since Fri 2025-07-11 07:53:33 UTC; 13s ago
     Process: 13063 ExecStart=/opt/aem/author/crx-quickstart/bin/start (code=exited, status=0/SUCCESS)
    Main PID: 13088 (java)
      Tasks: 80 (limit: 4670)
     Memory: 462.5M (peak: 462.7M)
        CPU: 25.591s
    CGroup: /system.slice/aem-author.service
            └─13088 java -server -Xmx1024m -XX:MaxPermSize=256M -Djava.awt.headless=true -Dsling.run.modes=author,crx3,crx3tar -Djava.locale.providers=CLDR,JRE...
```


```
Jul 11 07:53:33 ip-172-31-46-90 systemd[1]: Starting aem-author.service - AEM Author Instance...
Jul 11 07:53:33 ip-172-31-46-90 systemd[1]: Started aem-author.service - AEM Author Instance.
ubuntu@ip-172-31-46-90:/opt/aem/author$
```

Check listening port:

```
sudo netstat -nlt | grep 4502
```

```
ubuntu@ip-172-31-46-90:/opt/aem/author$ sudo netstat -nlt
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       PID/Program name
tcp        0      0 127.0.0.53:53          0.0.0.0:*               LISTEN      434/systemd-resolve
tcp        0      0 127.0.0.54:53          0.0.0.0:*               LISTEN      434/systemd-resolve
tcp6       0      0 :::22                  :::*                    LISTEN      1/systemd
tcp6       0      0 :::4502                 :::*                    LISTEN      14937/java
tcp6       0      0 127.0.0.1:36625        :::*                    LISTEN      14937/java
ubuntu@ip-172-31-46-90:/opt/aem/author$
```

🔗 Visit: <http://13.234.53.222:4502/>





## Start Publish Instance (Port: 4503)

Start the publish instance:

```
ubuntu@ip-172-31-46-90:/opt/aem/author$ cd /opt/aem/publish/
ubuntu@ip-172-31-46-90:/opt/aem/publish$ ls -l
total 544316
-rw-r--r-- 1 ubuntu ubuntu 557369047 Jul  2 05:47 aem-publish.jar
-rw-r--r-- 1 ubuntu ubuntu      228 Jul  2 06:52 license.properties
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

```
cd /opt/aem/publish
```

```
java -Xmx1024m -Dsling.run.modes=publish -jar aem-publish.jar -p 4503
```

It will again request the admin password (in a separate instance).

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ java -Xmx1024m -Dsling.run.modes=publish -jar aem-publish.jar -p 4503
Loading quickstart properties: default
Loading quickstart properties: instance
Low-memory action set to fork
Using 64bit VM settings, min.heap=1024MB, min.permgen=256MB, default fork arguments=[-Xmx1024m, -XX:MaxPermSize=256m]
The JVM reports a heap size of 1024 MB, meets our expectation of 1024 MB +/- 20
Setting properties from filename '/opt/aem/publish/aem-publish.jar'
Option '-r' set to 'publish' from filename aem-publish.jar
Setting 'sling.run.modes' to 'publish' from system property.
Ignoring value 'publish' from filename.
The admin password for this instance hasn't been defined yet.
Please enter the desired admin password:
Please re-enter password:
Verbose option not active, closing stdin and redirecting stdout and stderr
Redirecting stdout to /opt/aem/publish/crx-quickstart/logs/stdout.log
Redirecting stderr to /opt/aem/publish/crx-quickstart/logs/stderr.log
Press CTRL-C to shutdown the Quickstart server...
WARNING: An illegal reflective access operation has occurred
WARNING: Illegal reflective access by org.apache.felix.framework.ext.ClassPathExtenderFactory$DefaultClassLoaderExtender (file:/opt/aem/publish/crx-quickstart/launchpad/org.apache.sling.launchpad.base.jar.1752221319640) to method java.net.URLClassLoader.addURL(java.net.URL)
WARNING: Please consider reporting this to the maintainers of org.apache.felix.framework.ext.ClassPathExtenderFactory$DefaultClassLoaderExtender
WARNING: Use --illegal-access=warn to enable warnings of further illegal reflective access operations
WARNING: All illegal access operations will be denied in a future release

```

Monitor logs:

```
tail -f /opt/aem/publish/crx-quickstart/logs/stdout.log
```

```
ubuntu@ip-172-31-46-98:~$ cat /opt/aem/publish/crx-quickstart/logs/stdout.log
Loading quickstart properties: default
Loading quickstart properties: instance
Quickstart startup at Fri Jul 11 08:08:31 UTC 2025
UpgradeUtil.handleInstallAndUpgrade has mode INSTALL
11.07.2025 08:08:39.627 *INFO * [main] Setting sling.home=/opt/aem/publish/crx-quickstart (command line)
11.07.2025 08:08:39.630 *INFO * [main] Starting Apache Sling in /opt/aem/publish/crx-quickstart
11.07.2025 08:08:39.632 *INFO * [main] Sling Extension Lib Home : /opt/aem/publish/crx-quickstart/launchpad/ext
11.07.2025 08:08:39.633 *INFO * [main] Checking launcher JAR in folder /opt/aem/publish/crx-quickstart/launchpad
11.07.2025 08:08:39.641 *INFO * [main] Installing new launcher: jar:file:/opt/aem/publish/crx-quickstart/app/cq-quickstart-6.5.0-standalone-quickstart.jar!/resources/org.apache.sling.launchpad.base.jar, 6.0.2.2_6_36 (org.apache.sling.launchpad.base.jar.1752221319640)
11.07.2025 08:08:39.642 *INFO * [main] Loading launcher class org.apache.sling.launchpad.base.app.MainDelegate from org.apache.sling.launchpad.base.jar.1752221319640
11.07.2025 08:08:39.642 *INFO * [main] External Libs Home (ext) is null or does not exists.
11.07.2025 08:08:39.652 *INFO * [main] Setting sling.properties=conf/sling.properties
11.07.2025 08:08:39.652 *INFO * [main] Setting sling.home=/opt/aem/publish/crx-quickstart
11.07.2025 08:08:39.652 *INFO * [main] Setting sling.launchpad=/opt/aem/publish/crx-quickstart/launchpad
11.07.2025 08:08:39.652 *INFO * [main] Setting org.osgi.service.http.port=4503
11.07.2025 08:08:39.652 *INFO * [main] Starting launcher ...
11.07.2025 08:08:39.658 *INFO * [main] HTTP server port: 4503
```

```
Attempting to load ESAPI.properties via file I/O.
Attempting to load ESAPI.properties as resource file via file I/O.
Not found in 'org.owasp.esapi.resources' directory or file not readable: /opt/aem/publish/ESAPI.properties
Not found in SystemResourceDirectory/resourceDirectory: .esapi/ESAPI.properties
Not found in 'user.home' (/home/ubuntu) directory: /home/ubuntu/esapi/ESAPI.properties
Loading ESAPI.properties via file I/O failed. Exception was: java.io.FileNotFoundException
Attempting to load ESAPI.properties via the classpath.
SUCCESSFULLY LOADED ESAPI.properties via the CLASSPATH from '/' (root)' using class loader for DefaultSecurityConfiguration class!
Attempting to load validation.properties via file I/O.
Attempting to load validation.properties as resource file via file I/O.
Not found in 'org.owasp.esapi.resources' directory or file not readable: /opt/aem/publish/validation.properties
Not found in SystemResourceDirectory/resourceDirectory: .esapi/validation.properties
Not found in 'user.home' (/home/ubuntu) directory: /home/ubuntu/esapi/validation.properties
Loading validation.properties via file I/O failed.
Attempting to load validation.properties via the classpath.
SUCCESSFULLY LOADED validation.properties via the CLASSPATH from '/' (root)' using class loader for DefaultSecurityConfiguration class!
█
```

After seeing “**SUCCESSFULLY LOADED**”, stop using **Ctrl + C**.

## What Happens After Startup?

- A directory `crx-quickstart/` is created.
- Contains binary files, configuration, start/stop scripts, etc.

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ ll
total 544328
drwxr-xr-x  3 ubuntu ubuntu    4096 Jul 11 08:08 ./
drwxr-xr-x  4 ubuntu ubuntu    4096 Jul  2 08:53 ../
-rw-r--r--  1 ubuntu ubuntu 557369047 Jul  2 05:47 aem-publish.jar
drwxrwxr-x 11 ubuntu ubuntu    4096 Jul 11 08:13 crx-quickstart/
-rw-r--r--  1 ubuntu ubuntu     228 Jul  2 06:52 license.properties
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ ll crx-quickstart/
total 92
drwxrwxr-x 11 ubuntu ubuntu    4096 Jul 11 08:13 ./
drwxr-xr-x  3 ubuntu ubuntu    4096 Jul 11 08:08 ../
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:08 app/
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:08 bin/
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:08 conf/
-rw-rw-r--  1 ubuntu ubuntu    7968 Jul 11 08:08 eula-de_DE.html
-rw-rw-r--  1 ubuntu ubuntu    7004 Jul 11 08:08 eula-en_US.html
-rw-rw-r--  1 ubuntu ubuntu   8955 Jul 11 08:08 eula-fr_FR.html
-rw-rw-r--  1 ubuntu ubuntu  14458 Jul 11 08:08 eula-ja_JP.html
drwxrwxr-x  7 ubuntu ubuntu    4096 Jul 11 08:08 launchpad/
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:13 logs/
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:13 metrics/
drwxrwxr-x  6 ubuntu ubuntu    4096 Jul 11 08:08 opt/
-rw-rw-r--  1 ubuntu ubuntu     84 Jul 11 08:08 readme.txt
drwxrwxr-x  6 ubuntu ubuntu    4096 Jul 11 08:09 repository/
drwxrwxr-x  3 ubuntu ubuntu    4096 Jul 11 08:13 threaddumps/
ubuntu@ip-172-31-46-90:/opt/aem/publish$
ubuntu@ip-172-31-46-90:/opt/aem/publish$ ll crx-quickstart/bin/
total 52
drwxrwxr-x  2 ubuntu ubuntu    4096 Jul 11 08:08 ./
drwxrwxr-x 11 ubuntu ubuntu    4096 Jul 11 08:13 ../
-rw-rw-r--  1 ubuntu ubuntu    3118 Jul 11 08:08 GetProcessID.class
-rwxrwxr-x  1 ubuntu ubuntu    2946 Jul 11 08:08 quickstart*
-rw-rw-r--  1 ubuntu ubuntu    3044 Jul 11 08:08 quickstart.bat
-rwxrwxr-x  1 ubuntu ubuntu    4212 Jul 11 08:08 start*
-rw-rw-r--  1 ubuntu ubuntu    4402 Jul 11 08:08 start.bat
-rwxrwxr-x  1 ubuntu ubuntu     380 Jul 11 08:08 status*
-rw-rw-r--  1 ubuntu ubuntu     516 Jul 11 08:08 status.bat
-rwxrwxr-x  1 ubuntu ubuntu     716 Jul 11 08:08 stop*
-rw-rw-r--  1 ubuntu ubuntu     479 Jul 11 08:08 stop.bat
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

## Fix Default Port for Publish instance

By default, the quickstart config sets port 4502.

Fix to 4503 for publish:

```
sed -i 's/CQ_PORT=4502/CQ_PORT=4503/'  
/opt/aem/publish/crx-quickstart/bin/start
```

```
sed -i 's/CQ_PORT=4502/CQ_PORT=4503/'  
/opt/aem/publish/crx-quickstart/bin/quickstart
```

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ grep CQ_PORT /opt/aem/publish/crx-quickstart/bin/quickstart  
grep CQ_PORT /opt/aem/publish/crx-quickstart/bin/start  
# % CQ_PORT=1234 ./start  
CQ_PORT=4502  
if [ $CQ_PORT ]; then  
    START_OPTS="${START_OPTS} -p ${CQ_PORT}"  
# % CQ_PORT=1234 ./start  
if [ -z "$CQ_PORT" ]; then  
    CQ_PORT=4502  
if [ $CQ_PORT ]; then  
    START_OPTS="${START_OPTS} -p ${CQ_PORT}"  
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ sed -i 's/CQ_PORT=4502/CQ_PORT=4503/' /opt/aem/publish/crx-quickstart/bin/quickstart  
sed -i 's/CQ_PORT=4502/CQ_PORT=4503/' /opt/aem/publish/crx-quickstart/bin/start  
ubuntu@ip-172-31-46-90:/opt/aem/publish$  
ubuntu@ip-172-31-46-90:/opt/aem/publish$ grep CQ_PORT /opt/aem/publish/crx-quickstart/bin/quickstart  
grep CQ_PORT /opt/aem/publish/crx-quickstart/bin/start  
# % CQ_PORT=1234 ./start  
CQ_PORT=4503  
if [ $CQ_PORT ]; then  
    START_OPTS="${START_OPTS} -p ${CQ_PORT}"  
# % CQ_PORT=1234 ./start  
if [ -z "$CQ_PORT" ]; then  
    CQ_PORT=4503  
if [ $CQ_PORT ]; then  
    START_OPTS="${START_OPTS} -p ${CQ_PORT}"  
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

## Configure Systemd for Publish

Create the service file:

```
sudo nano /etc/systemd/system/aem-publish.service
```

```
[Unit]
Description=AEM Publish Instance
After=network.target
[Service]
Type=forking
User=ubuntu
Group=ubuntu
WorkingDirectory=/opt/aem/publish
ExecStart=/opt/aem/publish/crx-quickstart/bin/start
ExecStop=/opt/aem/publish/crx-quickstart/bin/stop
PIDFile=/opt/aem/publish/crx-quickstart/conf/cq.pid
SuccessExitStatus=0 143
Restart=on-failure
[Install]
WantedBy=multi-user.target
```

Enable and start:

```
sudo systemctl daemon-reexec
sudo systemctl daemon-reload
sudo systemctl enable aem-publish.service
sudo systemctl start aem-publish.service
sudo systemctl status aem-publish.service
```

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ sudo systemctl daemon-reexec
sudo systemctl daemon-reload
ubuntu@ip-172-31-46-90:/opt/aem/publish$ 
ubuntu@ip-172-31-46-90:/opt/aem/publish$ 
ubuntu@ip-172-31-46-90:/opt/aem/publish$ sudo systemctl start aem-publish.service
ubuntu@ip-172-31-46-90:/opt/aem/publish$ sudo systemctl status aem-publish.service
● aem-publish.service - AEM Publish Instance
   Loaded: loaded (/etc/systemd/system/aem-publish.service; disabled; preset: enabled)
   Active: active (running) since Fri 2025-07-11 08:22:32 UTC; 8s ago
     Process: 20154 ExecStart=/opt/aem/publish/crx-quickstart/bin/start (code=exited, status=0/SUCCESS)
    Main PID: 20179 (java)
      Tasks: 61 (limit: 4670)
     Memory: 368.8M (peak: 369.0M)
        CPU: 12.628s
    CGroup: /system.slice/aem-publish.service
            └─20179 java -server -Xmx1024m -XX:MaxPermSize=256M -Djava.awt.headless=true -Dsling.run.modes=author,crx3,crx3tar -Djava.locale.providers=CLDR,JRE...
```


```
Jul 11 08:22:32 ip-172-31-46-90 systemd[1]: Starting aem-publish.service - AEM Publish Instance...
Jul 11 08:22:32 ip-172-31-46-90 systemd[1]: aem-publish.service: Can't open PID file /opt/aem/publish/crx-quickstart/conf/cq.pid (yet?) after start: No such fi
Jul 11 08:22:32 ip-172-31-46-90 systemd[1]: Started aem-publish.service - AEM Publish Instance.
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

Verify:

```
sudo netstat -nlt | grep 4503
```

```
ubuntu@ip-172-31-46-90:/opt/aem/publish$ sudo netstat -nlt
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       PID/Program name
tcp        0      0 127.0.0.53:53          0.0.0.0:*               LISTEN      434/systemd-resolve
tcp        0      0 127.0.0.54:53          0.0.0.0:*               LISTEN      434/systemd-resolve
tcp6       0      0 127.0.0.1:33761        :::*                   LISTEN      21908/java
tcp6       0      0 127.0.0.1:35645        :::*                   LISTEN      22093/java
tcp6       0      0 :::22                  :::*                   LISTEN      1/systemd
tcp6       0      0 :::4502                 :::*                   LISTEN      21908/java
tcp6       0      0 :::4503                 :::*                   LISTEN      22093/java
ubuntu@ip-172-31-46-90:/opt/aem/publish$
```

🔗 Visit: <http://13.234.53.222:4503/>






## ✓ Verify Author → Publish Content


Visit the default content page:

<http://13.234.53.222:4503/content/we-retail/us/en.html>



Check related projects by the author:

<http://13.234.53.222:4502/projects.html/content/projects>





## Notes

- Author and Publish are independent instances.
- Maintain different run modes (**author**, **publish**).
- Systemd handles background services and autostart.
- Ensure **4502** and **4503** ports are open in the security group.