

A.YASWANTH VENKAT SAI
AP19110010225
CSE-G

ASSIGNMENT 5

1. Write a c program to reverse a string using stack

```
// C program to reverse a string using stack
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <limits.h>

struct Stack
{
    int top;
    unsigned capacity;
    char* array;
};

struct Stack* createStack(unsigned capacity)
{
    struct Stack* stack = (struct Stack*) malloc(sizeof(struct Stack));
    stack->capacity = capacity;
    stack->top = -1;
    stack->array = (char*) malloc(stack->capacity * sizeof(char));
    return stack;
}

int isFull(struct Stack* stack)
{ return stack->top == stack->capacity - 1; }

// Stack is empty when top is equal to -1
int isEmpty(struct Stack* stack)
{ return stack->top == -1; }
```

```

void push(struct Stack* stack, char item)
{
    if (isFull(stack))
        return;
    stack->array[++stack->top] = item;
}

```

```

char pop(struct Stack* stack)
{
    if (isEmpty(stack))
        return INT_MIN;
    return stack->array[stack->top--];
}

```

// A stack based function to reverse a string

```

void reverse(char str[])
{
    // Create a stack of capacity
    //equal to length of string
    int n = strlen(str);
    struct Stack* stack = createStack(n);

    // Push all characters of string to stack
    int i;
    for (i = 0; i < n; i++)
        push(stack, str[i]);

    // Pop all characters of string and
    // put them back to str
    for (i = 0; i < n; i++)
        str[i] = pop(stack);
}

```

```

int main()
{

```

```

char str[] = "Yaswanth";

reverse(str);
printf("Reversed string is %s", str);

return 0;
}

```

Output:

Reversed string is htnawsaY

2. Write a C program for Infix To Postfix Conversion Using Stack.

// C program to convert infix expression to postfix

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#include <stdlib.h>
```

```
struct Stack
```

```
{
```

```
    int top;
```

```
    unsigned capacity;
```

```
    int* array;
```

```
};
```

// Stack Operations

```
struct Stack* createStack( unsigned capacity )
```

```
{
```

```
    struct Stack* stack = (struct Stack*) malloc(sizeof(struct Stack));
```

```
    if (!stack)
```

```
        return NULL;
```

```
    stack->top = -1;
```

```
    stack->capacity = capacity;
```

```

    stack->array = (int*) malloc(stack->capacity * sizeof(int));

    return stack;
}
int isEmpty(struct Stack* stack)
{
    return stack->top == -1 ;
}
char peek(struct Stack* stack)
{
    return stack->array[stack->top];
}
char pop(struct Stack* stack)
{
    if (!isEmpty(stack))
        return stack->array[stack->top--] ;
    return '$';
}
void push(struct Stack* stack, char op)
{
    stack->array[++stack->top] = op;
}

```

```

// A utility function to check if the given character is operand
int isOperand(char ch)
{
    return (ch >= 'a' && ch <= 'z') || (ch >= 'A' && ch <= 'Z');
}

```

```

int Prec(char ch)
{
    switch (ch)
    {
        case '+':
        case '-':
            return 1;

```

```

    case '*':
    case '/':
        return 2;

    case '^':
        return 3;
    }
    return -1;
}

```

```

// The main function that converts given infix expression
// to postfix expression.
int infixToPostfix(char* exp)
{
    int i, k;

    // Create a stack of capacity equal to expression size
    struct Stack* stack = createStack(strlen(exp));
    if(!stack) // See if stack was created successfully
        return -1 ;

    for (i = 0, k = -1; exp[i]; ++i)
    {
        // If the scanned character is an operand, add it to output.
        if (isOperand(exp[i]))
            exp[++k] = exp[i];

        // If the scanned character is an '(', push it to the stack.
        else if (exp[i] == '(')
            push(stack, exp[i]);
        // If the scanned character is an ')', pop and output from the stack
        // until an '(' is encountered.
        else if (exp[i] == ')')
        {
            while (!isEmpty(stack) && peek(stack) != '(')

```

```

        exp[++k] = pop(stack);
        if (!isEmpty(stack) && peek(stack) != '(')
            return -1; // invalid expression
        else
            pop(stack);
    }
    else // an operator is encountered
    {
        while (!isEmpty(stack) && Prec(exp[i]) <= Prec(peek(stack)))
            exp[++k] = pop(stack);
        push(stack, exp[i]);
    }
}

// pop all the operators from the stack
while (!isEmpty(stack))
    exp[++k] = pop(stack );

exp[++k] = '\0';
printf( "%s", exp );
}

int main()
{
    char exp[] = "a+b*(c^d-e)^(f+g*h)-i";
    infixToPostfix(exp);
    return 0;
}

```

output:

abcd^e-fgh*+^*+i-

3. Write a C Program to Implement Queue Using Two Stacks

```
/* C Program to implement a queue using two stacks */
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
/* structure of a stack node */
```

```
struct sNode {  
    int data;  
    struct sNode* next;  
};
```

```
/* Function to push an item to stack*/
```

```
void push(struct sNode** top_ref, int new_data);
```

```
/* Function to pop an item from stack*/
```

```
int pop(struct sNode** top_ref);
```

```
/* structure of queue having two stacks */
```

```
struct queue {  
    struct sNode* stack1;  
    struct sNode* stack2;  
};
```

```
/* Function to enqueue an item to queue */
```

```
void enQueue(struct queue* q, int x)  
{  
    push(&q->stack1, x);  
}
```

```
/* Function to deQueue an item from queue */
```

```
int deQueue(struct queue* q)  
{  
    int x;
```

```
    /* If both stacks are empty then error */
```

```
    if (q->stack1 == NULL && q->stack2 == NULL) {  
        printf("Q is empty");
```

```

    getchar();
    exit(0);
}

/* Move elements from stack1 to stack 2 only if
   stack2 is empty */
if (q->stack2 == NULL) {
    while (q->stack1 != NULL) {
        x = pop(&q->stack1);
        push(&q->stack2, x);
    }
}

x = pop(&q->stack2);
return x;
}

/* Function to push an item to stack*/
void push(struct sNode** top_ref, int new_data)
{
    /* allocate node */
    struct sNode* new_node = (struct sNode*)malloc(sizeof(struct sNode));
    if (new_node == NULL) {
        printf("Stack overflow \n");
        getchar();
        exit(0);
    }

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*top_ref);

    /* move the head to point to the new node */
    (*top_ref) = new_node;
}

```



```
/* Function to pop an item from stack*/
```

```
int pop(struct sNode** top_ref)
```

```
{
```

```
    int res;
```

```
    struct sNode* top;
```

```
    /*If stack is empty then error */
```

```
    if (*top_ref == NULL) {
```

```
        printf("Stack underflow \n");
```

```
        getchar();
```

```
        exit(0);
```

```
    }
```

```
    else {
```

```
        top = *top_ref;
```

```
        res = top->data;
```

```
        *top_ref = top->next;
```

```
        free(top);
```

```
        return res;
```

```
    }
```

```
}
```

```
/* Driver function to test anove functions */
```

```
int main()
```

```
{
```

```
    /* Create a queue with items 1 2 3*/
```

```
    struct queue* q = (struct queue*)malloc(sizeof(struct queue));
```

```
    q->stack1 = NULL;
```

```
    q->stack2 = NULL;
```

```
    enqueue(q, 1);
```

```
    enqueue(q, 2);
```

```
    enqueue(q, 3);
```

```
    /* Dequeue items */
```

```
    printf("%d ", dequeue(q));
```

```
    printf("%d ", dequeue(q));
```

```
    printf("%d ", dequeue(q));
```

```
    return 0;
}
```

Output:

1 2 3

4. write a c program for insertion and deletion of BST.

```
#include <stdio.h>
```

```
#include <malloc.h>
```

```
struct node
```

```
{
    int info;
    struct node *lchild;
    struct node *rchild;
}*root;
```

```
void find(int item,struct node **par,struct node **loc)
```

```
{
    struct node *ptr,*ptrsave;

    if(root==NULL) /*tree empty*/
    {
        *loc=NULL;
        *par=NULL;
        return;
    }
    if(item==root->info) /*item is at root*/
    {
        *loc=root;
        *par=NULL;
        return;
    }
    /*Initialize ptr and ptrsave*/
```

```

if(item<root->info)
    ptr=root->lchild;
else
    ptr=root->rchild;
ptrsave=root;

while(ptr!=NULL)
{
    if(item==ptr->info)
    {
        *loc=ptr;
        *par=ptrsave;
        return;
    }
    ptrsave=ptr;
    if(item<ptr->info)
        ptr=ptr->lchild;
    else
        ptr=ptr->rchild;
}/*End of while */
*loc=NULL; /*item not found*/
*par=ptrsave;
}/*End of find()*/

void insert(int item)
{
    struct node *tmp,*parent,*location;
    find(item,&parent,&location);
    if(location!=NULL)
    {
        printf("Item already present");
        return;
    }

    tmp=(struct node *)malloc(sizeof(struct node));
    tmp->info=item;
    tmp->lchild=NULL;
    tmp->rchild=NULL;

    if(parent==NULL)

```

```

        root=tmp;
    else
        if(item<parent->info)
            parent->lchild=tmp;
        else
            parent->rchild=tmp;
}/*End of insert()*/

```

```

void case_a(struct node *par,struct node *loc )
{
    if(par==NULL) /*item to be deleted is root node*/
        root=NULL;
    else
        if(loc==par->lchild)
            par->lchild=NULL;
        else
            par->rchild=NULL;
}/*End of case_a()*/

```

```

void case_b(struct node *par,struct node *loc)
{
    struct node *child;

    /*Initialize child*/
    if(loc->lchild!=NULL) /*item to be deleted has lchild */
        child=loc->lchild;
    else /*item to be deleted has rchild */
        child=loc->rchild;

    if(par==NULL ) /*Item to be deleted is root node*/
        root=child;
    else
        if( loc==par->lchild) /*item is lchild of its parent*/
            par->lchild=child;
        else /*item is rchild of its parent*/
            par->rchild=child;
}/*End of case_b()*/

```

```

void case_c(struct node *par,struct node *loc)
{
    struct node *ptr,*ptrsave,*suc,*parsuc;

    /*Find inorder successor and its parent*/
    ptrsave=loc;
    ptr=loc->rchild;
    while(ptr->lchild!=NULL)
    {
        ptrsave=ptr;
        ptr=ptr->lchild;
    }
    suc=ptr;
    parsuc=ptrsave;

    if(suc->lchild==NULL && suc->rchild==NULL)
        case_a(parsuc,suc);
    else
        case_b(parsuc,suc);

    if(par==NULL) /*if item to be deleted is root node */
        root=suc;
    else
        if(loc==par->lchild)
            par->lchild=suc;
        else
            par->rchild=suc;

    suc->lchild=loc->lchild;
    suc->rchild=loc->rchild;
}/*End of case_c()*/
int del(int item)
{
    struct node *parent,*location;
    if(root==NULL)
    {
        printf("Tree empty");
    }
}

```

```

        return 0;
    }

    find(item,&parent,&location);
    if(location==NULL)
    {
        printf("Item not present in tree");
        return 0;
    }

    if(location->lchild==NULL && location->rchild==NULL)
        case_a(parent,location);
    if(location->lchild!=NULL && location->rchild==NULL)
        case_b(parent,location);
    if(location->lchild==NULL && location->rchild!=NULL)
        case_b(parent,location);
    if(location->lchild!=NULL && location->rchild!=NULL)
        case_c(parent,location);
    free(location);
}/*End of del()*/

int preorder(struct node *ptr)
{
    if(root==NULL)
    {
        printf("Tree is empty");
        return 0;
    }
    if(ptr!=NULL)
    {
        printf("%d ",ptr->info);
        preorder(ptr->lchild);
        preorder(ptr->rchild);
    }
}/*End of preorder()*/

void inorder(struct node *ptr)
{

```

```

if(root==NULL)
{
    printf("Tree is empty");
    return;
}
if(ptr!=NULL)
{
    inorder(ptr->lchild);
    printf("%d ",ptr->info);
    inorder(ptr->rchild);
}
}/*End of inorder()*/

```

```

void postorder(struct node *ptr)
{
    if(root==NULL)
    {
        printf("Tree is empty");
        return;
    }
    if(ptr!=NULL)
    {
        postorder(ptr->lchild);
        postorder(ptr->rchild);
        printf("%d ",ptr->info);
    }
}/*End of postorder()*/

```

```

void display(struct node *ptr,int level)
{
    int i;
    if ( ptr!=NULL )
    {
        display(ptr->rchild, level+1);
        printf("\n");
        for (i = 0; i < level; i++)
            printf(" ");
        printf("%d", ptr->info);
    }
}

```

```

        display(ptr->lchild, level+1);
    }/*End of if*/
}/*End of display()*/
main()
{
    int choice,num;
    root=NULL;
    while(1)
    {
        printf("\n");
        printf("1.Insert\n");
        printf("2.Delete\n");
        printf("3.Inorder Traversal\n");
        printf("4.Preorder Traversal\n");
        printf("5.Postorder Traversal\n");
        printf("6.Display\n");
        printf("7.Quit\n");
        printf("Enter your choice : ");
        scanf("%d",&choice);

        switch(choice)
        {
            case 1:
                printf("Enter the number to be inserted : ");
                scanf("%d",&num);
                insert(num);
                break;
            case 2:
                printf("Enter the number to be deleted : ");
                scanf("%d",&num);
                del(num);
                break;
            case 3:
                inorder(root);
                break;
            case 4:
                preorder(root);
                break;

```



```
case 5:
    postorder(root);
    break;
case 6:
    display(root,1);
    break;
case 7:
    break;
default:
    printf("Wrong choice\n");
}/*End of switch */
}/*End of while */
}/*End of main()*/
```