

Vel Tech Group of Institutions

Name: Gontu Yaswanth

Email: vtu33434@veltech.edu.in

Roll no: Vtu33434

Phone: null

Branch: VTU

Department: CSE

Batch: 2028

Degree: B.Tech - Computer Science and Engineering

Scan to verify results



2028_NeoColab_Competitive Coding II_L8

VTU_Week 4_MCQ

Attempt : 1

Total Mark : 15

Marks Obtained : 11

Section 1 : MCQ

1. The user performs the following operations on a stack of size 5 then, which of the following is the correct statement for the 1stack?

```
push(1);  
pop();  
push(2);  
push(3);  
pop();  
push(2);  
pop();  
pop();  
push(4);  
pop();  
pop();  
push(5);
```

Answer

Underflow occurs

Status : Correct

Marks : 1/1

2. If the sequence of operations - push (1), push (2), pop, push (1), push (2), pop, pop, pop, push (2), pop are performed on a stack, the sequence of popped out values

Answer

2,2,1,2,2

Status : Wrong

Marks : 0/1

3. What is the result of the following operation?

Top (Push (S, X))

Answer

X

Status : Correct

Marks : 1/1

4. Stack A has the entries a, b, c (with a on top). Stack B is empty. An entry popped out of stack A can be printed immediately or pushed to stack B. An entry popped out of the stack B can only be printed. In this arrangement, which of the following permutations of a, b, c are not possible?

Answer

b c a

Status : Wrong

Marks : 0/1

5. Pushing an element into the stack already has five elements. The stack size is 5, then the stack becomes

Answer

Overflow

Status : Correct

Marks : 1/1

6. In a Stack, if a user tries to remove an Element from Empty stack it is called

Answer

Underflow

Status : Correct

Marks : 1/1

7. The user performs the following operations on the stack of size 5 then at the end of the last operation, the total number of elements present in the stack is

```
push(1);  
pop();  
push(2);  
push(3);  
pop();  
push(4);  
pop();  
pop();  
push(5);
```

Answer

1

Status : Correct

Marks : 1/1

8. What will be the output after performing these sequence of operations

```
push(20);  
push(4);  
top();  
pop();
```

```
pop();  
pop();  
push(5);  
top();
```

Answer

Stack Underflow

Status : Correct

Marks : 1/1

9. A normal queue, if implemented using an array of size MAX_SIZE, gets full when _____.

Answer

rear = MAX_SIZE - 1

Status : Correct

Marks : 1/1

10. If the elements 'A', 'B', 'C', and 'D' are placed in a queue and are deleted one at a time, in what order will they be removed?

Answer

ABCD

Status : Correct

Marks : 1/1

11. After performing this set of operations, what does the final queue contain?

```
InsertFront(10);  
InsertFront(20);  
InsertRear(30);  
DeleteFront();  
InsertRear(40);  
InsertRear(10);  
DeleteRear();  
InsertRear(15);  
display();
```

Answer

20 30 40 10

Status : Wrong

Marks : 0/1

12. What is the purpose of defining the constant SIZE in a queue implementation using an array?

Answer

To limit the maximum number of elements in the queue

Status : Correct

Marks : 1/1

13. What does the condition front = NULL indicate in inserting an element into a queue?

Answer

The queue is empty

Status : Correct

Marks : 1/1

14. Which of the following is a valid condition for a successful dequeue operation in the array implementation of a queue?

Answer

Rear > 0

Status : Wrong

Marks : 0/1

15. The essential condition that is checked before insertion in a queue is?

Answer

Overflow

Status : Correct

Marks : 1/1