

Interview Questions | MCQs

HOME Interview Questions MCQs *LAB VIVA CLASS NOTES SEMINAR TOPICS
ONLINE TEST GATE CAT Internship ABOUT US Privacy Policy

Any Skill Search

[Home](#) » [Strength of Materials Mcqs](#) » **300+ TOP STRENGTH of Materials Multiple Choice Questions and Answers**

300+ TOP STRENGTH of Materials Multiple Choice Questions and Answers

Strength of Materials Multiple choice Questions :-

1. Strain is defined as the ratio of

- (a) change in volume to original volume
- (b) change in length to original length
- (c) change in cross-sectional area to original cross-sectional area
- (d) any one of the above
- (e) none of the above.

Ans: d

2. Hooke's law holds good up to

- (a) yield point
- (b) limit of proportionality
- (c) breaking point
- (d) elastic limit
- (e) plastic limit.

Ans: b

3. Young's modulus is defined as the ratio of

- (a) volumetric stress and volumetric strain
- (b) lateral stress and lateral strain
- (c) longitudinal stress and longitudinal strain
- (d) shear stress to shear strain
- (e) longitudinal stress and lateral strain.

Ans: c

4. The unit of Young's modulus is


- (a) mm/mm
- (b) kg/cm
- (c) kg
- (d) kg/cm²
- (e) kg cm².

Ans: d

5. Deformation per unit length in the direction of force is known as

- (a) strain
- (b) lateral strain
- (c) linear strain
- (d) linear stress
- (e) unit strain.

Ans: c



STRENGTH of Materials Multiple
Choice Questions

6. It equal and opposite forces applied to a body tend to elongate it, the stress so produced is called

- (a) internal resistance
- (b) tensile stress
- (c) transverse stress
- (d) compressive stress
- (e) working stress.

Ans: b

7. The materials having same elastic properties in all directions are called

- (a) ideal materials
- (b) uniform materials
- (c) isotropic materials
- (d) paractical materials
- (e) elastic materials.

Ans: c

8. A thin mild steel wire is loaded by adding loads in equal increments till it breaks. The extensions noted with increasing loads will behave as under

- (a) uniform throughout
- (b) increase uniformly
- (c) first increase and then decrease
- (d) increase uniformly first and then increase rapidly
- (e) increase rapidly first and then uniformly.

Ans: d

9. Modulus of rigidity is defined as the ratio of

- (a) longitudinal stress and longitudinal strain
- (b) volumetric stress and volumetric strain
- (c) lateral stress and lateral strain
- (d) shear stress and shear strain
- (e) linear stress and lateral strain.

Ans: d

10. If the radius of wire stretched by a load is doubled, then its Young's modulus will be

- (a) doubled
- (b) halved
- (c) become four times
- (d) become one-fourth
- (e) remain unaffected.

Ans: e

11. The ultimate tensile stress of mild steel compared to ultimate compressive stress is

- (a) same
- (b) more

- (c) less
- (d) more or less depending on other factors
- (e) unpredictable.

Ans: b

12. Tensile strength of a material is obtained by dividing the maximum load during the test by the

- (a) area at the time of fracture
- (b) original cross-sectional area
- (c) average of (a) and (b)
- (d) minimum area after fracture
- (e) none of the above.

Ans: b

13. The impact strength of a material is an index of its

- (a) toughness
- (b) tensile strength
- (c) capability of being cold worked
- (d) hardness
- (e) fatigue strength.

Ans: a

14. The Young's modulus of a wire is defined as the stress which will increase the length of wire compared to its original length

- (a) half
- (b) same amount
- (c) double
- (d) one-fourth
- (e) four times.

Ans: b

15. Percentage reduction of area in performing tensile test on cast iron may be of the order of

- (a) 50%
- (b) 25%
- (c) 0%
- (d) 15%
- (e) 60%.

Ans: c

16. The intensity of stress which causes unit strain is called

- (a) unit stress
- (b) bulk modulus
- (c) modulus of rigidity
- (d) modulus of elasticity
- (e) principal stress.

Ans: d

17. True stress-strain curve for materials is plotted between

- (a) load/original cross-sectional area and change in length/original length
- (b) load/instantaneous cross-sectional area original area and log.
- (c) load/instantaneous cross-sectional area and change in length/original length
- (d) load/instantaneous area and instantaneous area/original area
- (e) none of the above.

Ans: b

18. During a tensile test on a specimen of 1 cm cross-section, maximum load observed was 8 tonnes and area of cross-section at neck was 0.5 cm². Ultimate tensile strength of specimen is

- (a) 4 tonnes/cm²
- (b) 8 tonnes/cm²
- (c) 16 tonnes/cm²
- (d) 22 tonnes/cm²
- (e) none of the above.

Ans: b

19. For steel, the ultimate strength in shear as compared to in tension is nearly

- (a) same
- (b) half
- (c) one-third
- (d) two-third
- (e) one-fourth.

Ans: b

20. Which of the following has no unit

- (a) kinematic viscosity
- (b) surface tension

- (c) bulk modulus
- (d) strain
- (e) elasticity.

Ans: d

21. Which is the false statement about true stress-strain method

- (a) It does not exist
- (b) It is more sensitive to changes in both metallurgical and mechanical conditions
- (c) It gives, a more accurate picture of the ductility
- (d) It can be correlated with stress-strain values in other tests like torsion, impact, combined stress tests etc.
- (e) It can be used for compression tests as well.

Ans: a

22. In a tensile test on mild steel specimen, the breaking stress as compared to ultimate tensile stress is

- (a) more
- (b) less
- (c) same
- (d) more/less depending on composition
- (e) may have any value.

Ans: b

23. If a part is constrained to move and heated, it will develop

- (a) principal stress
- (b) tensile stress
- (c) compressive stress
- (d) shear stress
- (e) no stress.

Ans: c

24. Which of the following materials is most elastic

- (a) rubber
- (b) plastic
- (c) brass
- (d) steel
- (e) glass.

Ans: d

25. The value of modulus of elasticity for mild steel is of the order of

- (a) $2.1 \times 10^5 \text{ kg/cm}^2$
- (b) $2.1 \times 10^6 \text{ kg/cm}^2$
- (c) $2.1 \times 10^7 \text{ kg/cm}^2$
- (d) $0.1 \times 10^6 \text{ kg/cm}^2$ (<?) $3.8 \times 10^6 \text{ kg/cm}^2$.

Ans: b

26. The value of Poisson's ratio for steel is between

- (a) 0.01 to 0.1
- (b) 0.23 to 0.27
- (c) 0.25 to 0.33
- (d) 0.4 to 0.6
- (e) 3 to 4.

Ans: c

27. The buckling load for a given material depends on

- (a) slenderness ratio and area of cross-section
- (b) Poisson's ratio and modulus of elasticity
- (c) slenderness ratio and modulus of elasticity
- (d) slenderness ratio, area of cross-section and modulus of elasticity
- (e) Poisson's ratio and slenderness ratio.

Ans: d

28. The total elongation produced in a bar of uniform section hanging vertically downwards due to its own weight is equal to that produced by a weight

- (a) of same magnitude as that of bar and applied at the lower end
- (b) half the weight of bar applied at lower end
- (c) half of the square of weight of bar applied at lower end
- (d) one-fourth of weight of bar applied at lower end
- (e) none of the above.

Ans: b

29. The property of a material by virtue of which a body returns to its original, shape after removal of the load is called

- (a) plasticity
- (b) elasticity
- (c) ductility
- (d) malleability

(e) resilience.

Ans: b

30. The materials which exhibit the same elastic properties in all directions are called

- (a) homogeneous
- (b) inelastic
- (c) isotropic
- (d) isentropic
- (e) visco-elastic.

Ans: c

31. The value of Poisson's ratio for cast iron is

- (a) 0.1 to 0.2
- (b) 0.23 to 0.27
- (c) 0.25 to 0.33
- (d) 0.4 to 0.6
- (e) 3 to 4.

Ans: b

32. The property of a material which allows it to be drawn into a smaller section is called

- (a) plasticity
- (b) ductility
- (c) elasticity
- (d) malleability
- (e) drawabihty.

Ans: b

33. Poisson's ratio is defined as the ratio of

- (a) longitudinal stress and longitudinal strain
- (b) longitudinal stress and lateral stress
- (c) lateral stress and longitudinal stress
- (d) lateral stress and lateral strain
- (e) none of the above.

Ans: c

34. For which material the Poisson's ratio is more than unity

- (a) steel
- (b) copper

- (c) aluminium
- (d) cast iron
- (e) none of the above.

Ans: e

35. The property of a material by virtue of which it can be beaten or rolled into plates is called

- (a) malleability
- (b) ductility
- (c) plasticity
- (d) elasticity
- (e) reliability.

Ans: a

36. The change in the unit volume of a material under tension with increase in its Poisson's ratio will ,

- (a) increase
- (b) decrease
- (c) remain same
- (d) increase initially and then decrease
- (e) unpredictable.

Ans: b

37. The percentage reduction in area of a cast iron specimen during tensile test would be of the order of

- (a) more than 50%
- (b) 25—50%
- (c) 10—25%
- (d) 5—10%
- (e) negligible.

Ans: e

38. If a material expands freely due to heating it will develop

- (a) thermal stresses
- (b) tensile stress
- (c) bending
- (d) compressive stress
- (e) no stress.

Ans: e

39. In a tensile test, near the elastic limit zone, the

- (a) tensile strain increases more quickly
- (b) tensile strain decreases more quickly
- (c) tensile strain increases in proportion to the stress
- (d) tensile strain decreases in proportion to the stress
- (e) tensile strain remains constant.

Ans: a

40. The stress necessary to initiate yielding is

- (a) considerably greater than that necessary to continue it
- (b) considerably lesser than that necessary to continue it
- (c) greater than that necessary to stop it
- (d) lesser than that necessary to stop it
- (e) equal to that necessary to stop it.

Ans: a

Strength of Materials Interview Questions and Answers pdf :-

41. In the tensile test, the phenomenon of slow extension of the material, i. e. stress increasing with the time at a constant load is called

- (a) creeping
- (b) yielding
- (c) breaking
- (d) plasticity
- (e) none of the above.

Ans: a

42. The stress developed in a material at breaking point in extension is called

- (a) breaking stress
- (b) fracture stress
- (c) yield point stress
- (d) ultimate tensile stress
- (e) proof stress.

Ans: a

43. Rupture stress is

- (a) breaking stress
- (b) maximum load/original cross-sectional area
- (c) load at breaking point/A

(d) load at breaking point/neck area

(e) maximum stress.

Ans: d

44. The elasticity of various materials is controlled by its

(a) ultimate tensile stress

(b) proof stress

(c) stress at yield point

(d) stress at elastic limit

(e) tensile stress.

Ans: d

45. The ratio of lateral strain to the linear strain within elastic limit is known as

(a) Young's modulus

(b) bulk modulus

(c) modulus of rigidity

(d) modulus of elasticity

(e) Poisson's ratio.

Ans: e

46. The ratio of direct stress to volumetric strain in case of a body subjected to three mutually perpendicular stresses of equal intensity, is equal to

(a) Young's modulus

(b) bulk modulus

(c) modulus of rigidity

(d) modulus of elasticity

(e) Poisson's ratio.

Ans: b

47. The stress at which extension of the material takes place more quickly as compared to the increase in load is called

(a) elastic point of the material

(b) plastic point of the material

(c) breaking point of the material

(d) yielding point of the material

(e) ultimate point of the material.

Ans: d

48. In question 56, the internal reaction in bottom 80 cm length will be

- (a) same in both cases
- (b) zero in first case
- (c) different in both cases
- (d) data are not sufficient to determine same
- (e) none of the above.

Ans: b

49. Flow stress corresponds to

- (a) fluids in motion
- (b) breaking point
- (c) plastic deformation of solids
- (d) rupture stress
- (e) none of the above.

Ans: c

50. When it is indicated that a member is elastic, it means that when force is applied, it will

- (a) not deform
- (b) be safest
- (c) stretch
- (d) not stretch
- (e) none of the above.

Ans: c

51. The energy absorbed in a body, when it is strained within the elastic limits, is known as

- (a) strain energy
- (b) resilience
- (c) proof resilience
- (d) modulus of resilience
- (e) toughness..

Ans: a

52. Resilience of a material is considered when it is subjected to

- (a) frequent heat treatment
- (b) fatigue
- (c) creep
- (d) shock loading

(e) resonant condition.

Ans: d

53. The maximum strain energy that can be stored in a body is known as

- (a) impact energy
- (b) resilience
- (c) proof resilience
- (d) modulus of resilience
- (e) toughness.

Ans: c

54. The total strain energy stored in a body is termed as

- (a) resilience
- (b) proof resilience
- (c) modulus of resilience
- (d) toughness
- (e) impact energy.

Ans: a

55. Proof resilience per material is known as

- (a) resilience
- (b) proof resilience
- (c) modulus of resilience
- (d) toughness
- (e) impact energy.

Ans: c

56. The stress induced in a body due to suddenly applied load compared to when it is applied gradually is

- (a) same
- (b) half
- (c) two times
- (d) four times
- (e) none of the above.

Ans: c

57. The strain energy stored in a body due to suddenly applied load compared to when it is applied gradually is

- (a) same

- (b) twice
- (c) four times
- (d) eight times
- (e) half.

Ans: c

58. A material capable of absorbing large amount of energy before fracture is known as

- (a) ductility
- (b) toughness
- (c) resilience
- (d) shock proof
- (e) plasticity.

Ans: b

59. Coaxing is the method of increasing

- (a) strength by reversible cycling
- (b) corrosion resistance by spraying
- (c) hardness by surface treatment
- (d) fatigue resistance by over-stressing the metal by successively increasing loadings
- (e) creep by heat treatment.

Ans:

60. A beam is loaded as cantilever. If the load at the end is increased, the failure will occur

- (a) in the middle
- (b) at the tip below the load
- (c) at the support
- (d) anywhere
- (e) none of the above.

Ans: d

61. A non-yielding support implies that the

- (a) support is frictionless
- (b) support can take any amount of reaction
- (c) support holds member firmly
- (d) slope of the beam at the support is zero
- (e) none of the above.

Ans: d

62. The ratio of elongation in a prismatic bar due to its own weight (W) as compared to another similar bar carrying an additional weight (W) will be

- (a) 1:2
- (b) 1 : 3
- (c) 1 : 4
- (d) 1 : 2.5
- (e) 1 : 2.25.

Ans: b

63. In a prismatic member made of two materials so joined that they deform equally under axial stress, the unit stresses in two materials are

- (a) equal
- (b) proportional to their respective moduli of elasticity
- (c) inversely proportional to their moduli of elasticity
- (d) average of the sum of moduli of elasticity
- (e) none of the above.

Ans: b

64. In riveted boiler joints, all stresses, shearing, bearing and tensile are based on the

- (a) size of rivet
- (b) size of the drilled or reamed hole
- (c) average of size of rivet and hole
- (d) smaller of the two
- (e) any one of the above.

Ans: b

65. The distance between the centres of the rivets in adjacent rows of zig-zag riveted joint is known as

- (a) pitch
- (b) back pitch
- (c) diagonal pitch
- (d) diametral pitch
- (e) lap.

Ans: c

66. Efficiency of a riveted joint is the ratio of its strength (max. load it can resist without failure) to the strength of the unpunched plate

in

- (a) tension
- (b) compression
- (c) bearing
- (d) any one of the above
- (e) none of the above.

Ans: a

67. When two plates are butt together and riveted with cover plates with two rows of rivets, the joint is known as

- (a) lap joint
- (b) butt joint
- (c) single riveted single cover butt joint
- (d) double riveted double cover butt joint
- (e) single riveted double cover butt joint.

Ans: d

68. A riveted joint in which every rivet of a row is opposite to other rivet of the outer row, is known as

- (a) chain riveted joint
- (b) diamond riveted joint
- (c) criss-cross riveted joint
- (d) zig-zag riveted joint
- (e) none of the above.

Ans: a

69. A riveted joint in which the number of rivets decrease from innermost to outer most row is called

- (a) chain riveted joint
- (b) diamond riveted joint
- (c) criss-cross riveted joint
- (d) zig-zag riveted joint
- (e) none of the above.

Ans: b

70. If the rivets in adjacent rows are staggered and the outermost row has only one rivet, the arrangement of the rivets is called

- (a) chain riveting
- (b) zig zag riveting
- (c) diamond riveting

- (d) criss-cross riveting
- (e) none of the above.

Ans: c

71. Diamond riveted joint can be adopted in the case of following type of joint

- (a) butt joint
- (b) lap joint
- (c) double riveted lap joints
- (d) all types of joints
- (e) none of the above.

Ans: a

72. Rivets are made of following type of material

- (a) tough
- (b) hard
- (c) resilient
- (d) ductile
- (e) malleable.

Ans: d

73. The weakest section of a diamond riveting is the section which passes through

- (a) the first row
- (b) the second row
- (c) the central row
- (d) one rivet hole of the end row
- (e) none of the above.

Ans: d

74. The deformation of a bar under its own weight compared to the deformation of same body subjected to a direct load equal to weight of the body is

- (a) same
- (b) double
- (c) half
- (d) four times
- (e) one-fourth.

Ans: c

75. The force acting along the circumference will cause stress in the walls in a direction normal to the longitudinal axis of cylinder; this stress is called

- (a) longitudinal stress
- (b) hoop stress
- (c) yeiled stress
- (d) ultimate stress
- (e) none of the above.

Ans: b

76. A boiler shell 200 cm diameter and plate thickness 1.5 cm is subjected to internal pressure of 1.5 MN/m , then the hoop stress will be

- (a) 30 MN/m²
- (b) 50 MN/m²
- (c) 100 MN/m²
- (d) 200 MN/m²
- (e) 300 MN/m².

Ans: c

77. A cylindrical section having no joint is known as

- (a) jointless section
- (b) homogeneous section
- (c) perfect section
- (d) manufactured section
- (e) seamless section.

Ans: e

78. Longitudinal stress in a thin cylinder is

- (a) equal to the hoop stress
- (b) twice the hoop stress
- (c) half of the hoop stress
- (d) one-fourth of hoop stress
- (e) four times the hoop stress.

Ans: c

79. The safe twisting moment for a compound shaft is equal to the

- (a) maximum calculated value
- (b) minimum calculated value
- (c) mean value

- (d) extreme value
- (e) none of the above.

Ans: b

80. The torsional rigidity of a shaft is expressed by the

- (a) maximum torque it can transmit
- (b) number of cycles it undergoes before failure
- (c) elastic limit up to which it resists torsion, shear and bending stresses
- (d) torque required to produce a twist of one radian per unit length of shaft
- (e) maximum power it can transmit at highest possible-speed.

Ans: d

81. The value of shear stress which is induced in the shaft due to the applied couple varies

- (a) from maximum at the center to zero at the circumference
- (b) from zero at the center to maximum at the circumference
- (c) from maximum at the center to mini-mum at the cricumference
- (d) from minimum at the centro to maxi-mum at the circumference
- (e) none of the above.

Ans: b

82. A key is subjected to side pressure as well at shearing forces.

These pressures are called

- (a) bearing stresses
- (b) fatigue stresses
- (c) crushing stresses
- (d) resultant stresses
- (e) none of the above.

Ans: a

83. In a belt drive, the pulley diameter is doubled, the belt tension and pulley width remaining same. The changes required in key will be

- (a) increase key length
- (b) increase key depth
- (c) increase key width
- (d) double all the dimensions
- (e) none of the above.

Ans: c

84. Shear stress induced in a shaft subjected to tension will be

- (a) maximum at periphery and zero at center
- (b) maximum at center
- (c) uniform throughout
- (d) average value in center
- (e) none of the above.

Ans: e

85. If rain is falling in the opposite direction of the movement of a pedestrain, he has to hold his umbrella

- (a) more inclined when moving
- (b) less inclined when moving
- (c) more inclined when standing
- (d) less inclined when standing
- (e) none of the above.

Ans: d

86. A projectile is fired at an angle θ to the vertical. Its horizontal range will be maximum when θ is

- (a) 0°
- (b) 30°
- (c) 45°
- (d) 60°
- (e) 90° .

Ans: c

88. Limiting force of friction is the

- (a) tangent of angle between normal-reaction and the resultant of normal reaction and limiting friction
- (b) ratio of limiting friction and normal reaction
- (c) the friction force acting when the body is just about to move
- (d) the friction force acting when the body is in motion
- (e) minimum force of friction.

Ans: c

89. Coulomb friction is the friction between

- (a) bodies having relative motion
- (b) two dry surfaces
- (c) two lubricated surfaces
- (d) solids and liquids

(e) electrically charged particles.

Ans: a

90. Dynamic friction as compared to static friction is

- (a) same
- (b) more
- (c) less
- (d) may be less or more depending on nature of surfaces and velocity
- (e) has no correlation.

Ans: c

92. Tangent of angle of friction is equal to

- (a) kinetic friction
- (b) limiting friction
- (c) angle of repose
- (d) coefficient of friction
- (e) friction force.

Ans: d

93. Kinetic friction is the

- (a) tangent of angle between normal reaction and the resultant of normal reaction and the limiting friction
- (b) ratio of limiting friction and normal reaction
- (c) the friction force acting when the body is just about to move
- (d) the friction force acting when the body is in motion
- (e) dynamic friction.

Ans: d

95. The effort required to lift a load W on a screw jack with helix angle α and angle of friction ϕ is equal to

- (a) $W \tan(\alpha + \phi)$
- (b) $W \tan(\alpha - \phi)$
- (c) $W \cos(\alpha + \phi)$
- (d) $W \sin(\alpha + \phi)$
- (e) $W (\sin \alpha + \cos \phi)$.

Ans: a

96. A semi-circular disc rests on a horizontal surface with its top flat surface horizontal and circular portion touching down. The coefficient of friction between semi-circular disc and horizontal

surface is i. This disc is to be pulled by a horizontal force applied at one edge and it always remains horizontal. When the disc is about to start moving, its top horizontal force will

- (a) remain horizontal
- (b) slant up towards direction of pull
- (c) slant down towards direction of pull
- (d) unpredictable
- (e) none of the above.

Ans: c

97. A particle inside a hollow sphere of radius r , having coefficient of friction μ can rest upto height of

- (a) $r/2$
- (b) r/μ
- (c) r/μ^2
- (d) $0.134 r$
- (e) $3r/8$.

Ans: d

98. The algebraic sum of moments of the forces forming couple about any point in their plane is

- (a) equal to the moment of the couple
- (b) constant
- (c) both of above are correct
- (d) both of above are wrong
- (e) none of the above.

Ans: a

99. A single force and a couple acting in the same plane upon a rigid body

- (a) balance each other
- (b) cannot balance each other
- (c) produce moment of a couple
- (d) are equivalent
- (e) none of the above.

Ans: b

100. If three forces acting in one plane upon a rigid body, keep it in equilibrium, then they must either

- (a) meet in a point

- (b) be all parallel
- (c) at least two of them must meet
- (d) all the above are correct
- (e) none of the above.

Ans: d

STRENGTH of Materials Objective Questions pdf ::

101. The maximum frictional force which comes into play when a body just begins to slide over another surface is called

- (a) limiting friction
- (b) sliding friction
- (c) rolling friction
- (d) kinematic friction
- (e) dynamic friction.

Ans: a

102. The co-efficient of friction depends upon

- (a) nature of surfaces
- (b), area of contact
- (c) shape of the surfaces
- (d) ail of the above.
- (e) (a) and (b) above.

Ans: a

104. The necessary condition for forces to be in equilibrium is that these should be

- (a) coplanar
- (b) meet at one point ;
- (c) both (a) and (b) above
- (d) all be equal
- (e) something else.

Ans: c

105. If three forces acting in different planes can be represented by a triangle, these will be in

- (a) non-equilibrium
- (b) partial equilibrium
- (c) full equilibrium
- (d) unpredictable
- (e) none of the above.

Ans: a

106. If n = number of members and j = number of joints, then for a perfect frame, n =

- (a) $j-2$
- (b) $2j-1$
- (c) $2j-3$
- (d) $3j-2$
- (e) $2j-4$.

Ans: c

107. A body moves, from rest with a constant acceleration of 5 m per sec. The distance covered in 5 sec is most nearly

- (a) 38 m
- (b) 62.5 m
- (c) 96 m
- (d) 124 m
- (e) 240 m.

Ans: b

108. A flywheel on a motor goes from rest to 1000 rpm in 6 sec. The number of revolutions made is nearly equal to

- (a) 25
- (b) 50
- (c) 100
- (d) 250
- (e) 500.

Ans: b

109 Which of the following is the locus of a point that moves in such a manner that its distance from a fixed point is equal to its distance from a fixed line multiplied by a constant greater than one

- (a) ellipse
- (b) hyperbola
- (c) parabola
- (d) circle
- (e) none of the above.

Ans: b

111. Which of the following is not the unit of energy

- (a) kg m
- (b) kcal
- (c) watt
- (d) watt hours
- (e) $\text{kg m} \times (\text{m/sec})^2$.

Ans: c

112. A sample of metal weighs 219 gms in air, 180 gms in water, 120 gms in an unknown fluid. Then which is correct statement about density of metal

- (a) density of metal can't be determined
- (b) metal is twice as dense as water
- (c) metal will float in water
- (d) metal is twice as dense as unknown fluid
- (e) none of the above.

Ans: a

113. The C.G. of a solid hemisphere lies on the central radius $3r$

- (a) at distance — from the plane base $3r$
- (b) at distance — from the plane base $3r$
- (c) at distance — from the plane base $3r$
- (d) at distance — from the plane base or
- (e) at distance — from the plane base.

Ans: d

117. The C.G. of a plane lamina will not be at its geometrical centre in the case of a

- (a) right angled triangle
- (b) equilateral triangle
- (c) square
- (d) circle
- (e) rectangle.

Ans: a

119. The C.G. of a right circular solid cone of height h lies at the following distance from the base

- (a) $h/2$
- (b) $J/3$
- (c) $h/6$
- (d) $h/4$

(e) $3/5$.

Ans: d

122. The M.I. of hollow circular section about a central axis perpendicular to section as compared to its M.I. about horizontal axis is

- (a) same
- (b) double
- (c) half
- (d) four times
- (e) one fourth.

Ans: b

126. Which of the following is the example of lever of first order

- (a) arm of man
- (b) pair of scissors
- (c) pair of clinical tongs
- (d) all of the above
- (e) none of the above.

Ans: d

127. A pair of smith's tongs is an example of the lever of

- (a) zeioth order
- (b) first order
- (c) second order
- (d) third order
- (e) fourth order.

Ans: c

128. In the lever of third order, load W, effort P and fulcrum F are oriented as follows

- (a) W between P and F
- (b) F between W and P
- (c) P between W and F
- (d) W, P and F all on one side
- (e) none of the above.

Ans: a

129. The angle which an inclined plane makes with the horizontal when a body placed on it is about to move down is known as angle

of

- (a) friction
- (b) limiting friction
- (c) repose
- (d) kinematic friction
- (e) static friction.

Ans: c

148. In actual machines

- (a) mechanical advantage is greater than velocity ratio
- (b) mechanical advantage is equal to velocity ratio
- (c) mechanical advantage is less than velocity ratio
- (d) mechanical advantage is unity
- (e) none of the above.

Ans: c

149. In ideal machines

- (a) mechanical advantage is greater than velocity ratio
- (b) mechanical advantage is equal to velocity ratio
- (c) mechanical advantage is less than velocity ratio
- (d) mechanical advantage is unity
- (e) none of the above.

Ans: b

150. A cable with a uniformly distributed load per horizontal metre run will take the following shape

- (a) straight line
- (b) parabola
- (c) hyperbola
- (d) elliptical
- (e) part of a circle.

Ans: b

STRENGTH of Materials Mcqs Download ::

---- >> Related Posts Of Above Questions :::

----->>[MOST IMPORTANT]<<-----

1. 300+ [UPDATED] Strength of Materials Interview

Questions

2. **400+ TOP STRENGTH of MATERIALS LAB VIVA Questions and Answers**
3. **140 TOP Strength of Materials Multiple Choice Questions and Answers pdf free Downlod**
4. **250+ TOP MCQs on Strength of Materials and Answers**
5. **250+ TOP MCQs on Aircraft Materials – Tension Testing – Yield Strength and Yield Point Determination and Answers**
6. **300+ TOP STRENGTH of MATERIALS Interview Questions pdf Downlod**
7. **250+ TOP MCQs on Resilience and Answers**
8. **140 TOP Strength of Materials Interview Questions and Answers pdf**
9. **250+ TOP MCQs on Strain Constants – 2 and Answers**
10. **140 TOP STRENGTH of MATERIALS Interview Questions pdf free Downlod**
11. **250+ TOP MCQs on Stress Strain Diagrams & Mechanical Properties of Engineering Materials and Answers**
12. **250+ TOP MCQs on Elastic Constants Relationship – 1 and Answers**
13. **Strength of Materials Online Test – Multiple Choice Questions & Answers**
14. **300+ TOP ENGINEERING Materials Multiple Choice Questions and Answers**
15. **300+ TOP Theory of Structures Multiple Choice Questions-Answers**
16. **250+ TOP MCQs on Design Strength of Laterally Supported Beams – II and Answers**
17. **250+ TOP MCQs on Pure Bending Stress and Answers**
18. **250+ TOP MCQs on Elastic Constants Relationship – 2 and Answers**
19. **250+ TOP MCQs on Definition of Strain Energy and Answers**
20. **140 TOP ENGINEERING MECHANICS Multiple Choice Questions and Answers**

MULTIPLE CHOICE QUESTIONS AND ANSWERS”



Emmanuel

FEBRUARY 13, 2020 AT 4:41 AM

Pls send pdf files on solved problems on strength of materials

[REPLY](#)



raju

FEBRUARY 18, 2017 AT 5:41 PM

sir i sincerely request you, please send these questions and answers to gmail:rajaseshu.talari@gmail.com

[REPLY](#)



Md Muzammil

JANUARY 31, 2017 AT 6:33 AM

**Very benifitial
Kindly send PDF files of all mechanical subjects**

[REPLY](#)



SUMIT MALUSARE

JANUARY 28, 2017 AT 8:02 AM

**really helpful.
can you send me pdf of above data.
thanking You**

[REPLY](#)



Sunil bisht

NOVEMBER 24, 2016 AT 7:25 PM

**sir
Please send me pdf of above SOM question [..sunil-bisht764@gmail.com...](#)**

[REPLY](#)



wasim

AUGUST 30, 2016 AT 2:47 AM

very useful, kindly send the pdf of all topics in mechanical engineering mcq.

[REPLY](#)



sai kiran

AUGUST 13, 2016 AT 2:51 PM

Please send me the PDFs of all these subjects please I request these are beneficial

[REPLY](#)



Siva sankar

JULY 6, 2016 AT 11:31 AM

Pdf

[REPLY](#)



sachin

JUNE 27, 2016 AT 12:43 PM

this all matter would be quite for me. For this i request you to kindly send me the pdf file of the same.

[REPLY](#)



Suchitra

APRIL 30, 2016 AT 5:22 AM

Very benifitial

Kindly send PDF files of all mechanical subjects

[REPLY](#)



Rakhahari Mandal

APRIL 15, 2016 AT 1:05 PM

Really helpful.. kindly send pdf files of all topics in Mechanical Engineering.

[REPLY](#)



tammana

APRIL 13, 2016 AT 6:22 AM

This is very good matter kindly send pdf file in mechanical muti choice question

[REPLY](#)



Sarath

APRIL 12, 2016 AT 11:34 AM

Really helpful..Kindly send the pdf files of all topics in Mechanical engineering multiple choice qstns.

sarath.twistedangel@gmail.com

[REPLY](#)

LEAVE A REPLY

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *

Website

Post Comment

Engineering 2021 , Engineering Interview Questions.com , Theme by [Engineering](#)|| [Privacy Policy](#)|| [Terms and Conditions](#)|| [ABOUT US](#)|| [Contact US](#)||

Engineering interview questions,Mcqs,Objective Questions,Class Lecture Notes,Seminor topics,Lab Viva Pdf PPT Doc Book free download. Most Asked Technical Basic CIVIL | Mechanical | CSE | EEE | ECE | IT | Chemical | Medical MBBS Jobs Online Quiz Tests for Freshers Experienced .