

3D Neopac

TWORK APPROVAL

ISO - Doc No.: GRP/ F/02, Rev. No.: 04 Date - 01.08.2018

PSM/PSP-PSM-000-6820

AW006563

Version 01

Dhawal

27-Oct-2021

ORIFLAME INDIA PVT. LTD-CUSTOMER

(731189) LOVE NATURE REFRESHING CLEANSING CREAM WITH ORGANIC ALOE VERA COCONUT WATER-125G (34819.72)

A Dia (Circumference) Dia (Circonférence)	: 40 (125.48)
B Sleeve Length Longueur de jupe	_: 145
No Print Height at Shoulder Zone non imprimable	: 05
No Print Height at Open End Zone non imprimable	: 03
Eyemark/Registration distance at of Position du spot de repérage	open end : 03
Eyemark/Registration size Taille du spot	: 3x8
Non lacquering height Zone non vernie	: 09
	All ulmensions are in Milir

Tube Colour / Couleur du tube		
White		
Print Type / Procédé d'impression Offset Screen Flexo Flexo+Scree Print Colours / Couleurs d'impression	n	
PMS: P 9402 C		
PMS: Cyan	(Flexo)	
PMS: Magenta	(Flexo)	
PMS: Yellow	(Flexo)	
PMS: Black	(Flexo)	
PMS: P 7476 C	(Screen)	
PMS: Black_Text	(Screen)	
Print start from Neck limpression à l'épaulement		
Hot Foil / Marquage à chaud Colour		
Lacquer/Varnish / Type de vernis		

If Screen printing select lacquer sequence

Post lacquer / vernis sur impression

Si sérigraphie, choisissez la séquence du vernis Prelacquer / impression sur vernis

✓ Glossy / Brillant

Matt / mat

EN FR

The artwork file is not a colour proof. The file is meant to approve the nature and position of text and pattern which is to be printed as well as colour separation.

= 5

= 2

= 0

= 7

SC

HS

В

160 Le Bon A graver n'est pas une épreuve couleur. Le Bon A Graver valide la nature et le placement des textes et des motifs à imprimer ainsi que la séparation des teintes.

Satin matt / satiné mat

Semi matt / semi mat



ARTWORK VERSION HISTORY/HISTORIQUE DES VERSIONS

PSM-000-6820	AW006563
1 01V1-000-0020	A*************************************

VER	DATE	COMMENT
01	27-10-2021	As per file we developed artwork
		2. The color sequence is as per the old printed artwork no AW005031
		3. Please check all thoroughly

Note:- "If no print at open end is less than 10MM there is chance of ink cracking while sealing of tube (depends upon colour of sleeve and ink), we suggesting there should be a sealing test before commercial printing"