





ARTWORK APPROVAL

ISO - Doc No.: GRP/ F/02, Rev. No.: 04 Date - 01.08.2018

PSM/PSP-PSM-000-6335 Version 01

AW005880

Dhawal

13-Mar-2020

ORIFLAME INDIA PVT. LTD-CUSTOMER

(728056) MILK AND HONEY GOLD SMOOTHING HAND SCRUB 75G - 33447.72

A Dia (Circumference) Dia (Circonférence) : 35	(109.24)
B Sleeve Length Longueur de jupe	: 125
O No Print Height at Shoulder Zone non imprimable	: 07
No Print Height at Open End Zone non imprimable	: 20.3
Eyemark/Registration distance at open end Position du spot de repérage	: 03
Eyemark/Registration size Taille du spot	: 3x8
Non lacquering height Zone non vernie	: 09
All difficusion	is are itt iviivi

Screen

Screen

Pg: 1/2

INTERNAL REFE No of Stations Flexo = 1 Screen = 3 + 1 TH9-Foi = 0 Offset Total = 5 Flexo+Screen, Screen FL-2 HS SC Offset В APPROVAL / VAI Signature Date: The artwork file is not a co file is meant to approve position of text and pattern printed as well as colour s

	All dimensions a	re in 'MM _'
RENCE	Tube Colour / Couleur du tube Gold	
il	Print Type / Procédé d'impression Offset Screen Flexo Flexo+Screen Print Colours / Couleurs d'impression	
	PMS: P 146 C_For Halftone(Match as per sample	Flexo
	PMS: P 8961 C (Match as per sample)	Screen
	PMS: P 476 C_Text	Scree
	PMS: Glue	Scree
ПР	PMS: Gold Foil(Kurz Luxor 220.)	TH9
	PMS: PXXXX C	
DATION	PMS: PXXXX C	
	Print start from Neck limpression à l'épaulement	
	Hot Foil / Marquage à chaud	
	Colour Lacquer/Varnish / Type de vernis	
	Glossy / Brillant Satin matt / satiné	mat
	Matt / mat Semi matt / semi r	nat
lour proof. The the nature and hand which is to be eparation.	If Screen printing select lacquer sequence Si sérigraphie, choisissez la séquence du Prelacquer l'impression sur vernis	
	Post lacquer / vernis sur impression	

EN FR



ARTWORK VERSION HISTORY/HISTORIQUE DES VERSIONS

PSM-000-6335	AW005880
1 OW-000-000	A*************************************

VER	DATE	COMMENT
01	13-03-2020	As per received design we developed the artwork.
		2. we Center align both panel
		3. We add color as per old printed artwork (AW004846)

Note:- "If no pint at open end is less than 10MM there is chance of ink cracking while sealing of tube (depends upon colour of sleeve and ink), we suggesting there should be a sealing test before commercial printing"