



GROUND PLATFORM — UGV

TITAN

Unmanned ground robotic system — an autonomous or remotely operated vehicle for recovery and evacuation of equipment and UGVs up to 1000 kg on the line of contact and in grey zones. 700 kg manipulator, airless wheels, 360° camera coverage.

RECOVERY

UP TO 1000 KG

STARLINK

FHSS 430 MHZ

700 KG MANIPULATOR

1000 kg
PAYLOAD

700 kg
MANIPULATOR

240 min
RUNTIME

15 km/h
SPEED

20 km
LINK RANGE

PLATFORM

Base size (L×W×H)	1950 × 1900 × 660 mm
Payload capacity	1000 kg
Manipulator	up to 700 kg
Wheels	airless, multi-width
Sides	drop-to-ground loading
Role	vehicle & UGV recovery

DRIVE & POWER

Drive	geared motor + ESC
ESC generation	next-gen, in-house
Travel speed	15 km/h
Runtime	240 min (4 batteries)
Batteries	4 × pack
Charging	hybrid 240/400 v / generator

COMMS & NAVIGATION

Radio link	FHSS 430 MHz (720/865/915)
LOC channel	STARLINK (or any)
Range (radio)	up to 20 km
Control	radio handset
Station	mobile, remote antennas

CAMERAS & OPTIONS

Drive cameras	4 units
Pan cameras	2 units (lower view)
Control tablet	rugged + app
Carrier-drone mode	yes
Mounts	custom

PACKAGE CONTENTS

- 4 × battery packs + hybrid charging station
 - Mobile station with remote antennas
 - Mounting kit (custom)
- Rugged control tablet with proprietary app
 - Radio handset for drive control