Sofia University
Department of Mathematics and Informatics

Course : **OO Programming with Java**
Date: **October 8, 2018**
Student Name:

Lab No. 2a

Problem 1.

1. **Using the IntelliJ to create the UML model for**

class Celsius:

It has a double data member named *celsius*

Add a constructor, set and get methods, as well as, a method *double convertToFahrenheit()* using the following formula

```
fahrenheit  = 9.0 / 5.0 * celsius  + 32;
```

class Fahrenheit :

It has a double data member named *fahrenheit*

Add a constructor, set and get methods, as well as, a method *double convertToCelsius()* using the following formula

```
celsius = 5.0 / 9.0 * ( fahrenheit - 32 );
```

class TestConvert:

It has a *main()* method to:

Create objects of classes *Celsius* and *Fahrenheit, where the values needed to initialize these objects are collected through dialog boxes*

Executes the convertTo methods and the output is displayed in dialog boxes properly formatted.

2. **Generate the UML project with the UML plugin in IntelliJ (for reference view https://www.youtube.com/watch?v=ddHXKWguxWk) .Note, the UML plugin is readily available in IntelliJ Ultimate 2018**
3. **Submit the Java application project and the UML project**

Problem 2.

Generate UML diagram for the following **`class Rectangle`** with the UML plugin in IntelliJ (for reference view **`https://www.youtube.com/watch?v=ddHXKWguxWk`**) .Note, the UML plugin is readily available in IntelliJ Ultimate 2018

Update the source code generated by the UML plugin to test the **`Stock`** class. Write a **`StockTest`** class to test the design and code. Collect the user input through dialog boxes (JavaFX)

Submit the Java application project and the UML project



Problem 3.

Да се пресметне вероятността произволно избрано петцифрено число със следните свойства

- Първата цифра да е в интервала [3, 9]
- Втората цифра да е в интервала [2, 8]
- Третата цифра да е в интервала [4, 9]
- Четвъртата цифра да е в интервала [1, 6]
- Петата цифра да е в интервала [6, 9]

да се дели на 12. Заедно с пресметнатата вероятност да се изведе броят на числата с тези свойства, както и броят на числата със зададеното свойство.

Забележка: ***Използвайте*** `String.format()`, подходящи **форматиращи спесификатори и специални (escape) символи**

Create the Java application project for the following

Problem 4.

Generate UML diagram for the following **`class Stock`** with the UML plugin in IntelliJ (for reference view **`https://www.youtube.com/watch?v=ddHXKWguxWk`**) .Note, the UML plugin is readily available in IntelliJ Ultimate 2018

Update the source code generated by the UML plugin to test the **`Stock`** class. Write a **`StockTest`** class to test the design and code. Collect the user input through dialog boxes (JavaFX)

Submit the Java application project and the UML project


Stock
-symbol: String
-name: String
-previousClosingPrice: double
-currentPrice: double
+Stock(symbol: String, name: String)
+getSymbol():String
+getName():String
+getPreviousClosingPrice(): double
+getCurrentPrice(): double
+setPreviousClosingPrice(price: double): void
+setCurrentPrice(price: double): void
+changePercent(): double
The symbol of this stock.
The name of this stock.
The previous closing price of this stock.
The current price of this stock.
Constructs a stock with a specified symbol and a name.
Returns the symbol of this stock.
Returns the name of this stock.
Returns the previous closing price of this stock.
Returns the current price of this stock.
Sets the previous closing price of this stock.
Sets the current price of this stock.
Returns the percentage of change of this stock.