

Keywords `static`, and `final`

Shirley B. Chu

June 17, 2020

De La Salle University
College of Computer Studies

Instance Variables and Instance Methods

- *Instance variables* are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.

Instance Variables and Instance Methods

- *Instance variables* are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.
- *Instance methods* are methods declared inside the class. These methods belong to each object of this class that we create.

Instance Variables and Instance Methods

- *Instance variables* are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.
- *Instance methods* are methods declared inside the class. These methods belong to each object of this class that we create.

MyPuppy	
- name : String	
- weight : int	
+ MyPuppy()	
+ MyPuppy(n : String, w: int)	
+ MyPuppy(name : String)	
+ bark() : void	
+ eat(amt: int) : void	
+ getName () : String	
+ getWeight () : int	
+ setName (name: String) : void	

Instance Variables and Instance Methods

- *Instance variables* are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.
- *Instance methods* are methods declared inside the class. These methods belong to each object of this class that we create.

MyPuppy	
-	<code>name : String</code> <code>weight : int</code>
+	<code>MyPuppy()</code> <code>MyPuppy(n : String, w: int)</code> <code>MyPuppy(name : String)</code> <code>bark() : void</code> <code>eat(amt: int) : void</code> <code>getName () : String</code> <code>getWeight () : int</code> <code>setName (name: String) : void</code>



Instance Variables and Instance Methods

- *Instance variables* are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.
- *Instance methods* are methods declared inside the class. These methods belong to each object of this class that we create.

MyPuppy	
- name : String	
- weight : int	
+ MyPuppy()	
+ MyPuppy(n : String, w: int)	
+ MyPuppy(name : String)	
+ bark() : void	
+ eat(amt: int) : void	
+ getName () : String	
+ getWeight () : int	
+ setName (name: String) : void	

Instance Variables and Instance Methods

- **Instance variables** are variables declared inside the class. These variables (often called attributes) belong to each object of this class that we create.
- **Instance methods** are methods declared inside the class. These methods belong to each object of this class that we create.



Class Variables

- *Class variables* are declared as `static`.

Class Variables

- *Class variables* are declared as `static`.
- They are loaded in memory once the class is loaded.

- *Class variables* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be accessed without creating an instance of the class, by using the class name.

- *Class variables* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be accessed without creating an instance of the class, by using the class name.
- These variables are common to all objects of this class.

- *Class variables* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be accessed without creating an instance of the class, by using the class name.
- These variables are common to all objects of this class.
- In the UML diagram, these are underlined.

Class Variables

MyPuppy

- name : String
- weight : int

+ MyPuppy()
+ MyPuppy(n : String, w: int)
+ MyPuppy(name : String)
+ bark() : void
+ eat(amt: int) : void
+ getName () : String
+ getWeight () : int
+ setName (name: String) : void

```
public class MyPuppy
{
    private String name;
    private int weight;
    :
}
```

Class Variables

MyPuppy

- name : String
- weight : int
- count : int = 0

- + MyPuppy()
- + MyPuppy(n : String, w: int)
- + MyPuppy(name : String)
- + bark() : void
- + eat(amt: int) : void
- + getName () : String
- + getWeight () : int
- + setName (name: String) : void

```
public class MyPuppy
{
    private String name;
    private int weight;
    :
}
```

Class Variables

MyPuppy

- name : String
- weight : int
- count : int = 0

+ MyPuppy()
+ MyPuppy(n : String, w: int)
+ MyPuppy(name : String)
+ bark() : void
+ eat(amt: int) : void
+ getName () : String
+ getWeight () : int
+ setName (name: String) : void

```
public class MyPuppy
{
    private static int count = 0;
    private String name;
    private int weight;
    :
}
```

- *Class methods* are declared as `static`.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be invoked without creating an instance of the class, by using the class name.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be invoked without creating an instance of the class, by using the class name.
- These methods are common to all objects of this class.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be invoked without creating an instance of the class, by using the class name.
- These methods are common to all objects of this class.
- In the UML diagram, these are underlined.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be invoked without creating an instance of the class, by using the class name.
- These methods are common to all objects of this class.
- In the UML diagram, these are underlined.
- Class methods are used to access class variables.

Class Methods

- *Class methods* are declared as `static`.
- They are loaded in memory once the class is loaded.
- If visible, they may be invoked without creating an instance of the class, by using the class name.
- These methods are common to all objects of this class.
- In the UML diagram, these are underlined.
- Class methods are used to access class variables.

Some rules to take note of [► Rules](#)

Class Methods

MyPuppy

- name : String
- weight : int
- count : int = 0

- + MyPuppy()
- + MyPuppy(n : String, w: int)
- + MyPuppy(name : String)
- + bark() : void
- + eat(amt: int) : void
- + getName () : String
- + getWeight () : int
- + setName (name: String) : void

```
public class MyPuppy
{
    private static int count = 0;
    private String name;
    private int weight;
    :
}
}
```

Class Methods

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
    :  
}
```


Class Methods

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
    public static int getCount ()  
    {  
        return count;  
    }  
}
```

Using class variables

MyPuppy

- name : String
- weight : int
- count : int = 0

- + MyPuppy()
- + MyPuppy(n : String, w: int)
- + MyPuppy(name : String)
- + bark() : void
- + eat(amt: int) : void
- + getName () : String
- + getWeight () : int
- + setName (name: String) : void
- + getCount () : int

```
public class MyPuppy
{
    public MyPuppy ()
    {
        name = "puppy";
        weight = 10;
    }

    public MyPuppy (String name)
    {
        this ();
        this.name = name;
    }

    public MyPuppy (String n, int w)
    {
        name = n;
        this.weight = w;
    }
}
```

Using class variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
  
    public MyPuppy ()  
    {  
        name = "puppy";  
        weight = 10;  
        count++;  
    }  
  
    public MyPuppy (String name)  
    {  
        this ();  
        this.name = name;  
    }  
  
    public MyPuppy (String n, int w)  
    {  
        name = n;  
        this.weight = w;  
    }  
}
```

Using class variables

MyPuppy
<ul style="list-style-type: none">- name : String- weight : int- <u>count : int = 0</u>
<ul style="list-style-type: none">+ MyPuppy()+ MyPuppy(n : String, w: int)+ MyPuppy(name : String)+ bark() : void+ eat(amt: int) : void+ getName () : String+ getWeight () : int+ setName (name: String) : void+ <u>getCount () : int</u>

```
public class MyPuppy
{
    public MyPuppy ()
    {
        name = "puppy";
        weight = 10;
        count++;
    }

    public MyPuppy (String name)
    {
        this ();
        this.name = name;
    }

    public MyPuppy (String n, int w)
    {
        name = n;
        this.weight = w;
        count++;
    }
}
```

The keyword `final`

- Constants can be defined by declaring it `final`, e.g.

```
public final int SIZE = 30;
```

The keyword `final`

- Constants can be defined by declaring it `final`, e.g.

```
public final int SIZE = 30;
```

- Naming convention for constants: nouns or noun phrases; all uppercase letters separated by underscores _

The keyword `final`

- Constants can be defined by declaring it `final`, e.g.

```
public final int SIZE = 30;
```
- Naming convention for constants: nouns or noun phrases; all uppercase letters separated by underscores _
- In the UML diagram, these are encoded in all uppercase letters

The keyword `final`

- Constants can be defined by declaring it `final`, e.g.

```
public final int SIZE = 30;
```

- Naming convention for constants: nouns or noun phrases; all uppercase letters separated by underscores _
- In the UML diagram, these are encoded in **all uppercase letters**

Class Variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
}
```

Class Variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0  
+ RATE : int
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
}
```

Class Variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0  
+ RATE : int
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    public final int RATE;  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
}
```

Class Variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0  
+ RATE : int  
+ WT : int = 5
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    public final int RATE;  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
}
```

Class Variables

MyPuppy

```
- name : String  
- weight : int  
- count : int = 0  
+ RATE : int  
+ WT : int = 5
```

```
+ MyPuppy()  
+ MyPuppy(n : String, w: int)  
+ MyPuppy(name : String)  
+ bark() : void  
+ eat(amt: int) : void  
+ getName () : String  
+ getWeight () : int  
+ setName (name: String) : void  
+ getCount () : int
```

```
public class MyPuppy  
{  
    public final int RATE;  
    public static final int WT = 5;  
    private static int count = 0;  
    private String name;  
    private int weight;  
    :  
}
```

- A `final` variable can only be assigned a value once.

Blank final

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.

Blank final

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:

Blank final

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable
 - must be initialize at the constructor;


- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable
 - must be initialize at the constructor;
 - cannot be initialize in class methods.

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable
 - must be initialize at the constructor;
 - cannot be initialize in class methods.
 - A blank final class variable

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable
 - must be initialize at the constructor;
 - cannot be initialize in class methods.
 - A blank final class variable
 - cannot be left uninitialized.

- A `final` variable can only be assigned a value once.
- A `blank final` is a `final` variable that has not been initialized during declaration. Its value may be assigned at a later stage.
- Some points to remember:
 - A blank final instance variable
 - must be initialize at the constructor;
 - cannot be initialize in class methods.
 - A blank final class variable
 - cannot be left uninitialized.
 - cannot be initialized in constructor or class methods.

Alpha, Argus, Oreo, and Shane



😊 Thank you! 😊

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.
- Instance methods can access class variables and class methods directly.

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.
- Instance methods can access class variables and class methods directly.
- Class methods can access class variables and class methods directly.

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.
- Instance methods can access class variables and class methods directly.
- Class methods can access class variables and class methods directly.
- Class methods cannot access instance variables or instance methods directly?they must use an object reference.

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.
- Instance methods can access class variables and class methods directly.
- Class methods can access class variables and class methods directly.
- Class methods cannot access instance variables or instance methods directly?they must use an object reference.
- Also, class methods cannot use the `this` keyword as there is no instance for `this` to refer to.

Class Members and Instance Members

- Instance methods can access instance variables and instance methods directly.
- Instance methods can access class variables and class methods directly.
- Class methods can access class variables and class methods directly.
- Class methods cannot access instance variables or instance methods directly?they must use an object reference.
- Also, class methods cannot use the `this` keyword as there is no instance for `this` to refer to.