


Introduction to Programming in Java


Shirley B. Chu

July 3, 2020


De La Salle University
College of Computer Studies




Source Code



Compiled Languages



Compiled Languages



high-level programming languages,
e.g. C, C++, Pascal

Compiled Languages

Source Code

high-level programming languages,
e.g. C, C++, Pascal



Compiler

A software program that translates high level language program into an executable machine language program.



Executable File

Compiled Languages

Source Code

high-level programming languages,
e.g. C, C++, Pascal



Compiler

A software program that translates high level language program into an executable machine language program.



**Executable
File**

may be executed many times but on one type of computer only

Interpreted Languages

Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time

Interpreted Languages

Source Code


high-level programming languages,
e.g. Java, Python




Interpreter

translates and executes one instruction at a time

Interpreted Languages




high-level programming languages,
e.g. Java, Python




translates and executes one instruction at a time

Fetch
a statement

Interpreted Languages



high-level programming languages,
e.g. Java, Python



translates and executes one instruction at a time

Fetch
a statement



Interpret

Interpreted Languages

Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time

Fetch
a statement

Execute

Interpret



Interpreted Languages

Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time




Fetch
a statement


Execute

Interpret

Interpreted Languages



high-level programming languages,
e.g. Java, Python



translates and executes one instruction at a time

Fetch
a statement



Execute

Interpret

Interpreted Languages

Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time

Fetch
a statement

Execute

Interpret



Interpreted Languages

Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time



Fetch
a statement

Execute

Interpret

Interpreted Languages


Source Code

high-level programming languages,
e.g. Java, Python



Interpreter

translates and executes one instruction at a time



Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

Structure

- A Java application consists of **one or more** classes.
- All lines of code to be executed must be in a class.

Class Definition

```
public class SimpleApp
{
}
```

- Class name is `SimpleApp`
- Class names in Java starts with an uppercase letter.
- File name must be `SimpleApp.java`
- The keyword `class` is used to declare a new Java class.
- The keyword `public` is an access modifier. It indicates accessibility or scope.

main() method

- The `main()` method (function) is the entry point into the Java application.

main() method

- The `main()` method (function) is the entry point into the Java application.
- Each java class can declare at most one `main()` method.

main() method

- The `main()` method (function) is the entry point into the Java application.
- Each java class can declare at most one `main()` method.
- The signature of this method is:

```
public static void main (String[] args)
```

main() method

- The `main()` method (function) is the entry point into the Java application.
- Each java class can declare at most one `main()` method.
- The signature of this method is:

```
public static void main (String[] args)
```

Class Definition

```
public class SimpleApp
{

}

}
```

main() method

- The `main()` method (function) is the entry point into the Java application.
- Each java class can declare at most one `main()` method.
- The signature of this method is:

```
public static void main (String[] args)
```

Class Definition

```
public class SimpleApp
{
    public static void main (String[] args)
    {
    }
}
```

Compiling and Running Java Programs

Save File!

Source Code: SimpleApp.java



Compiling and Running Java Programs

Save File!



Source Code > Save File > SimpleApp.java


Compiling and Running Java Programs

Save File!




Source Code: SimpleApp.java


Compiling and Running Java Programs




Compiling and Running Java Programs




Compiling and Running Java Programs




Compiling and Running Java Programs



Compiling and Running Java Programs



Compiling and Running Java Programs



Write Once Run Anywhere

- Java is an interpreted language.

Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).

Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).

Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).



Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).



Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).



Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere




SimpleApp.java

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).




Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).



Write Once Run Anywhere

- Java is an interpreted language.
- The Java Compiler translates the source code (`.java` file) into machine code (*bytecode*).
- Java bytecode is the machine language for the Java Virtual Machine (JVM).



Comment

- used for internal documentation
- Types include

1. line comment

`// till end of this line`

Comment

- used for internal documentation
- Types include

1. line comment

```
// till end of this line
```

2. multi-line comment

```
/* multi-line possible
```

```
next line comment
```

```
*/
```

- used for internal documentation
- Types include

1. line comment

```
// till end of this line
```

2. multi-line comment

```
/* multi-line possible
```

```
next line comment
```

```
*/
```

3. Javadoc comments

```
/** SimpleApp is the  
first class to created  
for this course.
```

```
* @author My Name
```

```
* @version 1.0
```

```
*/
```


- used for internal documentation
- Types include

1. line comment

```
// till end of this line
```

2. multi-line comment

```
/* multi-line possible
```

```
next line comment
```

```
*/
```

3. Javadoc comments

```
/** SimpleApp is the  
first class to created  
for this course.
```

```
* @author My Name
```

```
* @version 1.0
```

```
*/
```

Refer to: [How to write Javadoc comments](#)

- Java is a strongly-typed language.

- Java is a strongly-typed language.

-

Primitive Types	

- Java is a strongly-typed language.

-

Primitive Types	Reference Types

- Java is a strongly-typed language.

-

Primitive Types		Reference Types
<code>boolean</code>	<code>int</code>	
<code>byte</code>	<code>long</code>	
<code>char</code>	<code>float</code>	
<code>short</code>	<code>double</code>	

- Java is a strongly-typed language.

-

Primitive Types		Reference Types
<code>boolean</code>	<code>int</code>	all non-primitive types, e.g. classes
<code>byte</code>	<code>long</code>	
<code>char</code>	<code>float</code>	
<code>short</code>	<code>double</code>	

- Java is a strongly-typed language.

-

Primitive Types		Reference Types
<code>boolean</code>	<code>int</code>	all non-primitive types, e.g. classes
<code>byte</code>	<code>long</code>	
<code>char</code>	<code>float</code>	
<code>short</code>	<code>double</code>	
holds <u>exactly one value</u> of its declared type at a time		

- Java is a strongly-typed language.

-

Primitive Types		Reference Types
<code>boolean</code>	<code>int</code>	all non-primitive types, e.g. classes
<code>byte</code>	<code>long</code>	
<code>char</code>	<code>float</code>	
<code>short</code>	<code>double</code>	
holds <u>exactly one value</u> of its declared type at a time		stores addresses

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

Output Statements

- Commonly used are

`System.out.print()`

`System.out.println()`

- Examples:

`System.out.print(3 + 5);`

Output Statements

- Commonly used are

`System.out.print()`

`System.out.println()`

- Examples:

`System.out.print("Hello");`

Output Statements

- Commonly used are

`System.out.print()`

`System.out.println()`

- Examples:

```
System.out.print('h' + "ello");
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print();
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

`System.out.print();`

Error!

Output Statements

- Commonly used are

`System.out.print()`

`System.out.println()`

- Examples:

`System.out.println();`

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print("ID" + 119);
```


Output Statements

- Commonly used are
 - `System.out.print()`
 - `System.out.println()`
- Examples:

```
System.out.print("ID" + 100 + 19);
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print("ID" + (100 + 19));
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print(100 + 19 + "ID");
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print('A' + 4);
```

Output Statements

- Commonly used are
 `System.out.print()`
 `System.out.println()`
- Examples:

```
System.out.print("A" + 4);
```

Output Statements

- Commonly used are

```
System.out.print()
```

```
System.out.println()
```

- Examples:

```
System.out.print(3 + 5);
```

8

```
System.out.print("Hello");
```

Hello

```
System.out.print('h' + "ello");
```

hello

```
System.out.print();
```

Error!

```
System.out.println();
```

```
System.out.print("ID" + 119);
```

ID119

```
System.out.print("ID" + 100 + 19);
```

ID10019

```
System.out.print("ID" + (100 + 19));
```

ID119

```
System.out.print(100 + 19 + "ID");
```

119ID

```
System.out.print('A' + 4);
```

69

```
System.out.print("A" + 4);
```

A4

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console

Input Statements using `Scanner`

`Scanner` class

- may be used to read inputs from the console
- found in the `java.util` package

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`

Input Statements using `Scanner`

`Scanner` class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`

Input Statements using `Scanner`

`Scanner` class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`

Input Statements using `Scanner`

`Scanner` class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source

Input Statements using `Scanner`

`Scanner` class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source
`kb = new Scanner (System.in);`

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source
`kb = new Scanner (System.in);`
 4. call the appropriate methods to read the inputs, e.g.

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source
`kb = new Scanner (System.in);`
 4. call the appropriate methods to read the inputs, e.g.
`int nVal = kb.nextInt ();`

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source
`kb = new Scanner (System.in);`
 4. call the appropriate methods to read the inputs, e.g.
`int nVal = kb.nextInt ();`
 5. close this `Scanner`

Input Statements using Scanner

Scanner class

- may be used to read inputs from the console
- found in the `java.util` package
- to use,
 1. include the package `java.util`
`import java.util.*;`
 2. declare a variable of type `Scanner`
`Scanner kb;`
 3. instantiate a `Scanner` object and specify `System.in` as the input source
`kb = new Scanner (System.in);`
 4. call the appropriate methods to read the inputs, e.g.
`int nVal = kb.nextInt ();`
 5. close this `Scanner`
`kb.close ();`

Simple Sample

The program computes for the sum of two numbers given by the user.

Simple Sample

The program computes for the sum of two numbers given by the user.

```
public class SimpleSample
{
    public static void main (String[] args)
    {
```

```
}
```

Simple Sample

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
```

```
}
```

Simple Sample

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
        Scanner kb = new Scanner (System.in);
```

```
}
```

Simple Sample

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
        Scanner kb = new Scanner (System.in);
        int nOne, nTwo;
```

```
}
```


Simple Sample

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
        Scanner kb = new Scanner (System.in);
        int nOne, nTwo;

        System.out.print ("Enter a number:  ");
        nOne = kb.nextInt ();
        System.out.print ("Enter another number:  ");
        nTwo = kb.nextInt ();

    }
}
```

Simple Sample

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
        Scanner kb = new Scanner (System.in);
        int nOne, nTwo;

        System.out.print ("Enter a number: ");
        nOne = kb.nextInt ();
        System.out.print ("Enter another number: ");
        nTwo = kb.nextInt ();

        System.out.println ("Sum is " + (nOne + nTwo));
        kb.close ();
    }
}
```

- Other methods in `Scanner`

```
nextInt ();  
nextDouble ();  
nextBoolean ();  
next ();  
nextLine ();
```

- To resolve issues when reading inputs, instead of directly using these methods, read the input as a `String` then convert to the appropriate type, e.g.
 - to read integer inputs,

```
int nOne = Integer.parseInt (kb.nextLine ());
```
 - to read real-number inputs,

```
double dVal = Double.parseDouble (kb.nextLine ());
```

Simple Sample... modified

The program computes for the sum of two numbers given by the user.

```
import java.util.*;
public class SimpleSample
{
    public static void main (String[] args)
    {
        Scanner kb = new Scanner (System.in);
        int nOne, nTwo;

        System.out.print ("Enter a number: ");
        nOne = Integer.parseInt (kb.nextLine ());
        System.out.print ("Enter another number: ");
        nTwo = Integer.parseInt (kb.nextLine ());

        System.out.println ("Sum is " + (nOne + nTwo));
        kb.close ();
    }
}
```

😊 Thank you! 😊