

Licensed Residual Complements for Macro-Closure Failure

Zihe Zhao

Independent Researcher
ybing2093@gmail.com
ORCID: 0009-0008-4692-4408

May 2026

Abstract

Coarse-graining and compression are often described as operations that discard information. This paper isolates a sharper closure boundary: compression may hide distinctions inside fibers, and some of these hidden distinctions may remain dynamically active by later re-entering the declared macro-readout. Given a microscopic state space $\mathcal{X}$, a compression map $\pi : \mathcal{X} \rightarrow \mathcal{M}$, and a microscopic evolution map $T : \mathcal{X} \rightarrow \mathcal{X}$, a closed macro-dynamics $F : \mathcal{M} \rightarrow \mathcal{M}$ exists exactly when every compression fiber is future-constant under the one-step macro-readout $\pi \circ T$. This closure condition is standard in quotient/factor dynamics and has a stochastic analogue in Markov lumpability; here it is used as the entry point for a licensing diagnostic rather than as a new closure theorem.

The paper does not claim that every macro-closure failure admits an automatic coordinate repair. When future-constancy fails, the declared macro-state has reached a closure boundary under the current package. A fiber-hidden distinction may then be reported as a feedback-active residual; only under an explicitly declared complement package can a coordinate be evaluated as a residual complement. A candidate coordinate is licensed only when its provenance, current-state accessibility, fiber relevance, boundary status, admissible class, and update/congruence test are declared. Passing that test is not part of candidate licensing; it is the additional condition required for the candidate to become closure-restoring. It becomes closure-restoring only when the enlarged compression satisfies the required enlarged-fiber congruence condition.

The paper classifies closure responses into four types: internal residual complement, external boundary extension, scale refinement or higher-order correction, and conceptual package replacement. It also defines a local complement-closure diagnostic $\chi^*(\mathcal{V}_{\text{comp}})$ after the complement package has been declared. This diagnostic is not a new framework primitive and is not a repair constructor; it only reports whether the declared admissible complement class is sufficient for the enlarged future-readout at the declared resolution. Finally, the paper defines interface-locked compensated macro-stability: a regime in which internal residual complement channels are nontrivially active while their projected macro-readout stays stable up to a declared threshold ε . Refinement reorganizes residual structure under a new declared package; it does not annihilate the original residual. Phase-transition-like examples are used as schematic instances of this licensing discipline, not as replacements for thermodynamic or renormalization-group theories.

Keywords: compression; coarse-graining; licensed residual complements; macro-closure; closure boundary; projected stability; quotient dynamics; Markov lumpability; future-constancy; threshold crossing; declared interface; structural gaps

Contents

1 Introduction

2

2	Relation to Existing Closure and Framework-Level Objects	3
3	Compression Fibers and Macro-Closure	5
4	Future-Readout Maps and Feedback-Active Residuals	6
5	Functional Types of Fiber Residuals	7
6	Types of Closure Response	7
7	Residual Complement Coordinates	8
7.1	Licensing conditions	8
8	Local Complement-Closure Diagnostic	12
9	Threshold-Crossing and Recursive Complement Closure	12
10	Interface-Locked Compensated Projected Stability	14
11	Example I: Markov Coarse-Graining	15
12	Example II: Temperature Compression and Phase-Transition-Like Behavior	16
13	Discussion	17
14	Conclusion	18

1 Introduction

Compression is indispensable in the analysis of multi-level systems. A microscopic configuration is replaced by a macro-state, a detailed trajectory by an endpoint, or a high-dimensional distribution by a small set of reportable observables. Such compression is often useful, but its usefulness does not by itself imply macro-level closure.

The structural issue addressed in this note is the following. A compression map may hide distinctions inside fibers. These hidden distinctions may be irrelevant for some tasks, but they may also remain dynamically active: two microscopic states with the same macro-report may evolve into states with different future macro-reports. In that case, the macro-state is not exactly closed under the declared evolution.

This paper proposes a minimal formal structure for this situation. The main claims are:

- (i) Exact macro-closure exists if and only if compression fibers are future-constant under the one-step macro-readout.
- (ii) Failure of future-constancy marks a closure boundary under the declared compression package and localizes feedback-active residual pairs.
- (iii) Fiber residuals have different functional types: some are inert under the declared future readout, some are closure-breaking, some are separated by a candidate coordinate, some become closure-relevant under a closure-restoring extension, and some participate in compensated projected stability.
- (iv) A feedback-active residual does not automatically license a complement coordinate. A coordinate becomes a licensed candidate internal residual complement only after its provenance, current-state accessibility, fiber relevance, boundary status, admissible extension class, and update/congruence test have been declared.

- (v) A licensed candidate complement restores enlarged macro-closure only when the enlarged-fiber congruence condition holds.
- (vi) Recursive complement closure is conditional: after each extension, the enlarged package must be re-declared and the enlarged fibers must be re-diagnosed.
- (vii) Multiple residual complement channels may compensate under a declared interface, producing a stable or quasi-stable projected macro-readout while internal residual activity persists; this projected stability is not, by itself, a closure theorem.

The first item is a closure criterion familiar from quotient or factor dynamics, with a stochastic analogue in Markov lumpability. The novelty of the present note does not lie in treating this condition as an isolated result. Rather, the closure criterion is used as a boundary diagnostic: once fiber future-constancy fails, the hidden within-fiber distinction is classified according to its future-readout role. It may then be evaluated as a possible complement only inside a declared complement package, and it is closure-restoring only when the enlarged compression satisfies the required congruence condition. The contribution is therefore the licensing discipline for residual complements built around closure failure, not the bare closure condition alone.

The note is intended as a standalone formal module. It is compatible with viewpoint/package-locked structural-gap diagnostics, endpoint-fiber diagnostics, and accumulated residual book-keeping, but it does not identify these objects by default. Its role is narrower: it states when compression-hidden residuals may be licensed as structural complements in an enlarged macro-system and when they should instead be reported as boundary extension, scale refinement, package replacement, or non-closure.

A guiding distinction used throughout the paper is the distinction between exact closure and report-level stability. Exact closure is a single-valued dynamics condition on the compressed state. Report-level closure or stability is a thresholded statement under a declared package and need not imply exact closure. Likewise, compensated projected stability is treated as a report-level phenomenon unless the enlarged state is also shown to satisfy an exact closure condition. Refinement relocates and reorganizes residuals under a new package; it does not annihilate them as object-level distinctions.

2 Relation to Existing Closure and Framework-Level Objects

This section positions the present construction without re-proving earlier work.

Declared interfaces and package locking. All report-level claims in this note are made relative to a declared interface or package $\mathcal{V}$. The package specifies what is visible, which comparisons are licensed, what counts as an admissible reconstruction, and which threshold ε determines report-level negligibility. This package-locking discipline follows the framework-level role developed in the companion structural-gap papers [1, 2, 4].

Relation to quotient dynamics and lumpability. The exact closure condition used in Proposition 3.2 is the standard well-definedness condition for a quotient or factor dynamics: the evolution must respect the equivalence relation induced by the compression map. In the stochastic finite-state setting, the corresponding condition is Markov lumpability: all microscopic representatives inside the same macro-fiber must induce the same macro-transition law [5, 6]. The present paper does not claim these closure criteria as new. It uses them as a diagnostic boundary: when they fail, the question becomes which fiber-hidden distinctions are functionally active, whether any of them are licensed as internal residual complement coordinates under the declared admissible class, and which licensed coordinates actually restore closure under the declared congruence condition.

Relation to projection and memory formalisms. Projection-based approaches often represent the effect of unresolved variables through memory, noise, or orthogonal-dynamics terms [7, 8]. The present note takes a complementary diagnostic route: it asks when an unresolved distinction is better treated as memory/noise/boundary influence and when it is licensed instead as an explicit complement coordinate so that an enlarged macro-state may satisfy a closure congruence condition.

Fiber residuals. The present construction uses the same basic geometric idea as endpoint/fiber diagnostics: if a compression map identifies several fine-grained states, the resulting fiber may still contain distinctions relevant to future reports [3]. The present paper adds a dynamical question: which hidden distinctions become functionally active under the declared future-readout map?

Fixed-slice gaps versus accumulated quantities. A fixed-slice residual, such as a compression–reconstruction gap, should not be identified with an accumulated residual along an evolution parameter. In this paper, compensation occurs at the level of residual complement channels under a declared projection, not as cancellation of a nonnegative accumulated bookkeeping quantity.

Extension principle. When a macro-report fails to be single-valued with respect to the declared future query, the appropriate response is not to force closure. The first output is a closure-boundary diagnosis. Only if a complement package is declared does one then ask whether a coordinate in the admissible class is licensed as a residual complement. If the missing variable lies outside the declared system boundary, the correct response is boundary extension rather than internal complementation.

No new Delta-type primitive. This note does not introduce a new Δ -type scalar as a primitive object. A gap or residual magnitude may be defined after a discrepancy and a report map are declared, but the primary object here is the closure mechanism by which compression-hidden distinctions become feedback-active residual complements.

Declared complement package. For the rest of this note, the minimal package underlying complement-closure statements is

$$\mathcal{V}_{\text{comp}} := (\mathcal{X}_{\text{adm}}, \pi, T, R_{\mathcal{V}}, D_{\mathcal{V}}, \varepsilon, k, \mathcal{C}_{\text{ext}}), \quad (1)$$

where $\mathcal{X}_{\text{adm}} \subseteq \mathcal{X}$ is the admissible or reachable domain, $\pi : \mathcal{X} \rightarrow \mathcal{M}$ is the declared compression map, T is the declared evolution on the required horizon, $R_{\mathcal{V}}$ is the report map, $D_{\mathcal{V}}$ is the licensed report discrepancy, $\varepsilon > 0$ is the reporting threshold, k is the declared future horizon, and $\mathcal{C}_{\text{ext}}$ is the admissible class of complement coordinate maps. In this paper, once a complement codomain $\mathcal{E}$ is fixed, the type convention is

$$\mathcal{C}_{\text{ext}} \subseteq \{c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}\}. \quad (2)$$

Thus $\mathcal{C}_{\text{ext}}$ licenses coordinate maps c , not enlarged compression maps as separate primitives; the enlarged compression is induced by c as $\pi_c^+ = (\pi, c)$. Throughout the paper, unless an explicit extension domain is declared, every complement coordinate is typed as $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$. When no ambiguity arises, π^+ is used only as shorthand for π_c^+ ; it does not denote an independent primitive object. All enlarged-fiber expressions are read as fibers of π_c^+ restricted to $\mathcal{X}_{\text{adm}}$. Unless otherwise stated, closure, residual activity, threshold crossing, and compensation claims are evaluated on $\mathcal{X}_{\text{adm}}$ under this package. We assume $T^j(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{X}_{\text{adm}}$ for the horizons j used in the corresponding claim; if this condition is not declared, the corresponding finite-horizon report is not licensed under $\mathcal{V}_{\text{comp}}$.

Relation to the earlier $H \rightarrow H^+$ language. Relative to the earlier structural-extension language, the present paper supplies an explicit coordinate-level implementation of the carrier extension: when closure restoration is licensed, the complement coordinate c carries declared within-fiber information required for closure under the declared future query. This does not identify the present complement coordinate with endpoint–path residuals, fixed-slice fiber diameters, or accumulated residual bookkeeping.

3 Compression Fibers and Macro-Closure

Let $\mathcal{X}$ be a microscopic state space and let

$$\pi : \mathcal{X} \rightarrow \mathcal{M} \quad (3)$$

be a compression or coarse-graining map into a macro-state space $\mathcal{M}$. For $m \in \mathcal{M}$, define the compression fiber

$$\text{Fib}_\pi(m) := \pi^{-1}(m) = \{x \in \mathcal{X} : \pi(x) = m\}. \quad (4)$$

Let

$$T : \mathcal{X} \rightarrow \mathcal{X} \quad (5)$$

be the microscopic evolution map.

Definition 3.1 (Exact macro-closure). *The compressed description $(\mathcal{M}, \pi)$ is exactly closed under T on the admissible domain $\mathcal{X}_{\text{adm}}$ if there exists a map*

$$F : \mathcal{M} \rightarrow \mathcal{M} \quad (6)$$

such that

$$\pi \circ T = F \circ \pi \quad \text{on } \mathcal{X}_{\text{adm}}. \quad (7)$$

In this case, F is called the induced exact macro-dynamics on the declared domain.

Proposition 3.2 (Exact macro-closure iff fiber future-constancy). *An exact closed macro-dynamics $F : \mathcal{M} \rightarrow \mathcal{M}$ satisfying (7) on $\mathcal{X}_{\text{adm}}$ exists if and only if, for all $x, x' \in \mathcal{X}_{\text{adm}}$,*

$$\pi(x) = \pi(x') \implies \pi(Tx) = \pi(Tx'). \quad (8)$$

Proof. Assume F exists. If $\pi(x) = \pi(x')$, then

$$\pi(Tx) = F(\pi(x)) = F(\pi(x')) = \pi(Tx'),$$

so (8) holds on $\mathcal{X}_{\text{adm}}$.

Conversely, assume (8) on $\mathcal{X}_{\text{adm}}$. Define F on $\pi(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{M}$ by

$$F(\pi(x)) := \pi(Tx). \quad (9)$$

The condition (8) guarantees that this definition is independent of the representative x chosen from the fiber. Extend F arbitrarily outside $\pi(\mathcal{X}_{\text{adm}})$ if necessary. Then $\pi \circ T = F \circ \pi$ on $\mathcal{X}_{\text{adm}}$. $\square$

Remark 3.3 (Meaning of failure). *Failure of (8) does not mean that the macro-variable is useless. It means that the macro-variable is insufficient for closed prediction under the declared evolution and readout. The missing information is localized inside compression fibers.*

4 Future-Readout Maps and Feedback-Active Residuals

The one-step condition in Proposition 3.2 is the minimal closure test. For applications, a residual may be invisible after one step but visible over a longer declared horizon. We therefore introduce a future-readout map.

Let $R_V : \mathcal{M} \rightarrow \mathcal{R}$ be a declared macro-report map and let D_V be a discrepancy on $\mathcal{R}$. For a horizon $k \geq 1$ licensed by $\mathcal{V}_{\text{comp}}$, define, for $x \in \mathcal{X}_{\text{adm}}$,

$$B_{V,k}(x) := (R_V(\pi(Tx)), R_V(\pi(T^2x)), \dots, R_V(\pi(T^kx))). \quad (10)$$

When $R_V = \text{id}_{\mathcal{M}}$, this records the declared macro-trajectory up to horizon k .

Definition 4.1 ($\mathcal{V}$ -report future-readout closure). *Fix the declared package $\mathcal{V}_{\text{comp}}$ and a product discrepancy $D_V^{(k)}$ on future-readout strings. The compression π is $\mathcal{V}$ -report closed at horizon k and threshold ε if, for all $x, x' \in \mathcal{X}_{\text{adm}}$,*

$$\pi(x) = \pi(x') \implies D_V^{(k)}(B_{V,k}(x), B_{V,k}(x')) < \varepsilon. \quad (11)$$

This is a thresholded report-level condition. Exact macro-closure from Proposition 3.2 is the stronger one-step case in which the macro-readout is required to be single-valued, rather than merely indistinguishable below ε . A $\mathcal{V}$ -report closure statement is not equivalent to exact macro-closure unless the declared report map separates the relevant macro-states and the threshold convention is replaced by exact equality.

Definition 4.2 (Fiber residual). *Let $x, x' \in \mathcal{X}_{\text{adm}}$ satisfy $\pi(x) = \pi(x')$. The pair (x, x') is called a fiber residual pair under π if $x \neq x'$. It is a distinction hidden by the compression map.*

Definition 4.3 (One-step feedback-active residual). *A fiber residual pair (x, x') is one-step feedback-active under (π, T) if*

$$\pi(x) = \pi(x') \quad \text{but} \quad \pi(Tx) \neq \pi(Tx'). \quad (12)$$

Equivalently, the residual is invisible at the current macro-readout but visible in the next macro-readout.

Definition 4.4 (Horizon- k feedback-active residual). *A fiber residual pair (x, x') is feedback-active under (π, T, R_V, k) if*

$$\pi(x) = \pi(x') \quad \text{but} \quad B_{V,k}(x) \neq B_{V,k}(x'). \quad (13)$$

It is ε -active if the discrepancy between the two future-readout strings is at least ε under the declared product discrepancy.

Corollary 4.5. *A compressed macro-description is not exactly closed under T if and only if there exists at least one one-step feedback-active residual pair.*

Proof. Immediate from Proposition 3.2. □

Remark 4.6 (No information-conservation claim). *The term “residual” should not be read as a universal information-conservation statement. It means that a distinction hidden by the declared compression remains dynamically relevant within the declared system boundary and future readout.*

5 Functional Types of Fiber Residuals

The existence of a fiber difference is not yet a structural conclusion. Its role is determined by how it behaves under the declared compression, evolution, report map, and possible macro-extension.

Definition 5.1 (Inert residual). *A fiber residual pair (x, x') is inert under (π, T, R_V, k) if*

$$\pi(x) = \pi(x') \quad \text{and} \quad B_{V,k}(x) = B_{V,k}(x'). \quad (14)$$

Such a distinction is hidden by the current compression and does not affect the declared future-readout over the horizon k .

Definition 5.2 (Closure-breaking residual). *A fiber residual pair (x, x') is closure-breaking for (π, T) if*

$$\pi(x) = \pi(x') \quad \text{and} \quad \pi(Tx) \neq \pi(Tx'). \quad (15)$$

Equivalently, it violates the fiber future-constancy condition (8).

Definition 5.3 (c -separated residual pair). *Let $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$ be a declared coordinate. A fiber residual pair (x, x') with $x, x' \in \mathcal{X}_{\text{adm}}$ is c -separated if*

$$\pi(x) = \pi(x') \quad \text{but} \quad c(x) \neq c(x'). \quad (16)$$

This is a local separation property of the coordinate c ; by itself it does not imply that c restores macro-closure.

Definition 5.4 (Closure-relevant residual pair). *Let $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$ and let $\pi_c^+ := (\pi, c)$. A c -separated residual pair (x, x') is closure-relevant for the declared extension π_c^+ if c is part of a closure-restoring residual complement coordinate in the sense of Definition 7.2. Thus closure-relevance is evaluated relative to the enlarged compression and its declared congruence condition, not from pairwise separation alone.*

Definition 5.5 (Compensatory residual). *A residual complement state $\eta_t = c(x_t)$ is compensatory on a time window I if it changes on I while the declared macro-readout of the enlarged state remains ε -stable. The precise report-level condition is stated in Definition 10.1.*

Remark 5.6 (Functional status is package-relative). *The functional status of a fiber residual is relative to (π, T, R_V, k) and, when an extension is used, to $\pi_c^+ = (\pi, c)$. The same microscopic distinction may be inert under one declared readout and closure-breaking under another.*

6 Types of Closure Response

Failure of future-constancy is a closure-boundary diagnosis, not a proof that an internal complement coordinate exists. The response depends on the declared source of the missing distinction and on the admissible class allowed by the report. This paper distinguishes four response types.

A. Internal residual complement. An internal residual complement is a current-state coordinate

$$c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E} \quad (17)$$

that refines the original compression fibers

$$\text{Fib}_\pi(m) = \{x \in \mathcal{X}_{\text{adm}} : \pi(x) = m\} \quad (18)$$

into enlarged fibers

$$\text{Fib}_{\pi_c^+}(m, a) = \{x \in \mathcal{X}_{\text{adm}} : \pi(x) = m, c(x) = a\}. \quad (19)$$

It is internal only when it is read from the present state inside the declared system boundary and separates distinctions inside the original fiber that are relevant to the declared future-readout. This is the primary object of the present paper.

B. External boundary extension. If the future macro-readout depends on an unmodeled environmental or control variable e_t , the correct representation has the form

$$x_{t+1} = T(x_t, e_t) \quad \text{or} \quad \mathcal{X} \longrightarrow \mathcal{X} \times E. \quad (20)$$

This is not an internal residual complement extracted from a compression fiber. It is a system-boundary enlargement and therefore defines a new declared package.

C. Scale refinement or higher-order correction. Some non-closure reports are handled not by adding a single complement coordinate but by refining the declared scale, truncation order, or approximation scheme:

$$\mathcal{V}_0 \longrightarrow \mathcal{V}_1 \longrightarrow \mathcal{V}_2 \longrightarrow \cdots. \quad (21)$$

Examples include higher-order corrections, effective descriptions with changing cutoffs, and renormalization-style refinements. In such cases the residual is redistributed across order terms, cutoff dependence, scheme dependence, or scale-dependent carriers. This is not automatically an internal residual complement.

D. Conceptual package replacement. In some cases the appropriate response is not coordinate extension inside the same macro-state, but replacement of the structural package itself. A new package may recover the previous package in a specified limiting regime, but it is not merely a coordinate repair of the old one.

Remark 6.1 (Classification rule). *The four responses are mutually useful distinctions, not an exhaustive metaphysical taxonomy. A report must state which response type is being invoked. Calling every successful refinement a residual complement would erase the compression problem and would conflict with the package-locking discipline used throughout this framework.*

7 Residual Complement Coordinates

When feedback-active residuals exist, one may ask whether the declared package licenses an internal complement coordinate. This question is conditional. A positive non-closure diagnosis does not by itself imply that an admissible complement coordinate exists.

7.1 Licensing conditions

A coordinate c is licensed as an internal residual complement only under the following package-level conditions.

- (L1) **Current-state provenance.** The coordinate must be readable from the current admissible state:

$$c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}. \quad (22)$$

A look-ahead coordinate such as $c(x) = \pi(Tx)$ is not licensed as an internal residual complement unless the declared package explicitly allows one-step oracle access or model-evaluation access before the complement is read. Without that declaration, it may serve as a diagnostic witness for non-closure, but not as an accessible internal complement coordinate.

- (L2) **Fiber relevance.** The coordinate must refine the original compression fiber and separate distinctions relevant to the declared future-readout:

$$\text{Fib}_\pi(m) \longrightarrow \text{Fib}_{\pi_c^+}(m, a) = \{x \in \mathcal{X}_{\text{adm}} : \pi(x) = m, c(x) = a\}. \quad (23)$$

Pairwise separation alone is insufficient; the separated distinction must be active under the declared future query.

(L3) **Boundary discipline.** If the missing distinction is supplied by an unmodeled environment, control input, boundary condition, or external field, the correct response is boundary extension, not internal complementation.

(L4) **Admissible complement class.** The coordinate must belong to the declared extension class:

$$c \in \mathcal{C}_{\text{ext}}. \quad (24)$$

Without this clause, the trivial choice $c(x) = x$ restores deterministic closure but cancels the compression question.

(L5) **Declared update/congruence test.** The complement package must declare the update rule or congruence condition by which a licensed candidate will later be tested for closure restoration. Declaring this test is part of candidate licensing. Satisfying the test is not part of candidate licensing; it is the additional condition required for closure restoration.

Thus (L1)–(L5) license a coordinate as a candidate residual complement. They do not assert exact enlarged macro-closure. Exact enlarged macro-closure requires the additional enlarged-fiber congruence condition stated in Definition 7.2 and Proposition 7.3.

Definition 7.1 (Licensed candidate residual complement coordinate). *A map*

$$c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E} \quad (25)$$

is called a licensed candidate residual complement coordinate for (π, T) under $\mathcal{V}_{\text{comp}}$ if $c \in \mathcal{C}_{\text{ext}}$ and the licensing clauses (L1)–(L5) are declared for c . Equivalently, c is admitted as a current-state coordinate that may be tested as a residual complement under the declared package.

This definition makes no exact-closure claim. In particular, a licensed candidate coordinate may separate feedback-active fiber residuals without restoring enlarged macro-closure. The enlarged compression induced by c is

$$\pi_c^+ : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{M} \times \mathcal{E}, \quad \pi_c^+(x) := (\pi(x), c(x)), \quad (26)$$

and its reachable enlarged macro-state space is

$$\mathcal{M}_c^+ := \pi_c^+(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{M} \times \mathcal{E}. \quad (27)$$

The coordinate is evaluated as a candidate only when it either separates at least one declared feedback-active fiber residual or belongs to a licensed family declared to carry compression-hidden information relevant to the declared future-readout.

Standing domain condition for closure restoration. In all exact closure-restoration statements involving $c(Tx)$, we assume that $T(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{X}_{\text{adm}}$. If this condition is not declared, the exact enlarged closure statement is not licensed under $\mathcal{V}_{\text{comp}}$.

Definition 7.2 (Closure-restoring residual complement coordinate). *A licensed candidate residual complement coordinate $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$ is closure-restoring for (π, T) on $\mathcal{X}_{\text{adm}}$ if the enlarged compression map $\pi_c^+ = (\pi, c)$ admits an exact closed enlarged macro-dynamics on the reachable enlarged macro-state space,*

$$F_c^+ : \mathcal{M}_c^+ \rightarrow \mathcal{M}_c^+, \quad (28)$$

satisfying

$$\pi_c^+ \circ T = F_c^+ \circ \pi_c^+ \quad \text{on } \mathcal{X}_{\text{adm}}. \quad (29)$$

Any extension of F_c^+ outside $\mathcal{M}_c^+$ is non-canonical and carries no additional closure claim.

Proposition 7.3 (Closure restoration iff enlarged-fiber congruence). *Assume $T(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{X}_{\text{adm}}$. Let $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$ be a licensed candidate residual complement coordinate for (π, T) under $\mathcal{V}_{\text{comp}}$, and set $\pi_c^+ = (\pi, c)$. The following are equivalent:*

(i) *c is closure-restoring for (π, T) on $\mathcal{X}_{\text{adm}}$.*

(ii) *For all $x, x' \in \mathcal{X}_{\text{adm}}$,*

$$\pi(x) = \pi(x') \text{ and } c(x) = c(x') \implies \pi(Tx) = \pi(Tx') \text{ and } c(Tx) = c(Tx'). \quad (30)$$

In this case, the induced enlarged macro-dynamics is defined on $\mathcal{M}_c^+ = \pi_c^+(\mathcal{X}_{\text{adm}})$ by

$$F_c^+(\pi_c^+(x)) := \pi_c^+(Tx). \quad (31)$$

Any extension outside $\mathcal{M}_c^+$ is non-canonical and is irrelevant to closure on the declared reachable domain.

Proof. Apply Proposition 3.2 to the enlarged compression map π_c^+ restricted to $\mathcal{X}_{\text{adm}}$. Condition (30) is exactly the fiber future-constancy condition for π_c^+ on $\mathcal{X}_{\text{adm}}$, with the reachable enlarged macro-state space restricted to $\mathcal{M}_c^+ = \pi_c^+(\mathcal{X}_{\text{adm}})$, and therefore is equivalent to the existence of an exact closed enlarged macro-dynamics satisfying Definition 7.2. $\square$

Remark 7.4 (State closure versus report closure). *The congruence condition used in Proposition 7.3 is a state-closure condition for the enlarged macro-state: it requires the next enlarged state $\pi_c^+(Tx)$ to be single-valued on enlarged fibers. A weaker report-closure condition may be defined by replacing π_c^+ with a declared report map $R_{\mathcal{Y}}^+$ and a thresholded discrepancy, but that weaker condition does not by itself produce an exact enlarged dynamics.*

Remark 7.5 (Trivial full-state closure and nontrivial complements). *In a deterministic setting, exact closure can always be restored trivially by taking a complement coordinate that preserves the full microscopic state, for example $c(x) = x$. Such an extension is not the diagnostic target of this paper. The nontrivial content of residual-complement closure appears only after an admissible extension class $\mathcal{C}_{\text{ext}}$, a reporting interface, and, when needed, a cost, minimality, or compression discipline have been declared. A residual complement coordinate is therefore not merely any coordinate that restores closure, but a licensed carrier of the feedback-active distinctions required by the declared macro-readout.*

Lemma 7.6 (Closure-restoring complements separate closure-breaking pairs). *Let $c : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}$ be closure-restoring for (π, T) on $\mathcal{X}_{\text{adm}}$. If $x, x' \in \mathcal{X}_{\text{adm}}$ satisfy*

$$\pi(x) = \pi(x') \quad \text{and} \quad \pi(Tx) \neq \pi(Tx'), \quad (32)$$

then

$$c(x) \neq c(x'). \quad (33)$$

Thus separating every one-step closure-breaking pair is necessary for exact closure restoration, although pairwise separation alone is not sufficient unless the full enlarged-fiber congruence condition holds.

Proof. If $c(x) = c(x')$, then $\pi_c^+(x) = \pi_c^+(x')$. Since c is closure-restoring, the enlarged compression satisfies the congruence condition in Proposition 7.3. Hence $\pi(Tx) = \pi(Tx')$, contradicting the assumed closure-breaking pair. $\square$

Remark 7.7 (Interpretation). *A closure-restoring residual complement coordinate c is not an arbitrary extra variable. It extracts enough feedback-active fiber information to make the enlarged macro-description exactly closed under the declared dynamics. A candidate coordinate need not restore closure unless the congruence condition in Proposition 7.3 holds.*

Coordinate map versus complement state. Throughout the rest of the paper, c denotes the residual complement coordinate map, while

$$\eta_t := c(x_t) \quad (34)$$

denotes the residual complement state realized along a trajectory $x_t = T^t x_0$. When the complement map has several components, we write

$$c = (c_1, \dots, c_r), \quad \eta_t = (\eta_{1,t}, \dots, \eta_{r,t}), \quad \eta_{i,t} := c_i(x_t). \quad (35)$$

Thus η_t is the activated residual-complement channel state induced by c along the trajectory, not a new primitive object independent of c .

Definition 7.8 (Minimal future-readout quotient). *Fix (π, T, R_V, k) . Define an equivalence relation on $\mathcal{X}_{\text{adm}}$ by*

$$x \sim_{V,k} x' \iff \pi(x) = \pi(x') \text{ and } B_{V,k}(x) = B_{V,k}(x'). \quad (36)$$

The horizon- k quotient coordinate

$$c_{V,k}^*(x) := [x]_{\sim_{V,k}} \quad (37)$$

separates exactly those fiber differences that change the declared future-readout over horizon k .

Remark 7.9 (Finite-horizon separation is not closure). *The coordinate $c_{V,k}^*$ is a minimal horizon- k separator. It is a diagnostic quotient, not automatically a licensed internal complement, because its definition uses the declared future-readout. It becomes a licensed complement only if $\mathcal{C}_{\text{ext}}$ explicitly admits such look-ahead or quotient coordinates under the declared access discipline. It is not, by itself, a closure-restoring complement coordinate unless the induced equivalence relation is T -invariant on $\mathcal{X}_{\text{adm}}$, or unless the construction is replaced by an infinite-horizon or stable-refinement version. Closure still requires the congruence condition in Proposition 7.3.*

Remark 7.10 (No demand to preserve all micro-information). *The construction does not require preservation of all microscopic distinctions. Only functionally active fiber differences, as measured by the declared future-readout and admitted by $\mathcal{C}_{\text{ext}}$, are candidates for internal complementation; closure restoration still requires the relevant congruence condition.*

Coordinate representation: residual counter-terms

When the macro-state space has a vector-space or charted structure, the influence of residual complements can be written as a counter-term. This is an optional coordinate representation, not the coordinate-free core of the construction.

Assumption 7.11 (Local chart). *Assume that $\mathcal{M}$ is locally represented in a coordinate chart so that differences of macro-readouts are meaningful in a normed vector space.*

Let $m_t = \pi(x_t)$ and $\eta_t = c(x_t)$. Suppose the enlarged dynamics can be written locally as

$$m_{t+1} = \mathcal{F}(m_t, \eta_t). \quad (38)$$

Choose a baseline macro-map $F_0 : \mathcal{M} \rightarrow \mathcal{M}$. Define the residual complement effect by

$$C(m_t, \eta_t) := \mathcal{F}(m_t, \eta_t) - F_0(m_t), \quad (39)$$

whenever this expression is meaningful in the declared chart.

Definition 7.12 (Residual counter-term). *The term $C(m, \eta)$ is a residual counter-term if it measures the reportable deviation in the macro-update induced by the feedback-active residual coordinate η relative to a baseline macro-update $F_0(m)$.*

Remark 7.13 (Coordinate dependence). *The counter-term representation is chart-dependent. The coordinate-free object is the failure of closure under π and the restoration of closure under the induced enlarged compression π_c^+ .*

8 Local Complement-Closure Diagnostic

After a complement package has been declared, one may define a local diagnostic for the declared admissible complement class. This quantity is not a new framework primitive and does not construct a complement. It only evaluates the residual left inside enlarged fibers after admissible complements have been specified. The diagnostic $\chi^*(\mathcal{V}_{\text{comp}})$ is a report-level complement-sufficiency diagnostic. It does not construct a complement coordinate and does not assert exact enlarged macro-closure unless the thresholded discrepancy is replaced by exact equality and the enlarged-fiber congruence condition is satisfied.

Notation for enlarged report maps. In the local optimization diagnostic, the enlarged report map may be written as $R_{\mathcal{V},c}^+$ because the reachable enlarged state space $\pi_c^+(\mathcal{X}_{\text{adm}})$ can depend on the chosen coordinate c . Once a complement codomain $\mathcal{E}$ and an ambient enlarged macro-state space $\mathcal{M}^+ = \mathcal{M} \times \mathcal{E}$ are fixed, we write the corresponding declared report map as $R_{\mathcal{V}}^+ : \mathcal{M}^+ \rightarrow \mathcal{R}$.

Assume that $\mathcal{V}_{\text{comp}}$ declares, for each licensed c , an enlarged-state report map $R_{\mathcal{V},c}^+ : \mathcal{M}_c^+ \rightarrow \mathcal{R}$, a product discrepancy $D_{\mathcal{V}}^{(k),+}$ on enlarged future-readout strings, and a licensed admissible class $\mathcal{C}_{\text{ext}}^{\text{lic}} \subseteq \mathcal{C}_{\text{ext}}$. For $c \in \mathcal{C}_{\text{ext}}^{\text{lic}}$, set

$$\pi_c^+(x) := (\pi(x), c(x)) \quad (40)$$

and define the enlarged future-readout string

$$B_{\mathcal{V},k}^{+,c}(x) := (R_{\mathcal{V},c}^+(\pi_c^+(Tx)), R_{\mathcal{V},c}^+(\pi_c^+(T^2x)), \dots, R_{\mathcal{V},c}^+(\pi_c^+(T^kx))). \quad (41)$$

The local complement-closure diagnostic is

$$\chi^*(\mathcal{V}_{\text{comp}}) := \inf_{c \in \mathcal{C}_{\text{ext}}^{\text{lic}}} \sup_{\substack{x, x' \in \mathcal{X}_{\text{adm}} \\ \pi_c^+(x) = \pi_c^+(x')}} D_{\mathcal{V}}^{(k),+}(B_{\mathcal{V},k}^{+,c}(x), B_{\mathcal{V},k}^{+,c}(x')), \quad (42)$$

whenever all displayed objects are declared and the optimization domain is nonempty.

Remark 8.1 (Status of χ^*). *The quantity $\chi^*(\mathcal{V}_{\text{comp}})$ is evaluated only after $\mathcal{V}_{\text{comp}}$ and the licensed complement class have been declared. It is not implied by a previous nonzero residual, and it is not a repair operator. If $\chi^*(\mathcal{V}_{\text{comp}}) < \varepsilon$, the declared complement class is report-level sufficient for the chosen enlarged future-readout under $\mathcal{V}_{\text{comp}}$. If $\chi^*(\mathcal{V}_{\text{comp}}) \geq \varepsilon$, the declared complement class remains insufficient at the reporting threshold. If the package does not declare the required objects, the diagnostic is undefined.*

Remark 8.2 (Threshold boundary for the infimum). *If the infimum in (42) is not attained, the statement $\chi^*(\mathcal{V}_{\text{comp}}) < \varepsilon$ still licenses report-level sufficiency because some admissible coordinate achieves a value below ε . By contrast, $\chi^*(\mathcal{V}_{\text{comp}}) = \varepsilon$ does not license report-level complement sufficiency under the strict $< \varepsilon$ convention.*

Remark 8.3 (Residual relocation under refinement). *Passing from $\mathcal{V}$ to $\mathcal{V}_{\text{comp}}$ does not erase the original closure-boundary diagnosis. It changes the declared reporting package and therefore requires a new diagnosis under the enlarged fibers. Refinement relocates and reorganizes residuals; it does not annihilate them.*

9 Threshold-Crossing and Recursive Complement Closure

The preceding sections describe a single closure attempt. The same mechanism can occur recursively. After a complement coordinate has been added, the enlarged macro-system may still have its own compression fibers and its own feedback-active residuals.

Let

$$\pi_n : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{M}_n \quad (43)$$

be the macro-interface at level n , equipped with report map $R_n : \mathcal{M}_n \rightarrow \mathcal{R}_n$, licensed product discrepancy $D_n^{(k_n)}$ on $\mathcal{R}_n^{k_n}$, threshold $\varepsilon_n > 0$, and horizon k_n . Define the level- n future-readout map

$$B_{n,k_n}(x) := (R_n(\pi_n(Tx)), \dots, R_n(\pi_n(T^{k_n}x))). \quad (44)$$

For $m \in \pi_n(\mathcal{X}_{\text{adm}})$, define the level- n fiber variation

$$\rho_{n,k_n}(m) := \sup_{x, x' \in \text{Fib}_{\pi_n}(m) \cap \mathcal{X}_{\text{adm}}} D_n^{(k_n)}(B_{n,k_n}(x), B_{n,k_n}(x')), \quad (45)$$

whenever the displayed discrepancy is licensed under the declared package.

Remark 9.1 (Relation to fiber-diameter diagnostics). *The quantity $\rho_{n,k_n}(m)$ is the dynamic future-readout analogue of a fiber diameter. In fixed-slice endpoint diagnostics, a fiber diameter measures the maximal discrepancy among outputs associated with states or histories that share the same endpoint. Here the endpoint is the level- n macro-report $\pi_n(x) = m$, and the readout being compared is the declared future-readout map B_{n,k_n} . Thus $\rho_{n,k_n}(m)$ plays the same structural role as a fiber diameter, but on a dynamical readout window. When $\rho_{n,k_n}(m) \geq \varepsilon_n$, the diagnostic diameter is not merely a measure of non-sufficiency; it becomes a closure-boundary signal. A residual complement coordinate c_n may be introduced only if a new admissible complement package licenses it. This is the point at which a fiber-diameter diagnostic becomes a conditional extension signal under the declared package [3].*

Definition 9.2 (Threshold-crossing residual). *A level- n fiber over $m \in \mathcal{M}_n$ contains a threshold-crossing residual if*

$$\rho_{n,k_n}(m) \geq \varepsilon_n. \quad (46)$$

When this occurs, the residual is reportably active at level n under the declared interface.

Definition 9.3 (Recursive residual-complement extension). *A recursive residual-complement extension is a sequence*

$$\pi_0 \longrightarrow \pi_1 \longrightarrow \pi_2 \longrightarrow \dots \quad (47)$$

constructed as follows. At level n , let $\pi_n : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{M}_n$ be the declared level- n compression. If the level- n package licenses a complement coordinate

$$c_n : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{E}_n, \quad (48)$$

then define

$$\pi_{n+1} : \mathcal{X}_{\text{adm}} \rightarrow \mathcal{M}_{n+1}, \quad \pi_{n+1}(x) := (\pi_n(x), c_n(x)), \quad (49)$$

where

$$\mathcal{M}_{n+1} := \pi_{n+1}(\mathcal{X}_{\text{adm}}) \subseteq \mathcal{M}_n \times \mathcal{E}_n. \quad (50)$$

The coordinate c_n is introduced, under the level- n complement package, only to separate threshold-crossing residuals at level n . Closure restoration at level $n+1$ still requires the corresponding enlarged-fiber congruence condition.

Remark 9.4 (No termination, uniqueness, or minimality claim). *The recursive construction does not imply finite termination, uniqueness of complement coordinates, or minimality of the resulting hierarchy unless additional admissibility and minimality clauses are declared. Each step begins with a threshold-crossing boundary diagnosis. A candidate extension is introduced only if the level-specific complement package licenses it, and closure restoration at the next level still requires the corresponding congruence condition.*

Remark 9.5 (Fractal-like, not automatically fractal). *The recursive construction creates nested fiber refinements*

$$\text{Fib}_{\pi_0} \supseteq \text{Fib}_{\pi_1} \supseteq \text{Fib}_{\pi_2} \supseteq \dots \quad (51)$$

whenever the maps are formed by adding coordinates. This gives a fractal-like residual hierarchy only if a declared rescaling or recurrence law identifies similar residual-complement patterns across levels. Without such a rescaling law, the structure is recursive but not automatically a fractal.

10 Interface-Locked Compensated Projected Stability

In this note, compensated projected stability means projected report-level stability under the declared interface while residual complement channels are nontrivially active. This condition alone is not a closure theorem. Exact compensated macro-closure requires, in addition, an enlarged state equipped with closed dynamics satisfying the required congruence condition.

Let $\mathcal{M}^+ = \mathcal{M} \times \mathcal{E}$ denote the ambient enlarged macro-state space for the chosen complement codomain, and let the enlarged state be

$$z_t = (m_t, \eta_t) \in \mathcal{M}^+. \quad (52)$$

Let

$$R_{\mathcal{V}}^+ : \mathcal{M}^+ \rightarrow \mathcal{R} \quad (53)$$

be a declared enlarged-state report map associated with a declared interface or package $\mathcal{V}$. The space $\mathcal{R}$ is equipped with a report-level discrepancy $D_{\mathcal{V}}$ and threshold $\varepsilon > 0$.

Definition 10.1 (Interface-locked compensated projected stability). *A trajectory $(z_t)_{t \geq 0}$ satisfies interface-locked compensated projected stability under $(R_{\mathcal{V}}^+, D_{\mathcal{V}}, \varepsilon)$ on a time window $I \subseteq \mathbb{N}$ if*

$$D_{\mathcal{V}}(R_{\mathcal{V}}^+(z_{t+1}), R_{\mathcal{V}}^+(z_t)) < \varepsilon \quad \text{for all } t, t+1 \in I, \quad (54)$$

while the residual complement coordinates are nontrivially active on I , i.e. there exists at least one t with $t, t+1 \in I$ such that

$$\eta_{t+1} \neq \eta_t \quad (55)$$

or, in a metric version,

$$d_{\eta}(\eta_{t+1}, \eta_t) > 0. \quad (56)$$

Remark 10.2 (Activity proxy). *The condition $\eta_{t+1} \neq \eta_t$ is only a minimal nontrivial-activity proxy on the window I . It does not assert persistent activity at every time step. Stronger compensated activity requires a declared internal effect norm or threshold, such as the channel-wise condition in Definition 10.3.*

Definition 10.3 (Channel-wise compensation). *Suppose $\eta = (\eta_1, \dots, \eta_N)$ and the residual complement effects decompose locally as*

$$C_{\text{tot}}(m, \eta) = \sum_{i=1}^N C_i(m, \eta_i). \quad (57)$$

Let $\|\cdot\|_{\text{int}}$ be a declared internal activity norm and let $\delta_{\text{int}} > 0$ be a declared internal activity threshold. The residual channels are compensated under the declared projection $\Pi_{\mathcal{V}}$ if

$$\sum_{i=1}^N \|C_i(m, \eta_i)\|_{\text{int}} \geq \delta_{\text{int}}, \quad (58)$$

while the projected report-level effect is negligible:

$$\left\| \Pi_{\mathcal{V}} \left(\sum_{i=1}^N C_i(m, \eta_i) \right) \right\|_{\mathcal{V}} < \varepsilon, \quad (59)$$

where $\|\cdot\|_{\mathcal{V}}$ is the report-level norm licensed by the declared interface. Equivalently, when the interface is expressed by a report map and discrepancy, condition (59) may be replaced by the corresponding $D_{\mathcal{V}}$ -inequality.

Remark 10.4 (No cancellation of accumulated residual bookkeeping). *Channel-wise compensation is not a claim that a nonnegative accumulated residual vanishes. It is a claim about projected complement effects under a declared interface. Gross residual activity and net report-level residual may differ.*

Remark 10.5 (Coordinate-level status of channel decomposition). *The decomposition $C_{\text{tot}} = \sum_i C_i$ is a coordinate-level representation licensed by the declared chart or local model. The coordinate-free claim is only that projected report-level variation may remain below ε while residual complement channels remain internally active.*

11 Example I: Markov Coarse-Graining

This section gives the stochastic analogue of Proposition 3.2. The deterministic map T is replaced by a Markov kernel K , and closure means the existence of a macro-kernel $\bar{K}(m, \cdot)$ whose value is independent of the chosen microscopic representative inside each fiber [9].

Let $\mathcal{X}$ be a finite microscopic state space, let $\pi : \mathcal{X} \rightarrow \mathcal{M}$ be a coarse-graining map, and let $K(x, \cdot)$ be a Markov transition kernel on $\mathcal{X}$. For each $x \in \mathcal{X}$, the induced one-step macro-transition law is the pushforward

$$\bar{K}_x(A) := K(x, \pi^{-1}(A)), \quad A \subseteq \mathcal{M}. \quad (60)$$

A closed Markov macro-kernel $\bar{K}(m, \cdot)$ exists if and only if the pushforward law is constant on compression fibers:

$$\pi(x) = \pi(x') \implies \bar{K}_x = \bar{K}_{x'}. \quad (61)$$

Condition (61) is the stochastic version of fiber future-constancy. When it holds, one defines $\bar{K}(m, \cdot) := \bar{K}_x(\cdot)$ for any representative $x \in \pi^{-1}(m)$, and the definition is representative-independent. In finite-state Markov terminology, this is the strong lumpability condition for the partition induced by π under the declared coarse-graining map.

The residual-complement reading begins after this standard closure test fails. In that case, the non-constant pushforward laws do not merely show that the coarse Markov kernel is undefined; they localize which within-fiber distinctions are feedback-active relative to the declared macro-transition query. A complement coordinate c is then evaluated not by whether it separates some microscopic states, but by whether the enlarged fibers of (π, c) make the induced macro-transition law constant.

For a concrete example, take $\mathcal{X} = \{1, 2, 3, 4\}$ and $\mathcal{M} = \{A, B\}$ with

$$\pi(1) = \pi(2) = A, \quad \pi(3) = \pi(4) = B. \quad (62)$$

If

$$K(1, \{3\}) = 1, \quad K(2, \{4\}) = 1, \quad (63)$$

then both microscopic states in $\text{Fib}_{\pi}(A)$ move to macro-state B with probability one, so the pair $(1, 2)$ is not feedback-active relative to the one-step macro-readout. If instead

$$K(1, \{3\}) = 1, \quad K(2, \{1\}) = 1, \quad (64)$$

then

$$\pi(1) = \pi(2) = A \quad \text{but} \quad \bar{K}_1 = \delta_B \neq \delta_A = \bar{K}_2. \quad (65)$$

Hence the macro-state A is not closed: the hidden distinction inside $\text{Fib}_\pi(A)$ changes the future macro-transition law. The displayed pair can be separated by a residual complement coordinate, for example

$$c(1) = 0, \quad c(2) = 1. \quad (66)$$

These two values only separate the active pair $(1, 2)$. The coordinate is an internal candidate complement only because it is read from the present microscopic state and refines the original macro-fiber. If the missing distinction were supplied instead by an unmodeled control input or external environment, the correct diagnosis would be boundary extension rather than internal residual complementation. A complete stochastic closure statement requires values on all states and constancy of the induced transition law on every enlarged fiber. For instance, if the remaining transitions are declared by

$$K(3, \{3\}) = 1, \quad K(4, \{4\}) = 1, \quad (67)$$

and one sets

$$c(3) = 0, \quad c(4) = 1, \quad (68)$$

then each enlarged fiber of (π, c) is a singleton in this toy example, and the enlarged macro-kernel is closed.

12 Example II: Temperature Compression and Phase-Transition-Like Behavior

This example is illustrative rather than a thermodynamic derivation of phase transitions [10]. It shows how a temperature-only readout can fail closure when phase composition or order-parameter-like structure becomes feedback-active. The example should therefore be read as a schematic complement-closure pattern, not as a full thermodynamic model.

This example should not be read as deriving the order parameter, free energy, critical exponents, or universality class of a thermodynamic transition. Its diagnostic target is different. Starting from a chosen temperature readout Θ together with a declared temperature resolution or binning rule, it asks whether the temperature-only report is closed under the declared heat-input protocol. When states in the same declared temperature bin differ in phase composition or order-parameter-like structure and therefore produce different future temperature responses, the temperature-only report is structurally insufficient as a closed macro-state. The complement coordinate ϕ is introduced not as a replacement for thermodynamic order-parameter theory, but as a candidate residual carrier under a declared experimental package. Whether ϕ is an internal complement, a boundary-driven variable, or part of a scale-refinement description depends on the declared protocol.

Let $\mathcal{X}$ denote microscopic thermal states and let

$$\Theta : \mathcal{X} \rightarrow \mathbb{R}, \quad \Theta(x) = \text{temperature of } x \quad (69)$$

be the temperature readout. For report-level closure, fix a declared temperature resolution $\varepsilon_\Theta > 0$ or, equivalently, a declared temperature-bin map $\widehat{\Theta} : \mathcal{X} \rightarrow \mathcal{B}_\Theta$. States in the same declared temperature bin may still differ in phase fraction, latent heat storage, interface geometry, density fluctuations, or local molecular organization. Let

$$\mathcal{T}_Q : \mathcal{X} \rightarrow \mathcal{X} \quad (70)$$

denote the declared microscopic thermal evolution under a fixed heat-input or control protocol Q . The protocol Q is understood to include the controlled external conditions relevant to the

readout, such as boundary conditions, pressure/volume constraints, heat-input schedule, or external fields when these are part of the declared experiment. In stochastic thermal descriptions, $\mathcal{T}_Q$ may be replaced by a declared transition kernel, with closure read in the same pushforward sense as in the Markov example. A temperature-only description is closed at the declared report resolution under this protocol only if

$$\widehat{\Theta}(x) = \widehat{\Theta}(x') \implies \widehat{\Theta}(\mathcal{T}_Q x) = \widehat{\Theta}(\mathcal{T}_Q x'). \quad (71)$$

Equivalently, in a metric version, states indistinguishable below the declared temperature resolution must have future temperature readouts indistinguishable below the corresponding future-report threshold. Near a transition window this condition can fail: two states in the same temperature bin may have different phase compositions and therefore respond differently to the same declared heat input.

Introduce, under the declared package, a candidate complement coordinate

$$\phi : \mathcal{X}_{\text{adm}} \rightarrow [0, 1], \quad (72)$$

where ϕ denotes a phase fraction or an order-parameter-like coordinate. This coordinate is treated as an internal residual complement only if it is readable from the current thermal state under the declared protocol and belongs to the admissible complement class; otherwise the appropriate diagnosis may be boundary extension or scale refinement. The enlarged macro-state coordinate package is

$$z = (\Theta, \phi). \quad (73)$$

Here $z = (\Theta, \phi)$ denotes the declared coordinate package. For a microscopic state x , the realized enlarged macro-state is

$$z(x) := (\Theta(x), \phi(x)). \quad (74)$$

During a transition window, the report-level temperature may remain approximately stable,

$$|\Theta_{t+1} - \Theta_t| < \varepsilon_\Theta, \quad (75)$$

while the complement coordinate changes,

$$|\phi_{t+1} - \phi_t| > 0. \quad (76)$$

Thus the temperature plateau is not interpreted as absence of internal change, but as an interface-locked compensated regime: under this declared interface, the temperature readout remains ε_Θ -stable while the complement coordinate changes. No thermodynamic closure theorem is asserted unless the enlarged state (Θ, ϕ) is equipped with a declared closed dynamics satisfying the relevant congruence condition.

13 Discussion

The construction separates seven notions that are often conflated:

- (i) **Compression:** the map $\pi : \mathcal{X} \rightarrow \mathcal{M}$ hides distinctions inside fibers.
- (ii) **Closure boundary:** failure of future-constancy shows that the current macro-state is not closed for the declared future query.
- (iii) **Residual activity:** some hidden distinctions remain relevant to future macro-readouts.
- (iv) **Functional residual type:** a fiber difference may be inert, closure-breaking, c -separated, closure-relevant, or compensatory depending on (π, T, R_γ, k) and the chosen extension.

- (v) **Candidate versus closure-restoring complement extension:** feedback-active residuals may be submitted for licensing as candidate macro-coordinates, but only congruence-satisfying licensed extensions restore exact closure.
- (vi) **Exact closure versus report-level closure:** exact closure requires single-valued macro-dynamics, whereas report-level closure is thresholded under a declared package.
- (vii) **Compensated stability:** the enlarged system may have active complement dynamics while the declared macro-readout remains stable up to threshold ε ; this projected stability is not itself a closure theorem.

The construction should therefore be read as a closure-extension module rather than as a new name for the closure condition itself. The closure condition tells us when a compressed macro-state is well-defined as a closed dynamics. The residual-complement construction begins when that condition fails: it identifies the active hidden distinctions, separates inert residuals from closure-breaking residuals, distinguishes merely separating coordinates from closure-restoring coordinates, and permits recursive extension only after a new package licenses the next complement attempt when the enlarged description still leaves threshold-crossing fiber variation. This is the structural increment supplied by the present note.

Not every fiber-hidden distinction should be treated as a complement coordinate. Only distinctions that produce variation under the declared future-readout map are functionally active. Among them, only those readable from the current state, internal to the declared boundary, and admitted by $\mathcal{C}_{\text{ext}}$ become licensed candidate complements; only those satisfying a declared congruence condition become closure-relevant. This prevents the construction from becoming a demand to preserve all microscopic information. Full-state embedding can restore closure trivially; the diagnostic target is a licensed, nontrivial complement inside the declared extension class.

The recursive extension in Section 9 also clarifies the relation between macro-level formation and threshold crossing. A macro-level is not only selected by compression; a new macro-level may be declared in response to dynamical threshold crossing inside fibers, after which candidate complement coordinates may be evaluated under the newly declared package. If the same residual-complement pattern recurs across levels under a declared rescaling law, the resulting hierarchy may be self-similar. Without such a law, the hierarchy remains recursive but not automatically fractal.

This suggests a structural reading of certain emergence and phase-transition-like phenomena. A macro-state may appear stable not because lower-level residuals vanish, but because residual complement channels are organized so that their projected report-level effect is stable or near-zero under a declared interface.

14 Conclusion

Compression does not by itself determine whether hidden distinctions are structurally irrelevant. The decisive exact-closure condition is future-constancy on compression fibers. When fiber-hidden distinctions affect future macro-readouts, the current macro-state has reached a closure boundary under the declared package. These distinctions may be reported as feedback-active residuals, but they do not automatically license a coordinate repair.

A coordinate becomes an internal residual complement only after its provenance, current-state accessibility, fiber relevance, boundary status, admissible class, and update/congruence rule have been declared. It becomes closure-restoring only when the enlarged compression satisfies the required enlarged-fiber congruence condition. After refinement, the enlarged package must be diagnosed again; the original residual has been relocated and reorganized, not annihilated. When residual variation inside enlarged fibers again crosses a declared threshold, the construction can

iterate only under a newly declared complement package. When multiple residual complement channels compensate under a declared interface, a stable projected macro-readout can coexist with persistent internal residual activity, without implying exact closure by itself.

The minimal slogan is:

A macro-state is exactly closed only when all states in the same compression fiber have the same future macro-readout. When this fails, the current package has reached a closure boundary. A complement coordinate is licensed only after its provenance, accessibility, admissible class, boundary status, and update rule are declared; closure restoration then requires the enlarged-fiber congruence condition.

In this sense, the paper does not replace existing closure, lumpability, thermodynamic, or phase-transition theories. It supplies a package-relative licensing language for deciding when a chosen compression fails closure, when a residual is only a diagnostic witness, when the correct move is boundary extension or scale refinement, and when an admissible coordinate deserves the name residual complement.

References

- [1] Zihe Zhao. *Relative-Entropy Endpoint-Path Gaps as a Diagnostic of RG Coarse-Graining Failure*. Zenodo, 2026. DOI: [10.5281/zenodo.18414030](https://doi.org/10.5281/zenodo.18414030).
- [2] Zihe Zhao. *The Ψ - Δ Framework: Structural Gaps and Their Dynamics in Multi-Level Systems*. Zenodo, 2026. DOI: [10.5281/zenodo.18456597](https://doi.org/10.5281/zenodo.18456597).
- [3] Zihe Zhao. *Why Hierarchical Attention Works: A Declared-Package Fiber-Diameter Diagnostic*. Zenodo, 2026. DOI: [10.5281/zenodo.18810251](https://doi.org/10.5281/zenodo.18810251).
- [4] Zihe Zhao. *From Endpoint Sufficiency to Structural Gaps: Clarifying the Framework-Level Content of a Cross-Level Diagnostic Program*. Zenodo, 2026. DOI: [10.5281/zenodo.19081150](https://doi.org/10.5281/zenodo.19081150).
- [5] John G. Kemeny and J. Laurie Snell. *Finite Markov Chains*. D. Van Nostrand, 1960.
- [6] C. J. Burke and Murray Rosenblatt. A Markovian function of a Markov chain. *The Annals of Mathematical Statistics*, 29(4):1112–1122, 1958.
- [7] Robert Zwanzig. Memory effects in irreversible thermodynamics. *Physical Review*, 124(4):983–992, 1961.
- [8] Hazime Mori. Transport, collective motion, and Brownian motion. *Progress of Theoretical Physics*, 33(3):423–455, 1965.
- [9] J. R. Norris. *Markov Chains*. Cambridge University Press, 1997.
- [10] Nigel Goldenfeld. *Lectures on Phase Transitions and the Renormalization Group*. CRC Press, 1992.