

Leipzig University
Institute of Computer Science
Degree Programme Computer Science, B.Sc.

The Title of the Thesis

Bachelor's Thesis

Yannick Brenning
Born Aug. 27, 2002 in Bamberg

Matriculation Number 3732848

1. Referee: Christopher Schröder
2. Referee: Christian Kahmann

Submission date: February 31, 2022

Declaration

Unless otherwise indicated in the text or references, this thesis is entirely the product of my own scholarly work.

Leipzig, February 31, 2022

.....
Yannick Brenning

Abstract

This is the L^AT_EX template for Bachelor and Master theses at Webis. This template contains several hints and conventions on how to structure a thesis, how to cite the work of others, and how to display your results besides plain text.

Contents

1	Introduction	2
2	Background/Related Work	4
2.1	Text Classification	4
2.2	Active Learning	5
2.3	Core-Set	5
2.4	Dimensionality Reduction	5
3	Approach	6
4	Experiment	7
4.1	Data	7
4.2	Experiment Setup	7
4.3	Experiment Results	7
5	Discussion	9
6	Conclusion	10
	Bibliography	11

Chapter 1

Introduction

Text is one of the most widespread and important sources of information, but extracting data and tangible knowledge from it can be a difficult and expensive task. With the advent of the digital age, enormous amounts of unstructured texts are available with more being generated by the day. Due to this increasingly large amount of textual data, processing information at a larger scale becomes infeasible and thus demands the use of computer-driven approaches.

The classification of text, meaning the assignment of a category or class to a document or piece of text is one of the most common and useful ways to gain information from a piece of text. As the amount of available text content continues to grow, text classification tasks become an increasingly important area of research within the field of natural language processing.

Thanks to machine learning and data science, we have been able to develop many methods of extracting information from text, and as a result, perform text classification at a larger scale. This possibility for automated organization of data can enhance insights and decision-making across industries such as healthcare, finance, and social sciences, among many others. Active Learning (AL) is a subfield of machine learning in which the learning algorithm is able to perform queries on an information source in order to reduce the total amount of annotated data. This method can offer significant advantages in improving model performances and especially in reducing labeling costs. Though there is no universally good strategy, AL has been proven to be useful in many cases where annotating data is expensive or the total amount of data is very large (Settles [2009]).

Oftentimes, there is a large amount of unlabelled available data for an AL model to learn from. In this case, selecting the most effective data points to be labelled by the information source from this large pool becomes a crucial, but difficult challenge to overcome.

One attempt at improving the effectiveness of AL in this regard is the Core-Set approach (Sener and Savarese [2018]). This method uses core-set selection to counter the issue of AL ineffectiveness on convolutional neural networks. The proposed approach selects a set of points from the pool such that a model learning over this subset can be consistent when provided the remaining data points. The method was shown to have improved results when compared to other approaches in the field of computer vision (Sener and Savarese [2018], Caramalau et al. [2021]), which encompasses tasks that focus on enabling computers to interpret and understand visual information from the world. This field involves a variety of different methods including image classification, object detection, and semantic segmentation, all of which have significant importance in scientific research, classification tasks, and pattern recognition.

However, Core-Set has been shown to have mixed results in cases of multi-class text classification using BERT (Prabhu et al. [2021]) and binary text classification using DNNs (Liu et al. [2021]). Particularly in the first case, the experiments show that Core-Set performs poorly even when compared to the random sampling strategy. In addition, the approach has even been shown to be less effective in computer vision tasks in cases with higher numbers of classes as well as higher-dimensional data points (Sinha et al. [2019]). The theoretical analysis shown in Sener and Savarese [2018] briefly mentions this within the context of higher class amounts, however it does not attempt to provide a potential solution to the problem.

This thesis aims to explore the possibility of improving the Core-Set approach for text classification tasks. By first explaining Core-Set’s functionality and the theoretical reasons for why it tends to underperform in certain classification tasks, I aim to then demonstrate the performance difference in comparison to various baseline approaches on large datasets of text content in order to verify this claim. Furthermore, this thesis looks to improve on the Core-Set approach within the context of text classification tasks and demonstrate this improvement as a part of its experiment.

In the following, Chapter 2 explains the background and related work on the topics of text classification (Section 2.1), active learning in general (Section 2.2), and the Core-Set approach to AL more specifically (Section 2.3). In Chapter 3, I will explain my approach to improving the performance of Core-Set for text classification using dimensionality reduction. In Chapters 4 and 5, I will present my experiment as well as discuss its results. Finally, Chapter 6 will conclude the thesis and provide insights on potential future developments of the method.

Chapter 2

Background/Related Work

2.1 Text Classification

Text classification is one of the most fundamental and important tasks in the field of Natural Language Processing (NLP). As a result, developing efficient automatic text classification methods has become an important research topic.

One of the most common applications of text classification is determining whether the opinion associated with a certain document has a positive or negative sentiment, also known as sentiment analysis. This has a wide range of uses, including the possibility for businesses to better gauge customer opinions on products and services (Liu and Zhang [2012]) in order to adapt accordingly. This application is a binary classification task, meaning the classifier has two classes with which each document can be labelled (positive or negative). Similarly, one might apply this binary classification task to the problem of spam filtering in e-mails, text messages and more.

Beyond that, many applications of text classification require multiple classes, such as news and content categorization. In this case, text classification algorithms can organize documents into specific topics or themes (e.g. Sports, Business, Politics, ...) (Sebastiani [2002]). Other applications include information retrieval, recommender systems, and document summarization (Kowsari et al. [2019]).

Generally, text classification methods can be divided into the following phases: data collection and preprocessing, feature extraction, classifier selection, and model evaluation (Kowsari et al. [2019], Mironczuk and Protasiewicz [2018], Ikonomakis et al. [2005]).

2.2 Active Learning

2.3 Core-Set

2.4 Dimensionality Reduction

As mentioned earlier, one of the major challenges of the Core-Set approach (among others) is handling data points with a higher dimensionality (Sinha et al. [2019]). Broadly speaking, this is a phenomenon coined by Richard E. Bellman known as the *curse of dimensionality* (François [2007]). As a result, many algorithms have been developed to transform data from a high-dimensional space into a low-dimensional space (Van Der Maaten et al. [2009]). This task directly poses another challenge: managing to reduce the dimensionality of the data while still being able to retain the highest possible amount of information.

Chapter 3

Approach

Chapter 4

Experiment

4.1 Data

This experiment was conducted across three datasets commonly used in the field of AL. These datasets are of three different types: sentiment analysis (S), questions (Q), and news (N). For binary classification, I used **Movie Review**, a sentiment analysis dataset (Pang and Lee [2005]) containing 5,331 positive and 5,331 negative samples. For multi-class text classification, **AG's News** (Zhang et al. [2015]), comprised of 120,000 training samples and 7,600 test samples, and **TREC** (Li and Roth [2006]), a question dataset containing 5,500 training samples and 500 test samples.

The test set was only provided in the case of AG's News and TREC, in the case of Movie Review I employed a split of the 10,662 samples myself.

4.2 Experiment Setup

4.3 Experiment Results

Dataset	Model	Query Strategy				
		RS	BT	CS	Unknown	
AG's News	BERT	0.78 ± 0.171	0.79 ± 0.161	0.727 ± 0.175	$0 \pm$	0
	SetFit	0.862 ± 0.044	0.877 ± 0.048	0.868 ± 0.052	$0 \pm$	0
Movie Review	BERT	0.747 ± 0.089	0.743 ± 0.091	0.715 ± 0.097	$0 \pm$	0
	SetFit	0.853 ± 0.015	0.863 ± 0.019	0.856 ± 0.018	$0 \pm$	0
TREC-6	BERT	0.668 ± 0.251	0.702 ± 0.246	0.592 ± 0.256	$0 \pm$	0
	SetFit	0.907 ± 0.076	0.916 ± 0.093	0.89 ± 0.111	$0 \pm$	0

Table 4.1: Final accuracy per dataset, model, and query strategy. We report the mean and standard deviation over five runs. The best result per dataset is printed in bold.

Dataset	Model	Query Strategy				
		RS	BT	CS	Unknown	
AG's News	BERT	0.79 ± 0.015	0.8 ± 0.009	0.735 ± 0.02	$0 \pm$	0
	SetFit	0.865 ± 0.007	0.881 ± 0.004	0.871 ± 0.005	$0 \pm$	0
Movie Review	BERT	0.75 ± 0.007	0.746 ± 0.011	0.718 ± 0.009	$0 \pm$	0
	SetFit	0.854 ± 0.002	0.864 ± 0.005	0.856 ± 0.003	$0 \pm$	0
TREC-6	BERT	0.674 ± 0.029	0.709 ± 0.008	0.594 ± 0.022	$0 \pm$	0
	SetFit	0.914 ± 0.011	0.923 ± 0.007	0.896 ± 0.015	$0 \pm$	0

Table 4.2: Final AUC per dataset, model, and query strategy. We report the mean and standard deviation over five runs. The best result per dataset is printed in bold.

Chapter 5

Discussion

Chapter 6

Conclusion

Bibliography

- Razvan Caramalau, Binod Bhattarai, and Tae-Kyun Kim. Sequential graph convolutional network for active learning. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, pages 9583–9592. Computer Vision Foundation / IEEE, 2021. doi: 10.1109/CVPR46437.2021.00946. URL https://openaccess.thecvf.com/content/CVPR2021/html/Caramalau_Sequential_Graph_Convolutional_Network_for_Active_Learning_CVPR_2021_paper.html.
- Damien François. High-dimensional data analysis. 2007.
- M Ikonomakis, Sotiris Kotsiantis, Vasilis Tampakas, et al. Text classification using machine learning techniques. *WSEAS transactions on computers*, 4 (8):966–974, 2005.
- Kamran Kowsari, Kiana Jafari Meimandi, Mojtaba Heidarysafa, Sanjana Mendu, Laura E. Barnes, and Donald E. Brown. Text classification algorithms: A survey. *Inf.*, 10(4):150, 2019. doi: 10.3390/info10040150. URL <https://doi.org/10.3390/info10040150>.
- Xin Li and Dan Roth. Learning question classifiers: the role of semantic information. *Nat. Lang. Eng.*, 12(3):229–249, 2006. doi: 10.1017/S1351324905003955. URL <https://doi.org/10.1017/S1351324905003955>.
- Bing Liu and Lei Zhang. A survey of opinion mining and sentiment analysis. In Charu C. Aggarwal and ChengXiang Zhai, editors, *Mining Text Data*, pages 415–463. Springer, 2012. doi: 10.1007/978-1-4614-3223-4_13. URL https://doi.org/10.1007/978-1-4614-3223-4_13.
- Qiang Liu, Yanqiao Zhu, Zhaocheng Liu, Yufeng Zhang, and Shu Wu. Deep active learning for text classification with diverse interpretations. In Gianluca Demartini, Guido Zuccon, J. Shane Culpepper, Zi Huang, and Hanghang Tong, editors, *CIKM '21: The 30th ACM International Conference on*

- Information and Knowledge Management, Virtual Event, Queensland, Australia, November 1 - 5, 2021*, pages 3263–3267. ACM, 2021. doi: 10.1145/3459637.3482080. URL <https://doi.org/10.1145/3459637.3482080>.
- Marcin Mironczuk and Jaroslaw Protasiewicz. A recent overview of the state-of-the-art elements of text classification. *Expert Syst. Appl.*, 106:36–54, 2018. doi: 10.1016/j.eswa.2018.03.058. URL <https://doi.org/10.1016/j.eswa.2018.03.058>.
- Bo Pang and Lillian Lee. Seeing stars: Exploiting class relationships for sentiment categorization with respect to rating scales. In Kevin Knight, Hwee Tou Ng, and Kemal Oflazer, editors, *ACL 2005, 43rd Annual Meeting of the Association for Computational Linguistics, Proceedings of the Conference, 25-30 June 2005, University of Michigan, USA*, pages 115–124. The Association for Computer Linguistics, 2005. doi: 10.3115/1219840.1219855. URL <https://aclanthology.org/P05-1015/>.
- Sumanth Prabhu, Moosa Mohamed, and Hemant Misra. Multi-class text classification using bert-based active learning. In Eduard C. Dragut, Yunyao Li, Lucian Popa, and Slobodan Vucetic, editors, *3rd Workshop on Data Science with Human in the Loop, DaSH@KDD, Virtual Conference, August 15, 2021*, 2021. URL <https://drive.google.com/file/d/1xVy4p29UPINmWl8Y70ospyQgHiYfH4wc/view>.
- Fabrizio Sebastiani. Machine learning in automated text categorization. *ACM Comput. Surv.*, 34(1):1–47, 2002. doi: 10.1145/505282.505283. URL <https://doi.org/10.1145/505282.505283>.
- Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL <https://openreview.net/forum?id=H1aIuk-RW>.
- Burr Settles. Active learning literature survey. Computer Sciences Technical Report 1648, University of Wisconsin–Madison, 2009.
- Samarth Sinha, Sayna Ebrahimi, and Trevor Darrell. Variational adversarial active learning. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, pages 5971–5980. IEEE, 2019. doi: 10.1109/ICCV.2019.00607. URL <https://doi.org/10.1109/ICCV.2019.00607>.

Laurens Van Der Maaten, Eric O Postma, H Jaap van den Herik, et al. Dimensionality reduction: A comparative review. *Journal of Machine Learning Research*, 10(66-71):13, 2009.

Xiang Zhang, Junbo Jake Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pages 649–657, 2015. URL <https://proceedings.neurips.cc/paper/2015/hash/250cf8b51c773f3f8dc8b4be867a9a02-Abstract.html>.