
Part Number: XH430-W350

1. Electrical & Mechanical Specifications (Standard Reference)

Parameter	Symbol	Specification Value	Test Condition / Notes
Part Number	ID	XH430-W350	DYNAMIXEL-X
Manufacturer	Vendor	ROBOTIS	Maxon Coreless DC
Rated Input Voltage	V_rated	12.0 V	Nominal DC Bus
Stall / Peak Torque	tau_stall	3.4 N.m (at 12.0V, 1.3A)	At 12.0 V
Continuous Torque Input	tau_cont	1.120 N.m (engineering estima	Estimate; verify manufacturer therma
No-Load Speed	omega_0	30 rpm (at 12.0V)	Unloaded output shaft
Actuator Mass (Weight)	m_act	82.0 g	Includes housing & internal gearhead
Internal Reduction	i_int	353.5 : 1	Integrated gear stage
Envelope Dimensions	W x H x D	28.5 x 46.5 x 34.0 mm	Outer housing envelope



XH430-W350 — Project Reference & Review Notes

2. Mechanical Mounting & Frame Integration
   - Housing Envelope: 28.5 mm x 46.5 mm x 34.0 mm
   - Catalog Mass (unverified): 82.0 g (0.0820 kg)
   - Mounting Pattern: Not verified; obtain manufacturer flange/shaft drawings.

3. Thermal & Duty-Cycle Notes
   - Catalog continuous torque is an input assumption until its manufacturer rating is check
   - The 0.33x stall estimate, where used, is a heuristic rather than a measured thermal rat
   - The linear torque-speed envelope is a screening model, not a measured performance curve

4. Project Reference Index
   - Part ID: XH430-W350 | Source Document: xh430-w350.pdf | Spec Table: Page 1