Securing the Next Version of HTTP

How QUIC and HTTP/3 Compare to HTTP/2

HTTP semantics mapping Stream multiplexing Stream flow control

TLS

Crypto handshake Record layer encryption

TCP

Congestion, flow control Transport handshake

HTTP/3

HTTP semantics mapping

QUIC

Stream multiplexing, flow control Connection congestion, flow control Record layer encryption Transport Handshake

TLS Crypto handshake

UDP

ΙP

HTTP semantics mapping Stream multiplexing Stream flow control

TLS

Crypto handshake Record layer encryption

TCP

Congestion, flow control

Transport handshake

HTTP/3

HTTP semantics mapping

QUIC

Stream multiplexing, flow control Connection congestion, flow control Record layer encryption

Transport Handshake

TLS Crypto handshake

UDP

Random Destination CID (R) Source CID (B)

. . .

CRYPTO frame

TLS ClientHello

- + transport_parameters
- + ...

Handshake Packet

Destination CID (A) Source CID (B)

...

CRYPTO frame

TLS Finished

ACK frame

Initial Packet

Destination CID (B) Source CID (A)

. . .

CRYPTO frame

TLS ServerHello

. . .

ACK frame

Handshake Packet

Destination CID (B) Source CID (A)

CRYPTO frame

TLS EncryptedExtensions

+ transport_parameters

• • •

Random Destination CID (R) Source CID (B)

...

CRYPTO frame

TLS ClientHello

- + transport_parameters
- + ...

Retry Packet

Destination CID (B) Source CID (A)

...

Retry Token (T)

Initial Packet

Random Destination CID (A) Source CID (B)

. . .

Token (T)

CRYPTO frame

. . .

Random Destination CID (R) Source CID (B)

...

CRYPTO frame

TLS ClientHello

- + transport_parameters
- + ...

Handshake Packet

Destination CID (A) Source CID (B)

...

CRYPTO frame

TLS Finished

ACK frame

Initial Packet

Destination CID (B) Source CID (A)

. . .

CRYPTO frame

TLS ServerHello

. . .

ACK frame

Handshake Packet

Destination CID (B) Source CID (A)

CRYPTO frame

TLS EncryptedExtensions

+ transport_parameters

• • •

Packet format invariants

```
Long Header Packet {
  Header Form (1) = 1,
  Version-Specific Bits (7),
  Version (32),
  Destination Connection ID Length (8),
  Destination Connection ID (0..2040),
  Source Connection ID Length (8),
  Source Connection ID (0..2040),
  Version-Specific Data (..),
}
```

```
Short Header Packet {
  Header Form (1) = 0,
  Version-Specific Bits (7),
  Destination Connection ID (..),
  Version-Specific Data (..),
}
```

QUIC Connection IDs

Used in place of 5-tuple to identify a QUIC connection

Variable length, issued by endpoint

Should appear to be random

HTTP semantics mapping Stream multiplexing Stream flow control

TLS

Crypto handshake

Record layer encryption

TCP

Congestion, flow control Transport handshake

HTTP/3

HTTP semantics mapping

QUIC

Stream multiplexing, flow control Connection congestion, flow control Record layer encryption Transport Handshake

TLS Crypto handshake

UDP

Random Destination CID (R) Source CID (B)

. . .

CRYPTO frame

TLS ClientHello

+ transport_parameters

+ ...

Handshake Packet

Destination CID (A) Source CID (B)

. . .

CRYPTO frame

TLS Finished

ACK frame

Initial Packet

Destination CID (B) Source CID (A)

. . .

CRYPTO frame

TLS ServerHello

. . .

ACK frame

Handshake Packet

Destination CID (B) Source CID (A)

CRYPTO frame

TLS EncryptedExtensions

+ transport_parameters

• • •

HTTP semantics mapping Stream multiplexing Stream flow control

TLS

Crypto handshake Record layer encryption

TCP

Congestion, flow control Transport handshake

HTTP/3

HTTP semantics mapping

QUIC

Stream multiplexing, flow control Connection congestion, flow control

Record layer encryption


Transport Handshake

TLS Crypto handshake

UDP

QUICv1 Record Protection

AEAD(K, N, P, A) = C



HTTP semantics mapping Stream multiplexing Stream flow control

TLS

Crypto handshake Record layer encryption

TCP

Congestion, flow control Transport handshake

HTTP/3

HTTP semantics mapping

QUIC

Stream multiplexing, flow control Connection congestion, flow control

Record layer encryption Transport Handshake

TLS Crypto handshake

UDP

Streams, flow control, and other frames

STREAM frames carry application data

Flow control updates sent in MAX_DATA (per connection), MAX_STREAM_DATA (per stream), and MAX_STREAMS frames

Packets acknowledged via ACK frames

PATH_CHALLENGE and PATH_RESPONSE used to validate new paths

Implementation considerations

Flow control

Path validation

CVE-2019-9517 "Internal Data Buffering"

0-RTT Connection Resumption

Combines TLS 1.3 0-RTT resumption handshake with address validation token from QUIC transport

Server sends address validation token in NEW_TOKEN frame on previous connection

Server sends 0-RTT capable NewSessionTicket in TLS handshake on previous connection

Random Destination CID (R) Source CID (B) Token (T)

. . .

CRYPTO frame

TLS ClientHello

- + transport_parameters
- + early_data
- + ...

0-RTT Packet

STREAM frame

• • •

Initial Packet

Destination CID (B) Source CID (A)

. . .

CRYPTO frame

TLS ServerHello

..

ACK frame

Handshake Packet

Destination CID (B) Source CID (A)

CRYPTO frame

TLS EncryptedExtensions

- transport_parameters
- + early_data

. . .

Summary

The HTTP/3 protocol stack has equivalent security as HTTP/2

HTTP/3's use of QUIC improves performance

QUIC improves privacy