

# COMP302: Programming Languages and Paradigms

Prof. Brigitte Pientka (Sec 01)

`bpientka@cs.mcgill.ca`


Francisco Ferreira (Sec 02)

`fferre8@cs.mcgill.ca`


School of Computer Science

McGill University

Week 2-1, Fall 2017



# Functional Tidbit: Evolution of Homer Simpson



“Pattern matching is so powerful and elegant! [...] it’s hard for me to return to languages without pattern-matching capabilities.” (Aliya Hameer)

## Data Types and Pattern Matching – Continued –


## Recap: User-Defined (Non-Recursive Data Types

How can we model a collection of cards?



## Recap: User-Defined (Non-Recursive Data Types

How can we model a collection of cards?



Declare a new type together with its elements

```
1 type suit = Clubs | Spades | Hearts | Diamonds
```

## Recap: How Do We Work with User-Defined Data?

```
1 type suit = Clubs | Spades | Hearts | Diamonds
```

# Recap: How Do We Work with User-Defined Data?

```
1 type suit = Clubs | Spades | Hearts | Diamonds
```

## Pattern Matching

```
1 (* dom : suit*suit -> bool
2    dom(s1,s2) = true
3    iff suit s1 beats or is equal to suit s2
4    relative to the ordering S > H > D > C
5 *)
6
7 let rec dom (s1, s2) = match (s1, s2) with
8   | (Spades, _)      -> true
9   | (Hearts, Diamonds) -> true
10  | (Hearts, Clubs)   -> true
11  | (Diamonds, Clubs) -> true
12  | (s1, s2)          -> s1 = s2
```

# What's in your hand?



# What's in your hand?

Describe the collection of cards in a `hand` inductively.

# What's in your hand?

Describe the collection of cards in a `hand` inductively.

- `Empty` is of type `hand`
- If `c` is a `card` and `h` is of type `hand`, then `Hand(c, h)` is of type `hand`.
- Nothing else is of type `hand`.

# What's in your hand?

Describe the collection of cards in a `hand` inductively.

- `Empty` is of type `hand`
- If `c` is a `card` and `h` is of type `hand`, then `Hand(c, h)` is of type `hand`.
- Nothing else is of type `hand`.

```
1 type hand = Empty | Hand of card * hand
```

# Sample Hands

```
1 let hand0:hand = Empty
2 let hand1:hand = Hand((Ace, Hearts), Empty)
3 let hand2:hand = Hand((Queen, Diamonds), hand1)
4 let hand5:hand = Hand((Ace, Spades),
5                       Hand((Ten, Diamonds),
6                           Hand((Seven, Clubs),
7                               Hand((Queen, Spades),
8                                   Hand((Eight, Clubs), Empty))))))
```

## Task: Extract it!

Write a function `extract: suit -> hand -> hand`

`extract s h` returns a hand containing all cards from `h` of suit `s`.

Demo

## Task: Find it!

Write a function `find` which when given a `rank` and a `hand`, finds the first card in `hand` of the specified `rank` and returns its corresponding `suit`.

## Task: Find it!

Write a function `find` which when given a `rank` and a `hand`, finds the first card in `hand` of the specified `rank` and returns its corresponding `suit`.

⇒ **Problem:** what to do if no such card exists?

# Task: Find it!

Write a function `find` which when given a `rank` and a `hand`, finds the first card in `hand` of the specified `rank` and returns its corresponding `suit`.

⇒ **Problem:** what to do if no such card exists?

Optional Data Type (predefined)

```
1 type 'a option = None | Some of 'a
```



# Task: Find it!

Write a function `find: rank * hand -> suit option`.

Given a rank `r` and a hand `h`, extract `r h`

- finds the first card with rank `r` in `h` and return its corresponding suit `s` as `Some s`.
- returns `None`, if there is no card with rank `r`.

## Demo