

COMP302: Programming Languages and Paradigms

Prof. Brigitte Pientka (Sec 01)

`bpientka@cs.mcgill.ca`


Francisco Ferreira (Sec 02)

`fferre8@cs.mcgill.ca`

School of Computer Science

McGill University

Week 4-1, Fall 2017



Functional Tidbit: Cool Kids!



“Higher-order functions; relatively simple once mastered yet very powerful and they make you look awesome! ”

Jeremie Poisson (TA for COMP 302)

Office Hours: Wed 12:00pm - 2:00pm



“Higher order functions are super cool!”

Eric Zhang (TA for COMP 302)

Office Hours: Wed 2:00pm - 4:00pm

Functions are first-class values!

Functions are first-class values!

- Pass functions as arguments (Continued)
- Return them as results (Today)



Functions are first-class values!

- Pass functions as arguments (Continued)
- Return them as results (Today)



Common Higher-Order Functions (Built-In)

Common Higher-Order Functions (Built-In)


- `List.map: ('a -> 'b) -> 'a list -> 'b list`
- `List.filter: ('a -> bool) -> 'a list -> 'a list`
- `List.fold_right: ('a -> 'b -> 'b) -> 'a list -> 'b -> 'b`
- `List.fold_left: ('a -> 'b -> 'a) -> 'a -> 'b list -> 'a`
- `List.for_all: ('a -> bool) -> 'a list -> bool`
- `List.exists : ('a -> bool) -> 'a list -> bool`

Check the OCaml `List` library for more built-in higher-order functions! They make great practice questions!

Slogan – Revisited

Functions are first-class values!

- Pass functions as arguments (Continued)
- **Return them as results (Today)**



What does it mean to return a function?

Let's go back to the beginning ... from the 1. week

```
1  (* We can also bind variable to functions. *)
2  let area : float -> float = function r -> pi *. r *. r
3
4  (* or more conveniently, we write usually *)
5  let area (r:float) = pi *. r *. r
6
```

- The variable name `area` is bound to the *value* `function r -> pi *. r *. r` which OCaml prints simply as `<fun>`.
- The type of the variable `area` is `float -> float`.

Switching your viewpoint

Write a function `curry` that

- takes as input a function $f:('a * 'b) \rightarrow 'c$
- returns as a result a function $'a \rightarrow 'b \rightarrow 'c$.



Haskell B. Curry

Switching your viewpoint

Write a function `curry` that

- takes as input a function `f:('a * 'b) -> 'c`
- returns as a result a function `'a -> 'b -> 'c`.



Haskell B. Curry

```
1 (* curry : (('a * 'b) -> 'c) -> 'a -> 'b -> 'c *)
2 (* Note : Arrows are right-associative.          *)
3 let curry f = (fun x y -> f (x,y))
```

Switching your viewpoint

Write a function `curry` that

- takes as input a function `f:('a * 'b) -> 'c`
- returns as a result a function `'a -> 'b -> 'c`.



Haskell B. Curry

```
1 (* curry : (('a * 'b) -> 'c) -> 'a -> 'b -> 'c *)
2 (* Note : Arrows are right-associative.          *)
3 let curry f = (fun x y -> f (x,y))
4
5 let curry_version2 f x y = f (x,y)
6
7 let curry_version3 = fun f -> fun x -> fun y -> f (x,y)
```

Switching your viewpoint

Write a function `curry` that

- takes as input a function `f:('a * 'b) -> 'c`
- returns as a result a function `'a -> 'b -> 'c`.




Haskell B. Curry

```
1 (* curry : (('a * 'b) -> 'c) -> 'a -> 'b -> 'c *)
2 (* Note : Arrows are right-associative.          *)
3 let curry f = (fun x y -> f (x,y))
4
5 let curry_version2 f x y = f (x,y)
6
7 let curry_version3 = fun f -> fun x -> fun y -> f (x,y)
```


Let's play!



Bonus: Approximating the Derivative



$f(2) = 3$ gives us a point on the graph.




$f'(2) = 1$ is the slope of the tangent line.


www.mathwarehouse.com

$$f'(x) = \frac{df}{dx} = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon) - f(x)}{\epsilon}$$

Bonus: Approximating the Derivative



$f(2) = 3$ gives us a point on the graph.



$f'(2) = 1$ is the slope of the tangent line.

www.mathwarehouse.com

$$f'(x) = \frac{df}{dx} = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon) - f(x)}{\epsilon}$$

Implement a function `deriv : (float -> float) * float -> float -> float` which

- given a function `f:float -> float` and an epsilon `dx:float`
- returns a function `float -> float` describing the derivative of `f`.

Bonus: Approximating the Derivative

$$f'(x) = \frac{df}{dx} = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon) - f(x)}{\epsilon}$$

Implement a function `deriv : (float -> float) * float -> float -> float` which

- given a function `f:float -> float` and an epsilon `dx:float`
- returns a function `float -> float` describing the derivative of `f`.

Bonus: Approximating the Derivative


$$f'(x) = \frac{df}{dx} = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon) - f(x)}{\epsilon}$$

Implement a function `deriv : (float -> float) * float -> float -> float` which


- given a function `f:float -> float` and an epsilon `dx:float`
- returns a function `float -> float` describing the derivative of `f`.

```
1 let deriv (f, dx) = fun x -> (f (x +. dx) -. f x) /. dx
```

Higher-order functions are super cool!



Higher-order functions are super cool!



Question: Do you know what the functions in the picture mean?

Functional Tidbit: Church and the Lambda-Calculus



- Logician and Mathematician
- June 14, 1903 – August 11, 1995
- Most known for the **Lambda-Calculus**:
 - a simple language consisting of variables, functions (written as $\lambda x.t$) and function application
 - we can define all computable functions in the Lambda-Calculus!

Church Encoding of Booleans:

$$\mathbf{T} = \lambda x.\lambda y.x$$

$$\mathbf{F} = \lambda x.\lambda y.y$$