



✓ **Congratulations! You passed!**

TO PASS 80% or higher

Keep Learning

GRADE  
100%

## Test your knowledge on code chunks

TOTAL POINTS 3

1. Fill in the blank: A delimiter is a character that marks the beginning and end of \_\_\_\_.

1 / 1 point

- ☒ a data item
- ☐ a command line
- ☐ an .rmd file
- ☐ an HTML report

✓ **Correct**

A delimiter is a character that marks the beginning and end of a data item. It can mark a single line of code, or a whole section of code in an .rmd file.

2. A data analyst has to create a monthly report for their stakeholders. What can they create to help them save time generating these reports?

1 / 1 point

- ☐ HTML report
- ☐ .rmd file
- ☐ R notebook
- ☒ Template

✓ **Correct**

Creating a template for your reports allows you to run one line of code to update your data without having to recreate the report from scratch. Templates can also help you customize the appearance of your final report.

3. A data analyst wants to mark the beginning of their code chunk. What delimiter should they type in their .rmd file?

1 / 1 point

- ☐ `+++{ x }`
- ☒ ````${ x }`
- ☐ `==={ x }`
- ☐ `***{ x }`

✓ **Correct**

Three backticks followed by the letter *r* in braces (````${ x }`) indicates the beginning of a code chunk in an .rmd file.