



**! Try again once you are ready**

TO PASS 80% or higher

Try again

GRADE  
70%

## Custom Layers

LATEST SUBMISSION GRADE

70%

1. Lambda layer allows to execute an arbitrary function only within a Sequential API model.

1 / 1 point

- ☐ True
- ☒ False

✓ Correct  
Correct!

2. Which one of the following is the correct syntax for mapping an increment of 2 to the value of "x" using a Lambda layer? (tf = Tensorflow)

0 / 1 point

- ☐ tf.keras.layers.Lambda(lambda x: tf.math.add(x, 2.0))
- ☐ tf.keras.Lambda(x: tf.math.add(x, 2.0))
- ☐ tf.keras.layers(lambda x: tf.math.add(x, 2.0))
- ☒ tf.keras.layers.Lambda(x: tf.math.add(x, 2.0))

**! Incorrect**  
Incorrect! Lambda function needs to be passed as argument to the lambda layer.

3. One drawback of Lambda layers is that you cannot call a custom built function from within them.

1 / 1 point

- ☐ True
- ☒ False

✓ Correct  
Correct!

4. A Layer is defined by having "States" and "Computation". Consider the following code and check all that are true:

0.5 / 1 point

```
class SimpleDense(Layer):  
  
    def __init__(self, units=32):  
        super(SimpleDense, self).__init__()  
        self.units = units  
  
    def build(self, input_shape):  
        w_init = tf.random_normal_initializer()  
        self.w = tf.Variable(name="kernel",  
                             initial_value=w_init(shape=(input_shape[-1], self.units),  
                                                    dtype='float32'), trainable=True)  
  
        b_init = tf.zeros_initializer()  
        self.b = tf.Variable(name="bias",  
                             initial_value=b_init(shape=(self.units,), dtype='float32'),  
                             trainable=False)  
  
    def call(self, inputs):  
        return tf.matmul(inputs, self.w) + self.b
```

- ☒ You use def build(self, input\_shape): to create the state of the layers and specify local input states.

✓ Correct  
Correct!

- ☒ After training, this class will return a  $w \cdot X + b$  computation, where  $X$  is the input,  $w$  is the weight/kernel tensor with trained values, and  $b$  is the bias tensor with trained values.

**! This should not be selected**  
Incorrect! bias  $b$  will not be trained, instead maintain its initial value, as the *trainable* parameter for it is set to False within the build function.

- ☐ In `def __init__(self, units=32)`: you use the `super` keyword to initialize all of the custom layer attributes
- ☒ `def call(self, inputs)`: performs the computation and is called when the Class is instantiated.

**! This should not be selected**  
Incorrect! This function is called during training.

5. Consider the following code snippet.

1 / 1 point

```
class SimpleDense(Layer):

    def __init__(self, units=32):
        super(SimpleDense, self).__init__()
        self.units = units

    def build(self, input_shape):
        w_init = tf.random_normal_initializer()
        self.w = tf.Variable(name="kernel",
                             initial_value=w_init(shape=(input_shape[-1], self.units),
                                                    dtype='float32'), trainable=True)

        b_init = tf.zeros_initializer()
        self.b = tf.Variable(name="bias",
                             initial_value=b_init(shape=(self.units,), dtype='float32'),
                             trainable=False)

    def call(self, inputs):
        return tf.matmul(inputs, self.w) + self.b
```

What are the function modifications that are needed for passing an activation function to this custom layer implementation?

- ☐ `def build(self, input_shape):`
- ```

    .
    .

    self.activation = tf.keras.activations.get(activation)

    def call(self, inputs):
        return self.activation(tf.matmul(inputs, self.w) + self.b)

```
- ☐ `def build(self, units=32, activation=None):`
- ```

    .
    .

    self.activation = activation

    def call(self, inputs):
        return self.activation(tf.matmul(inputs, self.w) + self.b)

```
- ☐ `def __init__(self, units=32):`
- ```

    .
    .

    self.activation = tf.keras.activations.get(activation)

    def call(self, inputs):
        return self.activation(tf.matmul(inputs, self.w) + self.b)

```
- ☒ `def __init__(self, units=32, activation=None):`
- ```

    .
    .

    self.activation = tf.keras.activations.get(activation)

    def call(self, inputs):
        return self.activation(tf.matmul(inputs, self.w) + self.b)

```

✓ Correct  
Correct!