



✓ **Congratulations! You passed!**

TO PASS 75% or higher

Keep Learning

GRADE
75%

Validation

TOTAL POINTS 4

1. Suppose we are given a huge dataset. We did a KFold validation once and noticed that scores on each fold are roughly the same. Which validation type is most practical to use?

1 / 1 point

- ☐ We should keep on using KFold scheme as the data is homogeneous and KFold is the most computationally efficient scheme.
- ☒ We can use a simple holdout validation scheme because the data is homogeneous.
- ☐ Leave-one-out because the data is not homogeneous.

✓ **Correct**

Correct! If scores on different folds are similar, we indeed can use holdout split. In fact, this is often the case.

2. Suppose we are given a medium-sized dataset and we did a KFold validation once. We noticed that scores on each fold differ noticeably. Which validation type is the most practical to use?

1 / 1 point

- ☒ KFold
- ☐ LOO
- ☐ Holdout

✓ **Correct**

Correct. This is the most frequent way to deal with this kind of situations. Also, scores deviation in KFold will help you to select statistically significant change in scores while tuning a model.

3. The features we generate depend on the train-test data splitting method. Is this true?

1 / 1 point

- ☐ False
- ☒ True

✓ **Correct**

Correct. For an explanation check out the third video in the module about choosing a train/test split.

4. What of these can indicate an expected leaderboard shuffle in a competition?

0 / 1 point

- ☒ Little amount of training or/and testing data

✓ **Correct**

In this case randomness can shuffle scores on the private leaderboard

- ☐ Most of the competitors have very similar scores

- ☒ Different public/private data or target distributions

✓ **Correct**

In this case competitors can receive quite unexpected scores on private LB.

You didn't select all the correct answers