

! Try again once you are ready  
TO PASS 80% or higher

Try again

GRADE  
63.33%


## Custom Models

LATEST SUBMISSION GRADE

63.33%

1. Following is an example of a deep and wide network structure.

0 / 1 point



- ☐ False
- ☒ True



Incorrect

Incorrect! You can see both input paths go through deep learning with multiple layers of neurons.

2. Consider the following code and check all that are true:

0.75 / 1 point

```

class MyModel(Model):
    def __init__(self, units=30, activation='relu', **kwargs):
        super().__init__(**kwargs)
        self.hidden1 = Dense(units, activation=activation)
        self.hidden2 = Dense(units, activation=activation)
        self.main_output = Dense(1)
        self.aux_output = Dense(1)

    def call(self, inputs):
        input_A, input_B = inputs
        hidden1 = self.hidden1(input_B)
        hidden2 = self.hidden2(hidden1)
        concat = concatenate([input_A, hidden2])
        main_output = self.main_output(concat)
        aux_output = self.aux_output(hidden2)
        return main_output, aux_output
  
```

- ☒ The *init* function initializes the *MyModel* Class objects, as well as the attributes that are inherited from the *Model* Class.



Correct  
Correct!

- ☐ The output layers cannot give more than 1 result each.
- ☐ The *concat* should be defined within the *init* function instead of the *call* function as it is also a hidden layer.
- ☐ The code is incomplete in the sense that you can only initialize and construct your model, you cannot perform training or inference.

You didn't select all the correct answers

3. You have learned that Sequential and Functional APIs have their limitations.

0.667 / 1 point

How can you build dynamic networks where the architecture changes on the fly, or networks where recursion is used? Check all that are true:

☒ Using Functional API

✓ Correct

Correct! With Functional APIs it is possible to build these networks, but it would require a lot of coding.

☒ Using model subclassing

✓ Correct

Correct! With model subclassing it is relatively easier to build these complex networks.

☒ Using Sequential API

! This should not be selected

Incorrect! With Sequential APIs it is not possible to build these type of networks.

4. Which one of the following is a false statement regarding model subclassing?

1 / 1 point



- ☒ You cannot introduce a branch structure in the architecture when doing model subclassing.
- ☐ You can make use of Functional and Sequential APIs when writing code for model subclassing.
- ☐ You can have modular architectures
- ☐ Instead of tweaking the entire architecture, you can have different modules and make changes in them as required, as opposed to entirely rewriting the structure.


✓ Correct

Correct! You can have branches within your network

5. Consider the following two images:

0.75 / 1 point





Check all that are true:

- ☒ Each Residual block has two hidden layers and one add layer in it.

✓ **Correct**  
Correct!

- ☐ You make a loop of *Residual Type 2* blocks because you want to reduce the depth of the network (making it less complex of an architecture)
- ☐ You loop *Residual Type 2* (*Dense* layers) because you cannot make a loop of *Conv2D* layers (*Residual Type 1*)
- ☒ When you make a loop of *Residual Type 2* blocks, each block could have the same weights.

✓ **Correct**  
Correct!

You didn't select all the correct answers