ECE260: Fundamentals of Computer Engineering

Supporting Nested Procedures

James Moscola
Dept. of Engineering & Computer Science
York College of Pennsylvania

Memory Layout [in MARS Simulator]

- ***Reserved*** – used by operating system, not for you
- ***Text*** – executable program instructions (i.e. your code)
  - Create with a *.text* directive
- ***Data*** – global and static variables
  - Create with a .data directive
- ***Heap*** – dynamically allocated memory
  - Request this from the operating system
- ***Stack*** – for storing local variables and stack frames
  - Grows towards the heap



MIPS Registers (now with more info!)

- MIPS architecture has a 32 × 32-bit register file (e.g. it has 32 32-bit registers)

Register Number	Register Name	Use	
0	$zero	Constant value 0	
1	$at	Assembler temporary	**Not for you!**
2 - 3	$v0 - $v1	Procedure return values	**Callee puts return value here**
4 - 7	$a0 - $a3	Procedure arguments	**Caller puts arguments here**
8 - 15	$t0 - $t7	Temporary values	**Callee may overwrite these**
16 - 23	$s0 - $s7	Saved temporary values	**Must be saved by callee if used**
24 - 25	$t8 - $t9	More temporary values	**Callee may overwrite these**
26 - 27	$k0 - $k1	Reserved for OS	**Also, not for you!**
28	$gp	Global pointer	**Easy access to constants/globals**
29	$sp	Stack pointer	**Top of stack**
30	$fp	Frame pointer	**Points to local variables on stack**
31	$ra	Return Address	**Where to go when returning from procedure**

What is Preserved Across a Procedure Call?

- **MIPS conventions dictate that a CALLER can expect the following behavior when calling a procedure**
  - Some registers and data are expected to be “preserved”
  - Other registers and data are NOT expected to be “preserved”
- **Registers and data that are “preserved” are expected by the CALLER to contain the same values both before and after a procedure call (i.e. they should saved/restored by a CALLEE)**

Preserved	Not Preserved
Saved registers: $s0 - $s7	Temporary registers: $t0 - $t9
Stack pointer register: $sp	Argument registers: $a0 - $a3
Return address register: $ra	Return value registers: $v0 - $v1
Stack above stack pointer	Stack below stack pointer

Non-Leaf Procedures

- A ***leaf procedure*** is a procedure that does NOT call another procedure
  - CALLEE (PROC_A) must save/restore and $sX registers that it uses



- A ***non-leaf procedure*** is a procedure that calls other procedures
  - **All** CALLEEs must save/restore $sX registers that they use (PROC_A, PROC_B, …)
  - Each CALLER needs to save/restore info on the stack prior to transferring control to next CALLEE
    - CALLER must save its return address
      - When the CALLER issues the **jal** instruction to call CALLEE the $ra register is overwritten
    - Any arguments ($aX registers) and temporaries $(tX registers) needed after the CALLEE returns
      - CALLER may reassign $aX registers to pass arguments to CALLEE, so save contents
      - CALLEE may become a CALLER itself and overwrite $aX registers!
      - No guarantee that a CALLEE will preserve values in $tX registers, so save contents



Non-Leaf Procedure – A Recursive Example

- Example C code
  - This function is **both** a CALLER and a CALLEE

```
int fact (int n) {
  if (n < 1)
    return 1;
  else
    return n * fact(n - 1);
}
```

BASE **Case – stops recursion**

RECURSIVE **Case – function calls itself**

- Assume the following:
  - Parameter n is passed in register $a0
  - Factorial function (fact) is called using a **jal** instruction that sets the $ra register
  - Return value is placed in register $v0 before the fact function returns

Non-Leaf Procedure – A Recursive Example (continued)

```
FACT:
    addi $sp, $sp, -8       # adjust $sp to make room on stack to save contents of 2 registers
    sw   $ra, 4($sp)        # As CALLER: save return address onto the stack ... may need restoring later
    sw   $a0, 0($sp)        # As CALLER: save argument onto the stack since $a0 may be used to call fact

    slti $t0, $a0, 1        # test for n < 1 ... $t0 is set to 1 if true, 0 otherwise
    beq  $t0, $zero, ELSE   # branch to ELSE if !(n < 1)

    addi $v0, $zero, 1      # otherwise, set return value to 1
    addi $sp, $sp, 8        # pop stack, no need to restore $a0 or $ra since never overwritten
    jr   $ra                # return from base case with a return value of 1
ELSE:
    addi $a0, $a0, -1       # decrement n into $a0 to set argument for recursive call
    jal  FACT               # recursive call, writes $ra – good thing we backed it up on the stack!
    ###  #### recursing, will eventually return here with a return value in $v0
    lw   $a0, 0($sp)        # As CALLER: restore original value for n when recursion returns
    lw   $ra, 4($sp)        # As CALLER: restore original value for $ra when recursion returns
    addi $sp, $sp, 8        # pop stack now that values have been restored to registers

    mul  $v0, $a0, $v0      # multiply n by result of last recursive call – n * fact(n – 1)
    jr   $ra                # previous mul instruction put result in $v0, now return it
```

BASE Case

RECURSIVE Case

Storing Local Data on the Stack

- A procedure may need memory space for local variables
  - May have locally defined array or simply too much data to store in registers
- If necessary, memory space for local variables is allocated on the stack
  - If not much local data, registers may be sufficient
  - **NOT** stored in .data segment of memory
  - Data is conserved on stack if procedure calls another procedure
  - Data is removed from stack when procedure returns
- ***Procedure frame*** (a.k.a. ***activation record***, a.k.a. ***stack frame***)
  - Segment of the stack containing a procedures saved registers and local variables

Storing Local Data on the Stack

Frame pointer ($fp) points to first word of the frame and doesn't move during a procedure

Stack pointer ($sp) points to the top of the stack and may move as stack grows/shrinks in a procedure



Stack BEFORE calling procedure PROC_X

Stack WHILE in procedure PROC_X

Stack AFTER in procedure PROC_X returns

Passing More than Four Arguments

- MIPS provides four registers, $a0 - $a3 for passing arguments to a procedure
- If a procedure expects more than four arguments they must be passed on the stack
  - CALLER places first four arguments in registers $a0 - $a3
  - CALLER places arguments 5 and up on stack immediately before executing **jal** instruction
    - Arguments should be LAST thing placed in CALLER's stack frame – easily accessible by CALLEE
  - Arguments placed on stack are placed in **reverse** order
- CALLEE can access arguments 5 and up by using the ***frame pointer***

```
add $t1, $zero, $a0        # access 1st argument
add $t2, $zero, $a1        # access 2nd argument

lw  $t5, 4($fp)            # access 5th argument
lw  $t6, 8($fp)            # access 6th argument
lw  $t7, 12($fp)           # access 7th argument
```

Stack Frame Overview

- The ***stack frame*** contains storage for the CALLER's data that it wants preserved after the invocation of CALLEEs
- The CALLEE uses the stack for the following:
  1. Accessing the arguments that the CALLER passes to it (specifically, the 5th and greater)
  2. "Preserving" non-temporary registers that it wishes to modify
  3. Storing/accessing its own local variables
- The ***frame pointer*** keeps track of the boundary between stack frames



Stack Frame Overview

- The ***stack frame*** contains storage for the CALLER's data that it wants preserved after the invocation of CALLEEs
- The CALLEE uses the stack for the following:
  1. Accessing the arguments that the CALLER passes to it (specifically, the 5th and greater)
  2. "Preserving" non-temporary registers that it wishes to modify
  3. Storing/accessing its own local variables
- The ***frame pointer*** keeps track of the boundary between stack frames



Caller Conventions

- **The CALLER will:**
  - Save all temp registers that it wants to survive subsequent procedure calls into its stack frame ($t0-$t9, $a0-$a3, and $v0-$v1)
  - Pass the first 4 arguments to a CALLEE in registers $a0-$a3 – save subsequent arguments on stack, in ***reverse*** order
  - Call CALLEE procedure, using a **jal** instruction which places the return address in register $ra
    - If this CALLER is also a CALLEE, you must save $ra before using **jal**
  - Access CALLEE procedure's return values in registers $v0-$v1 after CALLEE returns
  - Restore all temp registers that were saved prior to calling CALLEE
    - Be sure to grab return value from CALLEE prior to restoring any saved $v0-$v1 from stack or you will overwrite the CALLEE's return value
- **IMPORTANT NOTE: A CALLER MAY ALSO BE ALL CALLEE**

Callee Conventions

- **If needed the CALLEE will:**
  1) Allocate a stack frame with space for saved registers, local variables, and spilled args
  2) Save any "preserved" registers that it will use/overwrite: $ra, $sp, $fp, $gp, $s0-$s7
  3) If CALLEE has local variables -or- needs access to args on the stack, save CALLER's frame pointer and set $fp to 1st entry of CALLEE's stack
  4) EXECUTE procedure
  5) Place return values in $v0-$v1
  6) Restore saved registers including those that were preserved for CALLER
  7) Restore $sp to its original value
  8) Return to CALLER with jr $ra
- **IMPORTANT NOTE: A CALLEE MAY ALSO BE ALL CALLER**