

Final Year Project

Effects of ISI on Equal Gain Combining and Maximal-Ratio Combining with Sub-Optimal Design

Yann Donnelly
University College Cork

7th February 2014

INTRODUCTION

INTRODUCTION

BACKGROUND

- Communications Overview

- Detection Basics

- Aims of Project

RESULTS

- Achievements

- Results


OBSTACLES

- Problems Encountered

FUTURE WORK


- Future Work

A TYPICAL COMMUNICATIONS SYSTEM




DETECTION BASICS

Likelihood of receiving a signal




DETECTION BASICS

Received signal response




DETECTION BASICS

Received signal response with timing error




DETECTION BASICS

Likelihood of receiving a signal



DETECTION BASICS

Likelihood of receiving a signal with timing error



AIMS OF PROJECT

To determine the effects of Tikhonov-distributed timing offset on receiver performance, and develop a means of improving performance through redefining the decision region boundaries.

ACHIEVEMENTS

ACHIEVEMENTS

- ▶ Developed models of 4-PAM communications systems in Mathematica

ACHIEVEMENTS

- ▶ Developed models of 4-PAM communications systems in Mathematica
- ▶ Examined performance in non-fading (line-of-sight) environment

ACHIEVEMENTS

- ▶ Developed models of 4-PAM communications systems in Mathematica
- ▶ Examined performance in non-fading (line-of-sight) environment
- ▶ Examined performance in Rayleigh fading environment with EGC

ACHIEVEMENTS


- ▶ Developed models of 4-PAM communications systems in Mathematica
- ▶ Examined performance in non-fading (line-of-sight) environment
- ▶ Examined performance in Rayleigh fading environment with EGC
- ▶ Examined performance in Rayleigh fading environment with MRC

ACHIEVEMENTS

- ▶ Developed models of 4-PAM communications systems in Mathematica
- ▶ Examined performance in non-fading (line-of-sight) environment
- ▶ Examined performance in Rayleigh fading environment with EGC
- ▶ Examined performance in Rayleigh fading environment with MRC
- ▶ Positive results:
 - ▶ Lower optimum decision region boundaries in the presence of timing error
 - ▶ Performance increase from redesigning detector to take this into account

RESULTS

- ▶ EGC: Improvements of 20-33%
- ▶ MRC: Improvements of 7-20%



PROBLEMS ENCOUNTERED

PROBLEMS ENCOUNTERED

- ▶ Simulation speed: 6 ways to do anything, only one is fast
 - ▶ Solution: Read up on Mathematica functions, testing and timing each method
 - ▶ Solution: Reduce how often you have to do something
 - ▶ Solution: Functions with memory
 - ▶ Solution: Parallel computing

PROBLEMS ENCOUNTERED

- ▶ Simulation speed: 6 ways to do anything, only one is fast
 - ▶ Solution: Read up on Mathematica functions, testing and timing each method
 - ▶ Solution: Reduce how often you have to do something
 - ▶ Solution: Functions with memory
 - ▶ Solution: Parallel computing
- ▶ Running simulations across multiple headless machines
 - ▶ Solution: Remote access

PROBLEMS ENCOUNTERED

- ▶ Simulation speed: 6 ways to do anything, only one is fast
 - ▶ Solution: Read up on Mathematica functions, testing and timing each method
 - ▶ Solution: Reduce how often you have to do something
 - ▶ Solution: Functions with memory
 - ▶ Solution: Parallel computing
- ▶ Running simulations across multiple headless machines
 - ▶ Solution: Remote access
- ▶ Running simulations across multiple machines that can be switched off at any point
 - ▶ Solution: Output regularly
 - ▶ Solution: Make sure outputs are descriptive
 - ▶ Solution: Easily reconfigurable code

FUTURE WORK

FUTURE WORK

- Describe the effects of timing error offset analytically

FUTURE WORK

- ▶ Describe the effects of timing error offset analytically
- ▶ Determine the Gram-Charlier PDF approximation

FUTURE WORK

- ▶ Describe the effects of timing error offset analytically
- ▶ Determine the Gram-Charlier PDF approximation
- ▶ Summarize findings in a publication