AnchorMTM: Spatially Anchored Merge Tree Maps with Topology–Position Tradeoffs

Lele Wang[1,2*] Yu Dong[1,*] Yuxiang Meng[1,2] Guan Li[1,2] Zhe Wang[1,2] Guihua Shan[1,2,3] Jun Liu[1,2†]




Figure 1: Storms temporal overview ($\varepsilon = 5\%$): 744 hourly ERA5 sea-level-pressure fields, December 1999. Each frame's merge tree becomes a one-dimensional profile, rotated and stacked along time. The vertical axis is one fixed spatial direction a^* (arrow, west to east), so the rising track is a storm moving east, from the open Atlantic to Scandinavia; the snapshots identify the matched extremum, and blue outlines show its leaf-arc support. The map keeps every nesting and merge level within the 5% budget.

Abstract

Merge tree maps summarize a time-varying scalar field in one static image: each time step becomes a one-dimensional profile of its merge tree, and the profiles are stacked along time, so that nested features appear as nested bands. The vertical axis of these maps encodes tree order or relative distance rather than location, so an analyst sees how features nest but not where they are or how they move. We present AnchorMTM, a merge tree map whose vertical axis is one fixed spatial direction. Anchoring the axis exposes a conflict: a profile that shows the tree exactly keeps every subtree contiguous, whereas the locations of sibling subtrees may interleave along the direction. We derive lower bounds on the displacement this conflict forces, for exact topology, for features of finite width and for a bounded change of merge levels. The bounds depend only on the trees and the feature locations, so they apply to every merge tree map and are known before any layout is computed. AnchorMTM then builds the map under a single merge budget that limits how far the displayed merge levels may change. On five planar and two volumetric sequences, the bounds show that most of the positional error of existing merge tree maps is not forced by the tree. AnchorMTM attains the exact-topology bound for finite widths on most planar frames and, with the tree kept exactly, draws features much closer to their locations, while existing maps preserve neighborhoods better. Where conflicting subtrees merge at similar levels, a small budget removes most of the remaining displacement. The bounds make the positional price of a spatial axis measurable before a map is drawn.

Index Terms: Time-varying scalar fields, merge tree maps, topology-based visualization, spatial anchoring, lower bounds, constrained layout.

1 Introduction

Time-varying scalar fields record how quantities such as sea-level pressure, aerosol concentration or vorticity evolve over a spatial domain. Analysts study them through features, such as low-pressure systems, pollution episodes or shed vortices, and ask three questions about each: how it relates to the others, where it is, and how it moves. Animation keeps every time step in its spatial context but makes distant times hard to compare [45, 51]. Static overviews therefore assign one display axis to time and compress space into the other, so that a whole sequence fits into one image [2]. What that second axis means decides which of the three questions the overview can answer. The Hovmöller diagram of atmospheric science keeps a physical coordinate such as longitude and shows an eastward-moving system as a slanted streak [25], but it averages the field over the remaining coordinates, so neighboring features blend and their hierarchy disappears.

*Affiliations: [1] Advanced Interactive Technology and Application Laboratory, Computer Network Information Center, Chinese Academy of Sciences, Beijing, China; [2] University of Chinese Academy of Sciences, Beijing, China; [3] Hangzhou Institute for Advanced Study, UCAS, Hangzhou, China. E-mails: lelewang@cnic.cn; dongyu@cnic.cn; yxmeng@cnic.cn; liguan@sccas.cn; wangzhe@sccas.cn; sgh@sccas.cn; liujun@sccas.cn. Lele Wang and Yu Dong contributed equally to this work. Jun Liu is the corresponding author.

†Corresponding author. E-mail: liujun@sccas.cn.

Merge tree maps answer the first question. A merge tree records how sublevel sets connect as the threshold rises: its leaves are the extrema, and its internal nodes are the levels at which regions merge [13, 21]. Temporal merge tree maps (TMTM) draw the tree of each time step as a one-dimensional profile whose minima are the extrema and whose barriers are the merge levels, and they stack the profiles into one image [30]. Spatiotemporal merge tree maps (ST-MTM) additionally arrange the features by their pairwise distances and temporal coherence [10]. In both, the vertical axis follows the tree, temporal alignment or relative distance; neither fixes an origin or a direction in space. A storm that crosses the North Atlantic within a few days can therefore stay at the same height of the map, and the reader sees how it connects to neighboring lows but not where it is or which way it moves.

We give this axis a spatial meaning. Fixing one direction a^* in the domain assigns every extremum a reference position, the projection of its location onto a^*, and a map whose axis encodes location should draw each extremum at its reference (Fig. 1). The obstacle is the tree itself. A profile shows the tree exactly only if every subtree occupies one contiguous block of leaves, but the references of two sibling subtrees may interleave (Fig. 2d). No exact profile can then place every feature at its reference, whatever algorithm draws it. This conflict raises three questions: how much displacement the tree forces, where in the tree this displacement arises, and how much merge-level fidelity must be given up to remove it. Without answers, the positional error of a map cannot be attributed to the data or to its layout, and an analyst cannot judge whether a spatial axis is worth its cost.

We answer these questions with bounds and turn the answers into a construction. Three lower bounds, for exact topology, for features of finite width and for a bounded merge error, depend only on the trees, the references and the widths, so the positional price of the axis is known before any layout is computed and applies to every map that keeps the tree. AnchorMTM then computes the map directly from the field sequence and one merge budget ε. It searches leaf orders that the budget admits, using a closed-form test for the smallest merge error an order can show, places the extrema as close to their references as the chosen order allows, and reconstructs the profiles. With $\varepsilon = 0$, the map shows every tree exactly; with $\varepsilon > 0$, it releases the conflicts that a small change of merge levels can resolve and records the merge error each frame actually spends.

Our contributions are as follows.

- We formulate spatially anchored merge tree maps and derive three layout-independent lower bounds on the displacement that keeping the tree forces, for exact topology, finite widths and bounded merge error. The bounds locate the conflict in the tree and measure any merge tree map, including existing ones.
- We present AnchorMTM, which builds the leaf order and extremum positions of every frame from the projected locations, so that the height of a band reads as location and its drift as motion along a^*, while the profile keeps the nesting and merge levels of the tree. A merge budget ε, enforced through optimal merge barriers and checked on every rendered frame, controls how much merge-level fidelity may be traded for position.
- On five planar and two volumetric sequences, we show that the bounds are attained on controlled trees and on most real frames, that most of the order error of existing maps is not forced by the tree, and how a budget reshapes the displacement of individual frames.

2 Related Work

2.1 Linearizing Space for Temporal Overviews

Animation preserves the spatial context of each time step, whereas static overviews let viewers compare distant times directly; which




Figure 2: Mapping strategies on a common 35-sample field. (a) Domain traversal keeps samples; (b) a 22-sample feature summary keeps selected structures; (c) a topology-based profile keeps the hierarchy, but its axis has no spatial meaning. (d) AnchorMTM keeps the hierarchy and gives every extremum a target along one direction a^*; here the targets interleave the subtree blocks $\{A,B\}$ and $\{C,D\}$, the conflict that Sections 4 and 5 quantify and resolve.

serves better depends on the task [45, 51]. Bach et al. describe both, and the operations between them, as transformations of a space–time cube [2]. A static overview must linearize space, and Fig. 2 contrasts three ways to do so. *Domain-based* linearizations traverse the samples: Hovmöller diagrams keep one physical coordinate and average over the others [25], while geographic orderings, dense pixel displays and space-filling curves visit the whole domain [9, 20, 44], and volume lines and data-driven curves extend such traversals to volumes [57, 64]. *Feature-based* summaries order selected entities: one-dimensional projections, MotionRugs, stable visual summaries and MoReVis rank moving objects by position or stability [6, 18, 52, 60]. Every linearization distorts some spatial relations [1, 39]. These overviews keep a spatial coordinate but no feature hierarchy; AnchorMTM keeps the merge tree and makes explicit what a spatial coordinate then costs.

2.2 Topology of Time-Varying Scalar Fields

Merge trees and contour trees summarize how level sets connect, and persistence-based simplification controls their size [13, 21, 50]. Features are tracked over time by region overlap or attribute similarity [46, 47] and shown as tracking graphs and nested tracking graphs [35, 36, 58]. Time-varying merge trees have been computed and compared with Wasserstein and geometry-aware interleaving distances [40, 42, 61, 63], and such pipelines follow tropical cyclones and atmospheric rivers [31, 62]. The merge error we budget is a labelled cophenetic discrepancy that equals the labelled interleaving distance [19, 37, 38] and relates to distances between ordered merge trees [5]. Tracking graphs show how features appear, split and merge, but not where they are; merge tree maps additionally show the values and nesting of every time step, and AnchorMTM adds their location.

2.3 Drawing Hierarchies along One Axis

Topological landscapes draw a merge tree as a terrain or as a one-dimensional profile whose minima are the extrema and whose barriers are the merge levels [41, 55]; geometry-preserving and temporally coherent variants exist [4, 23], and contour trees have been drawn in the plane and in joint layouts [22, 34]. Temporal treemaps lay out evolving hierarchies along time [29]. TMTM aligns the




Figure 3: An augmented merge tree and its profile. Extrema and the regular samples of their leaf arcs fill each leaf interval; the gaps between leaves are filled from the paths to their lowest common ancestor (grey), so the largest value between two extrema shows their merge level. These gap fillings are what a relaxed order changes: AnchorMTM raises or lowers each gap to an optimal barrier (Proposition 4) instead of the original LCA level.

profiles of successive merge trees into one static map [30], and ST-MTM adds relative spatial distances and temporal stability [10]; their axes encode tree traversal or relative distance. Storyline layouts face a related problem for groups of entities and balance crossings and wiggles against group contiguity [33, 49].

The conflict we study arises whenever a hierarchy must respect an external order. Optimal leaf ordering selects a tree-consistent order of a dendrogram that keeps similar leaves adjacent [3, 14], and tree reordering seeks the tree-consistent permutation closest to a target order [7]. Spatially ordered treemaps and data–spatial grid maps trade hierarchy or data layout against geographic position [53, 59], geophylogenies connect leaf orders to map locations [27], and tanglegram layouts minimize crossings or displacement between two trees [17, 26]. Separation constraints keep laid-out objects disjoint [12, 32], minimax ultrametric fitting is closely related to our optimal barriers [16], and merge distortion and topology-preserving projections measure how much hierarchy a mapping retains [11,15]. These methods optimize crossings, sums or stress for a given instance. We instead bound, in closed form for points, the worst displacement that every tree-consistent layout must accept, together with the merge error that removes it.

3 Problem Formulation

3.1 Merge Trees, Profiles, and Feature Identity

For a sampled field f_t, the merge tree T_t records sublevel components created at minima and joined at saddles; negating the field handles maxima [50]. Extraction and persistence simplification precede layout. A leaf i has extremum location p_i^t and support S_i^t, comprising the samples on its leaf arc. Augmented internal arcs retain samples for filling the profile. Write $h_t(v)$ for a node's scalar level and $\mathscr{D}_t(v)$ for its descendant leaves. The fixed-label merge matrix is

$$V_{ij}^t = h_t(\mathrm{lca}(i,j)), \quad i \neq j; \qquad V_{ii}^t = f_t(p_i^t). \tag{1}$$

Equal-level merges form one multifurcation. A one-dimensional profile ψ_t places the extrema in leaf order π_t; the largest profile value between anchors i, j gives their displayed merge level $V_{ij}^{\psi_t}$. We call a profile *exact* if every displayed merge level equals that of the tree; this requires the leaves of every subtree to form one contiguous block.

On a fixed grid, one-to-one Hungarian matching maximizes $|S_i^{t-1} \cap S_j^t|$ and discards zero-overlap pairs [10]; a matched leaf inherits its track identity, and $\mu_t(i)$ denotes its predecessor. These links supply the temporal targets and the motion samples below, and the same matching is reused for every budget (Supplementary Fig. S1).

3.2 Fixed Spatial Reference

The default direction maximizes squared matched-extremum motion:

$$a^* \in \arg\max_{\|a\|=1} a^\top \Big(\sum_{t,i} \Delta p_i^t (\Delta p_i^t)^\top\Big) a, \tag{2}$$

where $\Delta p_i^t = p_i^t - p_{\mu_t(i)}^{t-1}$ over valid links. Its sign makes total projected motion nonnegative; the longest domain axis handles zero motion energy. An analyst may supply a physical direction instead. For nearly zero signed motion, the largest-magnitude direction component is made positive; repeated leading eigenvalues can be resolved using a chosen physical axis. This separates reference estimation from the layout search: a budget changes the admissible map, while the coordinate being approximated stays fixed. Projected domain corners define one origin o and extent L, giving

$$q_i^t = \langle a^*, p_i^t \rangle - o \in [0, L]. \tag{3}$$

Direction, origin and extent remain fixed across frames and budgets. Relative geometry uses support-centroid distances d_{ij}^t; the targets q_i^t use extremum locations. Thus support growth can change relative-distance terms without moving a feature's spatial target.

3.3 A Unified Layout Formulation

Each leaf occupies an interval of width $W_i = s m_i$ and center z_i, where m_i is its support measure and s is fixed. The layout set $\mathscr{L}(\pi; W)$ places these intervals in order π inside $[0, L]$, with gap at least g and anchor slack $|x_i - z_i| \leq \rho W_i/2$. Two order costs distinguish point ordering from packing:

$$\begin{aligned} \mathrm{NROE}(\pi) &= \frac{\max_{j \leq k} [q_{\pi(j)} - q_{\pi(k)}]^+}{2L}, \\ \tau(\pi) &= \min_{(x,z) \in \mathscr{L}(\pi;W)} \|x - q\|_\infty. \end{aligned} \tag{4}$$

The normalized reference-order error NROE is the smallest worst displacement, relative to the axis length, of point anchors kept in order π; we call it the *order error* of π. The fixed-order cost τ adds the intervals; it is the optimum of a minimax linear program and has a closed form (Supplementary Section S1). The merge error measures how far the displayed hierarchy departs from the tree:

$$d_{\mathrm{top}}(\psi, T) = \max_{i,j} |V_{ij}^{\psi} - V_{ij}|. \tag{5}$$

The diagonal includes extremum values. Under complete fixed labelling this cophenetic error equals labelled interleaving distance and bounds the unlabelled interleaving and bottleneck distances [19, 37, 38].

These variables separate layout priorities in the common model

$$\begin{aligned} &\min_{\pi \in \Pi,\, (x,z) \in \mathscr{L}(\pi;W)} \lambda_R E_R + \lambda_G E_G + \lambda_M E_M + \lambda_C E_C \\ &\text{s.t. } d_{\mathrm{top}} \leq \eta. \end{aligned} \tag{6}$$

Each term is a mean squared residual over the n_t leaves, the ordered pairs P_t or the matched leaves M_t of a frame:

$$\begin{aligned} E_R &= \tfrac{1}{n_t} \textstyle\sum_i (x_i - q_i)^2, & E_G &= \tfrac{1}{|P_t|} \textstyle\sum_{(i,j) \in P_t} (x_j - x_i - d_{ij})^2, \\ E_M &= \tfrac{1}{|M_t|} \textstyle\sum_{i \in M_t} (x_i - \hat{x}_i)^2, & E_C &= \tfrac{1}{n_t} \textstyle\sum_i (x_i - z_i)^2, \end{aligned} \tag{7}$$

with the temporal target $\hat{x}_i$ of Section 5. The allowance η, in scalar units, makes the tradeoff explicit: $\eta = 0$ demands the exact tree, and a larger η admits orders that follow the references more closely. Section 5 sets η from a merge budget ε given as a fraction of the scalar range. TMTM packs tree-compatible blocks and aligns them by overlap; ST-MTM fits relative geometry with temporal constraints. Both keep the tree ($\eta = 0$) and have no reference term ($\lambda_R = 0$), so nothing ties their axes to location. AnchorMTM adds E_R and a declared allowance.

3.4 Conflict Between Topology and Spatial Position

A projection can follow every q_i, but a profile that shows the tree exactly must keep each subtree in one block. In Fig. 2d, the tree joins A with B and C with D, while the references occur in the order A,C,B,D: the two blocks interleave, so some extrema must leave their references. Sibling blocks can also nest, as when C and D both lie between A and B (Fig. 5). Keeping the blocks displaces anchors; allowing some merge error may admit an order closer to the references. How far the anchors must move depends only on the tree, the references, the widths and the allowance, not on the algorithm that draws the map.

We address three questions: how much displacement exact topology forces (RQ1), how finite feature widths and interval constraints increase that cost (RQ2), and which conflicts can be released by bounded merge-level error (RQ3). The next section answers them in this order; the construction then uses the same quantities to select and place a map.

4 The Positional Price of Keeping the Tree

The positional cost comes from two sources: constraints imposed by the hierarchy and additional choices made by a layout. We first isolate the hierarchy in a point model, then account for interval packing, and finally allow a bounded merge error. This progression answers RQ1–RQ3 using the same reference coordinate. Suppress t, write $[v]^+ = \max(v,0)$ and take empty maxima as zero; the proofs are in Supplementary Section S2.

4.1 Exact Topology

The first question removes feature width and asks what the hierarchy alone forces. An exact profile keeps sibling subtrees in separate blocks, so their reference hulls determine the cost of either block orientation. Let $[m_X, M_X]$ be the reference hull of subtree X, the smallest interval that contains the references of its leaves.

Proposition 1 (Exact-topology bound)**.** *Every exact profile satisfies* $\mathrm{NROE}(\pi) \geq \nu^*$*, where*

$$\nu^* = \frac{1}{2L} \max_{v} \max_{X \neq Y \in \mathrm{ch}(v)} [\min(M_X - m_Y, M_Y - m_X)]^+. \tag{8}$$

Ordering the children of every node by the midpoints of their hulls attains ν^* *in* $O(n \log n)$ *time.*

Two sibling blocks must take one orientation, and each orientation inverts some references: placing X first costs $[M_X - m_Y]^+/2$, placing Y first $[M_Y - m_X]^+/2$, and midpoint order chooses the smaller. Every inverted pair of leaves is separated at its lowest common ancestor, so the midpoint order has no larger inversion. Any order error above ν^* is therefore chosen by the layout, not forced by the tree; we call it *not forced*.

4.2 Finite Widths

Set $H_i = \rho W_i/2$, $\ell_i = q_i - W_i/2 - H_i$, $h_i = q_i + W_i/2 + H_i$ and $s_i = W_i + g$. For a set S of leaves, the packing summaries

$$\begin{aligned} A(S) &= \max_{a \in S} \big(\ell_a + \sum_{i \in S : \ell_i \geq \ell_a} s_i\big), \\ B(S) &= \max_{b \in S} \big(\sum_{i \in S : h_i \leq h_b} s_i - h_b\big) \end{aligned} \tag{9}$$

bound how far right the intervals of S must reach and, negated, how far left they must begin, given their references and anchor slack. Define $\omega(X,Y) = \frac{1}{2}\min\{A(X)+B(Y), A(Y)+B(X)\} - g/2$ for two disjoint leaf sets, and the canvas term $E_\partial = \max\{0, B(\mathscr{F}) - g, A(\mathscr{F}) - g - L\}$ for the set $\mathscr{F}$ of all leaves.

Proposition 2 (Width-aware bound)**.** *For every exact interval layout in order* π*,*

$$\|x - q\|_\infty \geq \tau(\pi) \geq \mathscr{B}_w = \max\{E_\partial, \max_{(X,Y) \in \mathscr{P}_0} \omega(X,Y)\}, \tag{10}$$

where $\mathscr{P}_0$ *is the set of pairs of sibling subtrees, taken as leaf sets. With zero widths and gaps,* $\mathscr{B}_w = L\nu^*$*.*

The first and last anchors of a block must enclose its intervals and gaps, up to the anchor slack, and the two canvas ends add E_∂. Ordering alone therefore no longer determines the positional cost: even an order that attains the point bound may need further displacement to fit its intervals. $\mathscr{B}_w$ is in coordinate units, whereas ν^* is normalized by L. The construction therefore evaluates the exact packing cost τ of each candidate order before it places the anchors.

4.3 Bounded Merge Error

In a profile with $d_{\mathrm{top}} \leq \eta$, if leaf k lies between descendants i, j of node u, the interval between i and k lies inside that between i and j, so $V_{ik}^{\Psi} \leq V_{ij}^{\Psi}$ and hence $V_{ik} \leq h(u) + 2\eta$. Let $A_\eta(u)$ be the highest ancestor of u with $h(A_\eta(u)) - h(u) \leq 2\eta$. Form $\mathscr{P}_\eta$ from the pairs $(\mathscr{D}(u), \{k\})$ with $k \notin \mathscr{D}(A_\eta(u))$, and the pairs $(\mathscr{D}(u), \mathscr{D}(w))$ of internal nodes u, w in which each set is disjoint from the other's $\mathscr{D}(A_\eta(\cdot))$.

Proposition 3 (Bounded-merge-error bound)**.** *If* $d_{\mathrm{top}} \leq \eta$*, then for every pair* $(X,Y) \in \mathscr{P}_\eta$ *the leaves of* X *all precede or all follow those of* Y*. Thus*

$$\begin{aligned} \mathrm{NROE}(\pi) \geq C_\eta &= \max_{(X,Y) \in \mathscr{P}_\eta} \frac{[\min(M_X - m_Y, M_Y - m_X)]^+}{2L}, \\ \tau(\pi) \geq C_{w,\eta} &= \max\{E_\partial, \max_{(X,Y) \in \mathscr{P}_\eta} \omega(X,Y)\}. \end{aligned} \tag{11}$$

The test uses the accumulated level difference to the ancestor, so an allowance releases only the conflicts between subtrees that merge within 2η of each other. Flattening every node whose parent lies at most 2η above it and applying Propositions 1 and 2 to the flattened tree gives a second valid bound; neither dominates, and we report the larger. Together, the three bounds separate displacement forced by the tree from displacement chosen by a layout. They also suggest the construction: search orders by their exact fixed-order cost τ, admit an order only when its merge error fits the allowance, and limit further displacement when placing the anchors. A lower bound does not produce a map; the construction must still build one and check it.

5 AnchorMTM

Figure 4 summarizes the construction; its topology-budgeted layout panel contains the separate order-search and anchor-placement stages. Extract and Reference prepares the trees, identities and fixed targets defined in Section 3. Search Leaf Orders chooses an admissible order with low τ. Place Anchors balances spatial and temporal objectives within a cap on that order's displacement. Reconstruct and Assemble builds the scalar profiles and stacks them along time. The output of each stage fixes the constraints passed to the next. The control is a normalized merge allowance ε, with $\eta = (\varepsilon_0 + \varepsilon)\Delta_F$ for sequence scalar range Δ_F and numerical tolerance $\varepsilon_0 = 10^{-7}$. Exact Mode sets $\varepsilon = 0$; the exact experiments use zero labelled error. Budgeted Mode uses a positive allowance within the same construction. Balanced denotes an experimentally selected positive-budget configuration, not all budgeted maps. Widths, gap, slack and weights stay fixed during a budget sweep; the merge allowance controls hierarchical error rather than directly bounding positional error.




Figure 4: AnchorMTM workflow on a four-leaf example. Extract and reference: merge trees of the input frames $F(x,t)$, leaf supports matched across frames, and one direction $d = a^*$ that gives every extremum a reference position q; the bounds follow from these quantities alone. Topology-budgeted layout: with $\eta = 0$ the leaf order keeps every subtree contiguous and the anchors x leave their references; with $\eta > 0$ a relaxation candidate admits an order that follows them, and the anchors are placed under a displacement cap. Topology-to-1D mapping: leaf-arc samples and optimal barriers fill each profile ψ_t, every rendered frame is checked against the budget, and the stacked profiles form the map.

5.1 Order Selection and Optimal Barriers

Order search receives the prepared tree, reference targets, widths and merge allowance. A finite candidate pool $\mathscr{C}$ starts from midpoint orders of the strict tree, threshold flattenings and selective conflict flattenings. Width-aware block moves refine promising structures. The point bound supplies an exact-topology initialization, while the interval analysis motivates evaluating packing displacement. Each visited order is checked against the original merge matrix, and selection is lexicographic:

$$\pi^{\varepsilon} \in \arg\min_{\pi\in\mathscr{C}} \big(\tau(\pi), \mathrm{NROE}(\pi)\big) \quad \text{s.t.} \quad \delta^*(\pi) \le \eta. \tag{12}$$

The exact tree supplies a feasible strict-topology seed. Selective flattening releases additional permutations while retaining deeper blocks, as illustrated in Fig. 5.

Construction sequence. For each frame, generate and refine candidate orders; compute τ, NROE and δ^*; admit the budget-feasible orders; choose the lexicographic minimum; solve its capped QP; fill and correct the profile; then check the rendered merge matrix and append the temporal column. Supplementary Section S3 details candidate generation, refinement and rounding.

For gap k of an order, set $C_k = \min_{i\le k<j} V_{\pi(i)\pi(j)}$ and let F_k be the larger adjacent extremum value.

Proposition 4 (Optimal barriers)**.** *With fixed extrema, the least continuous merge error is*

$$\delta^*(\pi) = \max\Big\{0, \max_k (F_k - C_k), \tfrac{1}{2}\max_{i<j}\big(V_{\pi(i)\pi(j)} - \max_{i\le k<j} C_k\big)\Big\}, \tag{13}$$

attained by $b_k = C_k + \delta^*(\pi)$.

Indeed, error δ requires $F_k \le b_k \le C_k + \delta$; choosing the largest permitted barriers meets every pair's lower requirement exactly when $\delta \ge \delta^*$. This gives a closed-form admission test for candidate orders.




Figure 5: Selective flattening admits order A,C,D,B while retaining the C,D grouping. The displayed barrier levels are corrected against the original merge matrix.

5.2 Capped Spatiotemporal Placement

For the chosen order, the default weights are $(\lambda_R, \lambda_G, \lambda_M, \lambda_C) = (4, 1, 0.5, 0.1)$. Each term in Eq. 6 is a mean squared residual: anchor-to-reference distance, ordered anchor separation minus support-centroid distance, matched temporal-target error, or anchor-to-center offset. The temporal target follows projected motion:

$$\hat{x}_i^t = x_{\mu_t(i)}^{t-1} + q_i^t - q_{\mu_t(i)}^{t-1}. \tag{14}$$

The selected order is now fixed, so placement changes coordinates without revisiting the discrete search. Unmatched leaves have no temporal penalty. Placement solves the convex quadratic objective under the interval constraints and

$$\|x - q\|_\infty \le \tau(\pi^{\varepsilon}) + \beta_0, \tag{15}$$

with fixed slack β_0. Because τ is attained, this cap is feasible and transfers the selected order's displacement control to the final anchors. The cap prevents a relative-distance or temporal term from

Table 1: Comparison on five planar sequences (top) and two volumes (bottom). Bold/underline mark best/second distinct values among comparable local measurements only; ties share emphasis. Daggered SNS/TW values are published context and excluded from ranking. Curves use fixed default orientations.

Dataset	Hilbert			Morton			TMTM			ST-MTM			AnchorMTM (ours)			
	SNS↓	TW↑	NPE↓	SNS↓	TW↑	NPE↓	SNS↓	TW↑	NPE↓	SNS↓	TW↑	NPE↓	Mode	SNS↓	TW↑	NPE↓
Gaussian	0.1117	0.6719	0.7557	0.0393	0.8333	0.7359	0.25†	0.77†	0.1118	0.06†	1.00†	0.1154	Exact	**0.0353**	**0.9323**	**0.0089**
													Balanced	**0.0353**	**0.9323**	**0.0089**
Ring	**0.1252**	**0.9048**	0.5941	0.1489	0.7619	0.6033	0.28†	0.68†	0.1756	0.21†	0.88†	0.2463	Exact	0.1485	0.8571	0.0471
													Balanced	0.1334	0.8571	**0.0395**
Wildfires	0.1883	0.8303	0.3641	0.1304	0.8758	0.1560	0.44†	0.88†	0.2280	0.24†	0.91†	0.3180	Exact	**0.0426**	**0.9136**	0.0131
													Balanced	0.0447	0.8989	**0.0116**
Storms	0.1290	0.7403	0.3705	0.1180	0.7251	0.3468	0.34†	0.71†	0.5753	0.21†	0.94†	0.4579	Exact	0.0790	0.8463	0.0399
													Balanced	**0.0743**	**0.8766**	**0.0140**
PM2.5	0.2386	**0.8887**	0.8090	0.1760	0.8277	0.8823	0.3018	0.7781	0.5241	0.1897	0.8224	0.5577	Exact	0.1964	0.7884	0.1390
													Balanced	**0.1636**	0.7657	**0.0468**
Cylinder	–	–	–	–	–	–	0.2956	0.8017	0.4769	0.1346	**0.8989**	0.5160	Exact	0.1097	0.8136	0.0918
													10%	**0.0409**	0.8891	**0.0116**
Tangaroa	–	–	–	–	–	–	0.5255	0.6701	0.3063	**0.1655**	**0.8137**	0.3418	Exact	0.3621	0.7260	0.1118
													10%	0.3408	0.7540	**0.0615**

For the original four inputs, TMTM/ST-MTM Temporal SNS/TW (†) are published values; other entries are local measurements. Author inputs and coverage are unconfirmed. Local TW coverage (Gaussian/Ring/Wildfires/Storms) is 64/64, 1/40, 4/32, 11/744; ineligible frames are omitted. Published TW has two-decimal precision. Mode applies only to AnchorMTM. PM2.5 uses 744 shared-input local frames (TW $k = 1$, full coverage); its Balanced mode uses the fixed exploratory 5% case budget, without validation-set budget selection. ST-MTM uses the Storms preset with start frame 0; PM2.5 baseline metrics are all recomputed. Volumes: all entries local, TW $k = 1$, AnchorMTM in its default configuration with $\varepsilon = 0$ and 10%; the curves were not computed for the volumes.

moving an anchor arbitrarily far from its spatial target. Conversely, the fixed slack leaves room to improve these secondary relationships after the discrete order has been chosen. Within a frame the feasible set is linear and the objective quadratic; frame order enters only through matched predecessor targets.

5.3 Profile Reconstruction

The final stage receives the order, anchor intervals and optimal barriers. Leaf-arc samples fill the intervals and LCA paths fill their gaps [10, 30]. Barrier correction clips each inter-anchor interior to b_k and raises its peak when needed. Profiles share direction, origin, extent and pixel scale; their stack is $I^{\varepsilon}(t,u) = \psi_t^{\varepsilon}(u)$. Integer rounding can affect merge levels, so the rendered fixed-label matrix, including its diagonal, is checked after reconstruction.

6 Evaluation

The evaluation follows the argument of the paper. We first test the bounds and use them to measure how much of the positional error of existing maps the tree actually forces; this evidence does not depend on what AnchorMTM optimizes. We then compare where the maps draw features, examine how a merge budget changes individual frames, and read two maps against their source fields.

6.1 Data and Measures

Data. The five planar sequences are Gaussian (64 frames), Ring (40), Wildfires (32) and Storms (744), the inputs of the ST-MTM benchmark [10] reconstructed with its per-frame persistence fractions, and hourly $PM_{2.5}$ over northern China in January 2017 (744 frames, 5% persistence) [28]; Storms uses ERA5 sea-level-pressure anomalies [24] and Wildfires aggregated fire radiative power [18]. The volumes are the flow past a square cylinder (102 frames of the Q-criterion, 2% persistence) [8, 56] and the Tangaroa ship wake (201 speed fields, absolute persistence 0.2) [43]. Within each comparison, all methods share the fields, trees, identities and references.

Measures. Position is measured by NPE, the worst displacement of a frame relative to the axis length, averaged over frames: $\mathrm{NPE} = \frac{1}{T}\sum_t \max_i |x_i^t - q_i^t|/L$. Relative geometry is measured by scale-normalized stress (SNS) [48] and trustworthiness (TW) [54] of anchor distances against support-centroid distances, the goal of ST-MTM; for the four benchmark inputs, the published TMTM and ST-MTM values are quoted for context (daggers in Table 1). Neither baseline fixes the direction of its axis, so each is reflected once per sequence to agree with the reference; Hilbert and Morton curves use fixed orientations. ST-MTM was presented on planar data, but its inputs, the trees, the support-centroid distances and the temporal links, do not depend on the dimension; we therefore run it on the volumes with 3-D distances and its general parameters, without tuning (Supplementary Section S4.2).

Modes. Exact uses zero allowance. Balanced uses a positive budget selected once from 1–10% on the first chronological quarter of each benchmark input (1, 1, 5 and 10%); $PM_{2.5}$ uses a fixed 5%. On the volumes, Table 1 and Figs. 7 and 8 use one default configuration, with a 10% budget as the positive mode of the table; Supplementary Table S1 lists the remaining planar settings.

6.2 Tightness of the Bounds and Forced Error

Controlled trees. We first check the bounds where the optimum is known. Two sibling pairs merge below a root, with references $(0.2, 0.5, 0.5-d, 0.8-d)$; across 43 overlaps d, independent minimax linear programs over all 24 leaf orders, the width-aware bound and the selected order coincide at $\tau = \max(0, (d+0.04)/2)$, and for four parent gaps h all 364 budget tests release the conflict exactly at $2\varepsilon = h$, as Proposition 3 predicts.

Real trees. The selected Exact order attains the width-aware bound on 1,335 of 1,624 planar frames, so on these frames no exact-topology order has a smaller worst displacement. Gaussian and Ring attain it on every frame, Wildfires misses one frame and Storms 15. $PM_{2.5}$ attains it on 471 of 744 frames and leaves a small residual gap: the mean interval cost is 13.11% of the axis against a mean bound of 12.88%. We did not evaluate width-aware attainment on the volumes.

Forced and chosen error. Because midpoint ordering attains v^* on the same tree, the bound splits the order error of any exact map into a part the tree forces and a part its order rule chooses (Fig. 6a). On the real-data sequences, 83–98% of the order error of TMTM and ST-MTM on Wildfires and Storms and 56–60% on $PM_{2.5}$ lie above v^* and could be removed without changing the tree; on the two volumes the share is 31–54%. On Gaussian the bound is zero and the baseline order error small (0.1–0.3%), so their NPE of 11% comes almost entirely from placement. The bounds also reveal how strongly a field entangles its hierarchy with space: v^* is 0.16% of the axis on Wildfires and 2.6% on Storms, but 12.5% on $PM_{2.5}$,




Figure 6: Forced and chosen order error. (a) Maps that keep the tree, at zero merge error (log scale). No exact map can lie in the hatched region below the bound ν^* (Proposition 1). The point-model order of AnchorMTM (midpoint ordering) lies on the bound; TMTM and ST-MTM lie far above it. The grey line is order error that the tree does not force, and the right column gives its share of the TMTM and ST-MTM error. (b) The bound as the merge error grows (Proposition 3 and the flattened bound), each panel scaled to its own bound. The budgeted point-model order of AnchorMTM (ε from 0 to 100%; worst merge error on a square-root scale) runs along it; the projection keeps every reference but breaks the tree. Gaussian, whose bound is zero, is drawn at 0 left of the axis break in (a) and omitted from (b).




Figure 7: Recomputed feature positions on Tangaroa and Cylinder using the default-weight volume configuration. Grey reference points and signed-displacement colors connect feature positions to q. Each panel reports the feature-pooled mean absolute displacement and NPE (mean per-frame maximum); positive budgets also report maximum attained merge error. Baseline reflection minimizes pooled reference displacement. The runs are those of the volume rows of Table 1.

where nested pollution maxima interleave along the chosen direction. The bound under a merge budget shows what a budget releases (Fig. 6b). Where conflicting subtrees merge just below their parent, little is needed: 1% removes almost all forced order error on Wildfires (0.16% to 0.01%) and on Cylinder (12.2% to 0.2%). Where conflicts lie deep, position is expensive: $PM_{2.5}$ needs 10% to fall below 1%, and Tangaroa keeps more than 7% up to $\varepsilon = 5\%$. The projection reaches zero order error only by changing merge levels by 4–62% of the scalar range.

6.3 Absolute Spatial Positioning

At the same zero merge error, Exact lowers NPE relative to TMTM and ST-MTM by 73–96% on all five planar inputs and is also below the Hilbert and Morton curves, which break the tree (Table 1). Balanced, with a budget of at most 10%, lowers NPE further on Ring, Wildfires and Storms and leaves Gaussian unchanged. NPE is the quantity AnchorMTM is designed for, so these results show what an anchored axis delivers rather than a general ranking. The other measures show its cost on some inputs. Hilbert keeps better SNS and TW on Ring (0.1252 and 0.9048 against 0.1334 and 0.8571) and better TW on $PM_{2.5}$ (0.8887 against 0.7657), and on $PM_{2.5}$, where every score is measured locally, ST-MTM keeps a lower SNS and a higher TW than Exact (0.1897 and 0.8224 against 0.1964 and 0.7884).

The volumes show the same pattern (bottom of Table 1). With the tree kept exactly, Exact lowers NPE from 48–52% for TMTM and ST-MTM to 9.2% on Cylinder and from 31–34% to 11.2% on Tangaroa, and a 10% budget lowers it to 1.2% and 6.2%. ST-MTM keeps the highest TW on both volumes and the lowest SNS on Tangaroa, in line with its goal of preserving relative distances. Figure 7 shows the positions behind these numbers. TMTM and ST-MTM gather the Cylinder vortices in a band that does not follow the references, whereas Exact already reproduces the shedding pattern, and a 5% budget removes almost all of the rest (NPE 1.19%). The conflicts of Tangaroa lie deeper, and the pattern of the references appears only near $\varepsilon = 20\%$ (1.88%).

6.4 Where a Merge Budget Acts

A budget limits merge error, not displacement, so its effect depends on how many frames contain a conflict it can release (Fig. 8). Two




Figure 8: Where a merge budget acts. For each sequence and budget, the worst displacement of every frame is summarized over all frames: the median frame, the 90th percentile and the worst frame (log scale), and the mean over frames, which is NPE (dashed). Bottom: the share of frames whose attained merge error is positive, that is, frames that use the budget. Every frame stays within its budget. Gaussian, whose bound is zero, is not shown.

regimes appear. On Storms the budget acts on a tail: 35% of the frames use the allowance at $\varepsilon = 10\%$, the median displacement moves only from 1.10% to 0.84%, but the 90th percentile falls from 10.7% to 2.5% and the worst frame from 44.8% to 11.6%. On $PM_{2.5}$ and the volumes almost every frame contains a releasable conflict and the whole distribution moves: on $PM_{2.5}$, 97% of the frames use a 5% budget and the median falls from 14.5% to 2.1%; on Cylinder, 2% already lowers the median from 6.8% to 1.0%; on Tangaroa the median falls from 11.3% to 5.9% at 10% and to 1.2% at 20%. Ring lies in between: its median falls from 3.9% to 1.1% at 5%, while its 90th percentile stays at 8.5% up to 20%. The share of frames that use the budget is thus itself a diagnostic of how strongly a sequence entangles hierarchy and space. Exact has zero merge error on every input; Balanced attains at most 0, 0.982, 4.421 and 9.985% on Gaussian, Ring, Wildfires and Storms, and every frame passes the continuous and raster checks. Relative geometry can move either way: Wildfires SNS rises from 0.0426 to 0.0447, and $PM_{2.5}$ TW falls from 0.7884 at $\varepsilon = 0$ to 0.7580 at 20%; Supplementary Fig. S2 samples the budget more finely.

6.5 Reading Anchored Maps

A storm crossing the North Atlantic. Figures 1 and 9 follow one low from the open Atlantic to Scandinavia between 16 and 19 December 1999. In the AnchorMTM maps its band rises steadily along the axis, and the rise is the storm's eastward motion, while the profile still shows how it merges with the neighboring lows. TMTM aligns subtrees by temporal overlap and ST-MTM places them by relative distance, so both keep the storm near the same height and its motion cannot be read from the map. The budget changes the picture locally: at 0, 2 and 5% the maps coincide in this window, while 10 and 20% release the remaining conflict and move the storm onto its reference trajectory (insets).

Vortex shedding behind a cylinder. Figure 10 reads the wake of a square cylinder in a variant that guides the layout toward a central tree. Five stages separate clearly: an early, nearly steady wake (I), a transition (II), regular shedding (III), a second transition (IV) and the late wake (V), each matched by the source isosurfaces. The variant trades location for hierarchical unfolding: its ordinate is no longer the streamwise coordinate, and the frame-balanced streamwise error rises from 21.1% to 28.1% as the guidance weight grows from 1 to 16. A tree-ordered TMTM map shows the same stages (Supplementary Fig. S3); the anchored default configuration instead places the shed vortices at their streamwise positions (Fig. 7). The two readings are complementary: one shows when the wake changes regime, the other where each vortex is.

6.6 Implementation and Verification

Every figure is regenerated from labelled layouts and raster columns: each rendered column is checked against the fixed-label merge matrix of its source tree, together with interval order, capacity, gaps and anchor slack, and the bounds and baseline inversion errors are recomputed independently (Supplementary Section S4.7). Ordering and placement take 0.15–3.32 s per benchmark sequence and 200 s for the 744-frame $PM_{2.5}$ sequence on an Apple M4 (Supplementary Table S1). Supplementary Fig. S4 shows the $PM_{2.5}$ episode in three maps.

7 Discussion

What the bound reveals about the data. The exact-topology bound is a property of a field and a direction, not of a layout, and it is informative on its own. A small v^*, as on Wildfires and Storms, says that the hierarchy of the field and its geography largely agree: sibling subtrees occupy separate stretches of the axis, and any good order can draw features near their locations. A large v^*, as on hourly $PM_{2.5}$, says that nested maxima interleave in space; there, a map that keeps the tree must displace features, and the displacement measures how far the merge structure of the field departs from its spatial arrangement. Because the bound requires no layout, it can be computed for several candidate directions before a map is drawn and used to choose the axis along which hierarchy and space conflict least.

Forced error versus layout choice. The gap between existing maps and the bound is the most practical finding. Most of the order error of TMTM and ST-MTM on our real-data sequences is not forced by the tree; it follows from ordering leaves without a spatial reference. Any merge tree map that keeps the tree, including future ones, can be measured against the same bound and judged on how much of its displacement it chooses.

Spending topological fidelity deliberately. A merge budget changes merge levels by a declared amount; it never removes a feature, alters an extremum value or moves the data. Persistence simplification at a comparable threshold would delete features below it instead. The per-frame records show where the budget was spent, and the share of frames that use it distinguishes sequences whose conflicts are rare and deep, such as Storms, from sequences in which nearly every frame is entangled, such as $PM_{2.5}$ and the volumes. Marking the changed barriers in the map can keep this trade visible to the reader.




Figure 9: Storms event window, frames 355–460, drawn by AnchorMTM at five budgets and by TMTM and ST-MTM on the same fields and trees, on one $[-35, 35]$ hPa scale. The boxes state what each map adds to the one on its right: ST-MTM adds pairwise spatial distances to TMTM's tree order, and AnchorMTM gives the axis one fixed direction and controls the merge levels it may change. The dashed curve in the insets is the reference trajectory of the tracked storm.




Figure 10: Flow past a square cylinder (102 frames of the Q-criterion) in a central-tree guidance variant of AnchorMTM, with five source isosurfaces at a common camera and blue scalar scale. Stages I–V mark the early wake, the onset of shedding, regular shedding, a second transition and the late wake. In this variant the ordinate is a guided layout position rather than the streamwise coordinate.

One axis, several readings. A fixed spatial axis and a geometry-oriented embedding answer different questions. AnchorMTM supports reading position and motion along a chosen direction, ST-MTM preserves local neighborhoods better, and the central-tree variant of Fig. 10 exposes regime changes. A view that links these readings could serve analysts who need more than one.

Limitations and future work. AnchorMTM encodes one spatial direction; positions across it, and the full two- or three-dimensional geometry, are not shown on the axis. We plan to extend the bounds from one axis to a complete account of the fidelities a temporal map trades against one another, including position along several directions, temporal coherence and relative geometry, each with its own certificate. The default direction is estimated from the whole sequence, so streaming data need a direction chosen in advance. The order search is heuristic: it attains the width-aware bound on most planar frames but leaves a residual gap on $PM_{2.5}$ and on large volumetric trees. Finally, we have not yet measured how accurately analysts read position, motion and nesting from these maps; a controlled user study is the next step.

8 Conclusion

We presented AnchorMTM, a merge tree map whose vertical axis is one fixed spatial direction, so that the height of a band reads as location and its drift as motion, while the profile still shows how features nest. A spatial axis and an exact tree conflict wherever sibling subtrees interleave in space. Our lower bounds measure this conflict from the data alone: before a map is drawn, they tell how much displacement keeping the tree forces, which merges cause it, and how much merge error removes it. Applied to existing merge tree maps, the bounds separate the displacement the tree forces from the displacement a layout chooses; on our sequences, most of it was chosen. The tradeoff between topology and position thus becomes a quantity that an analyst can measure and set.

References

[1] M. Aupetit. Visualizing distortions and recovering topology in continuous projection techniques. *Neurocomputing*, 70(7-9):1304–1330, Mar. 2007. doi: 10.1016/j.neucom.2006.11.018 2

[2] B. Bach, P. Dragicevic, D. Archambault, C. Hurter, and S. Carpendale. A descriptive framework for temporal data visualizations based on generalized space-time cubes. *Computer Graphics Forum*, 36(6):36–61, 2017. doi: 10.1111/cgf.12804 1, 2

[3] Z. Bar-Joseph, D. K. Gifford, and T. S. Jaakkola. Fast optimal leaf ordering for hierarchical clustering. *Bioinformatics*, 17(Suppl. 1):S22–S29, June 2001. doi: 10.1093/bioinformatics/17.suppl_1.s22 3

[4] K. Beketayev, G. H. Weber, D. Morozov, A. Abzhanov, and B. Hamann. Geometry-preserving topological landscapes. In *Proc. SIGGRAPH Asia Workshop on Apps (WASA)*, pp. 155–160. ACM, New York, NY, USA, Nov. 2012. doi: 10.1145/2425296.2425324 2

[5] T. Beurskens, T. Ophelders, B. Speckmann, and K. Verbeek. Relating interleaving and Fréchet distances via ordered merge trees. In *Proc. ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pp. 5027–5050, 2025. doi: 10.1137/1.9781611978322.170 2

[6] J. Buchmüller, D. Jäckle, E. Cakmak, U. Brandes, and D. A. Keim. MotionRugs: Visualizing collective trends in space and time. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):76–86, Jan. 2019. doi: 10.1109/tvcg.2018.2865049 2

[7] L. Bulteau, P. Gambette, and O. Seminck. Reordering a tree according to an order on its leaves. In *Proc. CPM*, vol. 223 of *LIPIcs*, pp. 24:1–24:15. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, Dagstuhl, Germany, June 2022. doi: 10.4230/LIPIcs.CPM.2022.24 3

[8] S. Camarri, M.-V. Salvetti, M. Buffoni, and A. Iollo. Simulation of the three-dimensional flow around a square cylinder between parallel walls at moderate Reynolds numbers. In *XVII Congresso di Meccanica Teorica ed Applicata*, 2005. 6

[9] R. Dafner, D. Cohen-Or, and Y. Matias. Context-based space filling curves. *Computer Graphics Forum*, 19(3):209–218, 2000. doi: 10.1111/1467-8659.00413 2

[10] M. Diaz, J. Heredia, N. Ferreira, and J. Poco. Spatiotemporal merge tree maps: A topology and geometry aware visualization for temporal scalar data, 2026. Preprint, SSRN 6604235. doi: 10.2139/ssrn.6604235 2, 3, 6

[11] H. Doraiswamy, J. Tierny, P. J. S. Silva, L. G. Nonato, and C. Silva. TopoMap: A 0-dimensional homology preserving projection of high-dimensional data. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):561–571, Feb. 2021. doi: 10.1109/tvcg.2020.3030441 3

[12] T. Dwyer, Y. Koren, and K. Marriott. IPSep-CoLa: An incremental procedure for separation constraint layout of graphs. *IEEE Transactions on Visualization and Computer Graphics*, 12(5):821–828, Sept. 2006. doi: 10.1109/tvcg.2006.156 3

[13] H. Edelsbrunner, D. Letscher, and A. Zomorodian. Topological persistence and simplification. *Discrete & Computational Geometry*, 28(4):511–533, Nov. 2002. doi: 10.1007/s00454-002-2885-2 2

[14] M. B. Eisen, P. T. Spellman, P. O. Brown, and D. Botstein. Cluster analysis and display of genome-wide expression patterns. *Proceedings of the National Academy of Sciences*, 95(25):14863–14868, Dec. 1998. doi: 10.1073/pnas.95.25.14863 3

[15] J. Eldridge, M. Belkin, and Y. Wang. Beyond Hartigan consistency: Merge distortion metric for hierarchical clustering. In *Proc. COLT*, vol. 40 of *PMLR*, pp. 588–606. PMLR, July 2015. https://proceedings.mlr.press/v40/Eldridge15.html. 3

[16] M. Farach, S. Kannan, and T. Warnow. A robust model for finding optimal evolutionary trees. *Algorithmica*, 13(1-2):155–179, Feb. 1995. doi: 10.1007/bf01188585 3

[17] H. Fernau, M. Kaufmann, and M. Poths. Comparing trees via crossing minimization. *Journal of Computer and System Sciences*, 76(7):593–608, 2010. doi: 10.1016/j.jcss.2009.10.014 3

[18] M. Franke, H. Martin, S. Koch, and K. Kurzhals. Visual analysis of spatio-temporal phenomena with 1D projections. *Computer Graphics Forum*, 40(3):335–347, June 2021. doi: 10.1111/cgf.14311 2, 6

[19] E. Gasparovic, E. Munch, S. Oudot, K. Turner, B. Wang, and Y. Wang. Intrinsic interleaving distance for merge trees. *La Matematica*, 4(1):40–65, 2025. doi: 10.1007/s44007-024-00143-9 2, 3

[20] D. Guo and M. Gahegan. Spatial ordering and encoding for geographic data mining and visualization. *Journal of Intelligent Information Systems*, 27(3):243–266, 2006. doi: 10.1007/s10844-006-9952-8 2

[21] C. Heine et al. A survey of topology-based methods in visualization. *Computer Graphics Forum*, 35(3):643–667, 2016. doi: 10.1111/cgf.12933 2

[22] C. Heine, D. Schneider, H. Carr, and G. Scheuermann. Drawing contour trees in the plane. *IEEE Transactions on Visualization and Computer Graphics*, 17(11):1599–1611, 2011. doi: 10.1109/TVCG.2010.270 2

[23] M. Herick, V. Molchanov, and L. Linsen. Temporally coherent topological landscapes for time-varying scalar fields. In *Proc. 15th Int. Joint Conf. on Computer Vision, Imaging and Computer Graphics Theory and Applications (IVAPP)*, pp. 54–61, 2020. doi: 10.5220/0008956300540061 2

[24] H. Hersbach, B. Bell, P. Berrisford, et al. The ERA5 global reanalysis. *Quarterly Journal of the Royal Meteorological Society*, 146(730):1999–2049, July 2020. doi: 10.1002/qj.3803 6

[25] E. Hovmöller. The trough-and-ridge diagram. *Tellus*, 1(2):62–66, May 1949. doi: 10.1111/j.2153-3490.1949.tb01260.x 1, 2

[26] D. H. Huson. Displacement-optimized tanglegrams for trees and networks. *Molecular Biology and Evolution*, 43(3):msag066, Mar. 2026. doi: 10.1093/molbev/msag066 3

[27] J. Klawitter, F. Klesen, J. Y. Scholl, T. C. van Dijk, and A. Zaft. Visualizing geophylogenies – internal and external labeling with phylogenetic tree constraints. *Journal of Graph Algorithms and Applications*, 29(1):29–61, Mar. 2025. doi: 10.7155/jgaa.v29i1.2975 3

[28] L. Kong, X. Tang, J. Zhu, Z. Wang, J. Li, H. Wu, et al. A 6-year-long (2013–2018) high-resolution air quality reanalysis dataset in China based on the assimilation of surface observations from CNEMC. *Earth System Science Data*, 13(2):529–570, 2021. doi: 10.5194/essd-13-529-2021 6

[29] W. Köpp and T. Weinkauf. Temporal treemaps: Static visualization of evolving trees. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):534–543, Jan. 2019. doi: 10.1109/tvcg.2018.2865265 2

[30] W. Köpp and T. Weinkauf. Temporal merge tree maps: A topology-based static visualization for temporal scalar data. *IEEE Transactions on Visualization and Computer Graphics*, 29(1):1157–1167, Jan. 2023. doi: 10.1109/tvcg.2022.3209387 2, 6

[31] F. Lan, B. Gamelin, L. Yan, J. Wang, B. Wang, and H. Guo. Topological characterization and uncertainty visualization of atmospheric rivers. *Computer Graphics Forum*, 43(3):e15084, June 2024. doi: 10.1111/cgf.15084 2

[32] S. Li and H. Wang. Separating overlapped intervals on a line. *Journal of Computational Geometry*, 10(1):281–321, Sept. 2019. doi: 10.20382/jocg.v10i1a11 3

[33] S. Liu, Y. Wu, E. Wei, M. Liu, and Y. Liu. StoryFlow: Tracking the evolution of stories. *IEEE Transactions on Visualization and Computer Graphics*, 19(12):2436–2445, Dec. 2013. doi: 10.1109/tvcg.2013.196 3

[34] A.-P. Lohfink, F. Wetzels, J. Lukasczyk, G. H. Weber, and C. Garth. Fuzzy contour trees: Alignment and joint layout of multiple contour trees. *Computer Graphics Forum*, 39(3):343–355, 2020. doi: 10.1111/cgf.13985 2

[35] J. Lukasczyk, C. Garth, G. H. Weber, T. Biedert, R. Maciejewski, and H. Leitte. Dynamic nested tracking graphs. *IEEE Transactions on Visualization and Computer Graphics*, 26(1):249–258, 2020. doi: 10.1109/TVCG.2019.2934368 2

[36] J. Lukasczyk, G. Weber, R. Maciejewski, C. Garth, and H. Leitte. Nested tracking graphs. *Computer Graphics Forum*, 36(3):12–22, June 2017. doi: 10.1111/cgf.13164 2

[37] D. Morozov, K. Beketayev, and G. H. Weber. Interleaving distance between merge trees. https://mrzv.org/publications/interleaving-distance-merge-trees/, 2013. Manuscript presented at TopoInVis. 2, 3

[38] E. Munch and A. Stefanou. The ℓ^∞-cophenetic metric for phylogenetic trees as an interleaving distance. In *Research in Data Science*, pp. 109–127. Springer, Cham, Switzerland, 2019. doi: 10.1007/978-3-030-11566-1_5 2, 3

[39] L. G. Nonato and M. Aupetit. Multidimensional projection for visual analytics: Linking techniques with distortions, tasks, and layout enrichment. *IEEE Transactions on Visualization and Computer Graphics*, 25(8):2650–2673, Aug. 2019. doi: 10.1109/tvcg.2018.2846735 2

[40] P. Oesterling, C. Heine, G. H. Weber, D. Morozov, and G. Scheuermann. Computing and visualizing time-varying merge trees for high-dimensional data. In H. Carr, C. Garth, and T. Weinkauf, eds., *Topological Methods in Data Analysis and Visualization IV*, pp. 87–101. Springer, 2017. doi: 10.1007/978-3-319-44684-4_5 2

[41] P. Oesterling, C. Heine, G. H. Weber, and G. Scheuermann. Visualizing nD point clouds as topological landscape profiles to guide local data analysis. *IEEE Transactions on Visualization and Computer Graphics*, 19(3):514–526, 2013. doi: 10.1109/TVCG.2012.120 2

[42] M. Pont, J. Vidal, J. Delon, and J. Tierny. Wasserstein distances, geodesics and barycenters of merge trees. *IEEE Transactions on Visualization and Computer Graphics*, 28(1):291–301, Jan. 2022. doi: 10.1109/tvcg.2021.3114839 2

[43] S. Popinet, M. Smith, and C. Stevens. Experimental and numerical study of the turbulence characteristics of airflow around a research vessel. *Journal of Atmospheric and Oceanic Technology*, 21(10):1575–1589, 2004. doi: 10.1175/1520-0426(2004)021<1575:EANSOT>2.0.CO;2 6

[44] J. Rauscher, F. L. Dennig, U. Schlegel, D. A. Keim, and J. Fuchs. Visually assessing 1-D orderings of contiguous spatial polygons. *Computer Graphics Forum*, 44(3):e70100, May 2025. doi: 10.1111/cgf.70100 2

[45] G. Robertson, R. Fernandez, D. Fisher, B. Lee, and J. Stasko. Effectiveness of animation in trend visualization. *IEEE Transactions on Visualization and Computer Graphics*, 14(6):1325–1332, 2008. doi: 10.1109/tvcg.2008.125 1, 2

[46] H. Saikia and T. Weinkauf. Global feature tracking and similarity estimation in time-dependent scalar fields. *Computer Graphics Forum*, 36(3):1–11, 2017. doi: 10.1111/cgf.13163 2

[47] D. Silver and X. Wang. Tracking and visualizing turbulent 3D features. *IEEE Transactions on Visualization and Computer Graphics*, 3(2):129–141, 1997. doi: 10.1109/2945.597796 2

[48] K. Smelser, K. Gunaratne, J. Miller, and S. Kobourov. How scale breaks "normalized stress" and KL divergence: Rethinking quality metrics. arXiv:2510.08660, 2025. doi: 10.48550/arXiv.2510.08660 6

[49] Y. Tanahashi and K.-L. Ma. Design considerations for optimizing storyline visualizations. *IEEE Transactions on Visualization and Computer Graphics*, 18(12):2679–2688, 2012. doi: 10.1109/TVCG.2012.212 3

[50] J. Tierny, G. Favelier, J. A. Levine, C. Gueunet, and M. Michaux. The Topology ToolKit. *IEEE Transactions on Visualization and Computer Graphics*, 24(1):832–842, 2018. doi: 10.1109/TVCG.2017.2743938 2, 3

[51] B. Tversky, J. B. Morrison, and M. Bétrancourt. Animation: Can it facilitate? *International Journal of Human-Computer Studies*, 57(4):247–262, 2002. doi: 10.1006/ijhc.2002.1017 1, 2

[52] G. Valdrighi, N. Ferreira, and J. Poco. MoReVis: A visual summary for spatiotemporal moving regions. *IEEE Transactions on Visualization and Computer Graphics*, 30(4):1927–1941, Apr. 2024. doi: 10.1109/tvcg.2023.3250166 2

[53] N. van Beusekom, W. Meulemans, B. Speckmann, and J. Wood. Data-spatial layouts for grid maps. In *Proc. GIScience*, vol. 277 of *LIPIcs*, pp. 10:1–10:17. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, Dagstuhl, Germany, Sept. 2023. doi: 10.4230/LIPIcs.GIScience.2023.10 3

[54] J. Venna and S. Kaski. Neighborhood preservation in nonlinear projection methods: An experimental study. In *Proc. ICANN*, vol. 2130 of *LNCS*, pp. 485–491. Springer, Berlin, Germany, 2001. doi: 10.1007/3-540-44668-0_68 6

[55] G. H. Weber, P.-T. Bremer, and V. Pascucci. Topological landscapes: A terrain metaphor for scientific data. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1416–1423, Nov. 2007. doi: 10.1109/tvcg.2007.70601 2

[56] T. Weinkauf. 3D flow around a confined square cylinder. Public uniformly resampled simulation dataset. Accessed 22 October 2026. 6

[57] J. Weißenböck, B. Fröhler, E. Gröller, J. Kastner, and C. Heinzl. Dynamic volume lines: Visual comparison of 3D volumes through space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):1040–1049, 2019. doi: 10.1109/tvcg.2018.2864510 2

[58] W. Widanagamaachchi, C. Christensen, P.-T. Bremer, and V. Pascucci. Interactive exploration of large-scale time-varying data using dynamic tracking graphs. In *IEEE Symposium on Large Data Analysis and Visualization (LDAV)*, pp. 9–17. IEEE, 2012. doi: 10.1109/ldav.2012.6378962 2

[59] J. Wood and J. Dykes. Spatially ordered treemaps. *IEEE Transactions on Visualization and Computer Graphics*, 14(6):1348–1355, Nov. 2008. doi: 10.1109/tvcg.2008.165 3

[60] J. Wulms, J. Buchmüller, W. Meulemans, K. Verbeek, and B. Speckmann. Stable visual summaries for trajectory collections. In *Proc. PacificVis*, pp. 61–70. IEEE, Los Alamitos, CA, USA, Apr. 2021. doi: 10.1109/pacificvis52677.2021.00016 2

[61] L. Yan et al. Scalar field comparison with topological descriptors: Properties and applications for scientific visualization. *Computer Graphics Forum*, 40(3):599–633, 2021. doi: 10.1111/cgf.14331 2

[62] L. Yan, H. Guo, T. Peterka, B. Wang, and J. Wang. TROPHY: A topologically robust physics-informed tracking framework for tropical cyclones. *IEEE Transactions on Visualization and Computer Graphics*, 30(1):1249–1259, Jan. 2024. doi: 10.1109/tvcg.2023.3326905 2

[63] L. Yan, T. B. Masood, F. Rasheed, I. Hotz, and B. Wang. Geometry-aware merge tree comparisons for time-varying data with interleaving distances. *IEEE Transactions on Visualization and Computer Graphics*, 29(8):3489–3506, Aug. 2023. doi: 10.1109/tvcg.2022.3163349 2

[64] L. Zhou, C. R. Johnson, and D. Weiskopf. Data-driven space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):1591–1600, Feb. 2021. doi: 10.1109/tvcg.2020.3030473 2