AnchorMTM: Spatially Anchored Merge Tree Maps with Topology–Position Tradeoffs

Lele Wang[1,2*] Yu Dong[1,*] Yuxiang Meng[1,2] Guan Li[1,2] Zhe Wang[1,2] Guihua Shan[1,2,3] Jun Liu[1,2†]




Figure 1: Storms temporal overview ($\varepsilon = 5\%$): 744 hourly ERA5 sea-level-pressure fields, December 1999. Each frame's merge tree becomes a one-dimensional profile, rotated and stacked along time. The vertical axis is one fixed spatial direction a^* (west to east), so the rising track is a storm moving east, from the open Atlantic to Scandinavia; the snapshots identify the matched extremum, and blue outlines show its leaf-arc support. The map keeps every nesting and merge level within the 5% budget.

Abstract

Merge tree maps summarize a time-varying scalar field in one static image: each time step becomes a one-dimensional profile of its merge tree, and the profiles are stacked along time, so that nested features appear as nested bands. The vertical axis of these maps encodes tree order or relative distance rather than location, so an analyst sees how features nest but not where they are or how they move. We present AnchorMTM, a merge tree map whose vertical axis is one fixed spatial direction. Anchoring the axis exposes a conflict: a profile that shows the tree exactly keeps every subtree contiguous, whereas the locations of sibling subtrees may interleave along the direction. We derive lower bounds on the displacement this conflict forces, for exact topology, for features of finite width and for a bounded change of merge levels. The bounds depend on the trees, the feature locations and, for finite widths, the interval sizes, but not on any layout algorithm, so they are known before a map is drawn. AnchorMTM then builds the map under a single merge budget that limits how far the displayed merge levels may change. On four planar and two volumetric sequences, much of the order error and most of the displacement of existing merge tree maps prove not to be forced by the tree. AnchorMTM attains the exact-topology bound for finite widths on most planar frames and, with the tree kept exactly, draws features much closer to their locations, while ST-MTM, which optimizes relative distances, still preserves neighborhoods better at exact topology. Where conflicting subtrees merge at similar levels, a small budget removes most of the remaining displacement, and on both volumes it also brings relative-distance quality past that of ST-MTM. The bounds make the positional price of a spatial axis measurable before a map is drawn.

Index Terms: Time-varying scalar fields, merge tree maps, topology-based visualization, spatial anchoring, lower bounds, constrained layout.

1 Introduction

Time-varying scalar fields record how quantities such as sea-level pressure, aerosol concentration or vorticity evolve over a spatial domain. Analysts study them through features, such as low-pressure systems, pollution episodes or shed vortices, and ask three questions about each: how it relates to the others, where it is, and how it moves. Animation keeps every time step in its spatial context but makes distant times hard to compare [45, 51]. Static overviews therefore assign one display axis to time and compress space into the other, so that a whole sequence fits into one image [2]. What that second axis means decides which of the three questions the overview can answer. The Hovmöller diagram of atmospheric science keeps a physical coordinate such as longitude and shows an eastward-moving system as a slanted streak [25], but it averages the field over the remaining coordinates, so neighboring features blend and their hierarchy disappears.

Merge tree maps answer the first question. A merge tree records

*Affiliations: [1] Advanced Interactive Technology and Application Laboratory, Computer Network Information Center, Chinese Academy of Sciences, Beijing, China; [2] University of Chinese Academy of Sciences, Beijing, China; [3] Hangzhou Institute for Advanced Study, UCAS, Hangzhou, China. E-mails: lelewang@cnic.cn; dongyu@cnic.cn; yxmeng@cnic.cn; liguan@sccas.cn; wangzhe@sccas.cn; sgh@sccas.cn; liujun@sccas.cn. Lele Wang and Yu Dong contributed equally to this work. Jun Liu is the corresponding author.

†Corresponding author. E-mail: liujun@sccas.cn.

how sublevel sets connect as the threshold rises: its leaves are the extrema, and its internal nodes are the levels at which regions merge [13, 21]. Temporal merge tree maps (TMTM) draw the tree of each time step as a one-dimensional profile whose minima are the extrema and whose barriers are the merge levels, and they stack the profiles into one image [30]. Spatiotemporal merge tree maps (ST-MTM) additionally arrange the features by their pairwise distances and temporal coherence [10]. In both, the vertical axis follows the tree, temporal alignment or relative distance; neither fixes an origin or a direction in space. A storm that crosses the North Atlantic within a few days can therefore stay at the same height of the map, and the reader sees how it connects to neighboring lows but not where it is or which way it moves.

We give this axis a spatial meaning. Fixing one direction a^* in the domain assigns every extremum a reference position, the projection of its location onto a^*, and a map whose axis encodes location should draw each extremum at its reference (Fig. 1). The obstacle is the tree itself. A profile shows the tree exactly only if every subtree occupies one contiguous block of leaves, but the references of two sibling subtrees may interleave (Fig. 2). No exact profile can then place every feature at its reference, whatever algorithm draws it. This conflict raises three questions: how much displacement the tree forces, where in the tree this displacement arises, and how much merge-level fidelity must be given up to remove it. Without answers, the positional error of a map cannot be attributed to the data or to its layout, and an analyst cannot judge whether a spatial axis is worth its cost.

We answer these questions with bounds and turn the answers into a construction. Three lower bounds, for exact topology, for features of finite width and for a bounded merge error, depend only on the trees, the references and the widths, so the positional price of the axis is known before any layout is computed. AnchorMTM then computes the map directly from the field sequence and one merge budget ε. It searches leaf orders that the budget admits, using a closed-form test for the smallest merge error an order can show, places the extrema as close to their references as the chosen order allows, and reconstructs the profiles. With $\varepsilon = 0$, the map shows every tree exactly; with $\varepsilon > 0$, it releases the conflicts that a small change of merge levels can resolve and records the merge error each frame actually spends.

Our contributions are as follows.

- We formulate spatially anchored merge tree maps and derive three layout-independent lower bounds on the displacement that keeping the tree forces, for exact topology, finite widths and bounded merge error. The bounds locate the conflict in the tree and measure any merge tree map, including existing ones.
- We present AnchorMTM, which builds the leaf order and extremum positions of every frame from the projected locations, so that the height of a band reads as location and its drift as motion along a^*, while the profile keeps the nesting and merge levels of the tree. A merge budget ε, enforced through optimal merge barriers and checked on every rendered frame, controls how much merge-level fidelity may be traded for position.
- On four planar and two volumetric sequences, we show that the bounds are attained on controlled trees and on most real frames, that much of the order error and most of the displacement of existing maps are not forced by the tree, and how a budget reshapes the displacement of individual frames.

2 Related Work

2.1 Linearizing Space for Temporal Overviews

Animation preserves the spatial context of each time step, whereas static overviews let viewers compare distant times directly; which serves better depends on the task [45,51]. Bach et al. describe both, and the operations between them, as transformations of a space–time cube [2]. A static overview must linearize space, by traversing the domain, by ordering selected features or by following a topological hierarchy (Supplementary Fig. S1). *Domain-based* linearizations traverse the samples: Hovmöller diagrams keep one physical coordinate and average over the others [25], while geographic orderings, dense pixel displays and space-filling curves visit the whole domain [9, 20, 44], and volume lines and data-driven curves extend such traversals to volumes [57, 64]. *Feature-based* summaries order selected entities: one-dimensional projections, MotionRugs, stable visual summaries and MoReVis rank moving objects by position or stability [6, 18, 52, 60]. Every linearization distorts some spatial relations [1, 39]. These overviews keep a spatial coordinate but no feature hierarchy; AnchorMTM keeps the merge tree and makes explicit what a spatial coordinate then costs.

2.2 Topology of Time-Varying Scalar Fields

Merge trees and contour trees summarize how level sets connect, and persistence-based simplification controls their size [13, 21, 50]. Features are tracked over time by region overlap or attribute similarity [46, 47] and shown as tracking graphs and nested tracking graphs [35, 36, 58]. Time-varying merge trees have been computed and compared with Wasserstein and geometry-aware interleaving distances [40, 42, 61, 63], and such pipelines follow tropical cyclones and atmospheric rivers [31, 62]. The merge error we budget is a labelled cophenetic discrepancy that equals the labelled interleaving distance [19, 37, 38] and relates to distances between ordered merge trees [5]. Tracking graphs show how features appear, split and merge, but not where they are; merge tree maps additionally show the values and nesting of every time step, and AnchorMTM adds their location.

2.3 Drawing Hierarchies along One Axis

Topological landscapes draw a merge tree as a terrain or as a one-dimensional profile whose minima are the extrema and whose barriers are the merge levels [41, 55]; geometry-preserving and temporally coherent variants exist [4, 23], and contour trees have been drawn in the plane and in joint layouts [22, 34]. Temporal treemaps lay out evolving hierarchies along time [29]. TMTM aligns the profiles of successive merge trees into one static map [30], and ST-MTM adds relative spatial distances and temporal stability [10]; their axes encode tree traversal or relative distance. Storyline layouts face a related problem for groups of entities and balance crossings and wiggles against group contiguity [33, 49].

The conflict we study arises whenever a hierarchy must respect an external order. Optimal leaf ordering selects a tree-consistent order of a dendrogram that keeps similar leaves adjacent [3, 14], and tree reordering seeks the tree-consistent permutation closest to a target order [7]. Spatially ordered treemaps and data–spatial grid maps trade hierarchy or data layout against geographic position [53, 59], geophylogenies connect leaf orders to map locations [27], and tanglegram layouts minimize crossings or displacement between two trees [17, 26]. Separation constraints keep laid-out objects disjoint [12, 32], minimax ultrametric fitting is closely related to our optimal barriers [16], and merge distortion and topology-preserving projections measure how much hierarchy a mapping retains [11, 15]. These methods optimize crossings, sums or stress for a given instance. We instead bound, in closed form for points, the worst displacement that every tree-consistent layout must accept, together with the merge error that removes it.

3 Problem Formulation

3.1 Merge Trees, Profiles, and Feature Identity

For a sampled field f_t, the merge tree T_t records sublevel components created at minima and joined at saddles; negating the field

handles maxima [50]. Extraction and persistence simplification precede layout. A leaf i has extremum location p_i^t and support S_i^t, comprising the samples on its leaf arc. Augmented internal arcs retain samples for filling the profile (Supplementary Fig. S2). Write $h_t(v)$ for a node's scalar level and $\mathscr{D}_t(v)$ for its descendant leaves. The fixed-label merge matrix is

$$V_{ij}^t = h_t(\mathrm{lca}(i,j)), \quad i \neq j; \qquad V_{ii}^t = f_t(p_i^t). \tag{1}$$

Equal-level merges form one multifurcation. A one-dimensional profile ψ_t places the extrema in leaf order π_t; the largest profile value between anchors i, j gives their displayed merge level $V_{ij}^{\psi_t}$. We call a profile *exact* if every displayed merge level equals that of the tree; this requires the leaves of every subtree to form one contiguous block.

On a fixed grid, one-to-one Hungarian matching maximizes $|S_i^{t-1} \cap S_j^t|$ and discards zero-overlap pairs [10]; a matched leaf inherits its track identity, and $\mu_t(i)$ denotes its predecessor. These links supply the temporal targets and the motion samples below, and the same matching is reused for every budget (Supplementary Fig. S3).

3.2 Fixed Spatial Reference

The default direction maximizes squared matched-extremum motion:

$$a^* \in \arg\max_{\|a\|=1} a^\top \Big(\sum_{t,i} \Delta p_i^t (\Delta p_i^t)^\top \Big) a, \tag{2}$$

where $\Delta p_i^t = p_i^t - p_{\mu_t(i)}^{t-1}$ over valid links. Its sign makes total projected motion nonnegative; the longest domain axis handles zero motion energy. An analyst may supply a physical direction instead. This separates reference estimation from the layout search: a budget changes the admissible map, while the coordinate being approximated stays fixed. Projected domain corners define one origin o and extent L, giving

$$q_i^t = \langle a^*, p_i^t \rangle - o \in [0, L]. \tag{3}$$

Direction, origin and extent remain fixed across frames and budgets. Relative geometry uses support-centroid distances d_{ij}^t; the targets q_i^t use extremum locations. Thus support growth can change relative-distance terms without moving a feature's spatial target.

3.3 A Unified Layout Formulation

Each leaf occupies an interval of width $W_i = s m_i$ and center z_i, where m_i is its support measure and s is fixed. The layout set $\mathscr{L}(\pi; W)$ places these intervals in order π inside $[0, L]$, with gap at least g and anchor slack $|x_i - z_i| \leq \rho W_i/2$. Two order costs distinguish point ordering from packing:

$$\begin{aligned} \mathrm{NROE}(\pi) &= \frac{\max_{j \leq k} [q_{\pi(j)} - q_{\pi(k)}]^+}{2L}, \\ \tau(\pi) &= \min_{(x,z) \in \mathscr{L}(\pi;W)} \|x - q\|_\infty, \\ \mathrm{NPE} &= \frac{1}{T} \sum_t \frac{\|x^t - q^t\|_\infty}{L}. \end{aligned} \tag{4}$$

The normalized reference-order error NROE is the smallest worst displacement, relative to the axis length, of point anchors kept in order π; we call it the *order error* of π. The fixed-order cost τ adds the intervals; it is the optimum of a minimax linear program and has a closed form (Supplementary Section S1). The normalized position error NPE, which we propose here, is the worst displacement a drawn map actually has, relative to the axis length and averaged over frames. It takes the worst displacement of a frame because that is what the bounds of Section 4 constrain, so the two can be compared directly. The merge error measures how far the displayed hierarchy departs from the tree:

$$d_{\mathrm{top}}(\psi, T) = \max_{i,j} |V_{ij}^{\psi} - V_{ij}|. \tag{5}$$

The diagonal includes extremum values. Under complete fixed labelling this cophenetic error equals labelled interleaving distance and bounds the unlabelled interleaving and bottleneck distances [19, 37, 38].

These variables separate layout priorities in the common model

$$\begin{aligned} &\min_{\pi \in \Pi,\, (x,z) \in \mathscr{L}(\pi;W)} \lambda_R E_R + \lambda_G E_G + \lambda_M E_M + \lambda_C E_C \\ &\qquad \text{s.t. } d_{\mathrm{top}} \leq \eta. \end{aligned} \tag{6}$$

Each term is a mean squared residual over the n_t leaves, the ordered pairs P_t or the matched leaves M_t of a frame:

$$\begin{aligned} E_R &= \tfrac{1}{n_t} \textstyle\sum_i (x_i - q_i)^2, & E_G &= \tfrac{1}{|P_t|} \textstyle\sum_{(i,j) \in P_t} (x_j - x_i - d_{ij})^2, \\ E_M &= \tfrac{1}{|M_t|} \textstyle\sum_{i \in M_t} (x_i - \hat{x}_i)^2, & E_C &= \tfrac{1}{n_t} \textstyle\sum_i (x_i - z_i)^2, \end{aligned} \tag{7}$$

with the temporal target $\hat{x}_i$ of Section 5. The allowance η, in scalar units, makes the tradeoff explicit: $\eta = 0$ demands the exact tree, and a larger η admits orders that follow the references more closely. Section 5 sets η from a merge budget ε given as a fraction of the scalar range. TMTM packs tree-compatible blocks and aligns them by overlap, so its layout follows from the leaf order alone; ST-MTM fits relative geometry with temporal constraints, which corresponds to $\lambda_R = 0$ and a stationary temporal target. Both keep the tree ($\eta = 0$) and have no reference term, so nothing ties their axes to location. AnchorMTM adds E_R and a declared allowance. Eq. 6 states what each method optimizes; it does not rank them. A setting that gives position the largest weight is not expected to match, on relative distances, a method that optimizes only those.

3.4 Conflict Between Topology and Spatial Position

A projection can follow every q_i, but a profile that shows the tree exactly must keep each subtree in one block. In the exact panel of Fig. 2, the tree joins A with B and C with D, while the references occur in the order A, C, D, B: block $\{C, D\}$ lies inside the span of block $\{A, B\}$, so some extrema must leave their references. Keeping the blocks displaces anchors; allowing some merge error may admit an order closer to the references. How far the anchors must move depends only on the tree, the references, the widths and the allowance, not on the algorithm that draws the map.

We address three questions: how much displacement exact topology forces (RQ1), how finite feature widths and interval constraints increase that cost (RQ2), and which conflicts can be released by bounded merge-level error (RQ3). The next section answers them in this order; the construction then uses the same quantities to select and place a map.

4 The Positional Price of Keeping the Tree

The positional cost comes from two sources: constraints imposed by the hierarchy and additional choices made by a layout. We first isolate the hierarchy in a point model, then account for interval packing, and finally allow a bounded merge error. This progression answers RQ1–RQ3 using the same reference coordinate. Suppress t, write $[v]^+ = \max(v, 0)$ and take empty maxima as zero; the proofs are in Supplementary Section S2.

4.1 Exact Topology

The first question removes feature width and asks what the hierarchy alone forces. An exact profile keeps sibling subtrees in separate

blocks, so their reference hulls determine the cost of either block orientation. Let $[m_X, M_X]$ be the reference hull of subtree X, the smallest interval that contains the references of its leaves.

Proposition 1 (Exact-topology bound)**.** *Every exact profile satisfies* $\mathrm{NROE}(\pi) \geq \nu^*$*, where*

$$\nu^* = \frac{1}{2L} \max_{v} \max_{X \neq Y \in \mathrm{ch}(v)} [\min(M_X - m_Y, M_Y - m_X)]^+. \tag{8}$$

Ordering the children of every node by the midpoints of their hulls attains ν^* *in* $O(n \log n)$ *time.*

Two sibling blocks must take one orientation, and each orientation inverts some references: placing X first costs $[M_X - m_Y]^+/2$, placing Y first $[M_Y - m_X]^+/2$, and midpoint order chooses the smaller. Every inverted pair of leaves is separated at its lowest common ancestor, so the midpoint order has no larger inversion. Any order error above ν^* is therefore chosen by the layout, not forced by the tree; we call it *not forced*.

4.2 Finite Widths

Set $H_i = \rho W_i/2$, $\ell_i = q_i - W_i/2 - H_i$, $r_i = q_i + W_i/2 + H_i$ and $s_i = W_i + g$. For a set S of leaves, the packing summaries

$$\begin{aligned} A(S) &= \max_{a \in S} \big(\ell_a + \sum_{i \in S : \ell_i \geq \ell_a} s_i\big), \\ B(S) &= \max_{b \in S} \big(\sum_{i \in S : r_i \leq r_b} s_i - r_b \big) \end{aligned} \tag{9}$$

bound how far right the intervals of S must reach and, negated, how far left they must begin, given their references and anchor slack. Define $\omega(X,Y) = \frac{1}{2}\min\{A(X)+B(Y), A(Y)+B(X)\} - g/2$ for two disjoint leaf sets, and the canvas term $E_\partial = \max\{0, B(\mathscr{F}) - g, A(\mathscr{F}) - g - L\}$ for the set $\mathscr{F}$ of all leaves.

Proposition 2 (Width-aware bound)**.** *For every exact interval layout in order* π*,*

$$\|x - q\|_\infty \geq \tau(\pi) \geq \mathscr{B}_w = \max\{E_\partial, \max_{(X,Y) \in \mathscr{P}_0} \omega(X,Y)\}, \tag{10}$$

where $\mathscr{P}_0$ *is the set of pairs of sibling subtrees, taken as leaf sets. With zero widths and gaps,* $\mathscr{B}_w = L\nu^*$*.*

The first and last anchors of a block must enclose its intervals and gaps, up to the anchor slack, and the two canvas ends add E_∂. Ordering alone therefore no longer determines the positional cost: even an order that attains the point bound may need further displacement to fit its intervals. $\mathscr{B}_w$ is in coordinate units, whereas ν^* is normalized by L. The construction therefore evaluates the exact packing cost τ of each candidate order before it places the anchors.

4.3 Bounded Merge Error

In a profile with $d_{\mathrm{top}} \leq \eta$, if leaf k lies between descendants i, j of node u, the interval between i and k lies inside that between i and j, so $V^{\Psi}_{ik} \leq V^{\Psi}_{ij}$ and hence $V_{ik} \leq h(u) + 2\eta$. Let $\mathrm{Anc}_\eta(u)$ be the highest ancestor of u with $h(\mathrm{Anc}_\eta(u)) - h(u) \leq 2\eta$. Form $\mathscr{P}_\eta$ from the pairs $(\mathscr{D}(u), \{k\})$ with $k \notin \mathscr{D}(\mathrm{Anc}_\eta(u))$, and the pairs $(\mathscr{D}(u), \mathscr{D}(w))$ of internal nodes u, w in which each set is disjoint from the other's $\mathscr{D}(\mathrm{Anc}_\eta(\cdot))$.

Proposition 3 (Bounded-merge-error bound)**.** *If* $d_{\mathrm{top}} \leq \eta$*, then for every pair* $(X,Y) \in \mathscr{P}_\eta$ *the leaves of* X *all precede or all follow those of* Y*. Thus*

$$\begin{aligned} \mathrm{NROE}(\pi) \geq C_\eta &= \max_{(X,Y) \in \mathscr{P}_\eta} \frac{[\min(M_X - m_Y, M_Y - m_X)]^+}{2L}, \\ \tau(\pi) \geq C_{w,\eta} &= \max\{E_\partial, \max_{(X,Y) \in \mathscr{P}_\eta} \omega(X,Y)\}. \end{aligned} \tag{11}$$

The test uses the accumulated level difference to the ancestor, so an allowance releases only the conflicts between subtrees that merge within 2η of each other. Flattening every node whose parent lies at most 2η above it and applying Propositions 1 and 2 to the flattened tree gives a second valid bound; neither dominates, and we report the larger. Together, the three bounds separate displacement forced by the tree from displacement chosen by a layout. In every frame of a map that keeps the tree, $\nu^* \leq \mathrm{NROE}(\pi) \leq \tau(\pi)/L \leq \|x - q\|_\infty / L$: the first term is what the tree forces, and the three steps are what the leaf order, the intervals and the placement add. Averaged over frames, the last term is NPE. Under a merge budget, C_η takes the place of ν^*. They also suggest the construction: search orders by τ, admit an order only when its merge error fits the allowance, and limit further displacement when placing the anchors.

5 AnchorMTM

Figure 2 summarizes the construction. *Extract & reference* prepares the trees, identities and fixed targets defined in Section 3. *Topology-budgeted layout* first chooses an admissible leaf order with low τ and then places the anchors, balancing spatial and temporal objectives within a cap on that order's displacement. *Linearized space* builds the scalar profiles and stacks them along time. The output of each stage fixes the constraints passed to the next. The control is a normalized merge allowance ε, with $\eta = (\varepsilon_0 + \varepsilon)\Delta_F$ for sequence scalar range Δ_F and numerical tolerance $\varepsilon_0 = 10^{-7}$. Exact Mode sets $\varepsilon = 0$; the exact experiments use zero labelled error. Budgeted Mode uses a positive allowance within the same construction. Balanced denotes an experimentally selected positive-budget configuration, not all budgeted maps. Widths, gap, slack and weights stay fixed during a budget sweep; the merge allowance controls hierarchical error rather than directly bounding positional error.

5.1 Order Selection and Optimal Barriers

Order search receives the prepared tree, reference targets, widths and merge allowance. A finite candidate pool $\mathscr{C}$ starts from midpoint orders of the strict tree, threshold flattenings and selective conflict flattenings. Width-aware block moves refine promising structures. The point bound supplies an exact-topology initialization, while the interval analysis motivates evaluating packing displacement. Each visited order is checked against the original merge matrix, and selection is lexicographic:

$$\pi^\varepsilon \in \arg\min_{\pi \in \mathscr{C}} \big(\tau(\pi), \mathrm{NROE}(\pi)\big) \quad \text{s.t.} \quad \delta^*(\pi) \leq \eta. \tag{12}$$

The exact tree supplies a feasible strict-topology seed. Selective flattening releases additional permutations while retaining deeper blocks, as illustrated in Fig. 3.

Construction sequence. For each frame, generate and refine candidate orders; compute τ, NROE and δ^*; admit the budget-feasible orders; choose the lexicographic minimum; solve its capped QP; fill and correct the profile; then check the rendered merge matrix and append the temporal column. Supplementary Section S3 details candidate generation, refinement and rounding.

For gap k of an order, set $C_k = \min_{i \leq k < j} V_{\pi(i)\pi(j)}$ and let F_k be the larger adjacent extremum value.

Proposition 4 (Optimal barriers)**.** *With fixed extrema, the least continuous merge error is*

$$\delta^*(\pi) = \max\Big\{0, \max_k (F_k - C_k), \tfrac{1}{2} \max_{i<j} \big(V_{\pi(i)\pi(j)} - \max_{i \leq k < j} C_k\big)\Big\}, \tag{13}$$

attained by $b_k = C_k + \delta^*(\pi)$*.*




Figure 2: AnchorMTM workflow on a four-leaf example. Extract and reference: merge trees of the input frames $F(x,t)$, leaf supports matched across frames, and one direction $d = a^*$ that gives every extremum a reference position q; the bounds follow from these quantities alone. Topology-budgeted layout: with $\eta = 0$ the leaf order keeps every subtree contiguous and the anchors x leave their references; with $\eta > 0$ a relaxation candidate admits an order that follows them, and the anchors are placed under a displacement cap. Linearized space: leaf-arc samples and optimal barriers fill each profile ψ_t, every rendered frame is checked against the budget, and the stacked profiles form the map.




Figure 3: Selective flattening admits order A,C,D,B while retaining the C,D grouping. The displayed barrier levels are corrected against the original merge matrix.

Indeed, error δ requires $F_k \le b_k \le C_k + \delta$; choosing the largest permitted barriers meets every pair's lower requirement exactly when $\delta \ge \delta^*$. This gives a closed-form admission test for candidate orders.

5.2 Capped Spatiotemporal Placement

For the chosen order, the default weights are $(\lambda_R, \lambda_G, \lambda_M, \lambda_C) = (4, 1, 0.5, 0.1)$. Each term in Eq. 6 is a mean squared residual: anchor-to-reference distance, ordered anchor separation minus support-centroid distance, matched temporal-target error, or anchor-to-center offset. The temporal target follows projected motion:

$$\hat{x}_i^t = x_{\mu_t(i)}^{t-1} + q_i^t - q_{\mu_t(i)}^{t-1}. \tag{14}$$

The selected order is now fixed, so placement changes coordinates without revisiting the discrete search. Unmatched leaves have no temporal penalty. Placement solves the convex quadratic objective under the interval constraints and

$$\|x - q\|_\infty \le \tau(\pi^\varepsilon) + \beta_0, \tag{15}$$

with fixed slack β_0. Because τ is attained, this cap is feasible and transfers the selected order's displacement control to the final anchors. The cap prevents a relative-distance or temporal term from moving an anchor arbitrarily far from its spatial target. Conversely, the fixed slack leaves room to improve these secondary relationships after the discrete order has been chosen. Within a frame the feasible set is linear and the objective quadratic; frame order enters only through matched predecessor targets.

5.3 Profile Reconstruction

The final stage receives the order, anchor intervals and optimal barriers. Leaf-arc samples fill the intervals and LCA paths fill their gaps [10, 30]. Barrier correction clips each inter-anchor interior to b_k and raises its peak when needed. Profiles share direction, origin, extent and pixel scale; their stack is $I^\varepsilon(t,u) = \psi_t^\varepsilon(u)$. Integer rounding can affect merge levels, so the rendered fixed-label matrix, including its diagonal, is checked after reconstruction.

6 Evaluation

The evaluation follows the argument of the paper. We first test the bounds and use them to measure how much of the error of existing maps the tree actually forces; this evidence does not depend on what AnchorMTM optimizes. We then ask whether the anchored axis reaches its goal and what that costs in relative geometry and temporal behavior, examine how a merge budget changes individual frames, and read an anchored map against its source field.

6.1 Data and Measures

Data. The four planar sequences are Ring (40 frames), Wildfires (32) and Storms (744), our reconstructions of the ST-MTM benchmark [10] at its per-frame persistence fractions, because its processed arrays are not available, and hourly $PM_{2.5}$ over northern China in January 2017 (744 frames, 5% persistence) [28]; Storms

Table 1: Comparison on four planar sequences (top) and two volumes (bottom). Bold/underline mark best/second distinct values among the merge tree maps, over comparable local measurements; ties share emphasis. Daggered SNS/TW values are published context and excluded from ranking. The Hilbert and Morton curves are references in fixed orientations and are not ranked.

Dataset	Hilbert		Morton		TMTM			ST-MTM			AnchorMTM (ours)			
	SNS↓	TW↑	SNS↓	TW↑	SNS↓	TW↑	NPE↓	SNS↓	TW↑	NPE↓	Mode	SNS↓	TW↑	NPE↓
Ring	0.1252	0.9048	0.1489	0.7619	0.28†	0.68†	0.1756	0.21†	0.88†	0.2463	Exact	0.1485	0.8571	0.0471
											Balanced	**0.1334**	0.8571	**0.0395**
Wildfires	0.1883	0.8303	0.1304	0.8758	0.44†	0.88†	0.2280	0.24†	0.91†	0.3180	Exact	**0.0426**	0.9136	0.0131
											Balanced	0.0447	0.8989	**0.0116**
Storms	0.1290	0.7403	0.1180	0.7251	0.34†	0.71†	0.5753	0.21†	0.94†	0.4579	Exact	0.0790	0.8463	0.0399
											Balanced	**0.0743**	0.8766	**0.0140**
PM2.5	0.2386	0.8887	0.1760	0.8277	0.3018	0.7781	0.5241	0.1897	**0.8224**	0.5577	Exact	0.1964	0.7884	0.1390
											Balanced	**0.1636**	0.7657	**0.0468**
Cylinder	0.2798	0.7902	0.2071	0.8008	0.2956	0.8017	0.4769	0.1346	0.8989	0.5160	Exact	0.1097	0.8136	0.0918
											Balanced	**0.0405**	**0.8998**	**0.0133**
Tangaroa	0.3429	0.9222	0.3627	0.8893	0.5255	0.6701	0.3866	0.1655	0.8137	0.3286	Exact	0.1518	0.8061	0.0861
											Balanced	**0.1364**	**0.8476**	**0.0465**

For the three benchmark inputs, TMTM/ST-MTM Temporal SNS/TW (†) are published values; other entries are local measurements. These inputs are our reconstructions (Section 6). TW needs enough features per frame: only 1/40, 4/32 and 11/744 frames are eligible on Ring, Wildfires and Storms, so TW is not ranked there. Published TW has two-decimal precision. Mode applies only to AnchorMTM. The curves break the tree, and NPE is not given for them because a curve index corresponds to no spatial direction. PM2.5 uses 744 shared-input local frames (TW $k = 1$, full coverage); its Balanced mode uses the fixed exploratory 5% case budget, without validation-set budget selection. ST-MTM uses the Storms preset with start frame 0; PM2.5 baseline metrics are all recomputed. Volumes: all entries local, streamwise x reference, TW $k = 1$; Balanced is 1% (Cylinder) and 9% (Tangaroa) by the planar rule, attaining 0.99% and 9.0% merge error. ST-MTM was not proposed for volumes; its volume rows are our adaptation (Section 6).

uses ERA5 sea-level-pressure anomalies [24] and Wildfires aggregated fire radiative power [18]. We omit the Gaussian sequence of that benchmark, which has three features per frame and no conflict between hierarchy and position. The volumes are the flow past a square cylinder (102 frames of the Q-criterion, 2% persistence) [8, 56] and the Tangaroa ship wake (201 speed fields, absolute persistence 0.2) [43]. Within each comparison, all methods share the fields, trees, identities and references.

Compared maps. TMTM and ST-MTM keep the tree but define no origin or direction for their axis, so each is reflected once per sequence to agree with the reference. ST-MTM was proposed for planar data, and its authors make no claim about volumes; because it is the only existing map that optimizes relative geometry and its inputs do not depend on the dimension, we include our own 3-D adaptation, with 3-D distances and the method's general parameters and without tuning (Supplementary Section S4.2). Its volume rows report this adaptation, not a result of its authors. The Hilbert and Morton space-filling curves are references for neighborhood quality only: they order all samples of the domain and break the tree, and a curve index corresponds to no spatial direction, so we report no NPE for them and do not rank them.

Measures. Table 2 lists the measures. NPE is our own: AnchorMTM optimizes it and TMTM and ST-MTM do not, so it shows whether the anchoring goal is reached and does not rank the maps in general. The bound and the measures from prior work do not depend on it. SNS and TW compare anchor distances with support-centroid distances; for the three benchmark inputs, the published TMTM and ST-MTM values are quoted for context (daggers in Table 1). TW needs enough features per frame and is not ranked on Ring, Wildfires and Storms, where only 1, 4 and 11 frames are eligible.

Modes. Exact uses zero allowance. Balanced uses a positive budget selected once from 1–10% on the first chronological quarter of each benchmark input (1, 5 and 10%); $PM_{2.5}$ uses a fixed 5%. The volumes use the default configuration, the same Balanced rule and the streamwise axis of both flows as a supplied direction (Section 3.2; Supplementary Section S4.7 gives Tangaroa along its motion); Table S1 lists the other settings.

Table 2: Measures of the evaluation. Lower is better, except for TW (higher) and TD (no preferred value, since features do move).

Measure	Meaning	Source
ν^*	Smallest order error the tree forces (Eq. 8)	this paper
NROE	Order error: least worst displacement of a leaf order (Eq. 4)	this paper
NPE	Worst displacement of the drawn map (Eq. 4)	this paper
Merge	Largest change of a displayed merge level (Eq. 5)	[38]
SNS	Scale-normalized stress of distances	[48]
TW	Trustworthiness of neighbors	[54]
TD	Summed displayed motion of matched anchors	[10]
ME	Share of feature pairs whose displayed approach or separation contradicts the true one	–

6.2 Tightness of the Bounds and Forced Error

Controlled trees. On two sibling pairs below a root, minimax linear programs over all 24 leaf orders, the width-aware bound and the selected order coincide at all 43 overlaps, and all 364 budget tests release the conflict exactly at $2\varepsilon = h$, as Proposition 3 predicts.

Real trees. The selected Exact order attains the width-aware bound on 1,271 of 1,560 planar frames, so on these frames no exact-topology order has a smaller worst displacement. Ring attains it on every frame, Wildfires misses one frame and Storms 15. $PM_{2.5}$ attains it on 471 of 744 frames and leaves a small residual gap: the mean interval cost is 13.11% of the axis against a mean bound of 12.88%. We did not evaluate width-aware attainment on the volumes.

Forced and chosen error. Bounds are evaluated at the numerical tolerance ε_0 of Section 5, as the maps are; this matters only on Cylinder, where near-equal merge levels in 34 of 102 frames lower the mean ν^* from 12.2% to 7.7%. Figure 4a reads the steps of Section 4 for each map. Midpoint ordering attains ν^* on the same tree, so the step from ν^* to the order error is chosen by the order rule. On the real-data sequences, 83–98% of the order error of TMTM and ST-MTM on Wildfires and Storms and 56–60% on $PM_{2.5}$ lie above ν^* and could be removed without changing the tree; on the two volumes it is 38–72%, and on the synthetic Ring 26–64%. The step from order error to NPE comes from packing and placement: measured in NPE, 76–99% of the error of TMTM and ST-MTM lies above ν^*. The bounds also reveal how strongly a field entangles its hierarchy with space: ν^* is 0.16% of the axis on Wildfires and 2.6% on Storms, but 12.5% on $PM_{2.5}$, where nested pollution max-




Figure 4: Forced and chosen error. (a) The steps of Section 4 for maps that keep the tree (log scale). The hatched region is what the tree forces: no exact map can lie below the bound ν^*. Filled markers are the order error of each map, hollow markers its final displacement NPE. Midpoint ordering (blue, filled) lies on the bound; TMTM and ST-MTM lie far above it. The right columns give the share of TMTM and ST-MTM error above the bound. (b) The bound as the merge error grows (Proposition 3 and the flattened bound), each panel scaled to its own bound. The budgeted point-model order of AnchorMTM (ε from 0 to 100%; worst merge error on a square-root scale) runs along it; the projection keeps every reference but breaks the tree.




Figure 5: Where each map draws the features of Tangaroa and Cylinder along the streamwise axis; the TMTM, ST-MTM and $\varepsilon = 0$ columns are the runs of Table 1. The first column is the reference q, the actual location of each feature along a^* and the target of the comparison; light grey dots repeat it in the other panels, and color shows how far a feature is drawn from it. The bars give NPE, the worst displacement of a frame averaged over frames (% of the axis); for positive budgets, the value in parentheses is the merge error, the largest change of any displayed merge level (% of the scalar range), a magnitude and not an error rate. TMTM, ST-MTM and $\varepsilon = 0$ show the tree exactly. Each baseline is reflected once to reduce its displacement.

ima interleave along the chosen direction. The bound under a merge budget shows what a budget releases (Fig. 4b). Where conflicting subtrees merge just below their parent, little is needed: 1% removes almost all forced order error on Wildfires (0.16% to 0.01%) and on Cylinder (7.7% to 0.2%). Where conflicts lie deep, position is expensive: $PM_{2.5}$ needs 10% to fall below 1%, and Tangaroa 12%. The projection reaches zero order error only by changing merge levels by 4–62% of the scalar range.

6.3 Position and What It Costs

Position. NPE tells whether the anchored axis reaches its goal. With zero merge error, Exact lowers NPE relative to TMTM and ST-MTM by 73–96% on all four planar inputs, from 48–52% to 9.2% on Cylinder and from 33–39% to 8.6% on Tangaroa (Table 1). Balanced, with a budget of at most 10%, lowers it further on every input. Giving the baselines their best affine map of the axis per sequence, which favors them, still leaves 28–33% on Tangaroa and




Figure 6: How a merge budget acts across frames. For each sequence and budget, the worst displacement of every frame is summarized over all frames: the median frame, the 90th percentile and the worst frame (log scale), and the mean over frames, which is NPE (dashed). Bottom: the share of frames whose attained merge error is positive, that is, frames that use the budget. Every frame stays within its budget. The volumes were not run at 1%.

45% on Cylinder. In Fig. 5, TMTM and ST-MTM place the features of both volumes in bands that do not follow the references, whereas Exact already reproduces the shedding pattern of Cylinder, and a 5% budget removes almost all of the rest (NPE 1.2%). Because AnchorMTM optimizes NPE, these results show that the goal is reached, not that AnchorMTM is better in general; the next two paragraphs use measures that do not depend on it.

Relative geometry. SNS and TW measure the goal of ST-MTM. With the tree kept exactly, ST-MTM keeps the higher TW wherever every score is measured locally ($PM_{2.5}$ and both volumes); Exact has the lower SNS on both volumes, ST-MTM on $PM_{2.5}$. With a budget, Balanced improves on ST-MTM in both SNS and TW on both volumes, narrowly in TW on Cylinder (0.8998 against 0.8989), and in SNS on $PM_{2.5}$ (Table 1). The higher TW at exact topology follows from what ST-MTM optimizes, not from a weaker pipeline: ST-MTM is another setting of Eq. 6. Giving our placement the leaf order of the ST-MTM run, $\lambda_R = 0$, no position cap and a stationary temporal target yields SNS and TW of 0.1419 and 0.8925 on Cylinder and of 0.1439 and 0.8349 on Tangaroa, with NPE back at 48% and 29% (Supplementary Section S4.5). A map that drew every feature exactly at its reference would have TW 0.862 on Cylinder and 0.763 on Tangaroa, below ST-MTM: one spatial axis cannot keep the neighbors of a 2-D or 3-D field, as on all seven sequences we tested (Supplementary Table S3). As references, the curves reach a lower SNS on Ring (Hilbert 0.1252 against 0.1334) and a higher TW on $PM_{2.5}$ and Tangaroa (Hilbert 0.8887 and 0.9222), at the price of the tree.

Temporal behavior. TD is small for a map that holds features still. On Cylinder, Exact has TD 57 against 43 for ST-MTM. Part of this is real motion, since drawing the references themselves gives 27; the rest comes from leaf-order changes between frames, which a 10% budget reduces to 29. On Tangaroa, Exact moves less than ST-MTM (107 against 139). Motion errors (ME) are fewer for Exact than for TMTM and ST-MTM on all seven sequences (33% against 46–67% on Cylinder, 59% against 70–97% on Tangaroa).

6.4 How a Merge Budget Acts across Frames

A budget limits merge error, not displacement, so its effect depends on how many frames contain a conflict it can release (Fig. 6). Two regimes appear. On Storms the budget acts on a tail: 35% of the frames use the allowance at $\varepsilon = 10\%$, the median displacement moves only from 1.10% to 0.84%, but the 90th percentile falls from 10.7% to 2.5% and the worst frame from 44.8% to 11.6%. On $PM_{2.5}$ and the volumes almost every frame contains a releasable conflict and the whole distribution moves: on $PM_{2.5}$, 97% of the frames use a 5% budget and the median falls from 14.5% to 2.1%; on Cylinder, 2% already lowers the median from 6.8% to 1.0%; on Tangaroa the median falls from 8.2% to 3.6% at 10% and to 2.7% at 20%. The share of frames that use the budget is thus itself a diagnostic of how strongly a sequence entangles hierarchy and space. Exact has zero merge error on every input; Balanced attains at most 0.982, 4.421 and 9.985% on Ring, Wildfires and Storms, and every frame passes the continuous and raster checks. Supplementary Fig. S4 samples the budget more finely.

6.5 Reading Anchored Maps

A storm crossing the North Atlantic. Figures 1 and 7 follow one low from the open Atlantic to Scandinavia between 16 and 19 December 1999. In the AnchorMTM maps its band rises steadily along the axis, and the rise is the storm's eastward motion, while the profile still shows how it merges with the neighboring lows. TMTM aligns subtrees by temporal overlap and ST-MTM places them by relative distance, so both keep the storm near the same height and its motion cannot be read from the map. The budget changes the picture locally: at 0, 2 and 5% the maps coincide in this window, while 10 and 20% release the remaining conflict and move the storm onto its reference trajectory (insets).

Vortex shedding behind a cylinder. The anchored default places the shed vortices at their streamwise positions (Fig. 5). When the wake changes regime is read better if the hierarchy is given priority: an exploratory variant that freezes the leaf order of a compact TMTM layout and guides the anchors toward it separates five stages of the wake, but gives up the spatial axis (Supplementary Section S4.8). The two readings complement each other. Supplementary Fig. S7 reads an hourly $PM_{2.5}$ episode in the three maps.

6.6 Implementation and Verification

Each rendered column is checked against the fixed-label merge matrix of its source tree, together with interval order, capacity, gaps and anchor slack, and the bounds and baseline inversion errors are recomputed independently (Supplementary Section S4.10). Ordering and placement take 0.15–3.32 s per benchmark sequence and 200 s for the 744-frame $PM_{2.5}$ sequence on an Apple M4 (Supplementary Table S1).




Figure 7: Storms event window, frames 355–460, drawn by AnchorMTM at five budgets and by TMTM and ST-MTM on the same fields and trees, on one $[-35, 35]$ hPa scale. The lower comparison illustrates two improvements: ST-MTM adds pairwise spatial distances to TMTM's tree order, and AnchorMTM gives the axis one fixed direction and controls the merge levels it may change. The dashed curve in the insets is the reference trajectory of the tracked storm.

7 Discussion

What the bound reveals about the data. The exact-topology bound is a property of a field and a direction, not of a layout, and it is informative on its own. A small ν^*, as on Wildfires and Storms, says that hierarchy and geography largely agree; a large ν^*, as on hourly $PM_{2.5}$, says that nested maxima interleave in space, so a map that keeps the tree must displace them. Because the bound requires no layout, it can be computed for several candidate directions before a map is drawn and used to choose the axis along which hierarchy and space conflict least. On Tangaroa its mean ranges from 4.7% to 10.1% over 400 directions; the streamwise axis of our runs lies near the median (6.1%), the direction of strongest motion near the upper end (9.2%), so the direction that best shows motion need not be the one with the lowest price.

Forced error versus layout choice. The gap between existing maps and what the tree forces is the most practical finding. With the tree kept exactly, AnchorMTM removes 73–96% of the NPE of TMTM and ST-MTM, so at least that share of their displacement is not forced; it follows from ordering and placing leaves without a spatial reference. How much of it is ordering varies: the share of order error above the bound ranges from 26% on Ring to 98% on Wildfires. Any merge tree map that keeps the tree, including future ones, can be measured against the same bound and judged on how much of its displacement it chooses.

Spending topological fidelity deliberately. A merge budget changes merge levels by a declared amount; it never removes a feature, alters an extremum value or moves the data. Persistence simplification at a comparable threshold would delete features below it instead. The share of frames that use it distinguishes sequences whose conflicts are rare and deep, such as Storms, from sequences in which nearly every frame is entangled, such as $PM_{2.5}$ and the volumes.

One axis, several readings. A fixed spatial axis and a geometry-oriented embedding answer different questions. AnchorMTM supports reading position and motion along a chosen direction, ST-MTM preserves local neighborhoods better at exact topology, and a hierarchy-guided variant exposes regime changes (Supplementary Section S4.8). A Hovmöller diagram also keeps one physical coordinate, but it averages over the others and shows no hierarchy; we did not compare the two directly.

Limitations and future work. AnchorMTM encodes one spatial direction; positions across it, and the full two- or three-dimensional geometry, are not shown on the axis. We plan to extend the bounds from one axis to a complete account of the fidelities a temporal map trades against one another, including position along several directions, temporal coherence and relative geometry, each with its own certificate. The default direction is estimated from the whole sequence, so streaming data need a direction chosen in advance. The order search is heuristic: it attains the width-aware bound on most planar frames but leaves a residual gap on $PM_{2.5}$ and on large volumetric trees. The order is chosen per frame, so it can change between frames where conflicts are dense, as the stripes of the $PM_{2.5}$ map show (Supplementary Fig. S7). Finally, we have not yet measured how accurately analysts read position, motion and nesting from these maps; a controlled user study is the next step.

8 Conclusion

We presented AnchorMTM, a merge tree map whose vertical axis is one fixed spatial direction, so that the height of a band reads as location and its drift as motion, while the profile still shows how features nest. A spatial axis and an exact tree conflict wherever sibling subtrees interleave in space. Our lower bounds measure this conflict from the data alone: before a map is drawn, they tell how much displacement keeping the tree forces, which merges cause it, and how much merge error removes it. Applied to existing merge tree maps, the bounds separate the displacement the tree forces from the displacement a layout chooses; on our sequences, most of it was chosen. The tradeoff between topology and position thus becomes measurable and controllable.

References

[1] M. Aupetit. Visualizing distortions and recovering topology in continuous projection techniques. *Neurocomputing*, 70(7-9):1304–1330, Mar. 2007. doi: 10.1016/j.neucom.2006.11.018 2

[2] B. Bach, P. Dragicevic, D. Archambault, C. Hurter, and S. Carpendale. A descriptive framework for temporal data visualizations based on generalized space-time cubes. *Computer Graphics Forum*, 36(6):36–61, 2017. doi: 10.1111/cgf.12804 1, 2

[3] Z. Bar-Joseph, D. K. Gifford, and T. S. Jaakkola. Fast optimal leaf ordering for hierarchical clustering. *Bioinformatics*, 17(Suppl. 1):S22–S29, June 2001. doi: 10.1093/bioinformatics/17.suppl_1.s22 2

[4] K. Beketayev, G. H. Weber, D. Morozov, A. Abzhanov, and B. Hamann. Geometry-preserving topological landscapes. In *Proc. SIGGRAPH Asia Workshop on Apps (WASA)*, pp. 155–160. ACM, New York, NY, USA, Nov. 2012. doi: 10.1145/2425296.2425324 2

[5] T. Beurskens, T. Ophelders, B. Speckmann, and K. Verbeek. Relating interleaving and Fréchet distances via ordered merge trees. In *Proc. ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pp. 5027–5050, 2025. doi: 10.1137/1.9781611978322.170 2

[6] J. Buchmüller, D. Jäckle, E. Cakmak, U. Brandes, and D. A. Keim. MotionRugs: Visualizing collective trends in space and time. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):76–86, Jan. 2019. doi: 10.1109/tvcg.2018.2865049 2

[7] L. Bulteau, P. Gambette, and O. Seminck. Reordering a tree according to an order on its leaves. In *Proc. CPM*, vol. 223 of *LIPIcs*, pp. 24:1–24:15. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, Dagstuhl, Germany, June 2022. doi: 10.4230/LIPIcs.CPM.2022.24 2

[8] S. Camarri, M.-V. Salvetti, M. Buffoni, and A. Iollo. Simulation of the three-dimensional flow around a square cylinder between parallel walls at moderate Reynolds numbers. In *XVII Congresso di Meccanica Teorica ed Applicata*, 2005. 6

[9] R. Dafner, D. Cohen-Or, and Y. Matias. Context-based space filling curves. *Computer Graphics Forum*, 19(3):209–218, 2000. doi: 10.1111/1467-8659.00413 2

[10] M. Diaz, J. Heredia, N. Ferreira, and J. Poco. Spatiotemporal merge tree maps: A topology and geometry aware visualization for temporal scalar data, 2026. Preprint, SSRN 6604235. doi: 10.2139/ssrn.6604235 2, 3, 5, 6

[11] H. Doraiswamy, J. Tierny, P. J. S. Silva, L. G. Nonato, and C. Silva. TopoMap: A 0-dimensional homology preserving projection of high-dimensional data. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):561–571, Feb. 2021. doi: 10.1109/tvcg.2020.3030441 2

[12] T. Dwyer, Y. Koren, and K. Marriott. IPSep-CoLa: An incremental procedure for separation constraint layout of graphs. *IEEE Transactions on Visualization and Computer Graphics*, 12(5):821–828, Sept. 2006. doi: 10.1109/tvcg.2006.156 2

[13] H. Edelsbrunner, D. Letscher, and A. Zomorodian. Topological persistence and simplification. *Discrete & Computational Geometry*, 28(4):511–533, Nov. 2002. doi: 10.1007/s00454-002-2885-2 2

[14] M. B. Eisen, P. T. Spellman, P. O. Brown, and D. Botstein. Cluster analysis and display of genome-wide expression patterns. *Proceedings of the National Academy of Sciences*, 95(25):14863–14868, Dec. 1998. doi: 10.1073/pnas.95.25.14863 2

[15] J. Eldridge, M. Belkin, and Y. Wang. Beyond Hartigan consistency: Merge distortion metric for hierarchical clustering. In *Proc. COLT*, vol. 40 of *PMLR*, pp. 588–606. PMLR, July 2015. https://proceedings.mlr.press/v40/Eldridge15.html. 2

[16] M. Farach, S. Kannan, and T. Warnow. A robust model for finding optimal evolutionary trees. *Algorithmica*, 13(1-2):155–179, Feb. 1995. doi: 10.1007/bf01188585 2

[17] H. Fernau, M. Kaufmann, and M. Poths. Comparing trees via crossing minimization. *Journal of Computer and System Sciences*, 76(7):593–608, 2010. doi: 10.1016/j.jcss.2009.10.014 2

[18] M. Franke, H. Martin, S. Koch, and K. Kurzhals. Visual analysis of spatio-temporal phenomena with 1D projections. *Computer Graphics Forum*, 40(3):335–347, June 2021. doi: 10.1111/cgf.14311 2, 6

[19] E. Gasparovic, E. Munch, S. Oudot, K. Turner, B. Wang, and Y. Wang. Intrinsic interleaving distance for merge trees. *La Matematica*, 4(1):40–65, 2025. doi: 10.1007/s44007-024-00143-9 2, 3

[20] D. Guo and M. Gahegan. Spatial ordering and encoding for geographic data mining and visualization. *Journal of Intelligent Information Systems*, 27(3):243–266, 2006. doi: 10.1007/s10844-006-9952-8 2

[21] C. Heine et al. A survey of topology-based methods in visualization. *Computer Graphics Forum*, 35(3):643–667, 2016. doi: 10.1111/cgf.12933 2

[22] C. Heine, D. Schneider, H. Carr, and G. Scheuermann. Drawing contour trees in the plane. *IEEE Transactions on Visualization and Computer Graphics*, 17(11):1599–1611, 2011. doi: 10.1109/TVCG.2010.270 2

[23] M. Herick, V. Molchanov, and L. Linsen. Temporally coherent topological landscapes for time-varying scalar fields. In *Proc. 15th Int. Joint Conf. on Computer Vision, Imaging and Computer Graphics Theory and Applications (IVAPP)*, pp. 54–61, 2020. doi: 10.5220/0008956300540061 2

[24] H. Hersbach, B. Bell, P. Berrisford, et al. The ERA5 global reanalysis. *Quarterly Journal of the Royal Meteorological Society*, 146(730):1999–2049, July 2020. doi: 10.1002/qj.3803 6

[25] E. Hovmöller. The trough-and-ridge diagram. *Tellus*, 1(2):62–66, May 1949. doi: 10.1111/j.2153-3490.1949.tb01260.x 1, 2

[26] D. H. Huson. Displacement-optimized tanglegrams for trees and networks. *Molecular Biology and Evolution*, 43(3):msag066, Mar. 2026. doi: 10.1093/molbev/msag066 2

[27] J. Klawitter, F. Klesen, J. Y. Scholl, T. C. van Dijk, and A. Zaft. Visualizing geophylogenies – internal and external labeling with phylogenetic tree constraints. *Journal of Graph Algorithms and Applications*, 29(1):29–61, Mar. 2025. doi: 10.7155/jgaa.v29i1.2975 2

[28] L. Kong, X. Tang, J. Zhu, Z. Wang, J. Li, H. Wu, et al. A 6-year-long (2013–2018) high-resolution air quality reanalysis dataset in China based on the assimilation of surface observations from CNEMC. *Earth System Science Data*, 13(2):529–570, 2021. doi: 10.5194/essd-13-529-2021 5

[29] W. Köpp and T. Weinkauf. Temporal treemaps: Static visualization of evolving trees. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):534–543, Jan. 2019. doi: 10.1109/tvcg.2018.2865265 2

[30] W. Köpp and T. Weinkauf. Temporal merge tree maps: A topology-based static visualization for temporal scalar data. *IEEE Transactions on Visualization and Computer Graphics*, 29(1):1157–1167, Jan. 2023. doi: 10.1109/tvcg.2022.3209387 2, 5

[31] F. Lan, B. Gamelin, L. Yan, J. Wang, B. Wang, and H. Guo. Topological characterization and uncertainty visualization of atmospheric rivers. *Computer Graphics Forum*, 43(3):e15084, June 2024. doi: 10.1111/cgf.15084 2

[32] S. Li and H. Wang. Separating overlapped intervals on a line. *Journal of Computational Geometry*, 10(1):281–321, Sept. 2019. doi: 10.20382/jocg.v10i1a11 2

[33] S. Liu, Y. Wu, E. Wei, M. Liu, and Y. Liu. StoryFlow: Tracking the evolution of stories. *IEEE Transactions on Visualization and Computer Graphics*, 19(12):2436–2445, Dec. 2013. doi: 10.1109/tvcg.2013.196 2

[34] A.-P. Lohfink, F. Wetzels, J. Lukasczyk, G. H. Weber, and C. Garth. Fuzzy contour trees: Alignment and joint layout of multiple contour trees. *Computer Graphics Forum*, 39(3):343–355, 2020. doi: 10.1111/cgf.13985 2

[35] J. Lukasczyk, C. Garth, G. H. Weber, T. Biedert, R. Maciejewski, and H. Leitte. Dynamic nested tracking graphs. *IEEE Transactions on Visualization and Computer Graphics*, 26(1):249–258, 2020. doi: 10.1109/TVCG.2019.2934368 2

[36] J. Lukasczyk, G. Weber, R. Maciejewski, C. Garth, and H. Leitte. Nested tracking graphs. *Computer Graphics Forum*, 36(3):12–22, June 2017. doi: 10.1111/cgf.13164 2

[37] D. Morozov, K. Beketayev, and G. H. Weber. Interleaving distance between merge trees. https://mrzv.org/publications/interleaving-distance-merge-trees/, 2013. Manuscript presented at TopoInVis. 2, 3

[38] E. Munch and A. Stefanou. The ℓ^∞-cophenetic metric for phylogenetic trees as an interleaving distance. In *Research in Data Science*, pp. 109–127. Springer, Cham, Switzerland, 2019. doi: 10.1007/978-3-030-11566-1_5 2, 3, 6

[39] L. G. Nonato and M. Aupetit. Multidimensional projection for visual analytics: Linking techniques with distortions, tasks, and layout enrichment. *IEEE Transactions on Visualization and Computer Graphics*, 25(8):2650–2673, Aug. 2019. doi: 10.1109/tvcg.2018.2846735 2

[40] P. Oesterling, C. Heine, G. H. Weber, D. Morozov, and G. Scheuermann. Computing and visualizing time-varying merge trees for high-dimensional data. In H. Carr, C. Garth, and T. Weinkauf, eds., *Topological Methods in Data Analysis and Visualization IV*, pp. 87–101. Springer, 2017. doi: 10.1007/978-3-319-44684-4_5 2

[41] P. Oesterling, C. Heine, G. H. Weber, and G. Scheuermann. Visualizing nD point clouds as topological landscape profiles to guide local data analysis. *IEEE Transactions on Visualization and Computer Graphics*, 19(3):514–526, 2013. doi: 10.1109/TVCG.2012.120 2

[42] M. Pont, J. Vidal, J. Delon, and J. Tierny. Wasserstein distances, geodesics and barycenters of merge trees. *IEEE Transactions on Visualization and Computer Graphics*, 28(1):291–301, Jan. 2022. doi: 10.1109/tvcg.2021.3114839 2

[43] S. Popinet, M. Smith, and C. Stevens. Experimental and numerical study of the turbulence characteristics of airflow around a research vessel. *Journal of Atmospheric and Oceanic Technology*, 21(10):1575–1589, 2004. doi: 10.1175/1520-0426(2004)021<1575:EANSOT>2.0.CO;2 6

[44] J. Rauscher, F. L. Dennig, U. Schlegel, D. A. Keim, and J. Fuchs. Visually assessing 1-D orderings of contiguous spatial polygons. *Computer Graphics Forum*, 44(3):e70100, May 2025. doi: 10.1111/cgf.70100 2

[45] G. Robertson, R. Fernandez, D. Fisher, B. Lee, and J. Stasko. Effectiveness of animation in trend visualization. *IEEE Transactions on Visualization and Computer Graphics*, 14(6):1325–1332, 2008. doi: 10.1109/tvcg.2008.125 1, 2

[46] H. Saikia and T. Weinkauf. Global feature tracking and similarity estimation in time-dependent scalar fields. *Computer Graphics Forum*, 36(3):1–11, 2017. doi: 10.1111/cgf.13163 2

[47] D. Silver and X. Wang. Tracking and visualizing turbulent 3D features. *IEEE Transactions on Visualization and Computer Graphics*, 3(2):129–141, 1997. doi: 10.1109/2945.597796 2

[48] K. Smelser, K. Gunaratne, J. Miller, and S. Kobourov. How scale breaks "normalized stress" and KL divergence: Rethinking quality metrics. arXiv:2510.08660, 2025. doi: 10.48550/arXiv.2510.08660 6

[49] Y. Tanahashi and K.-L. Ma. Design considerations for optimizing storyline visualizations. *IEEE Transactions on Visualization and Computer Graphics*, 18(12):2679–2688, 2012. doi: 10.1109/TVCG.2012.212 2

[50] J. Tierny, G. Favelier, J. A. Levine, C. Gueunet, and M. Michaux. The Topology ToolKit. *IEEE Transactions on Visualization and Computer Graphics*, 24(1):832–842, 2018. doi: 10.1109/TVCG.2017.2743938 2, 3

[51] B. Tversky, J. B. Morrison, and M. Bétrancourt. Animation: Can it facilitate? *International Journal of Human-Computer Studies*, 57(4):247–262, 2002. doi: 10.1006/ijhc.2002.1017 1, 2

[52] G. Valdrighi, N. Ferreira, and J. Poco. MoReVis: A visual summary for spatiotemporal moving regions. *IEEE Transactions on Visualization and Computer Graphics*, 30(4):1927–1941, Apr. 2024. doi: 10.1109/tvcg.2023.3250166 2

[53] N. van Beusekom, W. Meulemans, B. Speckmann, and J. Wood. Data-spatial layouts for grid maps. In *Proc. GIScience*, vol. 277 of *LIPIcs*, pp. 10:1–10:17. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, Dagstuhl, Germany, Sept. 2023. doi: 10.4230/LIPIcs.GIScience.2023.10 2

[54] J. Venna and S. Kaski. Neighborhood preservation in nonlinear projection methods: An experimental study. In *Proc. ICANN*, vol. 2130 of *LNCS*, pp. 485–491. Springer, Berlin, Germany, 2001. doi: 10.1007/3-540-44668-0_68 6

[55] G. H. Weber, P.-T. Bremer, and V. Pascucci. Topological landscapes: A terrain metaphor for scientific data. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1416–1423, Nov. 2007. doi: 10.1109/tvcg.2007.70601 2

[56] T. Weinkauf. 3D flow around a confined square cylinder. Public uniformly resampled simulation dataset. Accessed 22 October 2026. 6

[57] J. Weißenböck, B. Fröhler, E. Gröller, J. Kastner, and C. Heinzl. Dynamic volume lines: Visual comparison of 3D volumes through space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):1040–1049, 2019. doi: 10.1109/tvcg.2018.2864510 2

[58] W. Widanagamaachchi, C. Christensen, P.-T. Bremer, and V. Pascucci. Interactive exploration of large-scale time-varying data using dynamic tracking graphs. In *IEEE Symposium on Large Data Analysis and Visualization (LDAV)*, pp. 9–17. IEEE, 2012. doi: 10.1109/ldav.2012.6378962 2

[59] J. Wood and J. Dykes. Spatially ordered treemaps. *IEEE Transactions on Visualization and Computer Graphics*, 14(6):1348–1355, Nov. 2008. doi: 10.1109/tvcg.2008.165 2

[60] J. Wulms, J. Buchmüller, W. Meulemans, K. Verbeek, and B. Speckmann. Stable visual summaries for trajectory collections. In *Proc. PacificVis*, pp. 61–70. IEEE, Los Alamitos, CA, USA, Apr. 2021. doi: 10.1109/pacificvis52677.2021.00016 2

[61] L. Yan et al. Scalar field comparison with topological descriptors: Properties and applications for scientific visualization. *Computer Graphics Forum*, 40(3):599–633, 2021. doi: 10.1111/cgf.14331 2

[62] L. Yan, H. Guo, T. Peterka, B. Wang, and J. Wang. TROPHY: A topologically robust physics-informed tracking framework for tropical cyclones. *IEEE Transactions on Visualization and Computer Graphics*, 30(1):1249–1259, Jan. 2024. doi: 10.1109/tvcg.2023.3326905 2

[63] L. Yan, T. B. Masood, F. Rasheed, I. Hotz, and B. Wang. Geometry-aware merge tree comparisons for time-varying data with interleaving distances. *IEEE Transactions on Visualization and Computer Graphics*, 29(8):3489–3506, Aug. 2023. doi: 10.1109/tvcg.2022.3163349 2

[64] L. Zhou, C. R. Johnson, and D. Weiskopf. Data-driven space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):1591–1600, Feb. 2021. doi: 10.1109/tvcg.2020.3030473 2