AnchorMTM: Spatially Anchored Merge Tree Maps with Topology–Position Tradeoffs

Lele Wang[1,2*] Yu Dong[1,*] Yuxiang Meng[1,2] Guan Li[1,2] Zhe Wang[1,2] Guihua Shan[1,2,3] Jun Liu[1,2†]

S1 Background and Problem Formulation (Sections 2 and 3)

Sections S1–S4 follow Sections 2–6 of the paper and contain only material the paper refers to but does not include. Unprefixed equation, figure, table and section numbers refer to the paper.

S1.1 Three Ways to Linearize a Field

Figure S1 contrasts the three families discussed in Section 2 of the paper on one small field.

S1.2 From an Augmented Tree to a Profile

Figure S2 shows the profile construction that AnchorMTM inherits from TMTM and ST-MTM [2, 4].

S1.3 Leaf Correspondence

Supports are compared as sets of sample identifiers that denote the same spatial sample in every frame; on a fixed grid the identifier is the sample index. When overlaps suggest one-to-many, many-to-one or ambiguous relations, only the links chosen by the assignment survive (Fig. S3); split and merge events are not reconstructed, and no link bridges a missing frame. A feature whose supports in consecutive frames share no sample loses its link, so it contributes neither a temporal target nor a motion sample to Eq. 2.

S1.4 Numerical Conventions of the Direction

The signed projected motion counts as zero below 10^{-12}, and the motion energy as zero below 10^{-20}; if several domain axes are equally long, the first is used. The relative gap between the two leading eigenvalues of the motion scatter is reported with every direction, so that a nearly isotropic motion, for which the direction is ill-defined, is visible.

S1.5 Closed Form of the Fixed-Order Cost

For a fixed order write $w_k = W_{\pi(k)}$, $Q_k = q_{\pi(k)}$ and $H_k = \rho w_k/2$, and let

$$D_k = \sum_{j<k} w_j + \tfrac{w_k}{2} + (k-1)g, \qquad R_k = \sum_{j>k} w_j + \tfrac{w_k}{2} + (n-k)g$$

be the distances of the kth center from the left and right canvas ends when all intervals are packed. If $\sum_k w_k + (n-1)g \le L$,

$$\tau(\pi) = \max\Big\{0,\ \max_k (D_k - Q_k - H_k),\ \max_k (Q_k - H_k - L + R_k),\ \max_{j<k} \tfrac{1}{2}(Q_j - Q_k + D_k - D_j - H_j - H_k)\Big\}. \tag{S1}$$

*Affiliations: [1] Advanced Interactive Technology and Application Laboratory, Computer Network Information Center, Chinese Academy of Sciences, Beijing, China; [2] University of Chinese Academy of Sciences, Beijing, China; [3] Hangzhou Institute for Advanced Study, UCAS, Hangzhou, China. E-mails: lelewang@cnic.cn; dongyu@cnic.cn; yxmeng@cnic.cn; liguan@sccas.cn; wangzhe@sccas.cn; sgh@sccas.cn; liujun@sccas.cn. Lele Wang and Yu Dong contributed equally to this work. Jun Liu is the corresponding author.

†Corresponding author. E-mail: liujun@sccas.cn.

Necessity. An anchor lies within H_k of a center that is at least D_k from the left end and at least R_k from the right end, and two centers in order $j<k$ are at least $D_k - D_j$ apart; each family of terms follows from one of these facts. *Sufficiency.* Write the centers as $z_{\pi(k)} = D_k + y_k$. The interval constraints become $0 \le y_1 \le \cdots \le y_n \le L - \sum_k w_k - (n-1)g$, and an anchor within distance t of its reference exists exactly when $Q_k - D_k - H_k - t \le y_k \le Q_k - D_k + H_k + t$. A nondecreasing y inside these windows exists if and only if every prefix maximum of the lower ends stays below the corresponding upper end; expanding this condition gives Eq. S1, and the prefix maxima themselves are feasible centers. The implementation evaluates Eq. S1 directly.

S2 Proofs (Section 4 and Proposition 4)

Since equal-level merges are single nodes, levels increase strictly from every node to its parent. Leaf k lies *between* leaves i and j if its anchor does. The proofs use the separation inequality derived at the start of Section 4.3.

Lemma S1 (Contiguity)**.** *If the parent of u lies more than 2η above u, the leaves of u are contiguous in every profile with $d_{\text{top}} \le \eta$. With $\eta = 0$ this holds for every node, so an exact profile keeps every subtree contiguous.*

Proof. Take $k \notin \mathscr{D}(u)$ and $i \in \mathscr{D}(u)$. Their lowest common ancestor is a proper ancestor of u, so $V_{ik} \ge h(\text{parent}(u)) > h(u) + 2\eta$, which the separation inequality forbids if k lay between two leaves of u.

Lemma S2 (Point order)**.** *For a fixed order π, the smallest worst displacement of point anchors $x_{\pi(1)} \le \cdots \le x_{\pi(n)}$ equals $L\,\text{NROE}(\pi)$.*

Proof. For $j \le k$ with $q_{\pi(j)} > q_{\pi(k)}$, ordered anchors give $(q_{\pi(j)} - x_{\pi(j)}) + (x_{\pi(k)} - q_{\pi(k)}) \ge q_{\pi(j)} - q_{\pi(k)}$, so one of the two displacements is at least half of this inversion. Conversely, let $P_k = \max_{j\le k} q_{\pi(j)}$ and $S_k = \min_{l\ge k} q_{\pi(l)}$ and set $x_{\pi(k)} = \frac{1}{2}(P_k + S_k)$. Both sequences are nondecreasing, so the anchors are ordered, and $x_{\pi(k)} - q_{\pi(k)} = \frac{1}{2}(P_k - q_{\pi(k)}) - \frac{1}{2}(q_{\pi(k)} - S_k)$, where both brackets are inversions of the order.

Proof of Proposition 1. *Bound.* Let X, Y be children of v. By Lemma S1 they occupy disjoint contiguous blocks. If X comes first, its leaf with reference M_X precedes the leaf of Y with reference m_Y; by Lemma S2, $\text{NROE}(\pi) \ge [M_X - m_Y]^+/(2L)$. The opposite placement gives $[M_Y - m_X]^+/(2L)$, so $\text{NROE}(\pi)$ is at least the smaller value for every sibling pair, and therefore at least ν^*. *Attainment.* The midpoint order is exact because it keeps every subtree contiguous. Let leaf a precede leaf b with $q_a > q_b$, and let $X \ni a$ and $Y \ni b$ be the children of $\text{lca}(a,b)$. X precedes Y, so $m_X + M_X \le m_Y + M_Y$, that is $M_X - m_Y \le M_Y - m_X$. Hence $q_a - q_b \le M_X - m_Y = \min(M_X - m_Y, M_Y - m_X) \le 2L\nu^*$, and Lemma S2 gives $\text{NROE}(\pi) \le \nu^*$. *Time.* Hulls are merged bottom-up in $O(n)$; sorting the children of all nodes costs $O(\sum_v \deg v \log \deg v) \subseteq O(n \log n)$.

Proof of Proposition 2. Fix a layout in order π with worst displacement t; the first inequality of Eq. 10 is the definition of τ. *Two ordered sets.* Suppose all leaves of X precede all leaves of Y. Choose $S_X \subseteq X$ and $S_Y \subseteq Y$, put $S = S_X \cup S_Y$, and let a and b be the first and last leaves of S. The intervals of S lie between




Figure S1: Mapping strategies on a common 35-sample field. (a) Domain traversal keeps samples [3]; (b) a 22-sample feature summary keeps selected structures [5]; (c) a topology-based profile, the construction of TMTM [4], keeps the hierarchy, but its axis has no spatial meaning.




Figure S2: An augmented merge tree and its profile. Extrema and the regular samples of their leaf arcs fill each leaf interval; the gaps between leaves are filled from the paths to their lowest common ancestor (grey), so the largest value between two extrema shows their merge level. These gap fillings are what a relaxed order changes: AnchorMTM raises or lowers each gap to an optimal barrier (Proposition 4) instead of the original LCA level.

the centers of a and b and are separated by gaps of at least g, so $z_b - z_a \geq \sum_{k\in S} s_k - g - W_a/2 - W_b/2$; with the anchor slack, $x_b - x_a \geq \sum_{k\in S} s_k - g - W_a/2 - W_b/2 - H_a - H_b$. Averaging $t \geq q_a - x_a$ and $t \geq x_b - q_b$ gives

$$t \geq \tfrac{1}{2}\Big[\ell_a + \sum_{k\in S} s_k - r_b - g\Big] \geq \tfrac{1}{2}\Big[\min_{S_X} \ell + \sum_{S_X} s_k + \sum_{S_Y} s_k - \max_{S_Y} r - g\Big].$$

With $S_X = \{k \in X : \ell_k \geq \alpha\}$ and $S_Y = \{k \in Y : r_k \leq \zeta\}$, maximizing over α and ζ independently yields $t \geq \frac{1}{2}[A(X) + B(Y) - g]$. Sibling subtrees take one of the two placements (Lemma S1), hence $t \geq \omega(X,Y)$. *Canvas ends.* If b is the last leaf of S, the intervals of S fit in $[0, z_b + W_b/2]$, so $z_b \geq \sum_{k\in S} s_k - g - W_b/2$ and $t \geq x_b - q_b \geq \sum_{k\in S} s_k - g - r_b$. Taking $S = \{k : r_k \leq \zeta\}$ over all leaves gives $t \geq B(\mathscr{F}) - g$; the first leaf and the right end give $t \geq A(\mathscr{F}) - g - L$ in the same way. *Zero widths.* Then $\ell = r = q$ and $s = 0$, so $A(X) = M_X$, $B(Y) = -m_Y$ and $\omega(X,Y) = \frac{1}{2}\min(M_X - m_Y, M_Y - m_X)$, while both canvas terms are nonpositive because $q \in [0, L]$.

The steps from the bound to NPE (Section 4). Proposition 1 gives $\nu^* \leq \mathrm{NROE}(\pi)$. Because $\rho \leq 1$, every anchor of a layout in $\mathscr{L}(\pi; W)$ stays inside its interval, so the anchors are ordered by π and Lemma S2 gives $\mathrm{NROE}(\pi) \leq \tau(\pi)/L$. The last step is the definition of τ.

Proof of Proposition 3. Let $k \notin \mathscr{D}(\mathrm{Anc}_\eta(u))$ and $i \in \mathscr{D}(u)$. Then $\mathrm{lca}(i,k)$ is a proper ancestor of $\mathrm{Anc}_\eta(u)$, whose level exceeds $h(u) + 2\eta$ by the maximality of $\mathrm{Anc}_\eta(u)$; by the separation inequality, k lies between no two leaves of u, which settles the pairs $(\mathscr{D}(u), \{k\})$. For a pair $(\mathscr{D}(u), \mathscr{D}(w))$, the two disjointness conditions give the same statement for every leaf of w relative to u and every leaf of u relative to w. If the earliest of these leaves belongs to u and some leaf of u followed a leaf of w, that leaf of w would lie between two leaves of u; so all leaves of u precede all leaves of w. The two possible placements of each pair then give Eq. 11 exactly as in the proofs of Propositions 1 and 2.

The flattened bound. Contract every internal node u with $h(\mathrm{parent}(u)) - h(u) \leq 2\eta$. By Lemma S1, every node that remains is contiguous whenever $d_{\mathrm{top}} \leq \eta$, so the order keeps every subtree of the contracted tree contiguous, and Propositions 1 and 2 apply to that tree. The two bounds are incomparable. Two leaves of width 0.2 with equal references under one root give an empty $\mathscr{P}_\eta$, whereas the contracted tree yields 0.1 (with $\rho = g = 0$). Conversely, a chain of ancestors whose single gaps are at most 2η but whose accumulated gap exceeds it separates pairs that the contraction merges.

Proof of Proposition 4. Let b_k be the maximum of ψ on the open interval from the kth to the $(k+1)$th anchor. The profile is continuous and both anchors are minima, so $b_k \geq F_k$, and the displayed merge level of the ith and jth leaf is $\max_{i\leq k<j} b_k$. A merge error of at most δ requires (i) $b_k \leq C_k + \delta$, because no pair spanning gap k may be displayed too high; (ii) $\max_{i\leq k<j} b_k \geq V_{\pi(i)\pi(j)} - \delta$ for every pair; and (iii) $b_k \geq F_k$. Raising barriers cannot violate (ii) or (iii), so some choice is feasible if and only if $b_k = C_k + \delta$ is. This is the case exactly when $\delta \geq F_k - C_k$ for every k and $2\delta \geq V_{\pi(i)\pi(j)} - \max_{i\leq k<j} C_k$ for every $i < j$; the least such $\delta \geq 0$ is Eq. 13. Any admissible barriers are realized by a profile with one peak per gap. For an exact order the ultrametric property makes every term of Eq. 13 nonpositive.

A direct evaluation of Eq. 13 costs $O(n^3)$ per order.

S3 Construction (Section 5)

S3.1 Candidate Generation and Refinement

There is one *threshold flattening* per distinct parent gap up to 2η; it contracts every internal node whose parent gap does not exceed that value. The *selective flattening* starts from the exact tree, finds the sibling pair with the largest order conflict, and tries to release one or both of its internal blocks while respecting accumulated ancestor gaps. Trials must pass the merge-error test and are compared by NROE, then merge error, then the number of released nodes; steps that do not increase NROE may continue the search, and the best




Figure S3: Leaf correspondence between frames t and $t+1$. Colored regions are leaf-arc supports, and hatching marks the samples a support shares with the previous frame. A and B continue their tracks, C_t has no successor and D_{t+1} starts a track. Birth and death are matching states, not detected physical events.

strictly improving state is kept. The best admissible midpoint order stays in the pool, so the final choice is never worse than it in τ.

Refinement starts from the exact tree and from the four best structures, ranked by τ, then by the sum of squared positive terms of Eq. S1, then by the number of released nodes. A move takes one child block of an internal node and inserts it elsewhere among its siblings: at every position for nodes with at most eight children, otherwise within distance three. In each pass, the internal nodes are visited in traversal order and the first move that improves (τ, squared sum) and passes the merge-error test is applied; refinement stops after eight passes or when no move is accepted. Every visited order enters a deduplicated pool. Exact ties in Eq. 12 are broken by the permutation itself so that runs are reproducible.

S3.2 Placement Solver

For the selected order, τ comes from Eq. S1, and the capped QP is solved by an interior-point conic solver (Clarabel) on the three benchmark inputs and by SciPy SLSQP from an LP-feasible start on the volumes, followed by numerical residual checks. Every valid match enters E_M with unit weight.

S3.3 Reconstruction and Rounding

Leaf intervals. The regular samples of a leaf arc are resampled to the free pixel positions of its interval and alternate between the two sides of the anchor; an arc without regular samples is interpolated between its end values. *Gaps.* The lowest common ancestor of two consecutive leaves decides which internal paths fill the gap between them; direct siblings, a direct and a deep leaf, and two deep leaves differ in how many internal paths contribute, and the ancestor level is inserted between them. After the barrier correction, interior samples may differ from the original samples; the input field itself is unchanged. *Rounding.* Anchors and interval ends are converted to pixels by one affine map for the whole sequence. The renderer keeps every extremum strict, which can raise a barrier slightly above its continuous optimum; for this reason the merge error is measured on the rendered column rather than taken from Eq. 13. *Failures.* Widths and gaps that exceed the canvas, too few pixels for the intervals, nonfinite values and solver failures are reported for the frame and not repaired. The per-frame records keep the requested budget, the bounds, τ, δ^*, the rendered merge error and the final displacement separately.

S4 Evaluation (Section 6)

S4.1 Inputs

Because the processed arrays of the ST-MTM authors are not available, the three benchmark inputs are reconstructions: Ring uses the archived generator, Wildfires aggregates fire radiative power into 32 grids, and Storms applies the archived moving mean and smoothing to the ERA5 anomalies. The ST-MTM persistence fractions $(0.1, 15, 10.5)\%$ were checked on all 816 frames. $PM_{2.5}$ is interpolated onto a 160×144 grid. For Cylinder, Q is computed from the original $192 \times 64 \times 48$ velocities before cropping, and $-Q$ is scaled once for the whole sequence [1, 7]. For Tangaroa, speed is clipped to $[0, 2]$ and values below 10^{-6} are replaced by the inflow value 1 [6].

S4.2 Measures and Baselines

TW uses $k = (3, 5, 3)$ neighbors on the three benchmark inputs, $k = 1$ on $PM_{2.5}$ and on the volumes, with $0 < k < n_t/2$; frames with too few features are skipped, which leaves 1, 4 and 11 frames on Ring, Wildfires and Storms. The curves pad the grid to a power of two, skip padded samples, and map the rank of each extremum among all grid samples to the canvas at the raster length of the sequence; they impose neither the tree nor finite widths [3]. No NPE is reported for them, because a curve index corresponds to no spatial direction. NPE takes the worst displacement of a frame so that it can be compared with the bounds; the mean absolute displacement gives the same picture on the volumes, 25.7%, 20.5% and 3.5% for TMTM, ST-MTM and Exact on Tangaroa and 26.6%, 24.3% and 3.8% on Cylinder. On the volumes they traverse the $300 \times 180 \times 120$ and $135 \times 64 \times 48$ grids with x varying fastest, and an extremum's rank among all samples, divided by the number of samples minus one, is its position, without raster rounding.

ST-MTM on the volumes. ST-MTM was designed for planar inputs; this adaptation is ours. The runs use the general parameters of ST-MTM without any tuning, and its geometric objective takes 3-D Euclidean distances between support centroids. Feature widths are physical volumes on Tangaroa and sample counts elsewhere, and the convex placement problem is solved with OSQP. The implementation needs binary trees, so a multifurcation is refined into binary nodes at the same level with fixed identifiers; this keeps every pairwise merge level but restricts the leaf orders that ST-MTM can choose.

Table S1: Parameter settings and runtime (seconds).

Parameter	Ring	Wildfires	Storms	PM2.5
N_r	196	4096	4096	4096
s_w	0.00328	0.00053	0.01170	0.00073
t_{opt}	0.150	3.324	2.600	199.975
t_{total}	0.486	4.424	63.447	231.177

s_w is the width per unit of support measure and N_r the raster length; $\rho = 0.5$ throughout. Times are single runs without a tree cache: t_{opt} covers ordering and placement, t_{total} the full pipeline. Volumes (default weights, $\rho = 0.5$): $s_w = 4.10$ on Tangaroa (physical volume; 2.88 along its motion direction, as s_w scales with L) and 2.71×10^{-5} on Cylinder (sample counts), gaps $L/240$ and $L/300$, slack $\beta_0 = L/120$; order search, QP and scoring take 50 s and 41 s at $\varepsilon = 0$ and at most 78 s at positive budgets on an Apple M2 Pro (Tangaroa timed along its motion direction).

S4.3 Settings

The Balanced budget minimizes $J = \frac{1}{2}\widehat{\text{NPE}} + \frac{1}{2}\widehat{\text{SNS}}$ over candidate budgets in 1% steps, where hats denote min–max normalization over the candidates whose attained maximum merge error stays within their budget; within 0.01 of the minimum, the smaller budget and then the smaller attained error are preferred. Budgets were fixed before the full runs. The full results include the selection frames, and exploratory runs preceded the selection, so the selection is not a held-out test. Table S1 gives the remaining planar settings and the runtimes. On the volumes, $\rho = 0.5$, and both flows take their streamwise axis as the reference (Section S4.7).

S4.4 The Budget Sampled Finely

Fig. S4 repeats the sweep of Section 6.4 with finer budget steps on the three benchmark sequences that contain conflicts. Displacement falls in steps, not continuously. Between steps, extra budget is not spent: the attained merge error stays flat and below the diagonal, as on Ring from 8 to 10% and on Wildfires beyond 5%. This is consistent with Proposition 3, under which a conflict is released only once twice the budget reaches its merge-level gap. Across all budgets, SNS moves by less than 0.025 on these sequences, so moving features toward their references leaves their relative distances largely intact.

S4.5 Moving within the Common Model

Table S2 moves from the default setting of AnchorMTM toward ST-MTM on the volumes, one change at a time. Removing the reference term alone leaves NPE almost unchanged, because the cap of Eq. 15 still holds the anchors near their references; SNS and TW move by at most 0.016. Removing the cap raises NPE to 28–31% and improves SNS, with at most a small gain in TW. The leaf order is what moves TW to the level of ST-MTM: with the leaf order that ST-MTM chose and a stationary temporal target, the same placement gives SNS and TW within 0.01 of the ST-MTM run on Cylinder and better than it on Tangaroa. These rows are not proposed configurations. They show that ST-MTM is a setting of Eq. 6 and that the difference from the default lies in what each setting optimizes. The first row is the limit of a map that follows the reference exactly.

S4.6 Temporal Behavior and the Limit of One Axis

In Table S3, the column q shows what the data imply along the axis. TW of the references lies below that of ST-MTM on every sequence, so the gap in TW is largely the cost of one spatial axis. TD of AnchorMTM is close to that of the references on Storms, OLR and $PM_{2.5}$, where it mostly records real motion. On Ring, Wildfires and the volumes the Exact map exceeds it by a factor of 2 to 6, because the leaf order changes between frames; a 10% budget brings Ring, Wildfires and Cylinder close to the references but leaves Tangaroa high, although there even Exact has a smaller TD than ST-MTM. Exact makes fewer motion errors than both baselines everywhere.

S4.7 Reference Axis of the Volumes

Both volumes are flows, and both use the streamwise x axis, along which the wake develops. The direction estimated from the motion of Tangaroa (Eq. 2) points almost along $-y$, across the wake. Along it (Table S4), AnchorMTM still has the lowest NPE and fewer motion errors than either baseline, but ST-MTM has the lower SNS and the higher TW, and the Exact map moves more than ST-MTM. The mean bound v^* also depends on the axis: on Tangaroa it is 6.1% along x, 9.6% along y, 12.4% along z and 9.2% along the motion direction; on Cylinder it is 7.7%, 8.2% and 33.6% along x, y and z at the numerical tolerance used throughout, but 12.2%, 9.7% and 34.2% with no tolerance, because near-equal merge levels in 34 of the 102 frames change which sibling blocks conflict. The streamwise axis therefore has the smallest bound on Tangaroa, and on Cylinder the ranking depends on the tolerance; we do not choose the axis by the bound, so that it has the same meaning in both flows. Tangaroa was first run along its motion direction, and the axis was changed with those results known, so the two axes are not compared on held-out data.

S4.8 Cylinder: A Hierarchy-Guided Variant

This variant does not use the anchored axis. It takes its leaf order from a compact TMTM layout, keeps it fixed and steers the anchors, with weight g, toward that central tree layout, while the reference survives only as a cap of 56% of the axis; its merge error is zero on every frame. Five stages separate in Fig. S5: an early, nearly steady wake (I), a transition (II), regular shedding (III), a second transition (IV) and the late wake (V), each matched by the source isosurfaces. The price is location: the mean absolute streamwise error rises from 21.1% to 28.1% of the axis as g grows from 1 to 16, whereas the anchored default keeps NPE at 9.2% with the tree exact (Fig. 5). A TMTM map shows the same stages (Fig. S6), whereas ST-MTM spreads the vortices by their relative distances, so its bands drift across the axis as the wake develops.

S4.9 Hourly $PM_{2.5}$, 22–27 January 2017

High-concentration features are the leaves of the join tree of the negated field; the display restores positive values. All three maps in Fig. S7 show the build-up from 23 January and the peak on 26 January, but they place the polluted features by different rules. TMTM and ST-MTM collect them into a compact band near the middle of the axis wherever they are. In AnchorMTM the band is as wide as the polluted area along the reference direction: on 25 January (c), when pollution covers most of the domain, it spans most of the axis, and on 26 January the strongest maxima drop to the lower part of the axis while TMTM keeps them in the middle. The compact bands are therefore not a more faithful picture; they omit where the features are. The vertical stripes of the AnchorMTM map are a real cost. On this sequence nested maxima cross each other along the direction more than on any other (Section 6.2), so the budget is spent in almost every hour (Section 6.4) and the leaf order changes from hour to hour. Over all 744 hours, the map spends at most 4.998% merge error. TMTM and ST-MTM are rebuilt with their original configurations, and their anchors match the stored table runs frame by frame.

S4.10 Recomputation

Controlled trees: a separate minimax LP for each of the 24 orders, compared with all 43 stored overlap records and 364 stored budget records; for widths of 0, 3, 6 and 9%, the LP optimum equals the width-aware bound to within 10^{-16}. *Planar sequences*: every map of Ring, Wildfires and Storms passes the per-frame profile and topology checks of its run; per-frame displacement is recomputed from the rendered anchors for all 9,168 frame–budget pairs of Ring, Storms and $PM_{2.5}$; one $PM_{2.5}$ QP at 2% failed numerically and was solved by a second solver with unchanged objective, constraints and budget, and its KKT certificate is kept with the records. *Volumes*: before the reference was changed, the default-configuration results along the motion direction (Exact and 10%,




Figure S4: Ring, Storms and Wildfires at 14 budgets from 0 to 30%. (a) NPE; the grey text gives the NPE of TMTM and ST-MTM from Table 1. (b) Attained merge error of the worst frame (solid) and its frame average (dashed); the dotted diagonal is the budget. (c) SNS. TW is not drawn because these sequences have too few eligible frames (Table 1).

Table S2: Moving within the common model of Eq. 6 at zero merge error. Same trees, references, widths and tracks as the volume rows of Table 1; the weights are $(\lambda_R, \lambda_G, \lambda_M, \lambda_C)$ and are the same on both volumes. NPE in % of the axis.

				Cylinder			Tangaroa		
Setting	Weights	Leaf order	Cap	SNS	TW	NPE	SNS	TW	NPE
Reference, $x = q$	–	–	–	0.050	0.862	0.0	0.153	0.763	0.0
AnchorMTM default (Table 1, Exact)	$(4, 1, .5, .1)$	τ-selected	yes	0.110	0.814	9.2	0.152	0.806	8.6
No reference term	$(0, 1, .5, .1)$	τ-selected	yes	0.096	0.810	9.2	0.141	0.821	8.8
No reference term, no cap	$(0, 1, .5, .1)$	τ-selected	no	0.086	0.838	28.1	0.131	0.822	31.3
ST-MTM leaf order, stationary target	$(0, 1, .5, .1)$	ST-MTM	no	0.142	0.892	47.8	0.144	0.835	29.2
ST-MTM run	–	ST-MTM	–	0.135	0.899	51.6	0.165	0.814	32.9

Table S3: Neighborhoods and temporal behavior. q draws every feature at its reference. TW uses $k = 1$; TD is the summed displayed motion of matched anchors, in axis lengths; ME is the share (%) of feature pairs whose displayed approach or separation contradicts the true one. Volume rows are the runs of Table 1; the planar rows are the sequences of an earlier audit, preprocessed differently from the benchmark reconstructions of Table 1.

	TW↑					TD					ME (%)↓				
Sequence	q	TMTM	ST-MTM	Exact	10%	q	TMTM	ST-MTM	Exact	10%	q	TMTM	ST-MTM	Exact	10%
Storms	0.710	0.824	0.965	0.770	0.752	23.0	10.1	7.2	27.8	23.8	13	47	41	24	19
Wildfires	0.848	0.817	0.919	0.875	0.876	2.5	11.2	8.0	8.1	3.2	27	39	36	35	35
OLR	0.958	0.814	0.975	0.956	0.962	8.7	8.7	2.3	8.9	8.8	7	45	21	5	7
$PM_{2.5}$ (daily)	0.723	0.760	0.922	0.751	0.727	68.9	38.8	7.8	76.4	69.2	47	45	52	44	49
Ring	0.679	0.707	0.917	0.686	0.707	1.8	1.3	2.4	3.6	2.1	14	65	35	31	11
Cylinder	0.862	0.802	0.899	0.814	0.889	27.1	85.0	43.2	56.6	29.2	19	67	46	33	19
Tangaroa	0.763	0.670	0.814	0.806	0.850	18.9	64.9	138.6	106.9	104.8	32	97	70	59	42

TMTM, ST-MTM) were reproduced to four decimals, and along x the default row of Table S2 reproduces the Exact row of Table 1; feature identities and source merge matrices checked against the baseline input, and every displayed pairwise merge rebuilt from the raster columns, for 1,515 frame–budget columns and 44,785 feature observations; baseline reflection is chosen by the feature-pooled absolute displacement.

References

[1] S. Camarri, M.-V. Salvetti, M. Buffoni, and A. Iollo. Simulation of the three-dimensional flow around a square cylinder between parallel walls at moderate Reynolds numbers. In *XVII Congresso di Meccanica Teorica ed Applicata*, 2005. 3

[2] M. Diaz, J. Heredia, N. Ferreira, and J. Poco. Spatiotemporal merge tree maps: A topology and geometry aware visualization for temporal




Figure S5: Flow past a square cylinder (102 frames of the Q-criterion) in the exploratory central-tree variant ($g = 16$), with five source isosurfaces at a common camera and blue scalar scale. Stages I–V mark the early wake, the onset of shedding, regular shedding, a second transition and the late wake. The ordinate is a guided layout position, not the streamwise coordinate.




Figure S6: Cylinder, all 102 frames: the central-tree variant of AnchorMTM (guidance weight 16), TMTM and ST-MTM, all three built from identical simplified trees. Each map uses its own layout coordinate; dotted lines mark the snapshot times of Fig. S5.

Table S4: Tangaroa with the reference along its motion direction (Eq. 2) instead of the streamwise axis. TD and ME as in Table S3.

Method	SNS↓	TW↑	NPE↓	TD	ME (%)↓
Reference, $x = q$	0.3409	0.7130	0	24.5	30
Hilbert	0.3429	0.9222	0.5897	–	–
Morton	0.3627	0.8893	0.5924	–	–
TMTM	0.5255	0.6701	0.3063	64.9	97
ST-MTM	0.1655	0.8137	0.3418	138.6	70
AnchorMTM, Exact	0.3621	0.7260	0.1118	173.8	52
AnchorMTM, Balanced (10%)	0.3408	0.7540	0.0615	140.3	41

On this axis the Balanced rule selects 10% (attained merge error 9.97%). SNS, TW, TD and ME of TMTM, ST-MTM and the curves do not depend on the axis.

scalar data, 2026. Preprint, SSRN 6604235. doi: 10.2139/ssrn.6604235 1

[3] M. Franke, H. Martin, S. Koch, and K. Kurzhals. Visual analysis of spatio-temporal phenomena with 1D projections. *Computer Graphics Forum*, 40(3):335–347, June 2021. doi: 10.1111/cgf.14311 2, 3

[4] W. Köpp and T. Weinkauf. Temporal merge tree maps: A topology-based static visualization for temporal scalar data. *IEEE Transactions on Visualization and Computer Graphics*, 29(1):1157–1167, Jan. 2023. doi: 10.1109/tvcg.2022.3209387 1, 2

[5] J. Lukasczyk, G. Weber, R. Maciejewski, C. Garth, and H. Leitte. Nested tracking graphs. *Computer Graphics Forum*, 36(3):12–22, June 2017. doi: 10.1111/cgf.13164 2

[6] S. Popinet, M. Smith, and C. Stevens. Experimental and numerical study of the turbulence characteristics of airflow around a research vessel. *Journal of Atmospheric and Oceanic Technology*, 21(10):1575–1589, 2004. doi: 10.1175/1520-0426(2004)021<1575:EANSOT>2.0.CO;2 3

[7] T. Weinkauf. 3D flow around a confined square cylinder. Public uniformly resampled simulation dataset. Accessed 22 October 2026. 3




Figure S7: Hourly $PM_{2.5}$, 22 January 00:00 to 27 January 12:00, 2017 (Beijing time, 133 hours), drawn by TMTM, ST-MTM and AnchorMTM ($\varepsilon = 5\%$) on one color scale. The vertical axes differ in meaning, as stated under each title. Dashed lines a–e mark the five snapshots below (110–120°E, 32–41°N, with province borders). Concentrations above 400 $\mu g/m^3$ saturate.