

AirSlide: Touch-Free Presentation Control Using Real-Time Hand Tracking

Authors: Nafiyad Fantaye, Yeabsira Alemu, Ezana Tadesse, Zerubabel Fekadu | Date: July 2026

Course: Human-Computer Interaction (HCI) | System Usability Scale (SUS): 84.25 (Grade A)

1. Abstract

AirSlide is a browser-based presentation controller that lets presenters change slides using hand gestures in front of a standard webcam. Traditional tools like leaning over a laptop, carrying clickers with dead batteries, or tapping phones distract both the speaker and the audience. AirSlide runs Google's MediaPipe HandLandmarker model entirely inside the browser via WebAssembly (WASM), processing video locally with zero lag and complete privacy. To prevent natural talking gestures from triggering slide turns accidentally ('Midas Touch' problem) and to avoid shoulder fatigue ('Gorilla Arm' syndrome), AirSlide uses static finger counting poses rather than waving swipes, triggers slide changes instantly, and applies a 2.0-second cooldown lock while the speaker rests their arm. In usability tests with 12 presenters across 850 gestures, AirSlide achieved a 100% completion rate, 96.4% gesture accuracy, and an SUS score of 84.25 (Grade A).

2. Human-Computer Interaction (HCI) Concepts & Design

2.1 Fitts' Law: Making Targeting Effortless

Fitts' Law states that the time needed to hit a target depends on target distance (D) and target width (W): $MT = a + b \cdot \log_2(2D / W)$. In typical mid-air gesture interfaces, aiming at small on-screen buttons is frustrating due to natural hand tremor. AirSlide solves this by removing button targeting completely: the entire camera view is the trigger zone. Because target width is effectively infinite ($W \rightarrow \infty$), difficulty drops to zero ($ID = 0$), allowing slides to change in ~180ms without looking. For the laser pointer mode, an Exponential Moving Average (EMA) filter smooths out hand shakes without causing lag.

2.2 Hick's Law: Simple, Memorable Gestures

Hick's Law shows that decision time increases with the number of choices: $RT = b \cdot \log_2(n + 1)$. AirSlide avoids complicated 15-gesture vocabularies and uses only 4 natural finger-counting gestures: (1) Peace Sign (2 fingers) for Next Slide, (2) Point Up (1 finger) for Previous Slide, (3) Open Palm (5 fingers) for Laser Pointer, and (4) Closed Fist (0 fingers) for Pause. Because finger counts match everyday habits, decision time is under 190ms.

2.3 Norman's Action Cycle: Clear Inputs and Immediate Feedback

Donald Norman identified the Gulf of Execution (how to do an action) and the Gulf of Evaluation (knowing if it worked). AirSlide bridges Execution with clear on-screen gesture hints and simple finger counts. It bridges Evaluation with a real-time 21-point colored hand skeleton, instant 0ms slide turns, and a circular cooldown timer.

2.4 Ergonomics: Preventing Arm Strain and False Triggers

Holding arms in the air tires shoulder muscles ('Gorilla Arm'). AirSlide uses quick-trigger gestures: raise your hand for half a second, then drop it back down to rest. When you lower your arm, moving fingers could trigger another slide change ('Midas Touch'). AirSlide prevents this with a 2.0-second cooldown lock right after every slide turn, completely ignoring hand drops while your arm returns to rest.

3. Usability Heuristics Audit (Nielsen's 10 Principles)

Heuristic	How AirSlide Implements It	Outcome
1. System Status Visibility	Live hand skeleton, FPS counter, detection badge, co	User always sees state
2. Match Real World Conventions	Natural pointing for laser; 1 and 2 finger counts fo	Matches human habits
3. User Control & Freedom	Keyboard arrows always override gestures; Fist pause	Full control always
4. Consistency & Standards	Standard presentation hotkeys, standard PDF controls	Familiar controls
5. Error Prevention	2.0s cooldown lock and 3-frame buffer eliminate fals	<0.1 false clicks/10m
6. Recognition over Recall	On-screen gesture guide is always one click away; li	Zero memorization
7. Flexibility of Use	Supports gestures, keyboard, and mouse; customizable	Great for all users
8. Minimalist Design	Clean dark presentation canvas; HUD controls stay ou	Distraction-free

9. Clear Error Recovery	Helpful alerts for low lighting, camera permission i	Easy troubleshooting
10. Help & Documentation	Interactive practice sandbox (/gestures), on-screen	Self-guided practice

4. Technical Architecture

AirSlide runs 100% locally inside the web browser. The video stream feeds into MediaPipe HandLandmarker running via WebAssembly (WASM) at 30+ FPS, extracting 21 3D hand coordinates. To detect which fingers are open, the app compares 3D distances between the wrist and each fingertip versus knuckles. The state machine cycles simply: IDLE -> DETECTING -> CONFIRMED (3 frames) -> TRIGGER (instant) -> COOLDOWN (2.0s lock) -> IDLE.

5. Usability Testing & Results

We tested AirSlide with 12 participants (4 university lecturers, 4 project managers, and 4 students) across three realistic presentation tasks, recording 850 total gestures:

Testing Metric	Measured Value	Target Benchmark	Outcome
Task Completion Rate	100.0%	>= 95.0%	All users finished
Gesture Recognition Accuracy	96.4% (820/850)	>= 90.0%	High reliability
Total Response Latency	34.9 ms (28.6 FPS)	< 50.0 ms	Instant response
Accidental Triggers while Speaking	0.08 / 10 min	< 0.5 / 10 min	Near zero false clicks
System Usability Scale (SUS)	84.25 / 100	>= 70.0	Grade A (Top 4%)
Time to Learn Gestures	1.12 seconds	< 5.0 seconds	Learned instantly
Physical Arm Strain (NASA-TLX)	18.4 / 100	< 30.0	Zero arm fatigue

6. Conclusion & References

AirSlide shows that touch-free presentation interfaces can be fast, reliable, and completely free of accidental clicks by focusing on core human-computer interaction principles. Using simple finger counting gestures and a 2.0-second safety cooldown enables presenters to speak naturally without being tethered to laptops or dealing with hardware remotes. References: (1) Fitts (1954), J. Exp. Psychol.; (2) Hick (1952), Q. J. Exp. Psychol.; (3) Norman (2013), Design of Everyday Things; (4) Nielsen (1994), Usability Engineering; (5) Shneiderman et al. (2016), Designing the UI; (6) Brooke (1996), SUS Scale; (7) Lugaresi et al. (2019), MediaPipe, arXiv:1906.08172.