



北京航空航天大学
人工智能研究院

Computer Graphics

Lecture 13: Shadow Mapping

潘成伟 (Chengwei Pan)

Email: pancw@buaa.edu.cn

Office: Room B1021, New Main Building

北京航空航天大学, 人工智能研究院

Institute of Artificial Intelligence, Beihang University

This Lecture

- Shadow
- Shadow Mapping
- Issues in Shadow Mapping

Shadows



Shadows



Shadows




Shadows

- Increase scene realism
 - real world has shadows
 - depth perception
 - immersive games
 - dramatic effects
 - spooky effects
- Other art forms use effectively




Shadows

- Shadows indicate spatial relationships between objects e.g. contact with floor.





Without shadow






With shadow

Shadows





Shadow components

- Umbra (本影)
- Penumbra (半影)




Lights and shadows

- Two basic approaches
 - Hard shadows – only point light sources
 - Soft shadows – area light sources




Hard shadow

- Point light source
 - A point is in a shadow if it is not visible from the light source



Soft shadow


- Three types of surface:
 - Shadow: light source completely hidden
 - Penumbra: light source partially hidden
 - Lit: light source completely visible




This Lecture

- Shadow
- Shadow Mapping
- Issues in Shadow Mapping


Common Real-time Shadow Techniques




*Projected
planar
shadows*



*Shadow
volumes*



Light maps



*Hybrid
approaches*

Shadow Mapping

- Image-space shadow determination
 - Two pass algorithm
 - Fast on today's GPUs
 - relatively easy to implement
- Important papers
 - William Reeves, David Salesin, and Robert Cook (Pixar), “Rendering antialiased shadows with depth maps,” SIGGRAPH 87
 - Mark Segal, et. al. (SGI), “Fast Shadows and Lighting Effects Using Texture Mapping,” SIGGRAPH 92

Shadow Mapping Overview


- 1st pass: create a z-buffer from light position
 - assume light source has a “view frustum” (like a camera)
 - render scene from light source’s position
 - save depth values only (shadow map)
- 2st pass: do rendering from eye position
 - render scene as usual
 - inverse map to world space
 - transform vertices to light space, too
 - for each fragment, compare depth
 - $Z_{\text{fragment}} > Z_{\text{shadow_map}} \Rightarrow$ fragment lies in shadow
 - fragment must be in light space!!!

Shadow Mapping

- The Shadow Map Comparison
 - Two values
 - $A = Z$ value from depth map at fragment's light XY position
 - $B = Z$ value of fragment's XYZ light position
 - If B is greater than A , then there must be something closer to the light than the fragment
 - then the fragment is shadowed
 - If A and B are approximately equal, the fragment is lit


Shadow Mapping with a Picture in 2D

- The $A < B$ shadowed fragment case




Shadow Mapping with a Picture in 2D


- The $A \cong B$ unshadowed fragment case



Involved Coordinate Systems



M ...
 V_{cam} ...
 V_{light} ...



1st pass: Create Shadow Map

```
// create the texture we'll use for the shadowmap
glGenTextures(1, &shadow_tex_ID);
glBindTexture(GL_TEXTURE_2D, shadow_tex_ID);
glTexImage2D (GL_TEXTURE_2D, 0, GL_DEPTH_COMPONENT24,
              SM_width, SM_height, 0,
              GL_DEPTH_COMPONENT, GL_UNSIGNED_BYTE, NULL);

// attach texture to an FBO
glGenFramebuffers(1, &shadow_FBO);
glBindFramebuffer(GL_FRAMEBUFFER, shadow_FBO);
glFramebufferTexture2D(GL_FRAMEBUFFER, GL_DEPTH_ATTACHMENT,
                      GL_TEXTURE_2D, shadow_tex_ID, 0);

glDrawBuffer(GL_NONE); // essential for depth-only FBOs!!!
glReadBuffer(GL_NONE); // essential for depth-only FBOs!!!


// then, just before rendering
glBindFramebuffer(GL_FRAMEBUFFER, shadow_FBO);
```

1st pass: Create Shadow Map

- Set view matrix of Light
- Set projection matrix of Light
- Turn off all effects when rendering to the shadow map
 - No textures, lighting, etc.

2st pass: Render from Eye's POV

- Transform vertices to eye space and project as usual
- transform vertices to projected light space
 - Calculate texture coords (shadow map)



- Compare depth => determine whether in shadow
- Shading

Shadow Mapping – Vertex Shader

- $\text{tex_mat} = M_T * M_S * P_{\text{light}} * V_{\text{light}}$

```
#version 140
```

```
uniform mat4 M; // model matrix
```

```
uniform mat4 V_cam; // view matrix for the camera
```

```
uniform mat4 P_cam; // projection matrix for the camera
```

```
uniform mat4 tex_mat;
```

```
in vec4 vertex; // attribute passed by the application
```

```
out vec4 SM_tex_coord; // pass on to the FS
```

```
void main(void) {
```

```
    // standard transformation
```

```
    gl_Position = P_cam * V_cam * M * vertex;
```

```
    // shadow texture coords in projected light space
```

```
    SM_tex_coord = tex_mat * M * vertex;
```

```
}
```

Shadow Mapping – Fragement Shader

```
#version 140
uniform sampler2D shadow_map; // shadow map is just a texture

in vec4 SM_tex_coord; // passed on from VS
out vec4 fragment_color; // final fragment color

void main(void) {
    // perform perspective division
    vec3 tex_coords = SM_tex_coord.xyz/SM_tex_coord.w;


    // read depth value from shadow map
    float depth = texture(shadow_map, tex_coords.xy).r;

    // perform depth comparison
    float inShadow = (depth < tex_coords.z) ? 1.0 : 0.0;
    // do something with that value ...
}
```

Visualizing Shadow Mapping


- A fairly complex scene with shadows

the point
light source




Visualizing Shadow Mapping

- Compare with and without shadows





with shadows



without shadows

Visualizing Shadow Mapping



- The scene from the light's point-of-view



FYI: from the
eye's point-of-view
again

Visualizing Shadow Mapping


- The depth buffer from the light's point-of-view



FYI: from the
light's point-of-view
again


Visualizing Shadow Mapping

- Comparing $\text{Dist}(\text{light}, \text{shading point})$ with shadow map
- Green is where the $\text{distance}(\text{light}, \text{shading point}) \approx \text{depth on the shadow map}$
- Non-green is where shadows should be



Visualizing Shadow Mapping

- Scene with shadows
 - Notice how specular highlights never appear in shadows
 - Notice how curved surfaces cast shadows on each other



This Lecture

- Shadow
- Shadow Mapping
- Issues in Shadow Mapping

Issues in Shadow Mapping


- Field of View
- Self occlusion – Resolution in Z coordinates
- Aliasing – Resolution in XY coordinates.

Field of View

- What if point to shadow is outside field of view of shadow map?

- Use cubical shadow map

- Use only spot lights!




Self occlusion

- comparison of floating point depth
- shadow map resolution (the sampling)




Self occlusion


- Adding a (variable) bias to reduce self occlusion
 - Choosing a good bias value can be very tricky
 - Using the midpoint between first and second depths in Shadow Map



Correct image





Not enough bias



Way too much bias


Aliasing

- Under-sampling of the shadow map
 - aliasing on the border of the shadow
 - one pixel is white, the next is black, without a smooth transition inbetween



Shadow Map Filtering

- Percentage closer filtering
 - Filtering depth values makes no sense
 - Perform shadow test before filtering



Percentage Closer Filtering



- Provides anti-aliasing at shadows' edges
 - 5x5 samples
 - Using a bigger filter produces fake soft shadows
 - Not for soft shadows (PCSS, Percentage Closer Soft Shadow)



Shadow Map

- Advantages
 - Very flexible: can handle arbitrary shadow casters
 - Maps well to hardware
 - It's fast
- Disadvantages
 - Aliasing problems (image based method)
 - Quality depends on the resolution of the shadow map and the numerical precision of the Z-buffer

Projective Texturing - Example




http://developer.nvidia.com/object/Projective_Texture_Mapping.html

Texture matrix

$$\begin{bmatrix} s \\ t \\ r \\ q \end{bmatrix} = \begin{bmatrix} \frac{1}{2} & 0 & 0 & \frac{1}{2} \\ 0 & \frac{1}{2} & 0 & \frac{1}{2} \\ 0 & 0 & \frac{1}{2} & \frac{1}{2} \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \textit{Light} \\ \textit{Frustrum} \\ \textit{(projection)} \\ \textit{Matrix} \end{bmatrix} \begin{bmatrix} \textit{Light} \\ \textit{View} \\ \textit{(lookat)} \\ \textit{Matrix} \end{bmatrix} \begin{bmatrix} \textit{Modeling} \\ \textit{Matrix} \end{bmatrix} \begin{bmatrix} x_0 \\ y_0 \\ z_0 \\ w_0 \end{bmatrix}$$

Projective Texturing

- Use a spotlight-style projected texture to give shadow maps a spotlight falloff



谢谢



北京航空航天大学
人工智能研究院