Problem-Solution fit canvas 2.0

PURPOSE & VISION: Protect student records in ServiceNow with script-controlled ACLs so users see and change only the records their role and branch allow, while administrators keep full access.

Define CS, fit into

1. CUSTOMER SEGMENT(S) CS

Primary: ServiceNow administrators / security administrators responsible for protecting student records.

Secondary: EEE branch users and faculty with the roles bb1 to bb4 who view and manage records, and other users who have no role.

6. CUSTOMER CONSTRAINTS CC

ACLs can be created only after elevating to the security_admin role.

Rules must work with the roles, users and data already in the instance.

Administrators must keep full access to all records.

Each rule must be tested by impersonating every user type.

5. AVAILABLE SOLUTIONS AS

Default table access: any user with basic access can view records; no protection.

Role-only ACLs: block users without a role but cannot filter by field value such as Branch.

Client-side hiding (UI policies): easy to bypass and not real security.

Manual checking or separate lists per branch: slow, error-prone and hard to maintain.

Explore AS, differentiate

Focus on J&P, tap into BE, understand

2. JOBS-TO-BE-DONE / PROBLEMS J&P

Job-to-be-done: Control which records each user can read, create, edit and delete based on role and Branch value.

Problems:

Any user with basic access can view, edit, create or delete sensitive student records.

No record-level rule checks the Branch field value.

Read, create, write and delete permissions are not separated by role.

9. PROBLEM ROOT CAUSE RC

The table has no record-level rules that check a user's role together with a field value (Branch).

Read, create, write and delete operations are not tied to separate roles (bb1 to bb4).

Without a script-controlled ACL, access is not denied by default.

7. BEHAVIOUR BE

Users open the Institution Details list directly (u_institution_details.list) and expect to see and manage their records.

Administrators verify access by impersonating the EEE user, a user without roles and the admin.

When a permission is missing, users notice a missing New button, no inline edit, no Delete action, or an empty list.

Focus on J&P, tap into BE, understand

Identify strong TR & EM

3. TRIGGERS TR

A user opens the Institution Details list or a record form.

A new user, role or branch is added to the system.

A data-protection requirement or audit review of student data.

4. EMOTIONS: BEFORE / AFTER EM

Before: Worried and concerned about data exposure and unauthorized changes.

After: Confident and relieved because bb1 users see only EEE records, users without roles see none, and the admin sees all.

10. YOUR SOLUTION SL

Script-controlled ACLs on u_institution_details:

READ: role bb1, data condition Branch is EEE, advanced script that allows admin and bb1 users.

CREATE: role bb2 (New button).

WRITE: role bb3 (edit records).

DELETE: role bb4 (delete records).

The rules are evaluated automatically on every access and verified by impersonating the EEE user, a user without roles and the admin.

8. CHANNELS of BEHAVIOUR CH

8.1 ONLINE

ServiceNow web UI: Institution Details list and forms, Access Control (ACL) list, Impersonate User option.

8.2 OFFLINE

Discussions with faculty and branch coordinators about who should access which records; institution data-protection policy.

Extract online & offline CH of BE

Problem-Solution fit canvas is licensed under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 license. Created by Daria / Amaltama.com