

# Setters

## Mutability, Problems, DTO and ORM

YEGOR BUGAYENKO

Lecture #4 out of 8

90 minutes

All visual and text materials presented in this slidedeck are either originally made by the author or taken from public Internet sources, such as website. Copyright belongs to their respected authors.



Mutability

Problems

ORM

Read and Watch

Chapter #1:

**Mutability**

[ [Definition](#) Gradients Constant NotConstant NotConstant NotConstant ]

## Which object is immutable?

```
1 class Book {  
2     private String title;  
3     Book(String t) { title = t; }  
4     void setTitle(String t) {  
5         this.title = t;  
6     }  
7     String getTitle() {  
8         return this.title;  
9     }  
10 }  
11 Book b = new Book("Object Thinking");  
12 b.setTitle("It");
```

```
1 class Book {  
2     private final String title;  
3     Book(String t) { title = t; }  
4     void withTitle(String t) {  
5         return new Book(t);  
6     }  
7     String getTitle() {  
8         return this.title;  
9     }  
10 }  
11 Book b1 = new Book("Object Thinking");  
12 Book b2 = b1.withTitle("It");
```

## There are four gradients of immutability

I. Constant

II. Not a Constant

III. Represented Mutability

VI. Encapsulated Mutability

## Gradient I: Constant

```
1 class Book {  
2     private final String t;  
3     Book(String t) { this.t = t; }  
4     String title() {  
5         return this.t;  
6     }  
7 }
```

```
1 Book b = new Book("Object Thinking");  
2 String t1 = b.title();  
3 String t2 = b.title();
```

[ Definition Gradients Constant [NotConstant](#) NotConstant NotConstant ]

## Gradient II: Not a Constant

```
1 class Book {  
2     private final String t;  
3     Book(String t) { this.t = t; }  
4     String title() {  
5         return String.format(  
6             "%s / %s", title, new Date()  
7         );  
8     }  
9 }
```

```
1 Book b = new Book("Object Thinking");  
2 String t1 = b.title();  
3 String t2 = b.title();
```

[ Definition Gradients Constant NotConstant [NotConstant](#) NotConstant ]

## Gradient III: Represented Mutability

```
1 class Book {  
2     private final Path path;  
3     Book(Path p) { this.path = p; }  
4     Book rename(String title) {  
5         Files.write(  
6             this.path,  
7             title.getBytes(),  
8             StandardOpenOption.CREATE  
9         );  
10        return this;  
11    }  
12    String title() {  
13        return new String(  
14            Files.readAllBytes(this.path)  
15        );  
16    }  
17 }
```

```
1 Book b = new Book("Object Thinking");  
2 String t1 = b.title();  
3 b.rename("Elegant Objects");  
4 String t2 = b.title();
```



## Gradient VI: Encapsulated Mutability

```
1 class Book {  
2     private final StringBuffer buffer;  
3     Book rename(String t) {  
4         this.buffer.setLength(0);  
5         this.buffer.append(t);  
6         return this;  
7     }  
8     String title() {  
9         return this.buffer.toString();  
10    }  
11 }
```

```
1 Book b = new Book("Object Thinking");  
2 String t1 = b.title();  
3 b.rename("Elegant Objects");  
4 String t2 = b.title();
```

## Chapter #2: Problems

## Side effects

With a side effect:


```
1 public String post(Request request) {  
2     request.setMethod("POST");  
3     return request.fetch();  
4 }  
5  
6 Request r = new Request("http://...");  
7 r.setMethod("GET");  
8 String first = this.post(r);  
9 String second = r.fetch();
```

Without a side effect:

```
1 public String post(Request request) {  
2     return request  
3         .withMethod("POST")  
4         .fetch();  
5 }  
6  
7 Request r = new Request("http://...")  
8     .withMethod("GET");  
9 String first = this.post(r);  
10 String second = r.fetch();
```

## Thread (un-)safety

```
1 class Books {  
2     private int c = 0;  
3     void add() {  
4         this.c = this.s + 1;  
5     }  
6 }
```



Goetz et al. explained the advantages of immutable objects in more details in their very famous book “Java Concurrency in Practice” (highly recommended!)

```
1 ExecutorService e =  
2     Executors.newCachedThreadPool();  
3 final Books books = new Books();  
4 for (int i = 0; i < 1000; i++) {  
5     e.execute(  
6         new Thread(  
7             () -> {  
8                 books.add();  
9             }  
10        )  
11    );  
12 }  
13 // What is the value of "books.c"?
```

## Temporal Coupling

```
1 Request r = new Request("http://...");  
2 r.method("POST");  
3 String first = r.fetch();  
4 r.body("text=hello");  
5 String second = r.fetch();
```

```
1 Request r = new Request("http://...");  
2 // r.method("POST");  
3 // String first = r.fetch();  
4 r.body("text=hello");  
5 String second = r.fetch();
```

## Identity Mutability

```
1 Date first = new Date(1L);  
2 Date second = new Date(1L);  
3 first.setTime(2L);  
4 assert first.equals(second); // false
```

```
1 Map<Date, String> map = new HashMap<>();  
2 Date date = new Date();  
3 map.put(date, "hello, world!");  
4 date.setTime(12345L);  
5 assert map.containsKey(date); // false
```

## Chapter #3:

# ORM

## Java Persistence API

```
1 @Entity
2 @Table(name = "movie")
3 public class Movie {
4     @Id
5     private Long id;
6     private String name;
7     private Integer year;
8     // ctors
9     // getters
10    // setters
11 }
```

```
1 EntityManager em = getEntityManager();
2 em.getTransaction().begin();
3 Movie movie = new Movie();
4 movie.setId(1L);
5 movie.setName("The Godfather");
6 movie.setYear(1972);
7 em.persist(movie);
8 em.getTransaction().commit();
```



## SQL speaking objects

```
1 interface Movie {  
2     int id();  
3     String title();  
4     String author();  
5 }
```

Here I'm using [jcabi-jdbc](#), an object-oriented wrapper around JDBC data source.

```
1 final class PgMovie implements Movie  
2     private final Source dbase;  
3     private final int number;  
4     public PgMovie(DataSource data, int id)  
5         this.dbase = data;  
6         this.number = id;  
7     public String title()  
8         return new JdbcSession(this.dbase)  
9             .sql("SELECT title FROM movie WHERE id = ?")  
10            .set(this.number)  
11            .select(new SingleOutcome<String>(String.class));  
12     public String author()  
13         return new JdbcSession(this.dbase)  
14            .sql("SELECT name FROM movie JOIN author ON  
15                ↪ author.id = movie.author WHERE movie.id = ?")  
16            .set(this.number)  
17            .select(new SingleOutcome<String>(String.class));
```

Chapter #4:

## Read and Watch

Why use getters and setters/accessors? in Stack Overflow

Objects Should Be Immutable by me

Gradients of Immutability by me

Immutable Objects Are Not Dumb by me

How an Immutable Object Can Have State and Behavior? by me

How Immutability Helps by me

ORM Is an Offensive Anti-Pattern by me