Static

Methods, Attributes, FastJson

YEGOR BUGAYENKO

Lecture #2 out of 8 80 minutes

The slidedeck was presented by the author in this YouTube Video

All visual and text materials presented in this slidedeck are either originally made by the author or taken from public Internet sources, such as web sites. Copyright belongs to their respected authors.

Pre-Test

Methods

Attributes

FastJson as Example

Chapter #1:
Pre-Test

[Entities]

How many static "entities" do you see here?

```
class FigureUtils {
  static final float PI = 3.1415926;
  static final FigureUtils INSTANCE;
  static {
    INSTANCE = new FigureUtils();
  }
  private FigureUtils() { /* empty */ }
  static float perimeter(Circle c) {
    return 2 * c.radius * PI;
  }
}
```

How many?

- three
- four
- five
- six
- maybe seven

Chapter #2:

Methods

What Static Methods Are For?

```
class Circle {
  public float radius;
}

class Circle {
  public float radius;
  float area() {
    return radius * radius * 3.14;
  }

return c.radius * c.radius * 3.14;
}

public float radius;
  float area() {
    return radius * radius * 3.14;
  }
}
```

Most notable Java examples [Bugayenko, 2015a]: FileUtils, IOUtils, and StringUtils from Apache Commons; Files from JDK 7; Iterators from Google Guava.





"Traditional computer thinking treats data as passive and helpless, manipulated and moved by active procedures. Procedures tend to be egocentric and think that all data, its definitions and its values, are properly determined by the procedure currently using that data. The result is data that is inconsistent in definition, inconsistent in value, inaccessible because some other procedure has possession, or needlessly duplicated."

— David West. *Object Thinking*. Pearson Education, 2004. doi:10.5555/984130

What's Wrong with "Utils"?

- 1) They are unbreakable dependencies
- 2) They are eager, not lazy
- 3) They are not cohesive

1) Tight Coupling

```
void paintIt(Circle c) {
  float s = GeometryUtils.calcArea(c);
  float p = s * 5.55;
  // paint it using the "p"
  }
  void paintIt(Circle c) {
   float s = c.area();
   float p = s * 5.55;
   // paint it using the "p"
  }
}
```

Which snippet is easier to test? Try to write a test for the first one, expecting s to be equal to 42.0 [Bugayenko, 2014].

2) Imperative, not Declarative

```
void paintIt(Circle c) {
  float s = GeometryUtils.calcArea(c);
  if (t) { return; }
  float p = s * 5.55;
  // paint it using the "p"
  }
  void paintIt(Circle c) {
  float s = new AreaOf(c);
  if (t) { return; }
  float p = s * 5.55;
  // paint it using the "p"
  }
}
```

Which snippet is more eager to calculate the area of the circle? Which one does it when it's really necessary? [Bugayenko, 2015b]

3) Low Cohesion

```
class GeometryUtils {
    static float calcArea(Circle c);
    static float calcPerimeter(Circle c);
    static float calcSinus(Angle a);
    static float calcCosinus(float s);
    // and many more...
    // and many
```

Which class looks more cohesive to you, the utility class GeometryUtils or the Circle?

Chapter #3:
Attributes

[Literals Singletons]

Public literals

We must solve the problem of functionality duplication, not just data duplication [Bugayenko, 2015c].

[Literals Singletons]

Singletons

Forget about singletons; never use them. Turn them into dependencies and pass them from object to object through the operator new [Bugayenko, 2016].

Chapter #4:

FastJson as Example

[JSONPath]



```
public int size(Object rootObject) {
    if (rootObject == null) {
        return -1;
    }

    init();

    Object currentObject = rootObject;
    for (int i = 0; i < segments.length; ++i) {
        currentObject = segments[i].eval(this, rootObject, currentObject);
    }

    return evalSize(currentObject);
}</pre>
```

```
public static int size(Object rootObject, String path) {
    JSONPath jsonpath = compile(path);
    Object result = jsonpath.eval(rootObject);
    return jsonpath.evalSize(result);
}
```

Some mind-blowing statistics:

- 3 constructors
- 1 interface implemented
- 59 methods at JSONPath
- 4,363 lines of code
- 34 inner static classes
- 74 times static keyword

https://github.com/alibaba/fastjson/blob/master/src/main/java/com/alibaba/fastjson/JSONPath.java

[JSONPath]

Bibliography

Yegor Bugayenko. OOP Alternative to Utility Classes. https://www.yegor256.com/140505.html, 5 2014. [Online; accessed 08-07-2024].

Yegor Bugayenko. Utility Classes Have Nothing to Do With

Functional Programming.

https://www.yegor256.com/150220.html, 2 2015a. [Online; accessed 08-07-2024].

Yegor Bugayenko. Composable Decorators vs. Imperative Utility Methods.

https://www.yegor256.com/150226.html, 2 2015b. [Online; accessed 08-07-2024].

Yegor Bugayenko. Public Static Literals ... Are Not a

Solution for Data Duplication.

https://www.yegor256.com/150706.html, 7 2015c. [Online; accessed 08-07-2024].

[Offiffic, accessed 00 07 2024].

Yegor Bugayenko. Singletons Must Die.

https://www.yegor256.com/160627.html, 6 2016. [Online; accessed 08-07-2024].

David West. *Object Thinking*. Pearson Education, 2004. doi:10.5555/984130.