

Symbolic Execution

...

YEGOR BUGAYENKO

Lecture #8 out of 10

90 minutes

All visual and text materials presented in this slidedeck are either originally made by the author or taken from public Internet sources, such as website. Copyright belongs to their respected authors.



In Theory

In Practice


Concolic Execution

Chapter #1:

In Theory

Control Flow Graph

```
int f(int x) {  
    int a = x * 2;  
    a = a - 4;  
    if (a == 0)  
        error("Div by zero!");  
    return 42 / a;  
}
```



Path Feasibility

A path is feasible if there exists an input \mathcal{I} to the program that covers the path; i.e., when program is executed with \mathcal{I} as input, the path is taken.


```
int f(int x) {  
    int a = x * 2;  
    a = a - 4;  
    if (a == 0)  
        error("Div by zero!");  
    return 42 / a;  
}
```



Infeasible Path

A path is infeasible if there exists no input \mathcal{I} that covers the path.

```
int f(int x) {  
    int a = x * x;  
    if (a < 0)  
        error("Too small!");  
    return 42 / a;  
}
```



Symbols


```
int f(int x) {  
    int a = x * 2;  
    a = a - 4;  
    if (a == 0)  
        error("Div by zero!");  
    return 42 / a;  
}
```



Path Conditions

Path condition is a condition on the input symbols such that if a path is feasible its path-condition is satisfiable.

```
int f(int x) {
  int a = x * 2;
  a = a - 4;
  if (a == 0)
    error("Div by zero!");
  return 42 / a;
}
```



Constraint Solver

A constraint solver is a tool that finds satisfying assignments for a constraint, if it is satisfiable.

A solution of the constraint is a set of assignments, one for each free variable that makes the constraint satisfiable.

Constraint:

$$x \mapsto X, a \mapsto 2X - 4$$
$$2X - 4 = 0$$

Solution:

$$X = 2$$

Chapter #2:

In Practice

SAT Solvers

SAT solver is a computer program which aims to solve the Boolean satisfiability problem: whether the variables of a given Boolean formula can be consistently replaced by the values TRUE or FALSE in such a way that the formula evaluates to TRUE.

Examples:

$$a \wedge b \rightarrow \dots$$

$$a \wedge b \wedge \neg a \rightarrow \dots$$

$$a \vee b \vee \neg a \rightarrow \dots$$

$$a \wedge (\mathbf{ff} \vee \mathbf{tt}) \rightarrow \dots$$

All expressions are in Boolean logic.

SMT Solvers

SMT solver is a computer program which aims to solve the satisfiability modulo theories: determine whether a mathematical formula is satisfiable.

Examples:

$$a < 5 \wedge a > 3 \rightarrow \dots$$

$$a < 5 \wedge f(a) > 42 \rightarrow \dots$$

$$a < 5 \vee a > 10 \vee \neg a \rightarrow \dots$$

$$a \wedge \mathbf{ff} \wedge x = 7 \rightarrow \dots$$

SMT solvers: Z3, cvc5, Yices, and many more...

Chapter #3:

Concolic Execution

In Theory In Practice Concolic Execution
[...]

14/15



In Theory In Practice Concolic Execution
[...]

15/15

...