



Annual network prices report

1 July 2010 – 30 June 2011

countryenergy

TABLE OF CONTENTS

1	BACKGROUND	4
1.1	Background	4
1.2	Our Proposal.....	4
1.3	Our Business.....	4
1.4	Network Investment and Challenges	5
2	PRICES FOR NETWORK DISTRIBUTION SERVICES.....	6
3	FORTHCOMING CHANGES IN NETWORK TARIFFS	7
4	REGULATORY COMPLIANCE	7
4.1	Overview	7
4.2	Weighted average price cap	7
4.3	Transmission-related cost recovery arrangements.....	8
4.4	Consumer price index.....	8
4.5	Climate change levy	8
4.6	Limits on network price movements.....	8
5	IMPACT OF FORTHCOMING CHANGES TO NETWORK TARIFFS	8
5.1	Expected network price increases 2010/11 to 2013/14.....	10
6	PRICING PRINCIPLES AND COST ALLOCATION.....	10
6.1	Network prices based on incremental and stand-alone cost principles	11
6.2	Network prices based on fully distributed cost principles.....	11
6.3	Network customer classes.....	11
6.3.1	Standard customer classes	12
6.3.2	Locational specific customer class	12
6.4	Overview of network pricing methodology	12
6.5	Calculation of annual revenue requirements	13
6.6	Network cost drivers	13
6.6.1	Customer related cost driver	13
6.6.2	Demand-related cost driver	14
6.6.3	Energy related cost driver	14
6.6.4	Common service costs	14
6.7	Network price components.....	14
6.7.1	Demand charges	15
6.7.2	Energy charges (network usage charges).....	15

6.7.3	Network access charges (fixed charges)	16
6.8	Fully distributed cost of supply modelling	16
6.8.1	Allocation of network costs to asset cost pools	16
6.8.2	Network asset categories (cost pools)	17
6.9	Cost allocation to asset categories	18
6.9.1	Asset related costs	18
6.9.2	Conversion of cost pools to usage-based network prices	19
6.9.3	CRNP customer class	19
6.9.4	Standard customer classes	20
6.9.5	Controlled load customer class	20
6.10	Allocation of transmission network costs	20
6.11	Incremental and stand alone cost allocation process	22
6.12	Setting of price structures and levels	23
6.12.1	Factors considered	23
6.12.2	Network tariff classes	23
6.12.3	Cost reflective network prices and cross subsidies	24
7	EXPECTED LEVELS OF SERVICE AND PROJECTED CAPITAL EXPENDITURE PROJECTS	25
7.1	Capital expenditure projects	25
7.1.1	Growth in demand and system augmentation	26
7.1.2	Asset renewal and replacement	26
7.1.3	Non-system requirements	27
7.2	Expected levels of service for the coming year	27

1 BACKGROUND

1.1 Background

The Australian Energy Regulator (AER) has economic regulation over distribution network service providers in New South Wales and requires Country Energy to publish an Annual Network Prices Report. This report establishes a process of price notification and review by AER for annual price changes.

The Annual Network Prices Report complies with the requirements of the NSW distribution determination 2009-10 to 2013-14 (the determination), the Electricity DNSP's annual information reporting requirements, section 6.18 of the transitional National Electricity Rules (the Rules) and specifically addresses the following:

- ✓ Prices for network distribution services
- ✓ Forthcoming changes in network prices
- ✓ Compliance with the regulatory arrangements relating to limits on price and revenue movements
- ✓ Impacts of the proposed changes on customers
- ✓ Pricing principles and the allocation of costs
- ✓ Expected levels of service and projected capital expenditure
- ✓ Expected consumption for major customer classes and maximum demand for the coming year.

Enquiries regarding this document should be directed to:

Network Pricing
PO Box 718
Queanbeyan NSW 2620
Email: networkpricing@countryenergy.com.au
Fax: (02) 6589 8483

1.2 Our Proposal

Country Energy is proposing an overall increase in average prices for network distribution services from 1 July 2010 of 19.3 per cent nominal. This increase consists of distribution services, CPI, transmission charges and climate change levy and each component is discussed in this report.

Country Energy is not proposing any changes to existing price structures, application of these price structures or associated criteria. The number of prices applicable to new connections, and the number of prices classed as obsolete and not available to new connections will not change. However a transitional demand tariff has been introduced for certain customers who consume more than 160MWh and are therefore required to move from a standard time of use tariff to a demand based tariff. Application of this tariff will be limited and only available for a maximum period of 12 months.

1.3 Our Business

Country Energy operates Australia's largest electricity network spanning 95 per cent of New South Wales, with over 200,000 kilometres of powerlines and 1.4 million power poles spanning diverse terrain and climatic conditions from subtropics to alps and plains.

Country Energy is a leading Australian energy business owned by the NSW Government, with around 4,500 employees serving almost 800,000 customers. Country Energy has a decentralised regional structure operating in 146 customer and field service centres and eight regional offices, assuring we are responsive to

local priorities and achieve consistently strong customer satisfaction levels. We are a leader in safety, with the lowest Lost Time Injury Frequency Rate (LTIFR) of any New South Wales electricity distributor.

The figure below illustrates our distribution area, which covers approximately 95 per cent of New South Wales.



Figure 1 Country Energy's distribution area

1.4 Network Investment and Challenges

The AER has approved Country Energy's \$3.8 billion (\$3,840 million) five year network investment program and \$2.1 billion (\$2,052 million) over five years to operate and maintain Country Energy's electricity network and services.

The network investment program builds on the \$2.1 billion already invested in essential infrastructure over the preceding five years. These programs ensure Country Energy can continue to deliver reliable, efficient and safe power to our growing customer base.

This investment recognises Country Energy needs to make further significant network investments to meet growth demands and safety requirements, renew ageing assets, deliver better reliability in the future and manage input cost increases such as fuel, skilled labour, materials and environmental standards which are increasing the overall costs of network projects and investments. It also addresses the challenges of:

- Much of Country Energy's 200,000 kilometre power network is across a vast and unique operating environment which has been in service for decades - to continue to deliver safe, reliable power we need to replace and upgrade key network equipment
- Many country and coastal centres are experiencing high population growth - the network is moving from high demand in winter to even higher demand in summer, predominantly driven by air conditioning
- Planning for Country Energy's Intelligent Network (IN) project is well advanced and trials and development of smart metering continues in New South Wales. Smart metering will improve network efficiency, and help customers manage their energy costs and carbon emissions via real-time updates on energy consumption and support for the growth of renewables like solar power. The Ministerial Council on Energy (MCE) has endorsed a distributor led rollout of smart metering where a jurisdictional implementation date has been set and where the benefits outweigh the costs.

2 PRICES FOR NETWORK DISTRIBUTION SERVICES

Country Energy provides network distribution services to all electricity customers connected within our distribution area. Customers may choose any retailer.

Network distribution services are those services performed by Country Energy to provide access to our power supply network. Those services are principally the ownership, planning, design, construction, operation and maintenance of the electricity distribution network - consisting of equipment such as poles, wires and substations - to supply a safe and reliable power supply.

The conditions under which these network services are provided are contained in Country Energy's Standard Form Customer Connection Contract. A copy of this agreement is available at www.countryenergy.com.au or on request by phoning 13 23 56.

Network prices are a use of system charge for the use of Country Energy's electricity distribution network and also include a charge for the use of the transmission system.

Network prices are subject to annual review in accordance with pricing determinations by the AER. The Network Price List is available on Country Energy's website www.countryenergy.com.au or on request. The network price list contains network prices effective from 1 July 2010. There is an additional price list for monopoly fees and miscellaneous charges effective from 1 July 2009.

Network access is under the terms and conditions contained within our Standard Form Customer Connection Contract. A negotiated network connection agreement is also available where specific contractual conditions are required.

Network distribution services supplied by Country Energy and covered by this Network Prices Report include:

- Distribution use of system services
- Private powerline inspections and customer installation inspections
- Miscellaneous services
- Monopoly services associated with contestable works
- Emergency recoverable works

3 FORTHCOMING CHANGES IN NETWORK TARIFFS

Country Energy is proposing an average increase in prices for network distribution services of 19.3 per cent. We believe our proposal will assist in establishing a financially sustainable level of network revenue that will ensure Country Energy has sufficient resources to meet its obligations, maintain its significant asset investment and to continue to efficiently deliver network distribution services to meet increasing customer expectations.

Country Energy is not proposing any changes to:

- application of price structures
- associated criteria
- the number of prices applicable to new connections
- the number of prices classed as obsolete and not available to new connections

A transitional demand tariff has been introduced for certain customers who consume more than 160MWh and are therefore required to move from a standard time of use tariff to a demand based tariff. Application of this tariff will be limited and only available for a maximum period of 12 months.

Country Energy has prepared this proposal in accordance with the determination and the Rules. All changes proposed are within the limits on price movements set out in the determination and are discussed further throughout this document.

4 REGULATORY COMPLIANCE

4.1 Overview

The AER has determined the regulatory arrangements that apply to network distribution services over the regulatory period and how it will regulate charges for network distribution services and other fees that electricity distributors are entitled to charge over the regulatory period. This annual network prices report explains how Country Energy's prices meet the regulatory arrangements, including limits on network price movements, weighted average price cap control formula and provide for the recovery of transmission related payments. Further detail on each of these items is contained below.

4.2 Weighted average price cap

Charges for network distribution services (distribution use of system (DUOS) prices, miscellaneous charges, monopoly fees and charges for recoverable works for emergency services) are regulated in accordance with a weighted average price cap (WAPC) formula which includes a CPI-X factor. The WAPC operates by restricting the (weighted) average change in Country Energy's prices to a limit (the 'X-factor') determined by the AER. The CPI-X factor is used to achieve a price path that ensures revenue raised reflects underlying costs.

The average allowable increase in distribution prices (or X-factor) for 2010-11 has been limited by the AER to 17.9 per cent (real \$2009-10). The x-factor is contained in the formula for the WAPC and determines how prices for network distribution services can change in real terms over the regulatory period.

In setting prices for the upcoming year, Country Energy must ensure that the average price change relative to the prices it is charging satisfies the constraint. Country Energy has applied the weighted average price control formula set out in clause 4.5 of the determination to each of the DUOS prices, miscellaneous service charges and monopoly service charges for 2010-11.

As part of the annual price setting process, the AER was provided with all supporting calculations and information including audited quantities necessary to demonstrate compliance with all of the requirements of clause 4.6 and appendix J of the determination. The application of the weighted average price cap formula

results in an average price increase of 20.05 per cent for network distribution services in accordance with the determination, and the AER has verified compliance with the determination.

4.3 Transmission-related cost recovery arrangements

The AER allows Country Energy to recover transmission-related costs by setting transmission cost recovery (TUOS) prices to recover:

- Transmission charges paid to transmission network service providers
- Avoided TUOS payments to embedded generators calculated in accordance with the Rules
- Inter-distributor transfer payments to other network distribution businesses

Clause 4.7 (referring to clause 6.12.1 of the transitional chapter 6 rules) and appendix I of the determination requires Country Energy to demonstrate to the AER compliance with transmission cost recovery requirements. As part of the 2010-11 price approval process, the AER has been provided with the expected cost of transmission related payments. In accordance with appendix I of the determination, Country Energy develops transmission cost recovery prices, using the methodology outlined in section 6 of this report, to recover the expected cost of transmission-related payments.

Country Energy will also be recovering avoided TuOS payments to generators who have advised they will be supplying energy into our Network. As this effectively represents less transmission from Transgrid's network Country Energy are required to pay avoided TuOS to the generators under section 5.5 of the Rules.

The total transmission revenue Country Energy requires in 2010-11 has increased by 17.4 per cent from the forecast amount for 2009-10.

4.4 Consumer price index

The CPI used in setting prices for 2010-11 is 1.82 per cent, the December four quarter all major cities CPI as published by the Australian Bureau of Statistics.

4.5 Climate change levy

The minister for department of Climate Change has legislated that Country Energy contribute \$35 million to the climate change levy in 2010-11. Country Energy is permitted to collect this contribution from its customers through network prices.

4.6 Limits on network price movements

In 2010-11 a side constraint of $CPI-X + 2$ percent applies to DUOS for each tariff class. The average increase in DUOS charges for each tariff class is less than this constraint.

5 IMPACT OF FORTHCOMING CHANGES TO NETWORK TARIFFS

This section demonstrates the impact of the forthcoming changes in Network Tariffs on typical customers' bills, including disclosing forecast average prices (based on typical account categories).

The following table demonstrates the average impact of the proposed prices to the residential and business customer classes. Displayed below are the average increases expected for each of the consumption types for residential and business network prices. These include standard supply, time of use, controlled load, and demand network prices for business customers.

Figure 2 Average increases for domestic and business customers

		Average annual MWh	Average annual current account	Average annual proposed account	Average increase per customer	Average increase (%)	Average current c/kWh	Average proposed c/kWh
Residential	Continuous	5.35	\$709.46	\$853.33	\$143.87	20.3%	13.27	15.96
	Time of Use	15.95	\$1,331.81	\$1,625.08	\$293.27	22.0%	8.35	10.19
	Controlled Load 1	2.80	\$69.05	\$80.88	\$11.83	17.1%	2.47	2.89
	Total	24.1	\$2,110.32	\$2,559.29	\$448.97	21.3%	8.76	10.62
Non Residential	Continuous	14.41	\$2,150.47	\$2,551.94	\$401.48	18.7%	14.93	17.71
	Time of Use	69.52	\$5,460.52	\$6,516.90	\$1,056.38	19.3%	7.85	9.37
	Controlled Load 2	2.71	\$136.04	\$161.65	\$25.61	18.8%	5.02	5.96
	Demand	674.23	\$61,366.06	\$72,782.29	\$11,416.23	18.6%	9.10	10.79
	Total	760.87	\$69,113.08	\$82,012.78	\$12,899.70	18.7%	9.08	10.78

The average domestic customer, without controlled load, in Country Energy's distribution area will see an increase of approximately \$143.87 or 20.3 per cent for the 2010-11 year based on an annual consumption of 5.35 MWh.

The average small business customer in Country Energy's distribution area will see an increase of approximately \$401.84 or 18.7 per cent for the 2010-11 year based on an annual consumption of 14.41 MWh.

A typical residential customer living in Country Energy's distribution area would generally be connected to the following network prices:

- BLNN2AU: Residential non-TOU
- BLNC1AU: Residential controlled load 1

Provided below is an analysis of the impacts of price increases for a low usage customer and a typical usage customer.

Figure 3 Impact of price increases for typical residential customers of Country Energy

Customer type	% controlled load	2009-10 Quarterly network bill	2010-11 Quarterly network bill	Increase in quarterly network bill
Low usage (3,5000 kWh)	40%	\$106.15	\$127.57	\$21.51
Typical usage (6,000 kWh)	40%	\$148.53	\$178.29	\$29.77

A typical small business customer operating in Country Energy's distribution area would generally be connected to the following network price:

- BLNN1AU: Urban business non-TOU

Provided below is an analysis of the impacts of price increases for a customer that consumes 20 MWh per annum and a customer that consumes 40 MWh per annum.

Figure 4 Impact of price increases for typical business customers of Country Energy

Customer type	2009-10 Monthly network bill	2010-11 Monthly network bill	Increase in Monthly network bill
20 MWh	\$242.51	\$288.72	\$46.21
40 MWh	\$468.94	\$560.75	\$91.81

5.1 Expected network price increases 2010/11 to 2013/14

For the remainder of the regulatory period Country Energy's price changes will be subject to the distribution X factors shown below in Figure 5. These X factors form part of the Australian Energy Regulator's 2009 Revenue Determination for NSW DNSPs, and drive annual escalations under the weighted average price cap. Price changes will also be subject to increases in transmission charges and recovery for CPI is also allowed under the weighted average price cap formula. Included in Country Energy's network revenue is an allowance for recovery of transmission related costs and the NSW Government's Climate Change Fund.

Figure 5 Transmission and distribution X factors for Country Energy

X - factors	2010-11	2011-12	2012-13	2013-14
Distribution	-17.90%	-17.90%	-14.75%	3.99%
Transmission	-17.54%	-5.61%	-5.61%	-5.61%

As part of complying with Clause 6.18.9(3) of the Rules, Country Energy has evaluated price trends for the regulatory control period. The results of this evaluation are provided in our Statement of Expected Price Trends 2010-11 to 2013-14 which is also available on our website. The forecasts of CPI, the Climate Change Fund and recoveries of transmission related costs are likely to change over the regulatory control period and cannot be determined with certainty. Distribution X - factors may also change if there is a pass through event.

6 PRICING PRINCIPLES AND COST ALLOCATION

Costs of the shared distribution network are characterised by economies of scale leading to large and lumpy investments, which occur at irregular intervals and generally have long lives. From a purely economic efficiency perspective, prices should reflect the marginal cost of providing customers with access to the electricity network. The long run marginal cost (LRMC) approach to pricing achieves economic efficiency by signalling the future cost of the next increment of network asset investment. Network prices would in this case send an economic signal to customers of the costs of the next increment of load and provide locational signals for future investment.

Country Energy strives to send customers accurate network price signals, which reflect the marginal costs of supply. However, the LRMC approach to pricing is difficult to implement. Also, network pricing based on economically efficient marginal costs do not recover the long run average costs, except where there is network congestion. This creates a significant tension between economically efficient prices and prices necessary for the commercial sustainability of the distributor.

A practical approach to minimising distortions is to recover the gap between marginal and average costs in a manner which does not vary between locations, contains a fixed component - and to the extent that a variable

component is necessary - includes both energy and demand components. Electricity prices for the great majority of customers are averaged in a conventional distributed cost of supply model as detailed below. Large individual customers and standard customer classes receive average network prices consisting of combinations of energy and demand price structures.

Country Energy has developed a cost of supply allocation and tariff structure model ('CoS Model') that is used to allocate the appropriate network costs that are to be recovered from network customers through network use of system charges. The CoS Model has been designed to provide a transparent and defensible allocation of network costs based on pricing principles and the methodology and pricing strategies described in this document.

6.1 Network prices based on incremental and stand-alone cost principles

There are two principles that can be used to test for cross subsidisation in monopoly services.

- **Stand-alone costs**
Cross subsidisation exists when customers pay more for a service than the costs another firm would incur if it served those customers on a stand-alone basis.
- **Incremental costs**
Cross subsidies do not exist when the revenues received for a service is less than the stand-alone cost, or are greater than the incremental or marginal cost of providing the service. The incremental cost test is appropriate when the goal is to show that prices for services are not 'unfair'.

The range of prices that lies between incremental cost and stand-alone cost is known as the subsidy-free pricing zone. Cross subsidisation occurs when prices lie outside this zone. Country Energy has developed a marginal cost and standalone CoS model for this purpose. This document provides details of the methodology used, incremental cost and standalone cost of supplying network distribution services to customers connected to Country Energy's network.

6.2 Network prices based on fully distributed cost principles

Network costs are largely fixed and sunk, and due to the meshed nature of electricity distribution networks, pricing must involve a substantial degree of averaging.

For these reasons, Country Energy's approach to allocating costs to customers is primarily founded on equity considerations, where there is some degree of averaging present in the calculation of standard network prices for the majority of customers belonging to general customer classes.

Country Energy has adopted the average or fully distributed cost approach for the allocation of the revenue requirement. Network revenue as a cost is allocated to standard customer classes based on the use of network assets, with prices averaged by customer class. This pricing policy is driven mainly by equity considerations. It is applied to individual prices for large customers and standard published network prices.

We believe this average allocation approach best reflects the manner in which costs are incurred by customer classes and provides equitable and reasonably efficient outcomes.

6.3 Network customer classes

Distribution services are provided to a range of tariff or customer classes. Segregation of customers by class is commonly carried out to assess their relative impact on network costs.

6.3.1 Standard customer classes

All but the largest Country Energy customers have network prices that are average for their customer class. Different customer classes have different consumption profiles and therefore impact differently on network costs.

Customer classes have been established taking into consideration historical pricing structures, existing metering and the cost effectiveness of metering options and connected voltage level.

Historically, customer classes have been grouped according to end use such as domestic, business, commercial, or industrial purposes. However, network costs are not necessarily driven by the end use of electricity but rather by the voltage of supply, the capacity being held in readiness for demand and the time of day that this demand occurs.

The assets required to provide network distribution services to each customer class is a major cost driver. Customer segmentation is carried out in different ways, largely dependent upon the availability of detailed cost information. It has been possible, to some degree, to segregate network costs by voltage level. Therefore, Country Energy's customer classes vary in accordance with the voltage level at which electricity is taken from the network.

Country Energy also offers controlled load services.

The definitions of network customer classes are detailed in section 6.12.2 below and can also be found in Country Energy's Network Price List upon approval by the AER. This list is updated each year or as required in consultation with AER.

6.3.2 Locational specific customer class

For large customers, Country Energy may provide an individual price which is a cost reflective network pricing (CRNP) applicable to the location of the customer's supply point.

The CRNP process is a cost allocation mechanism based on the structure of the present network using a fully distributed cost of supply analysis and is a reasonable assessment of long run incremental pricing for the individual assets through which energy is transported to the individual customer. The CRNP approach fulfils the requirements for an equitable sharing of past and future costs. This price comprises an allocation of the costs associated with only those assets used by the customer. The calculation of CRNP charges involves analysis of the network to which the customer is connected to determine the allocation of asset-related revenue recovery in proportion to the peak utilisation of the relevant assets. CRNP is assessed annually to allow the application of new prices by 1 July each year.

6.4 Overview of network pricing methodology

Country Energy has separated each network price into a DUOS price for providing distribution use of system services to distribution customers and a separate transmission cost recovery (TUOS) price. The methodology adopted by Country Energy for setting network prices is summarised as follows:

1. Project total network revenue requirements (total network cost) for the upcoming year taking into account distribution revenue derived from the WAPC form of regulation, the cost of transmission related payments, transmission under and over recovery balance, climate change levy and the forecast growth in the network.
2. Model fully distributed costs.
3. Model the long run marginal and stand-alone cost of supply to each customer class to establish the 'subsidy free zone'. The long run marginal cost of supply to customer classes is based on the usage of the network and other network services and the impact on future

capital expenditure made by each customer class. The stand-alone cost of supply is based on establishing an alternative source of supply to the customer class.

4. Assess the existing network prices to establish whether they fall between the marginal and stand-alone cost of supply.
5. Establish medium term price paths to move existing network prices steadily toward the subsidy free zone, whilst complying with the economic regulatory arrangements of the Determination and Country Energy's medium term network pricing strategy to progressively equalise prices across the network.

6.5 Calculation of annual revenue requirements

The first stage in the process involves calculating Country Energy's total revenue requirements based on the cost of providing network distribution services.

The form of economic regulation affects the annual revenue that Country Energy is able to receive for the provision of network services and the setting of prices. DUOS prices, miscellaneous charges, monopoly fees and charges for recoverable works for emergency services are regulated by the AER under a WAPC. The WAPC operates by restricting the weighted average change in Country Energy's prices to a limit - the 'X-factor' - determined by the AER.

To set the X-factor values for the WAPC - that is the amount by which average distribution prices can change in each year of the regulatory period - the AER undertook a cost building block analysis to determine the notional revenue requirement for each year of the regulatory period for Country Energy. The building block approach sets the base revenue and has been assessed on the basis of a wide range of factors including network operations, asset valuation, commercial risks, appropriate costs of capital, relative levels of efficiency, and reliability and quality of supply.

Then, taking into account Country Energy's growth forecast, the AER converted the notional revenue requirements to calculate the amount by which current average prices would need to rise or fall in each year of the regulatory period to generate the required revenue.

The Determination allows Country Energy to increase average distribution prices by CPI +17.9 per cent for 2010-11.

6.6 Network cost drivers

The costs drivers of owning and operating Country Energy's electricity distribution network are diverse and are driven by customer related, demand related and energy related cost drivers and common service costs.

It is appropriate to allocate and recover costs, to some degree, from customer classes in accordance with these cost drivers as discussed below.

6.6.1 Customer related cost driver

These costs relate to the individual customer and as such the number of customers drives total costs. The individual cost can vary with the size of the customer but not necessarily in proportion to energy or demand requirements. Customer related costs cover the maintenance of service connection equipment (such as metering, load control receivers and service lines) and the 'administrative' costs arising from the connection of a customer to the network such as meter reading, billing, collection, price setting and network-related customer account management. For standard customer classes these costs are averaged across all customers and are generally reflected in the Network Access Charge of the standard network prices.

6.6.2 Demand-related cost driver

The capacity of a distribution or transmission network is developed to serve the demand for electricity that customers impose upon it. The available capacity of the network is driven by the diversified demand-related usage of the low voltage system (not including service mains), distribution substations and of the higher voltage distribution and sub-transmission networks. Customer loads have an incremental effect on the overall and local diversified load pattern.

The demand served by the network is the most important driver of costs in the provision of network services containing the bulk of the direct asset-related costs. They are often referred to as maximum demand-related costs. It consists of the costs of financing and constructing the provision and maintenance of plant and equipment necessary to supply the cumulative demand of customers. These costs are principally fixed, proportional to the size of the peak demand supplied.

Network augmentation to increase capacity takes place at different levels throughout the network - subtransmission, high voltage, low voltage mains and substations. The need to augment the network arises when the power flow exceeds the capacity available in that part of the network.

At higher level voltages, augmentation of the network is necessary from time to time, to maintain adequate supply capacity and to maintain quality and reliability standards. Investment in the capacity of the network is achieved by a series of discrete, incremental augmentations and extensions. However, augmentation usually involves the provision of lumpy expensive network assets that have long lives. The cost of providing a given overall network capacity is made up of the sum of many of these augmentations in separate parts of the network.

Where demand is measured these costs can be directly applied, but for installations with energy only metering, it is common to regard energy consumption as a surrogate for demand, particularly for those standard customer classes with a predictable and relatively limited range of load profiles.

Demand related costs are distributed between all those customers who utilise the network so that each is allocated an equitable share according to their contribution to the total demand-related costs. Country Energy uses a mathematical process called the "Method of Intercepts" to allocate demand-related costs according to the relative contribution per customer class to the network maximum demand.

6.6.3 Energy related cost driver

These costs tend to be less influenced by a customer's capacity requirements. They include costs which are related to the utilisation of the network and include the costs of general operation and maintenance of the shared network and referred costs such as transmission charges and demand management payments. These costs are most equitably allocated according to the amount of energy used by the customer (kilowatt hours consumed).

6.6.4 Common service costs

These costs relate to the provision of corporate services which are provided internally in support of network distribution services and other business units and cannot be reliably allocated by any one of the above three cost drivers. In order to carry out a fully distributed cost analysis, these costs are distributed according to one or a combination of the above drivers.

6.7 Network price components

Country Energy's network prices contain the following price components, also referred to as charging parameters.

6.7.1 Demand charges

The demand imposed by larger customers has a more direct and significant impact on future network costs than smaller customers. The diversity of demand is more significant for smaller customers. It is therefore appropriate that larger customers should have pricing based on measured demand or supply capacity where the costs recovered through the demand charge represent those that could be directly impacted by the customer's demand on the network.

Demand based prices provide the customer with a clear signal relating to the benefits of load management to improve their average load and avoid short duration load peaks. Customer load factors can vary considerably from mining customers, with load factors in the range of 0.7-0.8, to irrigation loads with annual load factors less than 0.3. The load factor is a measure of how "peaky" a load is and therefore the nature of the demand placed on the network. A load factor of 1 indicates a constant flat load, which therefore uses the network in a consistent fashion regardless of the time of day or season. The \$/kWh or per unit network charge for a customer with a low load factor would be significantly greater than for high load factor customers. Poor load factor customers on a demand price would, as a consequence, need to alter their usage patterns, if feasible, to minimise costs. Customers with typical load factors will generally find the standard demand time of use price results in a much lower average network charge.

Customers' loads consume both real and reactive power and as such the maximum demand is metered in kVA to reflect the customer's power factor. Customers on a demand based price can achieve significant savings by improving their power factor to as close to unity as possible to minimise the kVA demand. For smaller customers the cost of reactive compensation is less economic, and signalling of kW demand would be appropriate. For smaller customers, the time of use energy acts as a reasonable surrogate for the demand.

The factor, which drives augmentation, is the coincident demand at different levels of the network. However, there are issues arising from attempting to pass on a coincident demand-related price signal, such as:

- The coincident demand is dependent upon the actions of a group of customers rather than the actions of an individual
- A coincident demand charge can only be calculated after the event, when all customer contributions are known
- The coincident demand at different levels in the network each will have a different impact upon future costs
- The coincident demand carries with it a significant degree of complexity in terms of incorporation into the network billing system.

For these reasons, it is more appropriate for the customer's recorded non-coincident demand to be used to determine the demand charge.

6.7.2 Energy charges (network usage charges)

Where a customer does not have a meter capable of recording demand, the metered energy consumption, either in the form of a single anytime energy rate or as a time of use energy rate, provides the only means of signalling future augmentation costs to the customer.

Energy based charges are most commonly on an anytime basis with a single rate as most domestic and small business meters presently only record consumption in this form.

The peak and shoulder components of the time of use price provide a reasonable surrogate for the signalling of the costs of demand during those time periods that drive investment in the network.

6.7.3 Network access charges (fixed charges)

Most network prices have a fixed Network Access Charge, which is independent of the demand and energy supplied. Fixed charges are non-discretionary in nature and represent the means of cost recovery for those costs which are fixed and reflect the costs that vary due to customer numbers. They are unrelated to actual consumption.

The Network Access Charge is associated with the provision of the following network services, which are fixed in terms of costs:

- Maintenance of assets dedicated to the customer's supply such as connection and metering assets, low voltage assets and for larger customers, the substation circuit breaker and instrument transformers used for metering
- Customer related operation and maintenance costs such as the 24 hour/7 day control centre, emergency and technical response crews
- Meter reading, billing and account processing
- The distribution substation and high voltage power.

The Network Access Charge does not fully recover the fixed costs of some customer classes.

6.8 Fully distributed cost of supply modelling

Once the total annual revenue requirement (total network cost) is determined, then it must be apportioned to customers connected to the network.

Due to the meshed nature of the electricity distribution networks and largely fixed and sunken nature of costs, pricing must involve a substantial degree of cost averaging. Country Energy has adopted the fully distributed cost approach to allocate all network costs to each network customer class and large network customers based on the assets required to serve the customers and their usage of network distribution services. This approach is largely based on current costs, with new capital investment rolled into the regulatory asset base. We believe this general principle best reflects the manner in which costs are incurred by general customer classes and provides equitable and reasonably efficient outcomes.

Fully distributed cost of supply modelling involves three fundamental steps:

1. The determination of the total network revenue requirements/costs for the networks business to provide the desired standard of network distribution service
2. The allocation of network costs to separate asset categories (cost pools) within classes of network distribution services
3. Conversion of cost pools to usage-based network prices for different individual customers and classes of customers, based on factors such as voltage level and their use of the distribution system (load shape) to determine cost reflective prices. The structure of these prices varies for customer classes as outlined in the previous section.

6.8.1 Allocation of network costs to asset cost pools

Electricity may be supplied directly to a single large customer or indirectly to a homogeneous class of customers such as low voltage customers. There is dedicated connection equipment associated with each customer and to varying degrees each customer makes use of the shared distribution network assets. If the assets are for the sole use of one customer, then the cost allocation process is straightforward as all costs are totally attributable to that customer. However, when assets are shared, such as the shared distribution network, then the task is more difficult in allocating costs in an equitable and consistent manner between customers.

The cost components of a customer using the distribution system relate to those portions of the network, and as such asset groups, which are being used. The model allocates the network cost components into separate cost pools, which have varying cost drivers or inputs. The cost pools generally reflect the different voltage levels of the network.

The model takes as inputs the following quantities:

- The total distribution network cost and transmission related payments
- Optimised network asset values for each asset class and each individual subtransmission element
- Operating and maintenance costs for each asset class and each individual subtransmission network element
- Depreciation allowances and the effective return on capital for each asset class and each individual subtransmission network element
- Connectivity of subtransmission elements
- Forecast customer numbers, energy consumption and demand
- Load profile characteristics for individual customers and major customer classes.

An intermediate stage in the cost allocation process to the derivation of desired network prices is the separation of the network into several asset categories.

6.8.2 Network asset categories (cost pools)

In order to apportion the total revenue required to network elements, network assets are first subdivided into several asset categories. The cost of supply model apportions the allowable network revenue as a cost into “cost pools” for these various major asset classes of the network.

Network assets are segregated into several asset categories based on voltage level:

- **Distribution network assets**

Distribution network assets are all the assets between the transmission point of connection and the distribution connection assets supplying a customer or group of customers. All the customers connected to the distribution network share these assets to a greater or lesser extent. The following voltage based asset categories, and as such cost pools, are used:

- Sub-transmission network mains – overhead and underground mains
- Zone substations
- High voltage distribution network mains – overhead and underground distribution
- Distribution substations
- Low voltage network mains - overhead and underground.

The cost of these asset categories comprises operation and maintenance, depreciation and a return on the capital employed.

- **Connection assets**

Customers are connected at all voltages within Country Energy’s network, either directly to substations or embedded within the network. Connection assets (also referred to as exit assets) are those fully dedicated to a customer, or group of customers, at their point of connection to the network where power exits the network. Examples of these include service lines, metering and where applicable instrument transformers, load control or circuit breakers in a zone substation supplying a single large customer. The costs associated with these assets form the basis for the Network Access Charge.

▪ **Common service assets**

Common service assets are those that benefit all customers and which cannot be reasonably allocated on an individual network asset basis. Common service assets are subdivided into the following asset categories:

- Network common service assets include system control and communication systems, voltage regulators and reactive plant providing voltage support, spare parts, land and buildings not associated with lines or substations. Network common service includes network management and support costs
- Controlled load common service assets include off-peak load management equipment such as load control signal generators and injection plant
- Corporate common service assets include an allocation to the networks business of those assets and costs associated with the management and administration of the total business.

A customer connected to the high voltage network would be allocated a share of the costs from the transmission, sub-transmission mains, zone substations, high voltage distribution mains, and connection assets cost pools and those common service assets, which provide high voltage support. It is for this reason that prices vary with connected voltage level. The average network price that a typical customer may experience will increase with connections at lower voltages. A typical customer connected at high voltage will generally have an average price which is lower than a typical low voltage customer.

6.9 Cost allocation to asset categories

In a fully distributed cost model, the annual revenue requirement is determined for each of the above asset categories (cost pools) using similar principles to that applied by the AER in the Determination. That is, each network “cost pool” is assigned an asset-related cost (asset depreciation and a return on the assets employed) and efficient operating costs as follows:

Allocation to cost pool = operating costs + return of capital + return on capital + cost of tax.

Where information is available, the direct costs of an asset category or individual element are directly attributed to that asset cost pool. Amounts related to allocated ‘indirect’ costs as well as the returns required on the optimised values of assets are calculated and stored for each asset category or element.

In some cases, average unit operating cost (particularly maintenance cost per kilometre for network mains and maintenance cost per asset value for sub-transmission substations) is used to determine the elemental costs.

If the above process is carried out for each of the asset categories listed above, then the sum of the annual revenue requirements for all of the asset categories, plus the allocation of shared corporate common services, would equal Country Energy’s regulated distribution revenue requirements for that year, not including pass-through costs such as transmission related costs.

The relative proportions of operating costs and asset returns vary with each asset class due to the differences in asset values, depreciated life and operating expenditure requirements.

6.9.1 Asset related costs

Prior to calculating any asset-related returns, the value of assets financed by capital contributions is deducted from the total value of each asset category. Assets financed by capital contributions are not subject to a rate of return or depreciation charge, and only efficient maintenance and operation costs are recovered for these assets through network charges.

To arrive at an asset-related return for a particular asset category, the ODRC (excluding contributed assets) is multiplied by Country Energy's effective regulated rate of return to arrive at the return on assets for that asset category. To this is added the depreciation charge, based on the ODRC valuation and effective asset lives, to arrive at the total asset-related return for that asset category.

6.9.2 Conversion of cost pools to usage-based network prices

Once the costs have been determined for each of the shared asset categories, the next step is to apportion them to individual major customers and standard customer classes.

In this case the utilisation of these assets for the individual large customer or customer class is matched with the costs assigned to those assets. A technique called the "Method of Intercepts" is fundamental to shared network cost allocation process and is used to determine the contribution or impact of each on the demand that must be met by the network. This process utilises load profiles derived from estimates or samples.

The following steps provide an overview of the process that is used by Country Energy to apportion the annual revenue requirement for shared network assets to nodes in the network.

6.9.3 CRNP customer class

For those customers eligible for CRNP pricing the following cost allocation process is used:

- The assets providing supply to the large individual customer are itemised and costs assigned (efficient operating costs, depreciation and return on asset) as a portion of the pool costs for the shared asset classes using the process described above. This enables the annual revenue requirement for each individual asset to be determined. Allocation is based on the optimised asset valuation of each asset category. Network common service costs are included in the allocation process as a component of the annual revenue requirement for each asset. All exit nodes from the sub-transmission network are identified as part of this process
- An annual load profile dissected into hourly demand periods is obtained for each node on the sub-transmission network. By summing the load profiles of customers downstream from each node either from estimates or samples, the load profile of that network node can be derived. Financial responsibilities for upstream assets can then be allocated in proportion to demands at each network node. In this way all of the operating costs, depreciation and return on assets for the sub-transmission network can be related to individual customers and/or customer classes. Hourly metered load data for each day of the previous year is used. This data is summarised to produce an average daily load curve for the node. The load curve is converted to a load duration curve by the software for the allocation process. The load profile of each large CRNP customer is overlaid onto the load profile for the node. This identifies which customer contributes most to the peak periods and therefore drives the need for greater system capacity
- Costs are allocated using the "Method of Intercepts" process, which apportions the required revenue at shared nodes so that each customer bears an equitable portion of the input cost at that node. The method of intercepts may be thought of as producing a "flow rate" of annual revenue costs per hour per megawatt (\$/hour/MW). This approach places an increasing value on the use of the network during periods of high demand. A load that has a high peak utilisation will receive a proportionally higher sharing of costs. This method is based on the fact that a customer not only has a maximum demand at a certain moment of time, but also a varying demand at other times, and that this varying demand, however small, is also making use of Country Energy's supply facilities. That is equal proportions of network costs are assigned to equal increments of load. The resulting cost allocation takes into account the proportion of use. Thus the sharing of annual revenue requirement is based not just on a proportion of the maximum demand but rather on an integrated function of both demand and duration
- The outcome is an annual demand-related cost at each node on the sub-transmission network that includes an allocated portion of all the upstream network costs, which are recovered in proportion to a customer's utilisation of the assets

- Customer-related costs are also determined for the dedicated connection assets. Customer dedicated assets are identified and costs, associated with these assets, are applied to the individual customer including operating and maintenance costs and a capital return. These costs are normally applied as a fixed charge. Dedicated assets paid for by customers do not attract a capital return
- Corporate common service costs are allocated to customers based on an average rate per kWh. A simple approach to cost sharing based on energy consumption is used for these cost components, as this quantity is easily measured or can be estimated for all customers supplied by the network
- For customers satisfying the criteria for individual customer pricing, the total cost at the customer's exit node is then calculated including transmission use of system, distribution network use of system (as per the method of intercepts allocation), common service and connection service components. This annual revenue requirement at the exit nodes for CRNP customers is translated into price levels and structure.

6.9.4 Standard customer classes

For standard class customers the following process is used:

- Annual revenue requirements are allocated to asset cost pools in accordance with the process set out above. From these the costs assigned to CRNP customers are deducted. Usage-based network prices are then derived for each of the asset cost pools, from the allocated costs and the energy consumption for each customer class. The forecast energy projections for each class are derived from readings of metering equipment for the previous year
- The cumulative usage-based prices (shared distribution use of system) for each standard customer class is derived by adding together the usage price for each asset category utilised down to the point of exit from the network for that particular class. That is, each customer class is allocated a usage based revenue requirement in accordance with the assets (sub-transmission, high voltage, distribution substation and low voltage) utilised
- Added to this shared distribution use of system charge is the transmission use of system, and the customer-related costs such as common service and connection service components which includes metering, service lines and load control receivers. A portion of these costs is recovered through the Network Access Charge
- Connection service costs are allocated on an average rate per kWh approach using standard charges for different customer classes. Where the connection assets have been provided by customers or are the subject of a capital contribution, the costs are adjusted accordingly.

The cumulative usage based prices generated for each customer class in this manner is reflective of the asset-related costs and operating costs which would be attributed to the customer loads connected at each voltage level.

6.9.5 Controlled load customer class

Due to the ability to control a customer's load to avoid system peaks, the allocation of network service charges to controlled load network prices does not include any demand component. However, the principal residential and business network price includes a demand cost allocation. The controlled load network price includes the cost of a customer's load control equipment and an allocation for the load control signal injection equipment.

6.10 Allocation of transmission network costs

Country Energy's total revenue requirement incorporates transmission related payments. Transmission charges are a significant cost component for Country Energy and are recovered as part of the total network charges levied on our customers.

Transmission related payments include:

- The cost of transmission related costs for use of transmission networks owned by TransGrid, EnergyAustralia and Powerlink
- Avoided TUOS payments to embedded generators calculated in accordance with the Rules
- Payments for network services to other distributors for inter-distributor transfers.

Transmission charges are not in a form that readily translates into network price structures. Country Energy translates historical energy and kilowatt demand charges from transmission authorities into equivalent peak, shoulder and off-peak energy rates in order to allocate those charges to the network use of system tariffs.

Country Energy allocates transmission charges to network prices using the following principles:

- The total TUOS allocated to network prices aligns with total expected transmission related payments to be made by Country Energy
- Transmission charges are allocated to network prices in a way that reflects the cost drivers present in transmission
- The pass through of transmission charges and the structure of network prices have been aligned wherever possible by Country Energy
- CRNP customers have transmission charges allocated in a way that preserves the location and time signals of transmission pricing as per chapter 6 of the Rules
- Network prices for standard customer classes have transmission charges allocated on an average basis due to the difficulties associated with equitably allocating the general and common service fixed charge as a fixed network access charge, and passing through location price signals which cannot be preserved when the end price is applied to many customers within the network.

For larger customers connected in close electrical proximity to transmission connection points, transmission charges constitute the majority of the network price. It is therefore important that TUOS price is cost reflective and that the structure is mapped, as directly as possible, into network prices. For large customers with individual prices, the individual cost of transmission is directly assigned to the customer. The balance is allocated to standard customer classes.

Direct mapping to network prices for standard customer classes has not been possible due to the large fixed transmission charges that cannot be directly included in network price structures for these customers, which typically have a small fixed charge. More importantly, the customer's metering generally does not readily permit it. Due to these limitations, it is therefore not possible to pass the same transmission cost drivers through to all customers in the same format as they are provided to Country Energy.

While the allocation of the large fixed charge component is reasonably discretionary, it has been apportioned between customer classes on the basis of their consumption. Allocation to customers in this way is a balance between equity and efficiency. Only the peak and shoulder energy component can be readily passed on to customers through distribution prices.

The transmission charges are allocated on their non time of use energy, peak and shoulder energy consumption, and/or demand and are added to the distribution network costs for each customer class. The intention of this mapping methodology is to preserve within the customer's price, to the extent possible, the cost drivers inherent in the transmission charge.

- Non-TOU price – the total transmission charge allocation for the class is divided by the total class consumption and added to the energy rate for the price. Average transmission charges would apply to smaller customers.

- TOU price – the transmission allocation relating to the transmission demand and energy components is divided by the peak, shoulder and off peak consumption and added to the peak, shoulder and off peak energy rates. The transmission allocation relating to the fixed transmission component is added to the TOU energy rates.
- Demand TOU price – the transmission allocation relating to the transmission demand and energy components is divided by the peak, shoulder and off peak consumption and added to the peak, shoulder and off peak energy rates. The transmission allocation relating to the fixed transmission component is added to the TOU energy rates.

The fixed component of the transmission charge was originally largely determined from an ‘anytime’ energy allocation of costs. This component is apportioned between individual customers and customer classes on the basis of their anytime energy consumption. Allocation to customers in this way is a balance between equity and efficiency. The allocation of the transmission demand charge using peak and shoulder energy is justified on the basis that in the long run, the augmentation of the transmission network - and hence future costs - is related to peak and shoulder utilisation of the network.

6.11 Incremental and stand alone cost allocation process

Country Energy’s cost of supply model assesses cost allocations to customer classes both on a LRMC and stand-alone basis. It is inappropriate for network distribution service charges to be below the incremental cost (LRMC) of supply as it results in inefficient pricing signals. It is also inappropriate for charges to exceed that which the customer could pay for an alternative equivalent service, the stand-alone cost.

The stand-alone cost of supply is based on establishing an alternative source of supply to the customer class. Stand-alone costs are assessed by calculating the costs of various alternative supplies to our distribution network such as the construction of an alternative grid or the use of a community or individual generator. The lowest of the various stand-alone costs is chosen for the comparison.

Marginal costs are established by assessing the marginal component of the cost pools and allocating these costs to customer classes. This process takes into account the usage of the distribution network and other distribution network services and the impact on future capital expenditure made by each customer class. The LRMC of the distribution network is determined by separately identifying capacity related expenditure and averaging this over a forecast change in output (the Average Incremental Cost Approach).

The below steps are followed in the determination of Country Energy’s marginal costs:

1. Marginal cost components are allocated to the following cost pools:
 - Customer** – marginal costs reflect the costs that vary due to additional customer numbers, i.e. building and maintaining the low voltage network, customer inquiries, and emergency response and outage restoration
 - Demand** – marginal costs accrue due to the customer’s peak loading that contributes to network capacity requirements and augmentation
 - Energy** – marginal costs accrue due primarily to the structure of transmission charges.
2. Growth related capital expenditure is allocated to the customer and demand cost pools based on forward estimates of average annual growth related network augmentation required over the next ten years
3. Asset renewal expenditure is based on forward estimates of average annual capital expenditure on asset refurbishment or replacement required to meet load growth. These assets would otherwise be unsatisfactory to supply existing loads

4. Capital expenditure for reliability and quality enhancement, and environmental, safety and statutory obligations are allocated to the customer and demand cost pools
5. Operation and maintenance marginal costs excluding administration and overheads are allocated to the customer and demand cost pools according to the relevant activity
6. Marginal transmission costs including both TransGrid and Powerlink demand and energy charges are allocated to the relevant cost pools. The transmission fixed charges are not allocated as marginal costs
7. The allocation of the demand cost pool to customer classes is based on the asset utilisation by each class of customer
8. The allocation of the energy pool is based on energy consumption for each customer class
9. The customer cost pool is allocated according to a weighted customer value representing relevant customer servicing costs.

The network price for each customer class is then compared with the stand-alone costs and LRMC to determine if any cross-subsidisation exists.

Attachment 1 demonstrates the relationship between current network prices and LRMC and stand-alone costs over a range of consumptions in each price class. The table and graphs show that network prices lie above the long run marginal cost of supply and below the lowest cost stand-alone alternative throughout the range of consumption.

6.12 Setting of price structures and levels

6.12.1 Factors considered

Final network prices and structures for standard network customer classes are established taking into consideration the following factors:

- Previous price structures and limits on price movements
- Nature and extent of their usage
- Nature of their connection to the network
- Cost effectiveness of metering requirements
- Demand management
- Simplicity

6.12.2 Network tariff classes

Country Energy's network prices may be separated into six broad categories that address the price setting principles listed above.

- **Low voltage - energy**
This tariff class relates to customers with a low voltage connection to the network and are billed on usage. It includes the customer classes of:
 - Residential continuous
 - Residential time of use
 - Controlled load 1
 - Controlled load 2
 - Business continuous
 - Business time of use < 100 MWh
 - Low voltage time of use > 100 MWh

- **Low voltage - demand**

This tariff class relates to customers with a low voltage connection to the network and are billed on usage and demand. It includes the customer classes of:

- Low voltage - average daily demand
- Low voltage – one rate demand
- Low voltage – three rate demand

- **High voltage - demand**

This tariff class relates to customers with a high voltage connection to the network and are billed on usage and demand. It includes the customer classes of:

- High voltage - average daily demand
- High voltage – one rate demand
- High voltage – three rate demand

- **Subtransmission**

This tariff class relates to customers with a subtransmission connection to the network and are billed on usage and demand. It includes the customer classes of:

- Subtransmission - three rate demand
- Cost reflective network customers

- **Inter distributor transfer**

- This tariff class relates to specific connection points between distributors

- **Unmetered**

This tariff class relates to customers that do not have a meter and includes:

- Streetlighting usage charges
- Any other unmetered supply

Further information on Country Energy's network price structures for standard customer classes can be obtained from the Network Price List. The Network Price List is available on Country Energy's website at www.countryenergy.com.au or on request.

6.12.3 Cost reflective network prices and cross subsidies

Some network prices do not reflect the fully allocated cost of providing the service. Country Energy's fully distributed cost of supply model indicates that some prices are not cost-reflective.

The term 'cross-subsidy' is frequently used when discussing the level of cost reflectivity in prices. However, a large proportion of a network operator's costs are fixed, and allocation of fixed costs to various customer classes is an arbitrary process. Caution must therefore be taken when interpreting discussions of cross-subsidies in network pricing which have been determined by this allocation of fixed costs to various customer classes.

It is important to understand the various interpretations of what constitutes a cross subsidy.

The generally accepted view is that cross-subsidies do not exist if the cost of providing a service exceeds its incremental cost.

Despite this very valid proposition, there are two significant issues for setting network prices that need to be taken into account:

- First, there is subjectivity in the definition of marginal costs for distribution network services. In the short run, marginal costs are negligible as energy losses are traded in the market. In the longer term, incremental costs would trend to average costs as per a fully distributed cost of supply of an optimised network.

- Second, network distribution assets are long lived and their cost recovery needs to be considered over an extended timeframe.

7 EXPECTED LEVELS OF SERVICE AND PROJECTED CAPITAL EXPENDITURE PROJECTS

Country Energy's capital investment program over the five years from 2009-10 to 2013-14 totals \$3,826 million with \$758 million forecast to be invested during 2010-11 (in real 2008-09 dollars).

7.1 Capital expenditure projects

Capital expenditure is invested efficiently by Country Energy to deliver the greatest benefit to all stakeholders. Our medium-term capital investment program is designed to meet targeted programs and to continue to improve the current levels of service to customers. Specifically the program takes into account the following factors:

- The needs of our customers and all other stakeholders
- Current and projected levels of service standards, including long-term network reliability across the network and the specific targeting of those parts of the network that are delivering the lowest service levels
- Independently assessed forecasts of demand growth
- Condition and age of assets
- Regulatory, environmental and safety compliance requirements
- Non system investment requirements
- Efficient alternatives to capital expenditure including efficient operating and maintenance expenditure, demand management, and new generation.

Country Energy's \$757.5 million capital investment program for 2010-11 includes:

- \$150.6 million to renew or refurbish aging assets
- \$256.9 million to support growth across the network
- \$174.0 million to support improvements in reliability and quality of service to customers
- \$38.4 million to meet environmental, safety and statutory obligations

As part of the electricity distribution determination process, the AER undertook a review of the forecast capital expenditure and engaged engineering consultants to undertake a detailed analysis of capital expenditure requirements. The consultants endorsed the levels of capital expenditure proposed by Country Energy and concluded that the investment program is efficient and justified. The AER has adopted the capital expenditure allowances for Country Energy that align with the recommendations of their consultants.

The following section outlines the major capital expenditure categories and provides a brief description of major capital expenditure projects planned for the 2010-11 financial year necessary to meet:

- Growth in demand and system augmentation requirements to maintain system performance and system security
- Asset replacement and renewal requirements to maintain system performance, safety and integrity of the network and to meet customer requirements for network quality and improve reliability
- Non-system investment requirements to support the operations of the distribution business.

7.1.1 Growth in demand and system augmentation

Growth-related expenditure relates to investments that are required to ensure that the network has adequate capacity to meet increasing demand.

Country Energy's distribution network is operating at or near its maximum capacity in some areas. The strong growth areas include the major regional centres and the northern and southern coastal strips, the latter areas representing some of the fastest growing areas in the state. This reflects continued residential and commercial development, with expansion forecast to continue into the future. Over the medium term, Country Energy will need to continue to expand and reinforce the network in these areas to meet the high growth in demand. In regions west of the ranges, the general rate of growth in residential development is moderate.

A selection of specific growth-related projects for 2010-11 is outlined below:

Figure 8 growth-related projects for 2010-11

Region	Project Description	Cost \$ millions
South Eastern	Cooma to Bega construction of additional 132,000 volt circuit	39.1
Far North Coast	Koolkhan to Maclean construction of 66,000 volt line (40 kilometres)	24.0
Southern	Finley 132 Substation to Mulwala 132,000/22,000 volt substation - Convert existing 66,000 volt line to 132,000 volt (49km)	17.3
Southern	Deniliquin to Moama construction of new 66,000 volt line (69km)	22.6
Mid North Coast	Nabiac Possum Brush Bulk Supply Point establishment of new 132,000/66000/11000 volt substation	12.5
Far North Coast	Lismore Uni construction of new zone substation	9.1
Southern	Mulwala establishment of new 132,000/22,000 volt zone substation	5.2
Northern	Tamworth South establishment of zone substation stage 2 and 3	4.6
Far North Coast	Casino North establishment of 66,000/11,000 volt substation	3.4
North West	Narromine 132,000/66,000 volt establishment of new 132,000 volt switching station and 132,000/66,000 volt substation (1 x 132,000/66,000 volt 60MVA)	6.5
Far West	Buronga town establishment of new substation	2.7
Southern	Wagga Ashmont rebuild existing 66,000/11,000 volt substation	2.9
Central West	Forbes to West Jemalong construction of new subtransmission line (40km)	2.7

7.1.2 Asset renewal and replacement

A significant component of the overall network-related capital program is the replacement and renewal of aged assets. Network assets have a finite life. Replacement and renewal investment ensures the timely replacement or refurbishment of network assets that have become unserviceable, that frequently fail in

service, have significantly deteriorated to an unsafe or risky condition or where the present-value cost of maintaining the asset exceeds the cost of replacement. Asset replacement expenditure increases gradually over time due to the ageing of the network. This trend is already evident and will continue through the new regulatory period. Where the condition of the assets has deteriorated and ongoing maintenance is not effective, system assets must be replaced.

Replacement is also driven by environmental, regulatory and industry safety compliance considerations. General distribution related reliability capital expenditure to maintain existing service levels are also included in this category. More than 40 per cent of Country Energy's network assets are over 40 years old and are rapidly ageing. In the areas of the network west of the ranges, the network assets are generally older and the condition of some assets is increasingly requiring replacement in order to maintain the performance level of the network.

7.1.3 Non-system requirements

This category includes capital items that will be required to support the electricity distribution business including:

- Information systems development and computer hardware, software and upgrades, licences, plant and equipment relating to IT assets, and related expenditure required to operate the business. A number of Country Energy's core IT assets have reached the end of their useful business life and as such expenditure will continue being required throughout the current regulatory period to June 2014
- Motor vehicles and plant
- Communication systems such as trunk mobile radio, faxes, mobile phones
- A number of other miscellaneous expenditures such as general office equipment, furniture and whitegoods, small plant and test equipment, and building and property works

Expenditure related to this category will ensure the continued efficient management and support of the electricity distribution business.

7.2 Expected levels of service for the coming year

Country Energy is proud of the service standards achieved within a difficult and unique operating environment.

During the electricity distribution pricing review, the AER accepted Country Energy's reliability performance objectives for the five-year period commencing July 2009. The feeder category objectives are as mandated in the DWE "Design, Reliability and Performance Licence Conditions - 1st December 2007". The Country Energy wide target is derived from the feeder category targets by proportioning based on customer numbers per category. Country Energy will continue implementing a range of programs to improve the network's reliability to ensure the targets are met. These include increased segmentation of the network by installing a large number of reclosers, increased vegetation management and the development of the intelligent network project.

The SAIDI reliability performance objectives for 2010-11 for different components of the network are tabled below. SAIDI represents the total number of minutes on average that each customer installation connection to the distribution system (or to those components) is without a supply of electricity.

Figure 9 SAIDI Reliability Performance Objectives for 2010-11

Component of distribution system	2010-11 SAIDI objective (minutes)
Whole distribution system	319
Urban feeders	125
Rural short feeders	300
Rural long feeders	700