

Notice of change to ETSA Utilities' distribution tariffs from 1 July 2005.

Pursuant to clause 1.9.2 of the Electricity Distribution Price Determination Part B as varied on 9 June 2005 notice is hereby given that the following changes to ETSA Utilities tariffs have been approved by the Essential Services Commission of South Australia. The altered distribution tariffs are set out in the table below and are to be applied from the year 1 July 2005 to 30 June 2006.

The charges incorporate the introduction of a "stepped tariff" in the residential distribution tariff structure providing benefits to all residential customers. The benefit is derived from customers receiving a lower usage charge for consumption below the first step of 4,000kWh pa. A fixed supply charge will continue to apply for Residential Tariff customers.

Additionally, ETSA Utilities has eliminated the supply charge for the controlled load (hot water) distribution tariff. This will lead to a decrease for most residential customers with controlled load.

Business Single Rate customers face an increase to the network component of their bill equivalent to half that of inflation, approximately 1.2%.

For Business Two Rate customers, while the First Step Peak Consumption rate has increased, a Business Two Rate customer's supply charge has been more than halved from approximately \$220 pa to \$105 pa incl GST. The Business Two Rate Balance Peak Consumption price is in line with the 2004/05 Peak price while the Off Peak price has been reduced.

A new structure for demand customers (kVA) was also introduced, with a declining block tariff for low voltage customers (this encompasses the medium, low voltage and large low voltage demand customers). As part of this new structure, we have removed an incentive for some customers to request more demand than they require.

As required under the National Electricity Code, for individual connection points with a load above 10MW and/or consumption above 40GWh pa, the transmission component of ETSA Utilities' charges is a direct passthrough of ElectraNetSA's transmission pricing. As a result, an unique tariff will be applied to each of the connection points. Please contact ETSA Utilities for further details.

No new tariffs have been introduced effective 1 July 2005. No additional existing tariffs have been closed.

If retailers require clarification on invoicing matters, please contact ETSA Utilities' Manager Retailer Relationships, Paul Erwin on (08) 8404 9486.

ETSA UTILITIES NETWORK TARIFFS
APPLIES TO USAGE FROM 1 JULY 2005

Customer Category	Units	Min Qty.	TUOS excl GST	DUOS excl GST	Total excl GST	Total incl GST
Low Voltage Residential - Single Rate Type 5 or 6 Meter Read Quarterly						
QRSR						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Low Voltage Residential - Single Rate Type 5 or 6 Meter Read Monthly						
MRSR						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Low Voltage Residential - Single Rate Type 1-4 Meter						
MRSRI						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Low Voltage Residential - Single Rate Type 5 or 6 Meter Read Quarterly with Controlled Load						
QRSROPCL						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Residential - Single Rate Type 5 or 6 Meter Read Monthly with Controlled Load						
MRSROPCL						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Residential - Single Rate Type 1-4 Meter with Controlled Load						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Block 1 Usage Rate	\$/kWh	=<333.3 kWh/mth [†]	0.015562	0.048961	0.064523	0.070975
Block 2 Usage Rate	\$/kWh	Balance Usage	0.015562	0.060098	0.075660	0.083226
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Controlled Load - Type 5-6 Read Quarterly						
QOPCL						
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Controlled Load - Type 5-6 Read Monthly						
MOPCL						
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Controlled Load - Type 1-4 Meter						
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431

ETSA UTILITIES NETWORK TARIFFS
APPLIES TO USAGE FROM 1 JULY 2005

Customer Category	Units	Min Qty.	TUOS excl GST	DUOS excl GST	Total excl GST	Total incl GST
Low Voltage Business - Single Rate Type 5 or 6 Meter Read Quarterly						
QBSR						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057931	0.074708	0.082178
Low Voltage Business - Single Rate Type 5 or 6 Meter Read Monthly						
MBSR						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057467	0.074244	0.081668
Low Voltage Business - Single Rate Type 1 to 4 Meter						
BSR124						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057467	0.074244	0.081668
Low Voltage Business - Single Rate Type 5 or 6 Meter Read Quarterly with Controlled Load						
QBSROPCL						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057931	0.074708	0.082178
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Business - Single Rate Type 5 or 6 Meter Read Monthly with Controlled Load						
MBSROPCL						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057467	0.074244	0.081668
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Business - Single Rate Type 1 to 4 Meter with Controlled Load						
BSR124OPCL						
Supply Rate	\$/day			0.226688	0.226688	0.249356
Anytime Usage Rate	\$/kWh		0.016777	0.057467	0.074244	0.081668
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Business - 2 Rate Type 5 or 6 Meter Read Quarterly						
QB2R						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.6667 kWh/mth [^]	0.021199	0.079295	0.100494	0.110543
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.059296	0.080495	0.088544
Off-Peak Usage Rate	\$/kWh		0.005418	0.023213	0.028631	0.031494
Low Voltage Business - 2 Rate Type 5 or 6 Meter Read Monthly						
MB2R						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.7 kWh/mth [^]	0.021199	0.078660	0.099859	0.109844
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.058822	0.080021	0.088023
Off-Peak Usage Rate	\$/kWh		0.005418	0.023027	0.028445	0.031289
Low Voltage Business - 2 Rate Type 1 to 4 Meter						
B2R124						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.7 kWh/mth [^]	0.021199	0.078660	0.099859	0.109844
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.058822	0.080021	0.088023
Off-Peak Usage Rate	\$/kWh		0.005418	0.023027	0.028445	0.031289
Low Voltage Unmetered Usage (Overnight Usage)						
LVUU						
Anytime Usage Rate	\$/kWh		0.008653	0.032588	0.041241	0.045365
Low Voltage Unmetered Usage (24 Hour Usage)						
LVUU24						
Anytime Usage Rate	\$/kWh		0.009015	0.036480	0.045495	0.050044
Other Unmetered Usage						
OUU						
Supply Rate	\$/day			0.130563	0.130563	0.143619
Peak Usage Rate	\$/kWh		0.021662	0.080187	0.101849	0.112033
Off-Peak Usage Rate	\$/kWh		0.005536	0.023474	0.029010	0.031911

ETSA UTILITIES NETWORK TARIFFS
APPLIES TO USAGE FROM 1 JULY 2005

Customer Category	Units	Min Qty.	TUOS excl GST	DUOS excl GST	Total excl GST	Total incl GST
Medium Low Voltage Demand (KVA)						
VMLV						
Supply Rate	\$/day			13.989052	13.989052	15.387957
Annual Demand Rate	\$/kVA/mth	100 KVA	1.910958	3.233829	5.144787	5.659265
Additional Demand	\$/kVA/mth			1.106326	1.106326	1.216958
Peak Usage Rate	\$/kWh		0.005912	0.017361	0.023273	0.025600
Off-Peak Usage Rate	\$/kWh		0.005318	0.013275	0.018593	0.020452
Low Voltage Demand (KVA)						
VLV						
Supply Rate	\$/day			24.480814	24.480814	26.928895
Annual Demand Rate	\$/kVA/mth	250 KVA	1.910958	1.957307	3.868265	4.255091
Additional Demand	\$/kVA/mth			1.106326	1.106326	1.216958
Peak Usage Rate	\$/kWh		0.005912	0.017361	0.023273	0.025600
Off-Peak Usage Rate	\$/kWh		0.005318	0.013275	0.018593	0.020452
Large Low Voltage Demand (KVA)						
VLLV						
Supply Rate	\$/day			44.065384	44.065384	48.471922
Annual Demand Rate	\$/kVA/mth	1,000 KVA	1.910958	1.361569	3.272527	3.599779
Additional Demand	\$/kVA/mth			1.106326	1.106326	1.216958
Peak Usage Rate	\$/kWh		0.005912	0.017361	0.023273	0.025600
Off-Peak Usage Rate	\$/kWh		0.005318	0.013275	0.018593	0.020452
High Voltage (KVA)						
VHV						
Supply Rate	\$/day			32.486297	32.486297	35.734926
Annual Demand Rate	\$/kVA/mth	1,000 KVA	1.875001	1.317505	3.192506	3.511756
Additional Demand	\$/kVA/mth			0.898331	0.898331	0.988164
Peak Usage Rate	\$/kWh		0.005802	0.013839	0.019641	0.021605
Off-Peak Usage Rate	\$/kWh		0.005218	0.009882	0.015100	0.016610
Zone Sub-station (KVA) (Load <10MW and Consumption <40GWh pa)						
VZS						
Supply Rate	\$/day			41.704414	41.704414	45.874855
Annual Demand Rate	\$/kVA/mth	5,000 KVA	1.837263	0.761106	2.598369	2.858205
Additional Demand	\$/kVA/mth			0.591937	0.591937	0.651130
Peak Usage Rate	\$/kWh	25 GWh pa	0.005685	0.007104	0.012789	0.014067
Off-Peak Usage Rate	\$/kWh		0.005113	0.005074	0.010187	0.011205
Zone Sub-station (KVA) Locational						
TUoS Supply Charge	\$/day		See Individual Locational TUoS Charges Below			
Supply Rate	\$/day			41.704414	41.704414	45.874855
Annual Demand Rate	\$/kVA/mth	5,000 KVA		0.761106	0.761106	0.837216
Additional Demand	\$/kVA/mth			0.591937	0.591937	0.651130
Peak Usage Rate	\$/kWh	25 GWh pa		0.007104	0.007104	0.007814
Off-Peak Usage Rate	\$/kWh			0.005074	0.005074	0.005581
Subtransmission (KVA) Locational						
TUoS Supply Charge	\$/day		See Individual Locational TUoS Charges Below			
Supply Rate	\$/day			0.000000		
Annual Demand Rate	\$/kVA/mth	10,000 KVA		0.378396	0.378396	0.416235
Additional Demand	\$/kVA/mth			0.297150	0.297150	0.326865
Peak Usage Rate	\$/kWh			0.002975	0.002975	0.003272
Off-Peak Usage Rate	\$/kWh			0.001915	0.001915	0.002106

ETSA UTILITIES NETWORK TARIFFS
APPLIES TO USAGE FROM 1 JULY 2005

Customer Category	Units	Min Qty.	TUOS excl GST	DUOS excl GST	Total excl GST	Total incl GST
OBSOLETE TARIFFS						
Medium Low Voltage Demand (KW)						
WMLV						
Supply Rate	\$/day			2.204332	2.204332	2.424765
Annual Demand Rate	\$/kW/mth	100 KW	2.330450	4.570438	6.900888	7.590976
Additional Demand	\$/kW/mth			2.512062	2.512062	2.763268
Peak Usage Rate	\$/kWh		0.005912	0.035985	0.041897	0.046086
Off-Peak Usage Rate	\$/kWh		0.005318	0.024270	0.029588	0.032546
Low Voltage Demand (KW)						
WLV						
Supply Rate	\$/day			4.353405	4.353405	4.788745
Annual Demand Rate	\$/kW/mth	300 KW	2.330450	3.265773	5.596223	6.155845
Additional Demand	\$/kW/mth			1.955869	1.955869	2.151455
Peak Usage Rate	\$/kWh		0.005912	0.025217	0.031129	0.034241
Off-Peak Usage Rate	\$/kWh		0.005318	0.017331	0.022649	0.024913
Large Low Voltage Demand (KW)						
WLLV						
Supply Rate	\$/day			4.353405	4.353405	4.788745
Annual Demand Rate	\$/kW/mth	1,000 KW	2.330450	2.758779	5.089229	5.598151
Additional Demand	\$/kW/mth			1.733802	1.733802	1.907182
Peak Usage Rate	\$/kWh		0.005912	0.021476	0.027388	0.030126
Off-Peak Usage Rate	\$/kWh		0.005318	0.014677	0.019995	0.021994
High Voltage (KW)						
WHV						
Supply Rate	\$/day			4.212482	4.212482	4.633730
Annual Demand Rate	\$/kW/mth	1,000 KW	2.205898	2.125551	4.331449	4.764593
Additional Demand	\$/kW/mth			1.446205	1.446205	1.590825
Peak Usage Rate	\$/kWh		0.005802	0.016654	0.022456	0.024701
Off-Peak Usage Rate	\$/kWh		0.005218	0.011734	0.016952	0.018647
Zone Sub-station (KW) (Load <10MW and Consumption <40GWh pa)						
WZS						
Supply Rate	\$/day			17.529172	17.529172	19.282089
Annual Demand Rate	\$/kW/mth	5,000 KW	2.161438	0.997244	3.158682	3.474550
Additional Demand	\$/kW/mth			0.895661	0.895661	0.985227
Peak Usage Rate	\$/kWh	25 GWh pa	0.005685	0.007801	0.013486	0.014834
Off-Peak Usage Rate	\$/kWh		0.005113	0.005240	0.010353	0.011388
Zone Sub-station (KW) Locational						
TUoS Supply Charge	\$/day		See Individual Locational TUoS Charges Below			
Supply Rate	\$/day			17.529172	17.529172	19.282089
Annual Demand Rate	\$/kW/mth	5,000 KW		0.997244	0.997244	1.096968
Additional Demand	\$/kW/mth			0.895661	0.895661	0.985227
Peak Usage Rate	\$/kWh	25 GWh pa		0.007801	0.007801	0.008581
Off-Peak Usage Rate	\$/kWh			0.005240	0.005240	0.005764
Subtransmission (KW) Locational						
TUoS Supply Charge	\$/day		See Individual Locational TUoS Charges Below			
Supply Rate	\$/day			23.675952	23.675952	26.043547
Annual Demand Rate	\$/kW/mth	10,000 KW		0.443825	0.443825	0.488207
Additional Demand	\$/kW/mth			0.351896	0.351896	0.387085
Peak Usage Rate	\$/kWh			0.003758	0.003758	0.004133
Off-Peak Usage Rate	\$/kWh			0.002230	0.002230	0.002453
High Voltage Obsolete (KVA)						
VHVO						
Supply Rate	\$/day			4.212482	4.212482	4.633730
Annual Demand Rate	\$/kVA/mth	300 KVA	1.875001	2.262263	4.137264	4.550990
Additional Demand	\$/kVA/mth			1.054764	1.054764	1.160240
Peak Usage Rate	\$/kWh		0.005802	0.012562	0.018364	0.020200
Off-Peak Usage Rate	\$/kWh		0.005218	0.009054	0.014272	0.015699
High Voltage Obsolete (KW)						
WHVO						
Supply Rate	\$/day			4.212482	4.212482	4.633730
Annual Demand Rate	\$/kW/mth	250 KW	2.205898	2.125551	4.331449	4.764593
Additional Demand	\$/kW/mth			1.446205	1.446205	1.590825
Peak Usage Rate	\$/kWh		0.005802	0.016654	0.022456	0.024701
Off-Peak Usage Rate	\$/kWh		0.005218	0.011734	0.016952	0.018647

ETSA UTILITIES NETWORK TARIFFS
APPLIES TO USAGE FROM 1 JULY 2005

Customer Category	Units	Min Qty.	TUOS excl GST	DUOS excl GST	Total excl GST	Total incl GST
OBSOLETE TARIFFS						
Low Voltage Business - 2 Rate Type 5 or 6 Meter Read Quarterly with Controlled Load						
QB2ROPCL						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.7 kWh/mth [^]	0.021199	0.079295	0.100494	0.110543
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.059296	0.080495	0.088544
Off-Peak Usage Rate	\$/kWh		0.005418	0.023213	0.028631	0.031494
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Business - 2 Rate Type 5 or 6 Meter Read Monthly with Controlled Load						
MB2ROPCL						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.7 kWh/mth [^]	0.021199	0.078660	0.099859	0.109844
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.058822	0.080021	0.088023
Off-Peak Usage Rate	\$/kWh		0.005418	0.023027	0.028445	0.031289
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Business - 2 Rate Type 1 to 4 Meter with Controlled Load						
B2R124OPCL						
Supply Rate	\$/day			0.258221	0.258221	0.284043
Peak Block 1 Usage Rate	\$/kWh	=<1,666.7 kWh/mth [^]	0.021199	0.078660	0.099859	0.109844
Peak Block 2 Usage Rate	\$/kWh	Balance Usage	0.021199	0.058822	0.080021	0.088023
Off-Peak Usage Rate	\$/kWh		0.005418	0.023027	0.028445	0.031289
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Demand (KVA) with Controlled Load						
VLVOPCL						
Supply Rate	\$/day			24.480814	24.480814	26.928895
Annual Demand Rate	\$/kVA/mth	250 KVA	1.910958	1.957307	3.868265	4.255091
Additional Demand	\$/kVA/mth			1.106326	1.106326	1.216958
Peak Usage Rate	\$/kWh		0.005912	0.017361	0.023273	0.025600
Off-Peak Usage Rate	\$/kWh		0.005318	0.013275	0.018593	0.020452
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Medium Low Voltage Demand (KW) with Controlled Load						
WMLVOPCL						
Supply Rate	\$/day			2.204332	2.204332	2.424765
Annual Demand Rate	\$/kW/mth	100 KW	2.330450	4.570438	6.900888	7.590976
Additional Demand	\$/kW/mth			2.512062	2.512062	2.763268
Peak Usage Rate	\$/kWh		0.005912	0.035985	0.041897	0.046086
Off-Peak Usage Rate	\$/kWh		0.005318	0.024270	0.029588	0.032546
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431
Low Voltage Demand (KW) with Controlled Load						
WLVOPCL						
Supply Rate	\$/day			4.353405	4.353405	4.788745
Annual Demand Rate	\$/kW/mth	300 KW	2.330450	3.265773	5.596223	6.155845
Additional Demand	\$/kW/mth			1.955869	1.955869	2.151455
Peak Usage Rate	\$/kWh		0.005912	0.025217	0.031129	0.034241
Off-Peak Usage Rate	\$/kWh		0.005318	0.017331	0.022649	0.024913
Controlled Load Block 1 Usage Rate	\$/kWh	=<666.7 kWh/mth [#]	0.005361	0.015234	0.020595	0.022654
Controlled Load Block 2 Usage Rate	\$/kWh	Balance Usage	0.005361	0.023213	0.028574	0.031431

INDIVIDUAL LOCATIONAL TUOS CHARGES

APPLIES TO USAGE FROM 1 JULY 2005

NMI	Tariff	TUoS excl GST (\$/day)	TUoS incl GST (\$/day)
2001000378	Subtranmsission (KVA) Locational	1,345.224657	1,479.747122
2001000608	Zone Substation (KVA) Locational	935.841095	1,029.425204
2002112609	Subtranmsission (KVA) Locational	7,012.230136	7,713.453149
2002133131	Zone Substation (KVA) Locational	526.191780	578.810958
SAAAAAA018	Subtranmsission (KVA) Locational	4,074.400000	4,481.840000
SAAAAAA019	Zone Substation (KVA) Locational	881.002739	969.103012
SAAAAAA021	Zone Substation (KVA) Locational	2,695.257534	2,964.783287
SAAAAAA022	Zone Substation (KVA) Locational	2,288.800000	2,517.680000
SAAAAAA024	Zone Substation (KW) Locational	1,863.761643	2,050.137807
SAAAAAA026	Zone Substation (KVA) Locational	1,110.673972	1,221.741369
SAAAAAA029	Zone Substation (KW) Locational	1,503.109589	1,653.420547
SAAAAAA031	Zone Substation (KW) Locational	1,399.775342	1,539.752876
SAAAAAA035	Zone Substation (KW) Locational	1,145.131506	1,259.644656
SAAAAAA084	Subtranmsission (KW) Locational	2,505.147945	2,755.662739
SAAAAAA438	Zone Substation (KVA) Locational	938.690410	1,032.559451
SAAAAAB557	Subtranmsission (KW) Locational	1,540.684931	1,694.753424

Notes accompanying 2005/ 2006 Tariffs

† - Approximate annual consumption of 4,000 kWh.

- Approximate annual consumption of 8,000 kWh.

^ - Approximate annual peak consumption of 20,000 kWh.

Notes:

1. Distribution tariffs are determined on a GST exclusive basis. GST is added to the distribution tariffs.
2. ETSA Utilities must assign each Distribution Network User to a distribution tariff in respect of each of its connection points in accordance with the following principles.
 - (a) A Distribution Network User that has an agreed maximum demand of 250kVA or more in respect of a connection point, must be assigned to a distribution tariff that includes a demand component in respect of that connection point.
 - (b) A Sub-Transmission (kVA) Network User is a Distribution Network User taking supply at 66kV, or at 33kV outside of the Adelaide Metropolitan area. A minimum annual demand of 10 MVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.90 pf). These tariffs are invoiced monthly.
 - (c) A Zone Substation (kVA) customer is a Distribution Network User taking supply generally at 11kV from the low voltage transformer terminals. Supply may also be taken at lower voltages that exceed 1kV. A minimum annual demand of 5 MVA and a minimum annual usage of 25GWh apply. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.90 pf). These tariffs are invoiced monthly.
 - (d) A High Voltage Demand (kVA) customer is a Distribution Network User taking supply generally at 11kV. Supply may also be taken at lower voltages that exceed 1kV or at 33kV in metropolitan Adelaide. A minimum annual demand of 1 MVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.85 pf). These tariffs are invoiced monthly.
 - (e) A High Voltage (kVA) (Obsolete) customer is a Distribution Network User taking supply generally at 11kV. This tariff is available only to Distribution Network Users that were taking supply under the High Voltage Demand (kW) (Obsolete) tariff as at 11 October 1999. Supply may also be taken at lower voltages that exceed 1kV or at 33kV in metropolitan Adelaide. A minimum annual demand of 300kVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.85 pf). These tariffs are invoiced monthly.
 - (f) A Large Low Voltage Demand (kVA) customer is a Distribution Network User generally taking supply at less than 1kV and generally from the low voltage distribution transformer terminals. A minimum agreed maximum demand of 1MVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.85 pf). These tariffs are invoiced monthly.
 - (g) A Low Voltage Demand (kVA) customer is a Distribution Network User generally taking supply at less than 1kV and generally from the low voltage distribution transformer terminals. A minimum agreed maximum demand of 250kVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.85 pf). These tariffs are invoiced monthly.
 - (h) A Medium Low Voltage Demand (kVA) customer is a Distribution Network User generally taking supply at less than 1kV and using demand, peak and off-peak network charges. A minimum agreed maximum demand of 100kVA applies. A NEM compliant type 1-4 interval meter is required. Customers electing to switch to this tariff from 1 July 2002 must meet or exceed the minimum power factor requirements for their customer installation as set out in Part B of the Distribution Code (generally 0.85 pf). These tariffs are invoiced monthly.

- (i) A Low Voltage Business 2 rate – Type 1-4 Meter customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using peak and off-peak network charges. The User utilises a type 1-4 meter. Peak consumption is charged at two rates, one rate for consumption up to and including 1,666.7 kWh/mth[^] and another rate for the balance of peak consumption. Off Peak consumption is charged at a flat rate. An excluded service charge applies where ETSA Utilities is required to read the type 1-4 meter (eg for tier one customers and for tier two customers < 160MWh pa). This tariff is invoiced monthly.
- (j) A Low Voltage Business 2 rate – Type 5-6 Meter Read Monthly customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using peak and off-peak network charges. Peak consumption is charged at two rates, one rate for consumption up to and including 1,666.7 kWh/mth[^] and another rate for the balance of peak consumption. Off Peak consumption is charged at a flat rate. The User utilises a type 5-6 meter and requires ETSA Utilities to read the meter monthly for which an excluded service charge applies. This tariff is invoiced monthly.
- (k) A Low Voltage Business 2 rate – Type 5-6 Meter Read Quarterly customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using peak and off-peak network charges. Peak consumption is charged at two rates, one rate for consumption up to and including 1,666.7 kWh/mth[^] and another rate for the balance of peak consumption. Off Peak consumption is charged at a flat rate. The User utilises a type 5-6 meter which requires ETSA Utilities to read the meter. This tariff is invoiced quarterly.
- (l) A Low Voltage Business single rate – Type 1-4 Meter customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using single rate network charges. The User utilises a type 1-4 meter. An excluded service charge applies where ETSA Utilities is required to read the type 1-4 meter (eg for tier one customers and for tier two customers < 160MWh pa). This tariff is invoiced monthly.
- (m) A Low Voltage Business single rate – Type 5-6 Meter Read Monthly customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using single rate network charges. The User utilises a type 5-6 meter and requires ETSA Utilities to read the meter monthly for which an excluded service charge applies. This tariff is invoiced monthly.
- (n) A Low Voltage Business single rate – Type 5-6 Meter Read Quarterly customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using single rate metering. The User utilises a type 5-6 meter which requires ETSA Utilities to read the meter. This tariff is invoiced quarterly.
- (o) A Low Voltage Residential single rate – Type 1-4 Meter Read Monthly customer is a Distribution Network User that is a residential customer taking supply at less than 1kV. Consumption is charged at two rates, one rate for consumption up to and including 333.3 kWh/mth⁺ and another rate for the balance of consumption. The User utilises a type 1-4 meter. An excluded service charge applies where ETSA Utilities is required to read the type 1-4 meter (eg for tier one customers and for tier two customers < 160MWh pa). This tariff is invoiced monthly.
- (p) A Low Voltage Residential single rate – Type 5-6 Meter Read Monthly customer is a Distribution Network User that is a residential customer taking supply at less than 1kV. Consumption is charged at two rates, one rate for consumption up to and including 333.3 kWh/mth⁺ and another rate for the balance of consumption. The User utilises a type 5-6 meter and requires ETSA Utilities to read the meter monthly for which an excluded service charge applies. This tariff is invoiced monthly.
- (q) A Low Voltage Residential single rate – Type 5-6 Meter Read Quarterly customer is a Distribution Network User that is a residential customer taking supply at less than 1kV. Consumption is charged at two rates, one rate for consumption up to and including 333.3 kWh/mth⁺ and another rate for the balance of consumption. The User utilises a type 5-6 meter which requires ETSA Utilities to read the meter. This tariff is invoiced quarterly.
- (r) A Low Voltage Controlled Load is used by a Distribution Network User for permanently installed storage water heaters with a rated delivery of not less than 125 litres, storage space heaters and other approved applications involving a time switch and separate metering where the timing has been set in accordance with ETSA Utilities' requirements regarding the timing of loads. Consumption is charged at two rates, one rate for consumption up to and including 666.7 kWh/mth[#] and another rate for the balance of consumption. This tariff is available only to Distribution Network Users that were taking supply under the Controlled Load tariff as at 30 June 2003, or are utilising a business single or residential tariff at the NMI in conjunction with the controlled load. This tariff is invoiced at the same frequency as other tariffs used by the Distribution Network User at that NMI.
- (s) Unmetered Overnight Usage supply is defined as overnight use by a Distribution Network User for public lighting. These tariffs are generally invoiced monthly, unless otherwise agreed by ETSA Utilities.
- (t) Unmetered 24 Hour Usage supply is defined as constant 24 hour per day use by a Distribution Network User, typically public phones, traffic lights and telecommunications installations. These tariffs are generally invoiced monthly, unless otherwise agreed by ETSA Utilities.
- (u) Other Unmetered Supply is defined as unmetered use by Distribution Network Users other than public lighting or continuous use. These tariffs are generally invoiced monthly, unless otherwise agreed by ETSA Utilities.

- (v) A Sub-Transmission Network (kW) User is a Distribution Network User taking supply at 66kV, or at 33kV outside of the Adelaide metropolitan area. A minimum annual demand of 10MW applies. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.
- (w) A Zone Substation (kW) customer is a Distribution Network User taking supply generally at 11kV from the low voltage transformer terminals. Supply may also be taken at lower voltages that exceed 1kV. A minimum annual demand of 5MW and a minimum annual usage of 25GWh apply. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.
- (x) A High Voltage Demand (kW) customer is a Distribution Network User taking supply generally at 11kV. Supply may also be taken at lower voltages that exceed 1kV or at 33kV in metropolitan Adelaide. A minimum annual demand of 1MW applies. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.
- (y) The High Voltage Demand (kW) (Obsolete) tariff is available only to Distribution Network Users that were taking supply under this tariff as at 11 October 1999. Conditions applicable at that date apply. These tariffs are invoiced monthly.
- (z) A Large Low Voltage Demand (kW) customer is a Distribution Network User taking supply at less than 1kV and generally from the low voltage distribution transformer terminals. A minimum annual demand of 1MW applies. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.
- (aa) A Low Voltage Demand (kW) customer is a Distribution Network User taking supply at less than 1kV and generally from the low voltage distribution transformer terminals. A minimum annual demand of 300kW applies. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.
- (bb) A Medium Low Voltage Demand (kW) customer is a Distribution Network User that is not a residential customer taking supply at less than 1kV and using demand, peak and off-peak network charges. A minimum annual demand of 100kW applies. A NEM compliant type 1-4 interval meter is required. This tariff is available only to Distribution Network Users that were taking supply under this tariff as at 30 June 2001. These tariffs are invoiced monthly.

3. The supply and demand charges are levied and billed to Distribution Network Users periodically on a pro-rata basis.

4. Demand charges are determined on the basis of:

- (a) Agreed maximum demand (Annual Demand); and
 - (b) Agreed additional maximum demand (Additional Demand),
- determined in accordance with Schedule 2 of Part B of the 2005-2010 Electricity Distribution Price Determination.

5. Peak energy is energy consumed on business days between the hours of 0700 and 2100 (Central Standard Time). For Distribution Network Users with metering that does not recognise specific days, peak energy is energy consumed on each day between the hours of 0700 and 2100 (Central Standard Time).

6. Off-peak energy is energy consumed other than peak energy.