

MONGODB PRACTICE ENVIRONMENT INSTALLATION GUIDE

CONTENTS

1. Introduction – practice environments for EPAM Big Data course	2
2. Prerequisites for running the practice environment	2
3. Creating the MongoDB Docker container	2
4. Starting the MongoDB Docker container	3
5. Connecting to the Docker environment	3
6. Useful Docker commands.....	3
View Docker containers and their status.....	3
Stopping and Starting the Docker container	3
Remove a previously installed Docker container	3
Check container resource usage (RAM etc)	3
7. Stopping the Docker environment	4
8. MongoDB environment details	4
9. Troubleshooting the Docker environment.....	4

1. INTRODUCTION – PRACTICE ENVIRONMENTS FOR EPAM BIG DATA COURSE

- Practice environments are based on Docker containers, which can be downloaded and invoked on the student machines.
- To minimize resources, most topics will have their own dockers, running only the minimum required components
- For each Docker it will be stated what is the optimal resource allocation and what is the minimum resource requirements for using it.

2. PREREQUISITES FOR RUNNING THE PRACTICE ENVIRONMENT

- Docker
 - Install Docker
 - Mac: <https://docs.docker.com/docker-for-mac/install/>
 - Windows: <https://docs.docker.com/docker-for-windows/install/>
 - Linux: <https://docs.docker.com/engine/install/> (Choose your Linux distribution)
 - Configure Docker
 - Open Docker settings, and configure to 8GB RAM
 - For more details see here:
 - Mac: <https://docs.docker.com/docker-for-mac/>
 - Windows: <https://docs.docker.com/docker-for-windows/>
 - Install Docker Compose (Linux only):
 - Mac & Windows: Docker compose already included along with Docker Desktop.
 - Linux: <https://docs.docker.com/compose/install/>
- Minimum system requirements
 - 8 GB RAM
 - 2GHz CPU
 - 10GB free space on hard disk

3. CREATING THE MONGODB DOCKER CONTAINER

- To install the Docker container for the MongoDB practice, run the following command - `docker create --name mongo -it mongo`
 - Be sure to change the IP address to the IP you previously marked

`docker create --name mongo -it mongo`

- This can take anywhere from 2 minutes up to an hour, depending on your internet connection.

4. STARTING THE MONGODB DOCKER CONTAINER

- Start the Docker container using the following command:

```
docker start mongo
```

- Make sure the image is up and running:

```
docker ps -a
```

5. CONNECTING TO THE DOCKER ENVIRONMENT

- Open the command prompt and issue the following command:

```
docker exec -it mongo /bin/bash
```

6. USEFUL DOCKER COMMANDS

VIEW DOCKER CONTAINERS AND THEIR STATUS

```
docker ps -a
```

STOPPING AND STARTING THE DOCKER CONTAINER

```
docker stop mongo
```

```
docker start mongo
```

REMOVE A PREVIOUSLY INSTALLED DOCKER CONTAINER

```
docker rm mongo
```

CHECK CONTAINER RESOURCE USAGE (RAM ETC)

```
docker stats
```

7. STOPPING THE DOCKER ENVIRONMENT

- Run command -
docker stop mongo

8. MONGODB ENVIRONMENT DETAILS

Use root/example as user/password credentials

services:

mongo:

image: mongo

restart: always

environment:

MONGO_INITDB_ROOT_USERNAME: root

MONGO_INITDB_ROOT_PASSWORD: example

mongo-express:

image: mongo-express

restart: always

ports:

- 8081:8081

environment:

ME_CONFIG_MONGODB_ADMINUSERNAME: root

ME_CONFIG_MONGODB_ADMINPASSWORD: example

9. TROUBLESHOOTING THE DOCKER ENVIRONMENT

- See Guidelines document for troubleshooting issues.