

**Assignment 1 is due Feb 17 (Monday), 23:30.**

**Submission** A pdf copy of your own solutions to Problems 1 and 2 should be submitted at SUCourse.

**Grading** Full credit will be given to correct solutions that are described clearly.

**Problem 1 (Recurrences (10 points))** Give an asymptotic tight bound for  $T(n)$  in each of the following recurrences. Assume that  $T(n)$  is constant for  $n \leq 2$ . No explanation is needed.

(a)  $T(n) = 2T(n/2) + n^3$

(b)  $T(n) = 7T(n/2) + n^2$

(c)  $T(n) = 2T(n/4) + \sqrt{n}$

(d)  $T(n) = T(n-1) + n$

**Problem 2 (Longest Common Subsequence - Python)** Consider the two algorithms for the Longest Common Subsequence problem, shown in Figures 1 and 2. Each algorithm takes two strings,  $X$  and  $Y$ , and two natural numbers,  $i$  and  $j$ , and returns the length of the longest common subsequence (LCS) between the prefixes  $X[0..i]$  and  $Y[0..j]$  of the given strings. The algorithm shown in Figure 1 is a naive recursive algorithm whereas the algorithm shown in Figure 2 is a slight variation with memoization. We can compute the length of the LCS of two given strings, using these two algorithms, as illustrated in Figure 3.

In the following,  $m$  is the length of the string  $X$ , and  $n$  is the length of the string  $Y$ .

- (a) **(20 points)** According to the cost model of Python, the cost of computing the length of a string using the function `len` is  $O(1)$ , and the cost of finding the maximum of a list of  $k$  numbers using the function `max` is  $O(k)$ . Based on this cost model:
- (i) What is the best asymptotic worst-case running time of the naive recursive algorithm shown in Figure 1? Please explain.
  - (ii) What is the best asymptotic worst-case running time of the recursive algorithm with memoization, shown in Figure 2? Please explain.

```
def lcs(X,Y,i,j):
    if (i == 0 or j == 0):
        return 0
    elif X[i-1] == Y[j-1]:
        return 1 + lcs(X,Y,i-1,j-1)
    else:
        return max(lcs(X,Y,i,j-1),lcs(X,Y,i-1,j))
```

Figure 1: A recursive algorithm to compute the LCS of two strings

```
def lcs(X,Y,i,j):
    if c[i][j] >= 0:
        return c[i][j]

    if (i == 0 or j == 0):
        c[i][j] = 0
    elif X[i-1] == Y[j-1]:
        c[i][j] = 1 + lcs(X,Y,i-1,j-1)
    else:
        c[i][j] = max(lcs(X,Y,i,j-1),lcs(X,Y,i-1,j))
    return c[i][j]
```

Figure 2: A recursive algorithm to compute the LCS of two strings, with memoization

```
X = "acggacgggatctgggtccg"
Y = "tcccacatggtgcttccccg"

lX = len(X)
lY = len(Y)

#uncomment the next line to initialize c (for memoization)
#c = [[-1 for k in range(lY+1)] for l in range(lX+1)]

print "Length of LCS is ", lcs(X,Y,lX,lY)
```

Figure 3: An example: Computing the length of the LCS of two given DNA sequences

- (b) **(30 points)** Implement these two algorithms using Python. For each algorithm, determine its scalability experimentally by running it with different lengths of strings, in the worst case.

- (i) Fill in following table with the running times in seconds.

Algorithm	$m = n = 5$	$m = n = 10$	$m = n = 15$	$m = n = 20$	$m = n = 25$
Naive					
Memoization					

Specify the properties of your machine (e.g., CPU, RAM, OS) where you run your programs.

- (ii) Plot these experimental results in a graph.
- (iii) Discuss the scalability of the algorithms with respect to these experimental results. Do the experimental results confirm the theoretical results you found in (a)?
- (c) **(40 points)** For each algorithm, determine its average running time experimentally by running it with randomly generated DNA sequences of length  $m = n$ . For each length 5, 10, 15, 20, 25, you can randomly generate 30 pairs of DNA sequences, using Sequence Manipulation Suite.<sup>1</sup>

- (i) Fill in following table with the average running times in seconds ( $\mu$ ), and the standard deviation ( $\sigma$ ).

Algorithm	$m = n = 5$		$m = n = 10$		$m = n = 15$		$m = n = 20$		$m = n = 25$	
	$\mu$	$\sigma$	$\mu$	$\sigma$	$\mu$	$\sigma$	$\mu$	$\sigma$	$\mu$	$\sigma$
Naive										
Memoization										

- (ii) Plot these experimental results in a graph.
- (iii) Discuss how the average running times observed in your experiments grow, compared to the worst case running times observed in (b).

<sup>1</sup>[https://www.bioinformatics.org/sms2/random\\_dna.html](https://www.bioinformatics.org/sms2/random_dna.html).