


Deep Learning

Hung-yi Lee

李宏毅

Deep learning attracts lots of attention.

- I believe you have seen lots of exciting results before.



Deep learning trends at Google. Source: SIGMOD 2016/Jeff Dean

Ups and downs of Deep Learning

- 1958: Perceptron (linear model)
- 1969: Perceptron has limitation
- 1980s: Multi-layer perceptron
 - Do not have significant difference from DNN today
- 1986: Backpropagation
 - Usually more than 3 hidden layers is not helpful
- 1989: 1 hidden layer is “good enough”, why deep?
- 2006: RBM initialization
- 2009: GPU
- 2011: Start to be popular in speech recognition
- 2012: win ILSVRC image competition
- 2015.2: Image recognition surpassing human-level performance
- 2016.3: Alpha GO beats Lee Sedol
- 2016.10: Speech recognition system as good as humans


Three Steps for Deep Learning



Deep Learning is so simple



Neural Network




Neural Network

Different connection leads to different network structures


Network parameter θ : all the weights and biases in the “neurons”

Fully Connect Feedforward Network




Sigmoid Function


$$\sigma(z) = \frac{1}{1 + e^{-z}}$$



Fully Connect Feedforward Network



Fully Connect Feedforward Network




This is a function.

Input vector, output vector

$$f\left(\begin{bmatrix} 1 \\ -1 \end{bmatrix}\right) = \begin{bmatrix} 0.62 \\ 0.83 \end{bmatrix} \quad f\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}\right) = \begin{bmatrix} 0.51 \\ 0.85 \end{bmatrix}$$

Given network structure, define a function set


Fully Connect Feedforward Network



Deep = Many hidden layers

http://cs231n.stanford.edu/slides/winter1516_lecture8.pdf


8 layers



16.4%

AlexNet (2012)


7.3%



19 layers

VGG (2014)

22 layers



6.7%


GoogleNet (2014)

Deep = Many hidden layers

152 layers

101 layers

Special
structure



Ref:
<https://www.youtube.com/watch?v=dxB6299gpvl>

3.57%

16.4%

AlexNet
(2012)

7.3%

VGG
(2014)

6.7%


GoogleNet
(2014)

Residual Net
(2015)

Taipei
101




Matrix Operation




$$\sigma\left(\underbrace{\begin{bmatrix} 1 & -2 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ -1 \end{bmatrix} + \begin{bmatrix} 1 \\ 0 \end{bmatrix}}_{\begin{bmatrix} 4 \\ -2 \end{bmatrix}} \right) = \begin{bmatrix} 0.98 \\ 0.12 \end{bmatrix}$$

Neural Network



Neural Network




$$y = f(x)$$

Using parallel computing techniques to speed up matrix operation

$$= \sigma(W^L \dots \sigma(W^2 \sigma(W^1 x + b^1) + b^2) \dots + b^L)$$

Output Layer as Multi-Class Classifier


Feature extractor replacing
feature engineering



Example Application




Input



Ink \rightarrow 1

No ink \rightarrow 0


Output




Each dimension represents the confidence of a digit.

Example Application

- Handwriting Digit Recognition




Example Application



You need to decide the network structure to let a good function in your function set.

FAQ



- Q: How many layers? How many neurons for each layer?

Trial and Error

+

Intuition

- Q: Can the structure be automatically determined?
 - E.g. Evolutionary Artificial Neural Networks
- Q: Can we design the network structure?

Convolutional Neural Network (CNN)


Three Steps for Deep Learning



Deep Learning is so simple




Loss for an Example



Total Loss

For all training data ...



Total Loss:

$$L = \sum_{n=1}^N l^n$$


Find a function in function set that minimizes total loss L

Find the network parameters θ^* that minimize total loss L


Three Steps for Deep Learning



Deep Learning is so simple




Gradient Descent



$$\nabla L = \begin{bmatrix} \frac{\partial L}{\partial w_1} \\ \frac{\partial L}{\partial w_2} \\ \vdots \\ \frac{\partial L}{\partial b_1} \\ \vdots \end{bmatrix}$$

gradient

Gradient Descent




Gradient Descent

This is the “learning” of machines in deep learning

➡ Even alpha go using this approach.

People image



Actually



I hope you are not too disappointed :p

Backpropagation

- Backpropagation: an efficient way to compute $\partial L / \partial w$ in neural network



theano

Caffe



libdnn

台大周伯威
同學開發

Ref:

http://speech.ee.ntu.edu.tw/~tlkagk/courses/MLDS_2015_2/Lecture/DNN%20backprop.ecm.mp4/index.html

Three Steps for Deep Learning



Deep Learning is so simple



Acknowledgment

