


# Unsupervised Learning: Word Embedding

# Word Embedding

- Machine learns the meaning of words from reading a lot of documents without supervision



## 1-of-N Encoding

dimension reduction

## Word Embedding


apple = [ 1 0 0 0 0 ]

bag = [ 0 1 0 0 0 ]

cat = [ 0 0 1 0 0 ]




dog = [ 0 0 0 1 0 ]

elephant = [ 0 0 0 0 1 ]



## Word Class

利用clustering



# Word Embedding


- Machine learns the meaning of words from reading a lot of documents without supervision
- A word can be understood by its context

蔡英文、馬英九 are something very similar

You shall know a word by the company it keeps

馬英九 520宣誓就職

蔡英文 520宣誓就職



# How to exploit the context?

- **Count based**

- If two words  $w_i$  and  $w_j$  frequently co-occur,  $V(w_i)$  and  $V(w_j)$  would be close to each other
- E.g. Glove Vector:

<http://nlp.stanford.edu/projects/glove/>

$$V(w_i) \cdot V(w_j) \longleftrightarrow N_{i,j}$$

Inner product

Number of times  $w_i$  and  $w_j$   
in the same document


- **Prediction based**

# Prediction-based – Training

Collect data:

潮水 退了 就 知道 誰 ...  
不爽 不要 買 ...  
公道價 八萬 一 ...  
.....

**Minimizing  
cross entropy**



# Prediction-based - 推文接話

推 louisee :話說十幾年前我念公立國中時,老師也曾做過這種事,但

<https://www.ptt.cc/bbs/Teacher/M.1317226791.A.558.html>

推 AO56789: 我同學才扯好不好，他有一次要交家政料理報告  
→ AO56789: 其中一個是要寫一樣水煮料理的食譜，他居然給我寫

著名簽名檔 (出處不詳)


# Prediction-based

## – Language Modeling


$P(\text{"wreck a nice beach"})$

$= P(\text{wreck} | \text{START}) P(a | \text{wreck}) P(\text{nice} | a) P(\text{beach} | \text{nice})$

$P(b | a)$ : the probability of NN predicting the next word.









Bengio, Y., Ducharme, R., Vincent, P., & Jauvin, C. (2003). A neural probabilistic language model. *Journal of machine learning research*, 3(Feb), 1137-1155.

# Prediction-based




- Take out the input of the neurons in the first layer
- Use it to represent a word  $w$
- Word vector, word embedding feature:  $V(w)$





# Prediction-based

You shall know a word  
by the company it keeps



# Prediction-based

## – Sharing Parameters



The length of  $\mathbf{x}_{i-1}$  and  $\mathbf{x}_{i-2}$  are both  $|V|$ .

The length of  $\mathbf{z}$  is  $|Z|$ .


$$\mathbf{z} = \mathbf{W}_1 \mathbf{x}_{i-2} + \mathbf{W}_2 \mathbf{x}_{i-1}$$

The weight matrix  $\mathbf{W}_1$  and  $\mathbf{W}_2$  are both  $|Z| \times |V|$  matrices.

$$\mathbf{W}_1 = \mathbf{W}_2 = \mathbf{W} \Rightarrow \mathbf{z} = \mathbf{W} (\mathbf{x}_{i-2} + \mathbf{x}_{i-1})$$

# Prediction-based


## – Sharing Parameters



# Prediction-based


## – Various Architectures

- Continuous bag of word (CBOW) model





*predicting the word given its context*

- Skip-gram




*predicting the context given a word*

# Word Embedding



Source: <http://www.slideshare.net/hustwj/cikm-keynotenov2014>

# Word Embedding



Fu, Ruiji, et al. "Learning semantic hierarchies via word embeddings." *Proceedings of the 52th Annual Meeting of the Association for Computational Linguistics: Long Papers*. Vol. 1. 2014.



# Word Embedding

- Characteristics  $V(\text{Germany}) \approx V(\text{Berlin}) - V(\text{Rome}) + V(\text{Italy})$

$$V(\text{hotter}) - V(\text{hot}) \approx V(\text{bigger}) - V(\text{big})$$

$$V(\text{Rome}) - V(\text{Italy}) \approx V(\text{Berlin}) - V(\text{Germany})$$

$$V(\text{king}) - V(\text{queen}) \approx V(\text{uncle}) - V(\text{aunt})$$


- Solving analogies

Rome : Italy = Berlin : ?

Compute  $V(\text{Berlin}) - V(\text{Rome}) + V(\text{Italy})$   
Find the word  $w$  with the closest  $V(w)$

# Demo


- Machine learns the meaning of words from reading a lot of documents without supervision



# Demo

- Model used in demo is provided by 陳仰德
  - Part of the project done by 陳仰德、林資偉
  - TA: 劉元銘
  - Training data is from PTT (collected by 葉青峰)


# Multi-lingual Embedding




Bilingual Word Embeddings for Phrase-Based Machine Translation, Will Zou, Richard Socher, Daniel Cer and Christopher Manning, EMNLP, 2013



# Document Embedding

- word sequences with different lengths → the vector with the same length
  - The vector representing the meaning of the word sequence
  - A word sequence can be a document or a paragraph

  
word sequence  
(a document or paragraph)




# Semantic Embedding



Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

# Beyond Bag of Word

- To understand the meaning of a word sequence, the order of the words can not be ignored.



# Beyond Bag of Word

- **Paragraph Vector**: Le, Quoc, and Tomas Mikolov.  
"Distributed Representations of Sentences and Documents." ICML, 2014
- **Seq2seq Auto-encoder**: Li, Jiwei, Minh-Thang Luong, and Dan Jurafsky. "A hierarchical neural autoencoder for paragraphs and documents." arXiv preprint, 2015
- **Skip Thought**: Ryan Kiros, Yukun Zhu, Ruslan Salakhutdinov, Richard S. Zemel, Antonio Torralba, Raquel Urtasun, Sanja Fidler, "Skip-Thought Vectors" arXiv preprint, 2015.



# Acknowledgement

- 感謝 John Chou 發現投影片上的錯字