

Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for contents of text-input area (checked with vnu 26.6.26)

Checker Input

Show

☐ source

☐ outline

☐ image report

☐ errors & warnings only

Options...

Check by

text input

▼

☐ check as CSS

</svg>

<span id="nav-basket-count_mobile"

class="basket badge ">

1

</div>

<span id="nav-basket-total_mobile"

data-basket="total"

class="nav-basket-total"

aria-hidden="true">£35.00

</div>

</div>

<button class="navbar-toggler"

type="button"

Check

Use the Message Filtering button below to display options for hiding/showing particular messages, and to see total counts of errors and warnings.

Message Filtering 8 messages hidden by filtering

- Error** Attribute `hx-get` not allowed on element `div` at this point.

[From line 78, column 1; to line 83, column 6](#)

```
housing"><div id="nav-basket-wrapper_mobile" class="nav-basket-  
wrapper" hx-get="/basket/nav-basket" hx-trigger="basketUpdated  
from:body" hx-swap="outerHTML"><a
```

Attributes for element `div`:

[Global attributes](#)
- Error** Attribute `hx-trigger` not allowed on element `div` at this point.

[From line 78, column 1; to line 83, column 6](#)

```
housing"><div id="nav-basket-wrapper_mobile" class="nav-basket-
wrapper" hx-get="/basket/nav-basket" hx-trigger="basketUpdated
from:body" hx-swap="outerHTML"><a
```

Attributes for element [div](#):

[Global attributes](#)

3. **Error** Attribute `hx-swap` not allowed on element `div` at this point.

[From line 78, column 1; to line 83, column 6](#)

```
housing"><div id="nav-basket-wrapper_mobile" class="nav-basket-
wrapper" hx-get="/basket/nav-basket" hx-trigger="basketUpdated
from:body" hx-swap="outerHTML"><a
```

Attributes for element [div](#):

[Global attributes](#)

4. **Error** Attribute `hx-get` not allowed on element `div` at this point.

[From line 150, column 1; to line 155, column 6](#)

```
g-block"><div id="nav-basket-wrapper" class="nav-basket-wrapper"
hx-get="/basket/nav-basket" hx-trigger="basketUpdated from:body"
hx-swap="outerHTML"><a
```

Attributes for element [div](#):

[Global attributes](#)

5. **Error** Attribute `hx-trigger` not allowed on element `div` at this point.

[From line 150, column 1; to line 155, column 6](#)

```
g-block"><div id="nav-basket-wrapper" class="nav-basket-wrapper"
hx-get="/basket/nav-basket" hx-trigger="basketUpdated from:body"
hx-swap="outerHTML"><a
```

Attributes for element [div](#):

[Global attributes](#)

6. **Error** Attribute `hx-swap` not allowed on element `div` at this point.

[From line 150, column 1; to line 155, column 6](#)

```
g-block"><div id="nav-basket-wrapper" class="nav-basket-wrapper"
hx-get="/basket/nav-basket" hx-trigger="basketUpdated from:body"
hx-swap="outerHTML"><a
```

Attributes for element [div](#):

[Global attributes](#)

7. **Error** Attribute `hx-get` not allowed on element `form` at this point.

[From line 221, column 1; to line 227, column 25](#)

```
ard"><form id="sidebar-form-desktop" method="get"
class="manifest-form" hx-get="/accounts/dashboard/" hx-
```

Attributes for element [form](#):

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

8. **Error** Attribute `hx-target` not allowed on element `form` at this point.

[From line 221, column 1; to line 227, column 25](#)

```
ard"> <form id="sidebar-form-desktop" method="get"
class="manifest-form" hx-get="/accounts/dashboard/" hx-
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element [form](#):

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

9. **Error** Attribute `hx-trigger` not allowed on element `form` at this point.

[From line 221, column 1; to line 227, column 25](#)

```
ard"> <form id="sidebar-form-desktop" method="get"
class="manifest-form" hx-get="/accounts/dashboard/" hx-
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element [form](#):

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

10. **Error** Attribute `hx-push-url` not allowed on element `form` at this point.

From line 221, column 1; to line 227, column 25

```
ard"> <form id="sidebar-form-desktop" method="get"
class="manifest-form" hx-get="/accounts/dashboard/" hx-
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element `form`:

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

11. **Error** Attribute `hx-get` not allowed on element `form` at this point.

From line 271, column 1; to line 277, column 25

```
> <form id="sidebar-form-mobile" method="get"
class="manifest-form" hx-get="/accounts/dashboard/" hx-
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element `form`:

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

12. **Error** Attribute `hx-target` not allowed on element `form` at this point.

[From line 271, column 1; to line 277, column 25](#)

```
> <form id="sidebar-form-mobile" method="get"
class="manifest-form" hx-get="/accounts/dashboard/"
hx-target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element `form`:

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

13. **Error** Attribute `hx-trigger` not allowed on element `form` at this point.

[From line 271, column 1; to line 277, column 25](#)

```
> <form id="sidebar-form-mobile" method="get"
class="manifest-form" hx-get="/accounts/dashboard/"
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element `form`:

[Global attributes](#)

[accept-charset](#) — Character encodings to use for [form submission](#)

[action](#) — [URL](#) to use for [form submission](#)

[autocomplete](#) — Default setting for autofill feature for controls in the form

[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[method](#) — Variant to use for [form submission](#)

[name](#) — Name of form to use in the [document.forms](#) API

[novalidate](#) — Bypass form control validation for [form submission](#)

[target](#) — [Navigable](#) for [form submission](#)

[rel](#)

14. **Error** Attribute `hx-push-url` not allowed on element `form` at this point.

[From line 271, column 1; to line 277, column 25](#)

```
> <form id="sidebar-form-mobile" method="get"
class="manifest-form" hx-get="/accounts/dashboard/"
target="#manifest-results" hx-trigger="keyup changed delay:300ms,
```

Attributes for element `form`:

[Global attributes](#)[accept-charset](#) — Character encodings to use for [form submission](#)[action](#) — [URL](#) to use for [form submission](#)[autocomplete](#) — Default setting for autofill feature for controls in the form[enctype](#) — [Entry list](#) encoding type to use for [form submission](#)[method](#) — Variant to use for [form submission](#)[name](#) — Name of form to use in the [document.forms](#) API[novalidate](#) — Bypass form control validation for [form submission](#)[target](#) — [Navigable](#) for [form submission](#)[rel](#)15. **Error** Attribute `hx-boost` not allowed on element `a` at this point.[From line 342, column 5; to line 345, column 16](#)

```
t-2">␣␣␣<a href="?&pdf=1"␣␣␣hx-boost="false"␣␣␣class="btn
btn--industrial-ghost btn--accent-txt"␣␣␣download>Export
```

Attributes for element `a`:[Global attributes](#)[href](#) — Address of the [hyperlink](#)[target](#) — [Navigable](#) for [hyperlink navigation](#)[download](#) — Whether to download the resource instead of navigating to it, and its filename if so[ping](#) — [URLs](#) to ping[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource[hreflang](#) — Language of the linked resource[type](#) — Hint for the type of the referenced resource[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element**Document checking completed.**

Used the HTML parser.

Total execution time 2639 milliseconds.

[About this checker](#) • [Report an issue](#)