Rockchip PX30 Linux5.10 SDK Release Note

ID: RK-RB-YF-969

Release Version: V1.1.0

Release Date: 2023-04-20

Security Level: □Top-Secret □Secret □Internal ■Public

DISCLAIMER

THIS DOCUMENT IS PROVIDED "AS IS". ROCKCHIP ELECTRONICS CO., LTD.("ROCKCHIP")DOES NOT PROVIDE ANY WARRANTY OF ANY KIND, EXPRESSED, IMPLIED OR OTHERWISE, WITH RESPECT TO THE ACCURACY, RELIABILITY, COMPLETENESS, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY REPRESENTATION, INFORMATION AND CONTENT IN THIS DOCUMENT. THIS DOCUMENT IS FOR REFERENCE ONLY. THIS DOCUMENT MAY BE UPDATED OR CHANGED WITHOUT ANY NOTICE AT ANY TIME DUE TO THE UPGRADES OF THE PRODUCT OR ANY OTHER REASONS.

Trademark Statement

"Rockchip", "瑞芯微", "瑞芯" shall be Rockchip's registered trademarks and owned by Rockchip. All the other trademarks or registered trademarks mentioned in this document shall be owned by their respective owners.

All rights reserved. ©2023. Rockchip Electronics Co., Ltd.

Beyond the scope of fair use, neither any entity nor individual shall extract, copy, or distribute this document in any form in whole or in part without the written approval of Rockchip.

Rockchip Electronics Co., Ltd.

No.18 Building, A District, No.89, software Boulevard Fuzhou, Fujian, PRC

Website: <u>www.rock-chips.com</u>

Customer service Tel: +86-4007-700-590

Customer service Fax: +86-591-83951833

Customer service e-Mail: fae@rock-chips.com

Preface

Overview

The document presents Rockchip PX30 Linux5.10 SDK release notes, aiming to help engineers get started with PX30 Linux5.10 SDK development and debugging faster.

Intended Audience

This document (this guide) is mainly intended for:

Technical support engineers

Software development engineers

Chipset and System Support

| Chipset | Buildroot |
|-------------|-----------|
| PX30/PX30-S | Y |

Revision History

| Date | Version | Author | Revision History |
|------------|---------|------------|------------------|
| 2022-09-20 | V1.0.0 | LinJianHua | Initial version |
| 2023-04-20 | V1.1.0 | WJL | Update to V1.1.0 |

Contents

Rockchip PX30 Linux5.10 SDK Release Note

- 1. Overview
- 2. Main Functions
- 3. How to Get the SDK
 - 3.1 Get General PX30 Linux5.10 SDK
 - 3.1.1 Get Source Code from Rockchip Code Server
 - 3.1.2 Get Source Code from Local Compression Package
- 4. Software Development Guide
- 5. Hardware Development Guide
- 6. SSH Public Key Operation Introduction
 - 6.1 Multiple Machines Use the Same SSH Public Key
 - 6.2 One Machine Switches Different SSH Public Keys
 - 6.3 Key Authority Management
 - 6.4 Reference Documents

1. Overview

This SDK is based on Buildroot 2021.11, with kernel 5.10 and U-boot v2017.09. It is suitable for PX30/PX30-S EVB development boards and all other Linux products developed based on it.

This SDK is suitable for, but not limited to, AIoT products such as sweeping robot/dictionary pen, providing flexible data path combination interfaces to meet the customized requirements for free combination, please refer to the documents under the project's docs/ directory.

2. Main Functions

| Function | Module Name |
|--------------------|---|
| System | Buildroot |
| Partition table | uboot, misc, boot, recovery, rootfs, oem, userdata |
| File System Type | EXT2/4, SquashFS |
| Upgrade Recovery | OTA, Recovery |
| Secure Boot | SecureBoot |
| Stress Test Tool | ROCKCHIP_TEST |
| Data communication | Wi-Fi, Ethernet card, USB, SD card |
| Applications | Multimedia playback, camera preview, settings, browser, file management |

3. How to Get the SDK

The SDK is released by Rockchip server. Please refer to Chapter 4 <u>Software Development Guide</u> to build a development environment.

3.1 Get General PX30 Linux5.10 SDK

3.1.1 Get Source Code from Rockchip Code Server

To get PX30 Linux5.10 SDK software package, customers need an account to access the source code repository provided by Rockchip. In order to be able to obtain code synchronization, please provide SSH public key for server authentication and authorization when apply for SDK from Rockchip technical window. About Rockchip server SSH public key authorization, please refer to Chapter 6 SSH Public Key Operation Introduction.

PX30 Linux5.10 SDK download command is as follows:

```
repo init --repo-url ssh://git@www.rockchip.com.cn/repo/rk/tools/repo -u \
ssh://git@www.rockchip.com.cn/linux/rockchip/platform/manifests -b linux -m \
px30_linux5.10_release.xml
```

Repo, a tool built on Python script by Google to help manage git repositories, is mainly used to download and manage software repository of projects. The download address is as follows:

```
git clone ssh://git@www.rockchip.com.cn/repo/rk/tools/repo
```

3.1.2 Get Source Code from Local Compression Package

For quick access to SDK source code, Rockchip Technical Window usually provides corresponding version of SDK initial compression package. In this way, developers can get SDK source code through decompressing the initial compression package, which is the same as the one downloaded by repo.

Take PX30_LINUX5.10_SDK_RELEASE_V1.1.0_20230420.tgz as an example. After geting a initialization package, you can get source code by running the following command:

```
mkdir px30
tar xvf PX30_LINUX5.10_SDK_RELEASE_V1.1.0_20230420.tgz -C px30
cd px30
.repo/repo/repo sync -l
.repo/repo/repo sync -c
```

Developers can update via .repo/repo sync -c command according to update introductions that are regularly released by FAE window.

4. Software Development Guide

For software development, please refer to the quick start documents in the project directory:

```
<SDK>/docs/PX30/Quick-start/Rockchip_PX30_Quick_Start_Linux_EN.pdf
```

5. Hardware Development Guide

For hardware development, please refer to the user guide document in the project directory:

```
<SDK>/docs/PX30/Hardware/Rockchip_PX30_Hardware_Design_Guide_V1.3_20191206_EN.pdf
```

6. SSH Public Key Operation Introduction

Please follow the introduction in the "Rockchip_User_Guide_SDK_Application_And_Synchronization_CN" to generate an SSH public key and send the email to fae@rock-chips.com, to get the SDK code.

This document will be released to customers during the process of applying for permission.

6.1 Multiple Machines Use the Same SSH Public Key

If the same SSH public key should be used in different machines, you can copy the SSH private key file id_rsa to "~/.ssh/id_rsa" of the machine you want to use.

The following prompt will appear when using a wrong private key, please be careful to replace it with the correct private key.

```
~/tmp$ git clone git@172.16.10.211:rk292x/mid/4.1.1_r1
Initialized empty Git repository in /home/cody/tmp/4.1.1_r1/.git/
The authenticity of host '172.16.10.211 (172.16.10.211)' can't be established.
RSA key fingerprint is fe:36:dd:30:bb:83:73:e1:0b:df:90:e2:73:e4:61:46.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '172.16.10.211' (RSA) to the list of known hosts.
git@172.16.10.211's password:
```

After adding the correct private key, you can use git to clone code, as shown below.

```
~$ cd tmp/
~/tmp$ git clone git@172.16.10.211:rk292x/mid/4.1.1_r1
Initialized empty Git repository in /home/cody/tmp/4.1.1_r1/.git/
The authenticity of host '172.16.10.211 (172.16.10.211)' can't be established.
RSA key fingerprint is fe:36:dd:30:bb:83:73:e1:0b:df:90:e2:73:e4:61:46.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '172.16.10.211' (RSA) to the list of known hosts.
remote: Counting objects: 237923, done.
remote: Compressing objects: 100% (168382/168382), done.
Receiving objects: 9% (21570/237923), 61.52 MiB | 11.14 MiB/s
```

Adding ssh private key may result in the following error.

```
Agent admitted failture to sign using the key
```

Enter the following command in console to solve:

```
ssh-add ~/.ssh/id_rsa
```

6.2 One Machine Switches Different SSH Public Keys

You can configure SSH by referring to ssh_config documentation.

```
~$ man ssh_config
```

```
文件(F) 编辑(E) 查看(V) 终端(T) 帮助(H)

SSH_CONFIG(5) BSD File Formats Manual SSH_CONFIG(5)

NAME

ssh_config — OpenSSH SSH client configuration files

SYNOPSIS

~/.ssh/config
/etc/ssh/ssh_config

DESCRIPTION

ssh(1) obtains configuration data from the following sources in the following order:

1. command-line options
2. user's configuration file (~/.ssh/config)
3. system-wide configuration file (/etc/ssh/ssh_config)

For each parameter, the first obtained value will be used. The configuration files contain sections separated by "Host" specifications, and that section is only applied for hosts that match one of the patterns given in the specification. The matched host name is the one given on the command line.

Manual page ssh_config(5) line 1
```

Run the following command to configure SSH configuration of current user.

```
~$ cp /etc/ssh/ssh_config ~/.ssh/config
~$ vi .ssh/config
```

As shown in the figure, SSH uses the file "~/.ssh1/id_rsa" of another directory as an authentication private key. In this way, different keys can be switched.

6.3 Key Authority Management

Server can monitor download times and IP information of a key in real time. If an abnormality is found, download permission of the corresponding key will be disabled.

Keep the private key file properly. Do not grant second authorization to third parties.

6.4 Reference Documents

For more details, please refer to document

 $"/docs/Others/Rockchip_User_Guide_SDK_Application_And_Synchronization_CN.pdf"$