

ScriptLens — Regression Corpus Requirements

What to create, how to format it, what to label, and which variations to cover for the v3 structure engine (orphans, simulate cut/edit, clean false-positive guards, and NLP stress cases).

0. Quick targets

Corpus families	4 (A planted orphans, B clean, C cut/edit, D stress)
Micro-scripts (5–10 scenes)	50–60
Clean / connected scripts	~10–15 short + ~10 longer
Required format	Fountain (<code>.fountain</code>), UTF-8
Blind workflow	Keep labels private → run engine → cross-check → promote gold YAML to CI

Hard rule: every scene break must be a real Fountain slugline starting with `INT.` / `EXT.` / `INT/EXT.` / `I/E..`. Prose without sluglines collapses into one scene — orphan results become meaningless.

1. Four corpus families

A. Planted orphan micro-scripts	Recall: engine must find known orphans	40–50 × 5–10 scenes	<code>expected_orphans</code> + anchors	Yes — gate
B. Clean / connected scripts	Precision: must NOT invent orphans	10–15 short + ~10 longer	<code>expected_orphans: []</code>	Yes — FP gate
C. Simulate cut / edit goldens	Cut & rewrite impact correctness	15–20 (can overlap A)	delete + edit YAML rows	Yes — when labeled
D. Stress / edge variations	NLP resilience & exemptions	20–30 micro cases	Per-variation expectation	Unit + corpus

Blind workflow: hold labels privately → run ScriptLens → cross-check → only then copy gold YAML into `tests/corpus/ground_truth/structure/`.

2. File format requirements (every script)

Required

- Extension: `.fountain` (prefer not `.fountain.txt`)
- Encoding: UTF-8
- Scene headings on their own line, e.g. `INT. LOCATION - DAY`
- Important props in **ALL CAPS** on first plant
- Character cues in ALL CAPS above dialogue

- Stable id in filename, e.g. `A_H1_03_hard_orphan.fountain`

Avoid / defer

- PDF-only drafts (convert to Fountain first)
- Scanned / OCR PDFs without cleanup
- Prose with no `INT.` / `EXT.` breaks
- Copyrighted Hollywood PDFs in a public git repo
- Soft “feels disconnected” labels without anchors

Folder layout

- Blind batch drop: `scripts/regression testing/`
- CI gold pairs: `tests/corpus/structure/input/ + tests/corpus/ground_truth/structure/`
- Register each gold pair in `tests/corpus/ground_truth/structure/manifest.yaml`
- Template: `tests/corpus/ground_truth/_template.yaml`
- Annotation rules: `docs/SCRIPTLENS_ANNOTATION_GUIDELINE.pdf`

3. Label schema (what to write for each gold script)

Scene numbers = order of `INT.`/`EXT.` headings (1 = first). Scene ids = `scene_001`, `scene_002`, ... matching that order.

<code>expected_orphans</code>	Yes	List of <code>scene_XXX</code> , or <code>[]</code> if clean
<code>orphan_types</code>	Yes if orphans	<code>hard</code> <code>loose</code> <code>subplot_chain</code>
<code>orphan_exemptions</code>	If applicable	<code>prologue</code> / <code>montage</code> / <code>flashback</code> / <code>imagined</code> / <code>dream</code>
<code>orphan_anchors</code>	Yes for gold	<code>C/L/P/E</code> empty checks + evidence quote
<code>expected_simulate_delete</code>	For family C	<code>cut scene_id</code> → impacted ids + <code>expect_risk_in</code>
<code>expected_simulate_edit</code>	For family C	<code>modified_text</code> + removed and/or changed edge floors
<code>expected_scene_functions</code>	Optional	<code>plant</code> / <code>payoff</code> / <code>setup</code> roles
<code>notes</code>	Recommended	Intent of the planted situation

Soft / semantic orphans need two annotators. No anchor → silver only (do not CI-gate).

4. Family A — Planted orphan variations

Aim ~40–50 five-scene scripts. Each script plants **one primary situation**.

4.1 Hard orphans (engine must flag)

H1	Detached location + new cast	Unique place + characters never reused	That <code>scene_id</code> orphan
----	------------------------------	--	-----------------------------------

H2	Detached prop beat	Unique CAPS prop never mentioned again	orphan
H3	Mid-script digression	Orphan in scene 3 of 5 (not only edges)	orphan
H4	Late orphan	Orphan as penultimate scene	orphan
H5	Two hard orphans	Two unrelated digressions	both ids
H6	Orphan subplot chain (short)	2–3 scenes linked only to each other	subplot_chain or hard per rules

4.2 Must NOT be orphans (false-positive traps)

F1	Prop Chekhov chain	Plant CAPS prop → reuse later (briefcase/bowl/key)	[]
F2	Character continuity only	Same character, changing locations	[]
F3	Location continuity only	Same place, rotating cast	[]
F4	Imagined / dream insert	Slugline contains (IMAGINED) / DREAM / VISION	[] (exempt)
F5	Flashback + shared lead	FLASHBACK heading; same main character	[] (exempt)
F6	Prologue / cold open	PROLOGUE in early scenes	[] (exempt)
F7	Montage block	MONTAGE / SERIES OF SHOTS	[] (exempt)
F8	Soft prop alias	STEEL BRIEFCASE then “the briefcase” / “the case”	[]
F9	CONTINUOUS adjacency	Same place via CONTINUOUS / MOMENTS LATER	[]

5. Family B — Clear / clean corpus

Short clean (10–15)

- 5–10 scenes, fully connected on purpose
- Label: `expected_orphans: []`
- Cover genres: drama, comedy, action, mystery, romance, etc.

Longer clear (~10)

- 15–40 scenes; still Fountain with sluglines
- Same label: no hard orphans
- Keep copyrighted sources private / gitignored

Pass rule: engine orphan set must be empty (or only scenes you explicitly exempted). Any unexpected orphan is a false positive to log.

6. Family C — Simulate cut / edit variations

Can reuse Family A/B scripts. Add 1–2 labeled checks per script.

C1	Cut plant scene → payoffs break	expect_impacted = later payoff ids; risk high/medium
C2	Cut orphan → nothing breaks	expect_impacted: []
C3	Cut bridge scene	multiple downstream ids impacted
C4	Edit strips prop from plant	expect_edges_changed_min or removed_min ≥ 1
C5	Edit removes only character name	edges change/remove; note risk set
C6	Edit that should be no-op	cosmetic rewrite; removed/changed floors = 0

7. Family D — Stress / NLP edge variations

D1	Lowercased sluglines (int. kitchen - day)	Ingest / limited mode
D2	OCR noise (random chars, missing punctuation)	Graceful degradation
D3	Prop casing variants (Brass Key vs BRASS KEY)	Extraction robustness
D4	Dialogue-only prop callbacks	Soft alias / nickname
D5	Entity rename isomorphism seed	Same graph after rename map
D6	Adjacent independent digressions swap	Permutation locality
D7	Nested location (MUSEUM - FOYER vs HALL)	Spatial linkage nuance
D8	V.O. / O.S. heavy scenes	Speaker vs presence
D9	Same head-noun different props (two BOWLS)	Avoid over-linking
D10	Imagined without shared cast names	Exemption (story5 class)

Also extend `tests/corpus/ground_truth/structure/rename_and_chekhov_patterns.yaml` with rename maps and Chekhov plant/mid/payoff wording pairs.

8. Naming & packaging convention

Family + code + index	A_H1_03_hard_orphan.fountain
Clean set	B_clean_drama_02.fountain
Cut/edit set	C_cut_plant_01.fountain
Stress set	D_imagined_01.fountain
Private labels sheet	labels_blind.xlsx or labels_private.yaml