

HOW TO DEPLOY COMPONENTS IN COPADO ?

KB0100254 - Latest Version

☆☆☆☆☆ 3 views

REFERENCE: [KB0100254](https://humanaprod.service-now.com/kb_view.do?sysparm_article=KB0100254) (https://humanaprod.service-now.com/kb_view.do?sysparm_article=KB0100254).

The document provides the steps on HOW TO DEPLOY COMPONENTS IN COPADO

Deploying new Profile and Permission Sets

- Open user story
- Commit Changes
- Git Operation = Full Profiles and Permission Sets
- Select New profiles
- Commit Changes

The screenshot shows the Copado Console interface for a 'User Story Commit'. The 'Git Operation' dropdown is highlighted with a red circle and set to 'Full Profiles & Permission'. The 'Commit Message' is 'US-0000005: Add new field to account object'. The 'Git Snapshot Name' is 'Dev1' and the 'User Story Reference' is 'US-0000005'. Below this, the 'Select Metadata' table is displayed, showing a list of profiles to be deployed.

Select...	Retrieve ...	Name	Type	Last Modified By ID	Last Modified D...	Created By	Created Date
☐	☐	Chatter External User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	Chatter Free User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	Chatter Moderator User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	ContractManager	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	External Identity User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	Force%2Ecom - App Subscription User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	Guest License User	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	MarketingProfile	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08
☐	☐	ReadOnly	Profile	Dan Kellogg	2019/10/08	Pooled Org Admin	2019/10/08

Deploying updated Field Level Security for Existing Profiles/Permission Sets

- Open user story
- Commit Changes

- Select Profiles you updated the FLS for
- Select the Field you updated FLS for
 - Retrieve Only column if there are no updates to the field itself
- Commit Changes

Deploying Picklist Value Assignments in Record Types

Let's suppose that you have added a new value in a picklist field and the record type, or that you need to modify the values assigned in the record type. In order to commit and deploy the picklist value assignments in the record types using Copado, you need to commit the following components:

- For Standard picklist fields (e.g. Case Type):
 - Select the StandardValueSet metadata type and select the CaseType field name. This contains the picklist values.
 - Select the CustomField metadata type and select the Case.Type field name. This contains the field definition.
 - Select the RecordType metadata type and select the record type name. This will commit the field definition; the field's picklist values and the assignments in the record type.
- For custom picklist fields:
 - Select the CustomField metadata type and select the field name. This contains the field definition and the picklist values.
 - Select the RecordType metadata type and select the record type name. This will commit the field definition; the field's picklist values and the assignments in the record type.
- For custom picklist fields with global value set:
 - Select the CustomField metadata type and select the field name. This contains the field definition.
 - Select the GlobalValueSet metadata type and select the global value set used in the picklist field. This contains the picklist values.
 - Select the RecordType metadata type and select the record type name. This will commit the field definition; the field's picklist values and the assignments in the record type.

Deploying New Object

When you create a new custom object, the object is committed for the first time. In this case, you should commit all the nested components, fields and validation rules that you set up at the moment of the first commit. However, for future additions, Copado allows you to commit just the incremental changes (additions) such as new fields, changes in validation rules, list views, etc. rather than having to commit again the entire object.

- Select custom object and all components created and need to be pushed forwards
- Commit Changes

Deploying new field or updates to existing field

- Commit Changes

- Select field
- Commit changes



Revised by Regin Kanagappa
Last modified 1 week ago

Helpful?

Leave a comment