

# XML format for RBA models

S. Fischer, V. Fromion, A. Goelzer

August 9, 2017

# Contents

|          |                                   |          |
|----------|-----------------------------------|----------|
| <b>1</b> | <b>Introduction</b>               | <b>3</b> |
| <b>2</b> | <b>Conventions</b>                | <b>3</b> |
| 2.1      | Naming conventions . . . . .      | 3        |
| 2.2      | Boolean attributes . . . . .      | 3        |
| <b>3</b> | <b>metabolism.xml</b>             | <b>3</b> |
| 3.1      | RBAMetabolism container . . . . . | 3        |
| 3.1.1    | RBAMetabolism . . . . .           | 3        |
| 3.1.2    | Compartment . . . . .             | 4        |
| 3.1.3    | Species . . . . .                 | 4        |
| <b>4</b> | <b>parameters.xml</b>             | <b>5</b> |
| 4.1      | RBAMetabolism container . . . . . | 5        |
| 4.1.1    | RBAMetabolism . . . . .           | 5        |
| 4.1.2    | Compartment . . . . .             | 5        |
| 4.1.3    | Species . . . . .                 | 6        |

# 1 Introduction

In this document we present the XML structures used to define a RBA model. A complete RBA model is composed of the following files:

- metabolism.xml (definition of compartments, metabolic species and metabolic reactions).
- parameters.xml (definition of density constraints and user-defined functions).
- proteins.xml (definition of proteins).
- rnas.xml (definition of RNAs).
- dna.xml (definition of DNA).
- enzymes.xml (definition of enzymatic machineries catalyzing metabolic reactions).
- processes.xml (definition of cell processes necessary to growth and maintenance).

For every file, we present the nodes that composes the XML structure. For every node, we show a class diagram that shows the node's attributes and the children node that it may/must contain. We provide a brief description about the relevance of the node in the RBA model.

## 2 Conventions

### 2.1 Naming conventions

### 2.2 Boolean attributes

## 3 metabolism.xml

### 3.1 RBAMetabolism container

The metabolism file is strongly inspired by SBML. More precisely, it is a subpart of an SBML file.

#### 3.1.1 RBAMetabolism

The outermost portion of the metabolism file is an instance of class **RBAMetabolism**, shown in Figure 2.

Currently, **RBAMetabolism** has no simple attributes. It includes exactly one instance of **ListOf** container classes. All **ListOf** classes do not have own attributes, they are merely used to organize a list of instances from another class. This organization was inspired by SBML.




Figure 1: XML structure of metabolism document.

### 3.1.2 Compartment

The **Compartment** class is used to list existing cell compartments.

**The *id* attribute** The **id** attribute is a string defining the identifier of a compartment.

### 3.1.3 Species

The **Species** class is used to list *metabolic* species.

**The *id* attribute** The **id** attribute is a string defining the identifier of a metabolite.

**The *boundaryCondition* attribute** The **boundaryCondition** attribute is a boolean. If the attribute is set to true, the metabolite is considered to be at a constant concentration. In other words, it is not affected by reactions. This is typical for metabolites in the external medium.




Figure 2: XML structure of metabolism document.

## 4 parameters.xml

### 4.1 RBAMetabolism container

The metabolism file is strongly inspired by SBML. More precisely, it is a subpart of an SBML file.

#### 4.1.1 RBAMetabolism

The outermost portion of the metabolism file is an instance of class **RBAMetabolism**, shown in Figure 2.

Currently, **RBAMetabolism** has no simple attributes. It includes exactly one instance of **ListOf** container classes. All **ListOf** classes do not have own attributes, they are merely used to organize a list of instances from another class. This organization was inspired by SBML.

#### 4.1.2 Compartment

The **Compartment** class is used to list existing cell compartments.

**The *id* attribute** The *id* attribute is a string defining the identifier of a compartment.

### 4.1.3 Species

The **Species** class is used to list *metabolic* species.

**The *id* attribute** The **id** attribute is a string defining the identifier of a metabolite.

**The *boundaryCondition* attribute** The **boundaryCondition** attribute is a boolean. If the attribute is set to true, the metabolite is considered to be at a constant concentration. In other words, it is not affected by reactions. This is typical for metabolites in the external medium.