
Where to Aim, Not How Much to Cover: Segmentation-Free Anatomy Guidance for Masked Predictive Pretraining on Retinal OCT

Anonymous Author(s)

Affiliation

Address

email

Abstract

Masked predictive pretraining asks a model to reconstruct the representation of hidden image regions. Which regions are hidden is a free design choice, and in medical imaging there is an intuitive answer: hide the tissue that carries the diagnosis. We test that intuition under tightly controlled conditions. Six masking policies are continued from a single shared I-JEPA checkpoint on 3D retinal OCT, differing in how predictor targets are placed, and evaluated with a frozen linear-probe protocol for glaucoma classification (FairVision, $N=3000$). Each policy was continued once, so what follows describes these runs rather than an expected ranking over retrainings. *Region* matters: aiming the same rectangles — same shapes, sizes and counts — at retinal tissue rather than at the whole frame improves AUC by $+0.0120$ over unguided masking at the matched epoch, and a band located by a first-order intensity statistic, using no segmentation model at all, improves it by $+0.0109$ at epoch 100. Paired intervals for both arms exclude zero at all three epochs. Anatomical *precision* does not add. A policy that places 97% of masked patches on tissue, using a trained retinal segmentation model to shape the targets, does not separate from unguided masking at epoch 50 and falls *below* it by epoch 75, as does a coverage-constrained policy; carried to epoch 100 the latter does not merely stall but peaks at epoch 73 and then declines, and an audit found its targets are shortened after placement, so it does not test aggressive coverage. Direct measurement of mask geometry across 600 slices shows the winner hides the *least* anatomy of any guided policy: anatomy says where to aim, not how much to cover. Nor are the null’s background targets wasted — they are a genuine pretraining signal, even though background contributes almost nothing to the classifier. A subgroup audit over 23 probes finds the same worst-served group every time; all three disease-stage point estimates rise (largest for mild, $+0.0137$), and only the multiplicity-adjusted white race-group interval excludes zero. The gains are not separated from one another. The difficulty ordering is untouched: the severe-to-mild gap stays within 0.0114 of constant across every policy.

1 Introduction

Self-supervised learning has become the default route to representation quality in medical imaging, where expert annotation is expensive and pathology is rare [Azizi et al., 2021, Zhou et al., 2023, Qiu et al., 2024]. Joint-embedding predictive architectures such as I-JEPA [Assran et al., 2023] learn by predicting the *representation* of masked target blocks from a visible context block, avoiding pixel reconstruction and its bias toward high-frequency detail [He et al., 2022, Xie et al., 2022].

I-JEPA samples its targets geometrically: rectangles placed uniformly at random. In natural images this is defensible, since informative content is spread broadly across the frame. In a retinal OCT B-scan it is not obviously so. A large fraction of the image is dark vitreous and background; the diagnostic signal for glaucoma is concentrated in a thin band of retinal tissue. This motivates an intuitive hypothesis, one that several recent methods adopt [Li et al., 2022, 2024, Wang et al., 2025, Shi et al., 2022]: *direct the predictive objective at clinically meaningful anatomy rather than at arbitrary image regions.*

We test this hypothesis directly and at several strengths. Rather than proposing one anatomy-aware method and reporting that it beats a baseline, we construct a *ladder* of masking policies of increasing anatomical specificity — from unguided rectangles, through rectangles aimed at tissue, to ragged targets whose shape follows the segmented retina — and hold everything else fixed. All arms continue from one shared pretrained checkpoint, use identical optimiser, schedule, and effective batch size, and are evaluated under one frozen-probe protocol.

Anatomy turns out to matter for *where* targets are aimed rather than for how much anatomy they cover. The two policies whose targets track the segmented retina most faithfully have intervals spanning zero against unguided masking at epoch 50, and the one we carried further falls significantly below it by epoch 75, while two policies that merely place ordinary rectangles on tissue gain an order of magnitude more. One earlier shaped policy did exceed its rectangle counterpart at epoch 30, so the anatomy result is mixed rather than uniformly negative. The best performer locates a band by a per-column intensity centroid and consults no segmentation model.

Contributions.

- Masking policy is isolated in medical SSL by a controlled six-arm study with a shared ancestor checkpoint and one evaluation protocol (every probe fitted is listed in Appendix A).
- Guidance helps in these runs; anatomical precision does not reliably add to it. The gain is carried by the control that separates “avoid background” from “target anatomy”: rectangles aimed at retinal tissue.
- The most anatomically precise policy is not the best performer, from direct measurement of mask geometry for every policy on 600 slices, with an explicit accounting of the axes on which the anatomy arms are confounded.
- The subgroup ordering survives every policy tried, and the headline result reproduces to 10^{-5} from public weights on different hardware and precision.

2 Related work

Masked image modelling and JEPAs. Masked autoencoders reconstruct pixels [He et al., 2022, Xie et al., 2022]; BEiT [Bao et al., 2022] and iBOT [Zhou et al., 2022] predict discrete tokens; data2vec [Baevski et al., 2022] and I-JEPA [Assran et al., 2023] predict latent representations. Video and 3D extensions follow the same template [Bardes et al., 2024, Chen et al., 2023b, Taleb et al., 2020]. Recent analyses question how much of the benefit derives from the masking distribution itself [Balestriero and LeCun, 2025, He et al., 2025].

Informed masking. A substantial line of work argues that *what* is masked matters. ADIOS [Shi et al., 2022] learns an adversarial masking model; SemMAE [Li et al., 2022] uses learned semantic parts; AttMask [Kakogeorgiou et al., 2022] masks by attention; HardPatches [Wang et al., 2023] and AutoMAE [Chen et al., 2023a] target difficulty. In the medical domain, AnatoMask [Li et al., 2024], AnatomyMAE [Ceballos Arroyo et al., 2026], MSMAE [Mao et al., 2023], and VasoMIM [Huang et al., 2026] explicitly steer masking toward anatomy, and Wang et al. [2025] argue directly for masking clinically relevant regions. Our study is a controlled test of that family’s central premise on one task.

Evidence that informed masking is not uniformly better. The picture is less one-sided than that suggests. The original masked-modelling papers report that random sampling is hard to beat: MAE’s ablation puts random-75 at 73.5 linear against block-75 at 63.9 [He et al., 2022], and SimMIM finds random beats its best block variant [Xie et al., 2022]. Among informed schemes, AttMask sits within 0.2 points of random [Kakogeorgiou et al., 2022], AutoMAE ties MAE under full fine-tuning [Chen et al., 2023a], HPM gains only when randomness is retained and *loses* when restricted

to the hardest patches [Wang et al., 2023], and attention-guided MAE underperforms MAE in the low-label regime [Sick et al., 2025]. Most directly, SemMAE’s own ablation shows that *imperfect* semantic parts add nothing over no parts at all [Li et al., 2022], and Guo et al. [2025] reproduce SemMAE below random MAE, the deficit largest under frozen evaluation — also our protocol. Chen et al. [2023a] name the mechanism a “patch selection dilemma”: a slight foreground bias helps, but raising it too far starves the encoder of the evidence it must predict from. The closest positive precedent for our best policy is segmentation-free too: Lee et al. [2025] select foreground from normalised intensity alone and gain across five 3D medical benchmarks (Appendix M tabulates these). That random masking is a strong baseline, and semantic guidance wins only sometimes, is known and contested; we do not overturn that literature. We add a controlled measurement of where a *trained medical segmentation model* falls on that spectrum, in a setting — 3D retinal OCT, joint-embedding prediction, frozen probe — where we found no prior controlled comparison.

Retinal foundation models, OCT, and fairness. RETFound [Zhou et al., 2023], VisionFM [Qiu et al., 2024], URFound [Yu et al., 2024], and OCTCube [Liu et al., 2026] pretrain on large retinal corpora; OCT-specific masked modelling is explored by Pissas et al. [2024]. MIRAGE [Morano et al., 2025] provides multimodal OCT segmentation and supplies the anatomical guidance used by several of our arms, and deep glaucoma detection from OCT is established [Maetschke et al., 2019, Ran et al., 2019, Noury et al., 2022]. Performance disparities across demographic groups are widely documented [Seyyed-Kalantari et al., 2021, Larrazabal et al., 2020, Gichoya et al., 2022]; FairVision [Luo et al., 2024a] and Harvard-GF [Luo et al., 2024b] provide OCT data with demographic attributes, and FairMedFM [Jin et al., 2024] and Shi et al. [2025] benchmark fairness for medical foundation models.

3 Method: a ladder of masking policies

We test the informed-masking premise with a ladder of six masking policies of increasing anatomical specificity, identical in every other respect.

3.1 Background

I-JEPA samples from the token grid of an image a context block and M target blocks, which need not cover it. A context encoder embeds the visible tokens; a predictor maps that embedding plus positional queries to predicted representations of the target tokens; an exponential-moving-average target encoder supplies the regression targets. With a 16×16 token grid the design choice we vary is which of the 256 cells become targets.

3.2 The six policies

All policies produce $M=4$ target blocks and one context block under identical scale and aspect-ratio ranges. The rectangle arms differ only in placement.

RANDOM (null). Stock I-JEPA multiblock. Four rectangles placed uniformly at random anywhere in the grid. No image content is consulted.

ENVELOPE (random-within-retina). Identical rectangles — same shape, size and count as RANDOM — but rejection-sampled onto the retinal envelope predicted by MIRAGE [Morano et al., 2025]. Only *location* changes. This is the control that separates “stop wasting targets on background” from “target anatomy specifically”.

CENTROID (segmentation-free). A band whose vertical position is located per slice by a per-column intensity-weighted row centroid, smoothed across columns. It adapts to the retina’s position and curvature from a first-order intensity statistic, with no segmentation model and no ground-truth annotation of any kind.

ANATOMY-v1 / ANATOMY-v2. Ragged connected components grown on the MIRAGE score map, so target *shape* follows tissue rather than being rectangular. v2 additionally bridges diagonal adjacencies.

COVER f . Targets chosen greedily to cover the anatomy subject to a hard floor leaving a fraction f of tissue visible in the context. We pretrain $f=0.21$. An implementation defect means the delivered masks never reach f (Appendix G).




Figure 1: The six masking policies on one identical B-scan, drawn with the production samplers. Each target block has its own colour; the green contour is the anatomy reference. Anatomical specificity increases along the ladder: ENVELOPE and COVER place rectangles on tissue, while the anatomy arms grow targets that trace the retina almost exactly. Downstream AUC does not increase with that specificity (Table 1); Figure 4 repeats this over five B-scans.

Figure 1 shows all six on the same B-scans.

3.3 Hypotheses

The ladder yields three testable statements:

- H1** *Avoiding background helps.* ENVELOPE > RANDOM.
- H2** *Anatomical precision helps further.* anatomy arms > ENVELOPE.
- H3** *Any benefit is due to anatomical targeting, not to incidental changes in mask area, target count, or context size.*

4 Experimental setup

Data. FairVision [Luo et al., 2024a] glaucoma OCT volumes. Each volume is a 3D scan resampled to 100 B-scans of 256×256 after transform. The label is a binary glaucoma diagnosis. Splits are fixed and patient-disjoint as released; downstream evaluation uses a held-out test split of $N=3000$ volumes (1466 positive / 1534 negative), seed 42, fixed loader order. No test volume is used to fit or select the probe head, which is selected on a separate validation split; the study’s choices of policy, checkpoint, analysis and stopping horizon were made after repeated inspection of that same test split (Section 6). Labels are byte-identical across arms, so any two arms are paired-comparable on the same cases. Self-reported demographic attributes are used only for the subgroup analysis in Section 5.5 and never as model inputs.

Pretraining. Patch-level I-JEPA, ViT-Base, 256×256 crops, patch size 16, predictor depth 6, EMA target encoder. **Every arm resumes from the same epoch-25 checkpoint** and continues with identical optimiser, learning-rate and weight-decay schedules, and effective batch size (512 for all arms). Guidance is ramped linearly from epoch 25 to 30 and held at full strength thereafter. Within the rectangle family the *only* difference between arms is the mask sampler (Section 3); the anatomy family additionally differs in collation, and we quantify that in Section 5.

Arms differ in how far they were carried. RANDOM, CENTROID and ENVELOPE reach epoch 100. ANATOMY-V2 reaches epoch 75 (its epoch-75 and epoch-92 probes under an earlier target-precision splice are excluded and replaced by a clean fp32 continuation, Appendix F); we stopped that arm having seen its epoch-75 deficit, which is a selective stopping horizon and a real weakness — a trajectory can recover, and its epoch-100 value is unmeasured, not known to be worse. ANATOMY-V1 has only epoch 30. COVER $f=0.21$ reaches epoch 100, with an extra probe at its epoch-73

Table 1: Frozen MeanPool probe, FairVision test ($N=3000$, 1466 positive). All arms continue from one epoch-25 ancestor (AUC 0.8487). Δ is versus RANDOM at the *matched* epoch. The upper block is precision-matched (fp16 throughout) and carries every headline claim; the lower block is fp32, each Δ taken against an fp32 null re-probed at the same epoch, so it is matched on both epoch and precision. The measured fp16/fp32 gap is at most 2×10^{-4} (Appendix O).

policy	guidance signal	epoch 50		epoch 75		epoch 100	
		AUC	Δ	AUC	Δ	AUC	Δ
RANDOM	none (null)	0.8641	—	0.8723	—	0.8746	—
ENVELOPE	segmenter (location only)	0.8761	+0.0120	0.8803	+0.0080	0.8807	+0.0062
CENTROID	intensity centroid, no segmenter	0.8740	+0.0099	0.8836	+0.0113	0.8855	+0.0109
ANATOMY-V2	segmenter (target shape)	0.8654	+0.0013	0.8612	−0.0111	—	—
COVER $f=.21$	segmenter (coverage)	0.8643	+0.0002	0.8639	−0.0084	0.8577	−0.0168

166 peak. Epoch 50 is therefore the only epoch at which five policies are simultaneously available, and
 167 it carries every cross-policy comparison that involves the anatomy or coverage arms.

168 **Evaluation.** The encoder is frozen. Per-slice features are mean-pooled over the volume, followed
 169 by LayerNorm and a linear head. The head is selected by validation AUC and reported on the held-
 170 out test split. We report percentile bootstrap intervals for primary AUCs and paired deltas (10,000
 171 class-stratified subject resamples; fitted heads fixed and each draw shared across arms) and DeLong
 172 tests for correlated ROC curves [DeLong et al., 1988], both of which are valid here because all arms
 173 are evaluated on the same cases in the same order. Each test volume is a distinct subject, so case-
 174 level resampling is already subject-level and no cluster correction is required [Obuchowski, 1997,
 175 Rutter, 2000]. We follow Maier-Hein et al. [2024] in reporting the operating-point metrics alongside
 176 AUC rather than AUC alone (Appendix K).

177 **Numerical precision.** The probe harness defaults to mixed precision. The RANDOM, CEN-
 178 TROID and ENVELOPE long-horizon probes were fitted under that default (fp16); the ANATOMY-V1,
 179 ANATOMY-V2, COVER and ancestor probes were fitted with autocast explicitly disabled (fp32). Pro-
 180 tocol is therefore not uniform across probes, so we partition the comparisons: all headline contrasts
 181 in Table 1 are drawn from arms sharing both epoch *and* precision, and any contrast that would cross
 182 the precision boundary is marked as such and excluded from headline claims. Section 5.6 measures
 183 the precision effect.

184 5 Results

185 Region matters and coverage does not. Each policy was pretrained once, so the intervals below are
 186 sampling error over test subjects, not seed-to-seed variance (Section 6).

187 5.1 Region matters: where you aim beats not aiming at all

188 **H1 holds, and the study’s cleanest control carries it.** ENVELOPE differs from the unguided null
 189 in *location alone* — same rectangle shapes, sizes and counts, rejection-sampled onto the retinal
 190 envelope instead of the whole frame. Moving them onto tissue is worth +0.0120 AUC at epoch
 191 50, and CENTROID, a band located from a first-order intensity statistic with no segmentation model
 192 anywhere, is worth +0.0109 at epoch 100. Every ENVELOPE and CENTROID interval excludes zero
 193 at all three epochs, and all six contrasts survive Benjamini–Hochberg correction over that family of
 194 nine ($q \leq 0.0299$; Figure 2b, with the full paired inference on all nine precision-matched contrasts
 195 in Table 14, Appendix N).

196 Aiming is not containment: the rectangles are large, so fewer than half of ENVELOPE’s masked
 197 cells land on tissue (Table 2). Guidance changes where the predictor is repeatedly sent, not what
 198 it is forbidden to see. Why the unguided null nonetheless stays close has an answer of its own
 199 (Section 5.3).

200 **Precision beyond location does not add, and the evidence is mixed rather than uniformly neg-**
 201 **ative.** H2 predicts that the anatomy arms exceed ENVELOPE. Tested directly at the matched epoch




Figure 2: **(a)** Frozen-probe test AUC against pretraining epoch; note the truncated AUC axis. All arms fork from the same epoch-25 checkpoint (open circle). Solid lines are the precision-matched fp16 family; dashed lines are fp32 arms and must not be compared vertically against the solid lines. **(b)** The actual inference: paired differences against the unguided null on identical test cases, 10,000-resample percentile bootstrap intervals. Every ENVELOPE and CENTROID interval excludes zero; COVER straddles zero at epoch 50 and is negative thereafter. Paired differences replace per-arm error bars: marginal intervals carry between-case variance that cancels in a pairing and would understate the evidence.

202 50, ANATOMY-V2 sits -0.0107 below ENVELOPE (CI $[-0.0167, -0.0046]$). At epoch 30, however,
 203 ANATOMY-V1 sits $+0.0044$ above it (CI $[+0.0009, +0.0078]$). These are different implementations
 204 at different epochs, so we do not read either as settling H2; what the pair rules out is a uniform
 205 advantage for anatomical precision, not the possibility that some shaped policy helps somewhere.
 206 Nor is ANATOMY-V2 or COVER worse than the null at the matched epoch: both sit within a paired
 207 interval that comfortably contains zero (Figure 2b), so the data rule out monotone improvement with
 208 anatomical precision, not harm.

209 **Carried to epoch 100 the coverage arm degrades.** COVER is the only policy that uses the seg-
 210 menter to choose *how much* to hide, and carried to the full horizon it produces the study’s one
 211 *negative* result. It climbs normally to epoch 50, peaks at epoch 73, then *falls*, losing -0.0071 from
 212 its own peak ($p < 0.0001$) while the unguided null keeps improving (Figure 2); its gap against the
 213 null widens monotonically across the three matched epochs (Table 1).

214 We cannot read this as evidence that high coverage is harmful. An audit found that the collator short-
 215 ens predictor targets *after* COVER chooses its placement, so its delivered masks hide *less* anatomy
 216 than ENVELOPE’s (Table 2, Figure 3) and the arm never realised the coverage it was configured for;
 217 Appendix G gives the full account.

218 **The strongest policy consults no segmentation model.** CENTROID finds its band from a per-
 219 column intensity centroid: no model and no annotation. Its margin over the null is the largest at
 220 epoch 100 and does not decay with training, whereas ENVELOPE’s does (Table 1), and it exceeds
 221 the segmenter-guided ENVELOPE arm at epoch 100 by $+0.0047$ (CI $[+0.0004, +0.0091]$), though
 222 their paired intervals span zero at epochs 50 and 75.

223 5.2 Aim, not coverage

224 **Anatomy tells you where to aim, not how much to cover.** Of the four guided arms the best
 225 performer hides the *least* anatomy, while the arm that hides the most — masking almost nothing but
 226 tissue, at 97.1% purity — does not separate from the null. Both readings come from running each
 227 production sampler on 600 training slices and measuring the realised masks (Table 2, Figures 13
 228 and 14; provenance in Appendix D). What CENTROID does instead is leave more visible: it retains
 229 more context than any other rectangle arm, and the background stays maskable. Rank correlations
 230 over these arms are positive for both anatomy hidden and purity, but at $n=4-5$ arms they resolve
 231 nothing in either direction and we draw no inference from them. Occlusion attribution on the fine-
 232 tuned probes is correspondingly diffuse (Appendix J).

Table 2: Measured mask geometry, 600 training slices, production samplers. “purity” is the fraction of masked cells lying on tissue; “loss slots” is the number of predictor target *cells* entering the loss, summed over the M targets. AUC is quoted at the *matched* epoch 50, so the geometry-to-AUC association is not read across mixed epochs.

policy	anatomy hidden	purity	mask ratio	context kept	loss slots	AUC @ep50
RANDOM	54.0%	31.5%	44.5%	41.9%	159.9	0.8641
CENTROID	62.1%	40.0%	40.3%	45.5%	159.0	0.8740
ENVELOPE	77.6%	43.3%	46.5%	40.6%	159.7	0.8761
COVER	73.5%	44.2%	43.2%	43.2%	159.1	0.8643
ANATOMY-V2	79.9%	97.1%	21.3%	67.7%	64.0	0.8654

The anatomy arms are confounded on several axes simultaneously. ANATOMY-V2 retains more context still, but it also hides far less of the grid and collapses to 64 predictor loss slots against about 159 for every rectangle arm (Table 2, Figure 15) — a much easier prediction task. They and COVER also differ from ENVELOPE in guide provenance (Appendix P). Any of these could account for its deficit without invoking target shape at all. **H3 is therefore not identified by this design**, and we do *not* claim that irregular target shape is harmful.

These are not consequences of blob geometry: the anatomy arms resample every target to a fixed $K=16$ cells, so $4 \times 16 = 64$ loss slots follows by construction, while the rectangle arms do not set K . The two families are collated differently, which weakens “everything else held fixed” for the anatomy-versus-rectangle comparison specifically; contrasts within the rectangle family are unaffected (Appendix G).

5.3 Background matters — for pretraining, not for the classifier

Unguided masking spends most of its targets on background, and they are not wasted — the most surprising result in the study. At epoch 100 the null’s predictor beats a per-position, no-context reference by 0.680 on *background* targets, *above* its 0.633 on anatomy: predicting a background token takes more than knowing where it sits, even though such tokens start out nearly pure position (90.8% of across-position input variance there comes from `pos_embed`, against 40.8% at tissue). Pretraining spends real capacity on them, and background self-similarity falls from 0.784 untrained to 0.346. Yet almost none of it reaches the classifier. Pooled background features are 95.2% linearly reconstructible from pooled anatomy features; residualised, background predicts glaucoma at test AUC 0.5515 — barely above chance, though the interval excludes it — and appending it to anatomy *lowers* test AUC for the null arm. That split — a useful *pretraining* target, a near-useless *classification* feature — is why unguided masking is such a strong baseline, and why aiming at tissue buys a gain that is real but bounded. The mechanism is described rather than established: the two controls that would settle it were not run (Appendix H).

5.4 The advantage concentrates where labels are scarce

The observed margin is larger with fewer labels: at 5% of the labelled set ($n=300$) CENTROID leads the null by +0.0496, against +0.0108 at full supervision, more than four times the advantage. A policy that only helps when labels are plentiful is of limited clinical use, so we withdrew supervision and re-fitted the same probe, holding protocol and label subsets fixed — the subsampling seed depends on the fraction and repeat but never on the arm — and, across all four arms in this sweep, the full-supervision fits reproduce their corresponding epoch-100 entries in Table 1 to within 0.0009. Whether the gap genuinely widens as labels are withdrawn we did not test; the ordering across fractions is a point-estimate observation, and the absolute gains at full supervision are small. Appendix I gives the full curve.

5.5 Subgroups: the ordering never changes

Across seven stratifications and 23 probes spanning aggregate AUC 0.8483 to 0.8855, no masking policy reorders the subgroups. Predictions are joined to the released FairVision metadata in deterministic loader order, validated by exact label reconstruction (3000/3000 cases, every probe). Probes that the exclusion rules of Appendix F remove are removed here too.

The same group is worst served every time. The worst-performing group is the same in every one of the 23 probes for sex (female), race (black), ethnicity (hispanic) and disease severity (mild (−6,−2]). The probes share a test set, an epoch-25 ancestor and a probe seed, and several are different epochs of one branch, so they are *not* independent; we report this as a descriptive regularity and attach no *p*-value. What it shows is that the disparity is not introduced by any policy we tried.

Point estimates rise everywhere; few gaps reliably move. A widening max–min gap is easy to misread as harm. It is not harm. At epoch 100 the strongest policy raises the point estimate for *every* race stratum over the null, and the max–min gap widens only because the already-best asian subgroup gains most. Family-wise simultaneous paired intervals exclude zero only for the white subgroup (CI [+0.00286, +0.01972]); the black and asian intervals include it, the smaller strata being noisier (Table 8). The gains are therefore consistent in sign across race, not provably positive in every group. Nor is there a defensible gap *trend*. Across checkpoints the race gap correlates with aggregate AUC at $\rho = +0.473$ ($q = 0.0668$ after Benjamini–Hochberg over the seven attributes tested), but those checkpoints are not independent: they are 23 probes drawn from only 7 pretraining branches, so a branch probed at four epochs contributes four correlated points. Collapsing to one point per branch, the association disappears ($\rho = +0.321$). The checkpoint-level correlation is pseudo-replicated and does not show that better models are less fair. The same holds for severity in the opposite direction ($\rho = -0.449$ per checkpoint, -0.821 per branch). Only the sex gap survives checkpoint-level correction, and it *narrows* (branch-level $\rho = -0.821$, raw $p = 0.0234$; checkpoint-level $q = 0.0038$). Neither harm nor benefit to equity is established here. A property of threshold transfer, not of masking policy, matters more at deployment: a validation-selected threshold aimed at a fixed specificity does not transfer evenly, and the smaller stratum absorbs a higher false-positive rate under *both* arms (Appendix K).

Severity point estimates rise; differential benefit is unresolved. Scoring each severity stratum against the shared pool of all negatives, the strongest policy has a mild-disease point estimate of +0.0137 at matched epoch 100, with smaller moderate and severe estimates (Table 7). These are paired differences on the same subjects; all three point estimates are positive, but after adjustment over the declared 10-contrast family only the mild interval excludes zero; the moderate and severe intervals no longer do (Table 8). Whether mild improves *more* we did not test: that needs a paired contrast between the gains, not three contrasts against zero. What does not move is the difficulty ordering itself: the severe-to-mild gap stays within 0.0114 of constant across all 23 probes while aggregate AUC spans the full range above. For equity the quantity that matters is the paired *difference* between groups’ gains; between the worst- and best-served race strata it is -0.00091 (CI [−0.03285, +0.03104]), and by sex the interval likewise contains zero, so at these subgroup sizes we cannot resolve whether the improvement is evenly distributed. Appendix E gives every stratum, Appendix E.1 the race-by-sex cells, whose gap exceeds the race margin in every arm. No policy here is a fairness intervention and none should be presented as one.

5.6 Controls: the effect is not a precision artefact

A full re-fit of the probe pipeline at fp32 shifts every arm by less than 2×10^{-4} , orders of magnitude below the effects in Table 1, so the differing autocast settings of Section 4 are not the effect and every contrast is matched on precision (Appendix O). Every number here is generated by one script from stored per-case predictions; that script, the epoch-100 CENTROID encoder, its head and those predictions are released (links withheld for anonymity). Re-encoding the test split from those weights on different hardware, at fp32 rather than fp16 and with a different encoder chunk size, reproduces the reported AUC to 9.8×10^{-6} : 22 discordant pairs out of 2,248,844.

6 Discussion and limitations

What the evidence supports. Two things about a masking policy matter in these runs, one does not, and one cannot be separated. *Region* matters: restricting the same rectangles to tissue is worth +0.0120 at the matched epoch, and an intensity-located band is worth +0.0109 at epoch 100, with paired intervals excluding zero at every epoch measured. *Background* matters as a pretraining target. Anatomical *coverage* does not: using the segmenter more aggressively — to shape targets or to maximise coverage — does not add and can subtract, and the arm hiding the most anatomy loses to

the null. Whether what the mask *leaves visible* matters is *not* separable here: the arms that differ in retained context also differ in mask ratio and loss slots. For *this* task the segmentation stage bought no more than location, and a one-line intensity statistic recovered the whole benefit. We would not generalise that to tasks where anatomy is the output, such as layer segmentation or lesion localisation.

What it does not support. We cannot claim anatomy-shaped masking is *harmful*: at the matched epoch it sits +0.0013 from the null with an interval $([-0.0055, +0.0082])$ that comfortably contains zero, so it is not resolved as worse. Nor is target *shape* identified as the operative variable (Table 2), nor is CENTROID’s mechanism. Two explanations remain live: consistency of location (the encoder is repeatedly forced to represent the same region), and masking ratio or task difficulty. Distinguishing them requires an arm that randomises the band’s vertical position while holding area and context fixed, which we did not run.

One pretraining run per policy, and a replication in progress. This design holds the ancestor checkpoint, optimiser, schedule, effective batch size and probe protocol fixed across arms, leaving masking policy the only moving variable; what it does not resample is pretraining stochasticity, so each arm is one continuation. The paired bootstrap bounds sampling error on a fixed test set, so the intervals support statements about *these* continuations rather than an expected *ranking* over retrainings, which pairwise significance on one test set does not establish [Bouthillier et al., 2021]. Probe-seed variance is outside the design too: an earlier multi-seed probe check is not reproducible from retained artifacts, so we state no bound on probe noise. A replication addressing the first gap is running and every result of it is PENDING: six continuations — RANDOM, ENVELOPE and CENTROID at two further seeds — resume from the same epoch-25 ancestor, SHA-256 verified before each leg, under configurations asserted to differ only in the seed, and run to epoch 50, giving three continuations per policy at an endpoint where every arm already carries a frozen probe. Seeds do not randomise data visitation order, so the unit of inference is post-fork optimisation noise at a fixed data order. The analysis is fixed before any value is visible (Appendix B), and either outcome is informative: an ordering that does not reproduce establishes that Table 1 describes these runs rather than the policies.

Scope, coverage and an incomplete arm. All results are glaucoma classification from FairVision OCT; generality to other modalities, diseases, or segmentation-quality regimes is untested, and the anatomy arms depend on MIRAGE’s prediction quality on this data, so a better segmenter might change the conclusion. Only $f=0.21$ was pretrained for COVER, so we report no dose-response over the visible-tissue floor and make no claim that any floor is optimal. That arm reaches epoch 100, but the collation defect above (Appendix G) means its trajectory is not evidence about aggressive coverage. Its epoch-50 value is retained as a matched-epoch comparison against every other arm. Finally, one dataset and one test split were reused throughout this programme’s history, and policies, checkpoints and analyses were chosen after repeated inspection of that split; the intervals we report are therefore best read as descriptive rather than as confirmatory inference.

Broader impact and ethics. This study uses a public, de-identified retinal dataset under its release terms and involves no new data collection or human subjects, and no model reported here is clinically validated or intended for deployment (Appendix L).

7 Conclusion

In these runs anatomy mattered for *where* targets are aimed and not for *how much* anatomy they cover. Under a matched schedule, effective batch size and shared ancestor checkpoint, aiming ordinary rectangles at retinal tissue beat unguided masking and the best policy consulted no segmentation model, while shaping targets to trace the segmented retina did not separate from unguided masking at epoch 50 and fell below it by epoch 75. Nor are the null’s background targets wasted; they carry pretraining signal that barely reaches the classifier. A subgroup audit shows every positive disease-stage point estimate rises, but only the adjusted mild interval excludes zero; race gains consistent in sign, and the difficulty ordering untouched. What makes the best policy work is not identified here: this design cannot separate consistent target placement from mask ratio and task difficulty.

References

- Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15619–15629, 2023. doi: 10.1109/CVPR52729.2023.01499.
- Shekoofeh Azizi, Basil Mustafa, Fiona Ryan, Zachary Beaver, Jan Freyberg, Jonathan Deaton, Aaron Loh, Alan Karthikesalingam, Simon Kornblith, Ting Chen, et al. Big self-supervised models advance medical image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021.
- Alexei Baevski, Wei-Ning Hsu, Qiantong Xu, Arun Babu, Jiatao Gu, and Michael Auli. data2vec: A general framework for self-supervised learning in speech, vision and language. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 1298–1312. PMLR, 2022. URL <https://proceedings.mlr.press/v162/baevski22a.html>.
- Randall Balestriero and Yann LeCun. LeJEPa: Provable and scalable self-supervised learning without the heuristics, 2025. URL <https://arxiv.org/abs/2511.08544>.
- Hangbo Bao, Li Dong, Songhao Piao, and Furu Wei. BEiT: BERT pre-training of image transformers. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=p-BhZS59o4>.
- Adrien Bardes, Quentin Garrido, Jean Ponce, Xinlei Chen, Michael Rabbat, Yann LeCun, Mahmoud Assran, and Nicolas Ballas. Revisiting feature prediction for learning visual representations from video. *Transactions on Machine Learning Research*, 2024. URL <https://openreview.net/forum?id=QaCCuDFBk2>.
- Xavier Bouthillier, Pierre Delaunay, Mirko Bronzi, Assya Trofimov, Brennan Nichyporuk, Justin Szeto, Nazanin Mohammadi Sepahvand, Edward Raff, Kanika Madan, Vikram Voleti, Samira Ebrahimi Kahou, Vincent Michalski, Tal Arbel, Chris Pal, Gael Varoquaux, and Pascal Vincent. Accounting for variance in machine learning benchmarks. *Proceedings of Machine Learning and Systems*, 3:747–769, 2021. URL https://proceedings.mlsys.org/paper_files/paper/2021/hash/0184b0cd3cfb185989f858a1d9f5c1eb-Abstract.html.
- Alberto M. Ceballos Arroyo, Jisoo Kim, Chu-Hsuan Lin, Lei Qin, Geoffrey S. Young, and Huaizu Jiang. Anatomically-guided masked autoencoder pre-training for aneurysm detection. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 5693–5702, 2026. doi: 10.1109/WACV61042.2026.00552.
- Haijian Chen, Wendong Zhang, Yunbo Wang, and Xiaokang Yang. Improving masked autoencoders by learning where to mask. In *Pattern Recognition and Computer Vision*, pages 377–390. Springer, 2023a. doi: 10.1007/978-981-99-8543-2_31.
- Zekai Chen, Devansh Agarwal, Kshitij Aggarwal, Wiem Safta, Mariann Micsinai Balan, and Kevin Brown. Masked image modeling advances 3d medical image analysis. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1970–1980, 2023b. doi: 10.1109/WACV56688.2023.00201.
- Elizabeth R. DeLong, David M. DeLong, and Daniel L. Clarke-Pearson. Comparing the areas under two or more correlated receiver operating characteristic curves: A nonparametric approach. *Biometrics*, 44(3):837–845, 1988. doi: 10.2307/2531595. URL <https://doi.org/10.2307/2531595>.
- Judy Wawira Gichoya, Imon Banerjee, Ananth Reddy Bhimireddy, John L. Burns, Leo Anthony Celi, Li-Ching Chen, Ramon Correa, Natalie Dullerud, Marzyeh Ghassemi, Shih-Cheng Huang, Po-Chih Kuo, Matthew P. Lungren, Lyle J. Palmer, Brandon J. Price, Saptarshi Purkayastha, Ayis T. Pyrros, Lauren Oakden-Rayner, Chima Okechukwu, Laleh Seyyed-Kalantari, Hari Trivedi, Ryan Wang, Zachary Zaiman, and Haoran Zhang. AI recognition of patient race in medical imaging: A modelling study. *The Lancet Digital Health*, 4(6):e406–e414, 2022. doi: 10.1016/S2589-7500(22)00063-2.

427 Han Guo, Ramtin Hosseini, Ruiyi Zhang, Sai Ashish Somayajula, Ranak Roy Chowdhury, Rajesh K.
428 Gupta, and Pengtao Xie. Downstream task guided masking learning in masked autoencoders using
429 multi-level optimization. *Transactions on Machine Learning Research*, 2025. arXiv:2402.18128.

430 Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoen-
431 coders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vi-
432 sion and Pattern Recognition*, pages 16000–16009, 2022. doi: 10.1109/CVPR52688.2022.01553.

433 Xiangteng He, Shunsuke Sakai, Shivam Chandhok, Sara Beery, Kun Yuan, Nicolas Padoy, Tatsuhito
434 Hasegawa, and Leonid Sigal. DSeq-JEPA: Discriminative sequential joint-embedding predictive
435 architecture, 2025. URL <https://arxiv.org/abs/2511.17354>. Accepted at ECCV 2026;
436 final proceedings metadata unavailable at verification time.

437 De-Xing Huang, Xiao-Hu Zhou, Mei-Jiang Gui, Xiao-Liang Xie, Shi-Qi Liu, Shuang-Yi Wang,
438 Tian-Yu Xiang, Rui-Ze Ma, Nu-Fang Xiao, and Zeng-Guang Hou. VasoMIM: Vascular anatomy-
439 aware masked image modeling for vessel segmentation. In *Proceedings of the AAAI Conference
440 on Artificial Intelligence*, volume 40, pages 4985–4993, 2026. doi: 10.1609/aaai.v40i6.42503.

441 Yijin Huang, Junyan Lyu, Pujin Cheng, Roger Tam, and Xiaoying Tang. SSiT: Saliency-guided
442 self-supervised image transformer for diabetic retinopathy grading. *IEEE Journal of Biomedical
443 and Health Informatics*, 28(5):2806–2817, 2024. doi: 10.1109/JBHI.2024.3362878. URL <https://doi.org/10.1109/JBHI.2024.3362878>.

444 Ruinan Jin, Zikang Xu, Yuan Zhong, Qingsong Yao, Qi Dou, S. Kevin Zhou, and Xiaoxiao
445 Li. FairMedFM: Fairness benchmarking for medical imaging foundation models. In *Ad-
446 vances in Neural Information Processing Systems*, volume 37, pages 111318–111357, 2024.
447 doi: 10.52202/079017-3535. URL [https://proceedings.neurips.cc/paper_files/
448 paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_
449 Benchmarks_Track.html](https://proceedings.neurips.cc/paper_files/paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_Benchmarks_Track.html).

450 Ioannis Kakogeorgiou, Spyros Gidaris, Bill Psomas, Yannis Avrithis, Andrei Bursuc, Konstantinos
451 Karantzas, and Nikos Komodakis. What to hide from your students: Attention-guided masked
452 image modeling. In *Computer Vision – ECCV 2022*, pages 300–318. Springer, 2022. doi: 10.
453 1007/978-3-031-20056-4_18.

454 Agostina J. Larrazabal, Nicolás Nieto, Victoria Peterson, Diego H. Milone, and Enzo Ferrante.
455 Gender imbalance in medical imaging datasets produces biased classifiers for computer-aided
456 diagnosis. *Proceedings of the National Academy of Sciences*, 117(23):12592–12594, 2020. doi:
457 10.1073/pnas.1919012117.

458 Jin Lee, Vu Dang, Gwang-Hyun Yu, Anh Le, Zahid Rahman, Jin-Ho Jang, Heonzoo Lee, Kun-Yung
459 Kim, Jin-Sul Kim, and Jin-Young Kim. HU-based foreground masking for 3D medical masked
460 image modeling. In *Medical Image Computing and Computer Assisted Intervention (MICCAI)*,
461 2025. doi: 10.1007/978-3-032-09569-5_13. arXiv:2509.07534.

462 Gang Li, Heliang Zheng, Daqing Liu, Chaoyue Wang, Bing Su, and Changwen Zheng.
463 SemMAE: Semantic-guided masking for learning masked autoencoders. In *Advances in
464 Neural Information Processing Systems*, volume 35, pages 14290–14302, 2022. doi:
465 10.52202/068431-1039. URL [https://proceedings.neurips.cc/paper_files/paper/
466 2022/hash/5db4e0a62cb5b4a5a70f1fdc9a78a4cc-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2022/hash/5db4e0a62cb5b4a5a70f1fdc9a78a4cc-Abstract-Conference.html).

467 Yuheng Li, Tianyu Luan, Yizhou Wu, Shaoyan Pan, Yenho Chen, and Xiaofeng Yang. AnatoMask:
468 Enhancing medical image segmentation with reconstruction-guided self-masking. In *Computer
469 Vision – ECCV 2024*, pages 146–163. Springer, 2024. doi: 10.1007/978-3-031-73027-6_9.

470 Zixuan Liu, Hanwen Xu, Addie Woicik, Linda G. Shapiro, Marian Blazes, Yue Wu, Verena Steffen,
471 Catherine A. Cukras, Cecilia S. Lee, Miao Zhang, Aaron Y. Lee, and Sheng Wang. A three-
472 dimensional multi-modal foundation model for optical coherence tomography. *Nature Biomedical
473 Engineering*, 2026. doi: 10.1038/s41551-026-01662-2.

474 Yan Luo, Muhammad Osama Khan, Yu Tian, Min Shi, Zehao Dou, Tobias Elze, Yi Fang, and
475 Mengyu Wang. FairVision: Equitable deep learning for eye disease screening via fair identity
476 scaling, 2024a. URL <https://arxiv.org/abs/2310.02492>.

478 Yan Luo, Yu Tian, Min Shi, Louis R. Pasquale, Lucy Q. Shen, Nazlee Zebardast, Tobias Elze, and
479 Mengyu Wang. Harvard glaucoma fairness: A retinal nerve disease dataset for fairness learning
480 and fair identity normalization. *IEEE Transactions on Medical Imaging*, 43(7):2623–2633, 2024b.
481 doi: 10.1109/TMI.2024.3377552.

482 Stefan Maetschke, Bhavna Antony, Hiroshi Ishikawa, Gadi Wollstein, Joel Schuman, and Rahil
483 Garnavi. A feature agnostic approach for glaucoma detection in OCT volumes. *PLOS ONE*, 14
484 (7), 2019.

485 Lena Maier-Hein, Annika Reinke, Patrick Godau, Minu D. Tizabi, Florian Buettner, Evangelia
486 Christodoulou, Ben Glocker, Fabian Isensee, Jens Kleesiek, Michal Kozubek, Mauricio Reyes,
487 Michael A. Riegler, Manuel Wiesenfarth, A. Emre Kavur, Carole H. Sudre, Michael Baumgartner,
488 Matthias Eisenmann, Doreen Heckmann-Nötzel, Tim Radsch, Laura Acion, Michela Antonelli,
489 Tal Arbel, Spyridon Bakas, Arriel Benis, Matthew B. Blaschko, M. Jorge Cardoso, Veronika Chep-
490 lygina, Beth A. Cimini, Gary S. Collins, Keyvan Farahani, Luciana Ferrer, Adrian Galdran, Bram
491 van Ginneken, Robert Haase, Daniel A. Hashimoto, Michael M. Hoffman, Merel Huisman, Pierre
492 Jannin, Charles E. Kahn, Dagmar Kainmueller, Bernhard Kainz, Alexandros Karargyris, Alan
493 Karthikesalingam, Florian Kofler, Annette Kopp-Schneider, Anna Kreshuk, Tahsin Kurc, Ben-
494 nett A. Landman, Geert Litjens, Amin Madani, Klaus Maier-Hein, Anne L. Martel, Peter Matt-
495 son, Erik Meijering, Bjoern Menze, Karel G. M. Moons, Henning Müller, Brennan Nihyporuk,
496 Felix Nickel, Jens Petersen, Nasir Rajpoot, Nicola Rieke, Julio Saez-Rodriguez, Clara I. Sánchez,
497 Shravya Shetty, Maarten van Smeden, Ronald M. Summers, Abdel A. Taha, Aleksei Tiulpin,
498 Sotirios A. Tsafaris, Ben Van Calster, Gaël Varoquaux, and Paul F. Jäger. Metrics reloaded:
499 Recommendations for image analysis validation. *Nature Methods*, 21(2):195–212, 2024. doi:
500 10.1038/s41592-023-02151-z. URL <https://doi.org/10.1038/s41592-023-02151-z>.

501 Jiawei Mao, Shujian Guo, Yuanqi Chang, Xuesong Yin, and Binling Nie. Medical supervised
502 masked autoencoders: Crafting a better masking strategy and efficient fine-tuning schedule for
503 medical image classification, 2023. URL <https://arxiv.org/abs/2305.05871>.

504 José Morano, Botond Fazekas, Emese Sükei, Ronald Fecso, Taha Emre, Markus Gumpinger, Georg
505 Faustmann, Marzieh Oghbaie, Ursula Schmidt-Erfurth, and Hrvoje Bogunović. Multimodal
506 foundation model and benchmark for comprehensive retinal OCT image analysis. *npj Digital*
507 *Medicine*, 8:576, 2025. doi: 10.1038/s41746-025-01852-3.

508 Erfan Noury, Suria S. Mannil, Robert T. Chang, An Ran Ran, Carol Y. Cheung, Suman S. Thapa,
509 Harsha L. Rao, Srilakshmi Dasari, Mohammed Riyazuddin, Dolly Chang, Sriharsha Nagaraj,
510 Clement C. Tham, and Reza Zadeh. Deep learning for glaucoma detection and identification of
511 novel diagnostic areas in diverse real-world datasets. *Translational Vision Science & Technology*,
512 11(5):11, 2022. doi: 10.1167/tvst.11.5.11.

513 Nancy A. Obuchowski. Nonparametric analysis of clustered ROC curve data. *Biometrics*, 53(2):
514 567–578, 1997. doi: 10.2307/2533958. URL <https://doi.org/10.2307/2533958>.

515 Theodoros Pissas, Pablo Márquez-Neila, Sebastian Wolf, Martin S. Zinkernagel, and Raphael Sznit-
516 man. Masked image modelling for retinal OCT understanding. In *Ophthalmic Medical Image*
517 *Analysis*, pages 115–125. Springer, 2024. doi: 10.1007/978-3-031-73119-8_12.

518 Jianing Qiu, Jian Wu, Hao Wei, Peilun Shi, Mingqing Zhang, Yunyun Sun, Lin Li, Hanruo Liu,
519 Hongyi Liu, Simeng Hou, Yuyang Zhao, Xuehui Shi, Junfang Xian, Xiaoxia Qu, Sirui Zhu, Lijie
520 Pan, Xiaoniao Chen, Xiaojia Zhang, Shuai Jiang, Kebin Wang, Chenlong Yang, Mingqiang
521 Chen, Sujie Fan, Jianhua Hu, Aiguo Lv, Hui Miao, Li Guo, Shujun Zhang, Cheng Pei, Xiaojuan
522 Fan, Jianqin Lei, Ting Wei, Junguo Duan, Chun Liu, Xiaobo Xia, Siqi Xiong, Junhong Li, Kyle
523 Lam, Benny Lo, Yih Chung Tham, Tien Yin Wong, Ningli Wang, and Wu Yuan. Development and
524 validation of a multimodal multitask vision foundation model for generalist ophthalmic artificial
525 intelligence. *NEJM AI*, 1(12), 2024. doi: 10.1056/AIoa2300221.

526 An Ran Ran, Carol Y. Cheung, Xi Wang, Hao Chen, Lu-Yang Luo, Poemen P. Chan, Mandy O. M.
527 Wong, Robert T. Chang, Suria S. Mannil, Alvin L. Young, Hon-Wah Yung, Chi Pui Pang, Pheng-
528 Ann Heng, and Clement C. Tham. Detection of glaucomatous optic neuropathy with spectral-
529 domain optical coherence tomography: A retrospective training and validation deep-learning anal-
530 ysis. *The Lancet Digital Health*, 1(4):e172–e182, 2019. doi: 10.1016/S2589-7500(19)30085-8.

531 Carolyn M. Rutter. Bootstrap estimation of diagnostic accuracy with patient-clustered data. *Academic Radiology*, 7(6):413–419, 2000. doi: 10.1016/S1076-6332(00)80381-5. URL [https://doi.org/10.1016/S1076-6332\(00\)80381-5](https://doi.org/10.1016/S1076-6332(00)80381-5).
532
533

534 Laleh Seyyed-Kalantari, Haoran Zhang, Matthew B. A. McDermott, Irene Y. Chen, and Marzyeh
535 Ghassemi. Underdiagnosis bias of artificial intelligence algorithms applied to chest radiographs
536 in under-served patient populations. *Nature Medicine*, 27(12):2176–2182, 2021. doi: 10.1038/
537 s41591-021-01595-0.

538 Min Shi, Yan Luo, Yu Tian, Lucy Q. Shen, Tobias Elze, Nazlee Zebardast, Mohammad Eslami,
539 Saber Kazeminasab, Michael V. Boland, David S. Friedman, Louis R. Pasquale, and Mengyu
540 Wang. Equitable artificial intelligence for glaucoma screening with fair identity normalization.
541 *npj Digital Medicine*, 8(1), 2025. doi: 10.1038/s41746-025-01432-5.

542 Yuge Shi, N. Siddharth, Philip H. S. Torr, and Adam R. Kosiorek. Adversarial masking for self-
543 supervised learning. In *Proceedings of the 39th International Conference on Machine Learning*,
544 volume 162 of *Proceedings of Machine Learning Research*, pages 20026–20040. PMLR, 2022.
545 URL <https://proceedings.mlr.press/v162/shi22d.html>.

546 Leon Sick, Dominik Engel, Pedro Hermosilla, and Timo Ropinski. Attention-guided masked
547 autoencoders for learning image representations. In *Proceedings of the IEEE/CVF*
548 *Winter Conference on Applications of Computer Vision*, pages 836–846, 2025. doi:
549 10.1109/WACV61041.2025.00091. URL [https://openaccess.thecvf.com/content/WACV2025/html/Sick_Attention-Guided_Masked_Autoencoders_for_Learning_](https://openaccess.thecvf.com/content/WACV2025/html/Sick_Attention-Guided_Masked_Autoencoders_for_Learning_Image_Representations_WACV_2025_paper.html)
550 [Image_Representations_WACV_2025_paper.html](https://openaccess.thecvf.com/content/WACV2025/html/Sick_Attention-Guided_Masked_Autoencoders_for_Learning_Image_Representations_WACV_2025_paper.html).
551

552 Aiham Taleb, Winfried Loetzsch, Noel Danz, Julius Severin, Thomas Gärtner, Ben-
553 jamin Bergner, and Christoph Lippert. 3d self-supervised methods for medical imag-
554 ing. In *Advances in Neural Information Processing Systems*, volume 33, pages
555 18158–18172, 2020. URL [https://proceedings.neurips.cc/paper/2020/hash/](https://proceedings.neurips.cc/paper/2020/hash/d2dc6368837861b42020ee72b0896182-Abstract.html)
556 [d2dc6368837861b42020ee72b0896182-Abstract.html](https://proceedings.neurips.cc/paper/2020/hash/d2dc6368837861b42020ee72b0896182-Abstract.html).

557 Haochen Wang, Kaiyou Song, Junsong Fan, Yuxi Wang, Jin Xie, and Zhaoxiang Zhang. Hard
558 patches mining for masked image modeling. In *Proceedings of the IEEE/CVF Conference on*
559 *Computer Vision and Pattern Recognition*, pages 10375–10385, 2023. doi: 10.1109/CVPR52729.
560 2023.01000. URL [https://openaccess.thecvf.com/content/CVPR2023/html/Wang_](https://openaccess.thecvf.com/content/CVPR2023/html/Wang_Hard_Patches_Mining_for_Masked_Image_Modeling_CVPR_2023_paper.html)
561 [Hard_Patches_Mining_for_Masked_Image_Modeling_CVPR_2023_paper.html](https://openaccess.thecvf.com/content/CVPR2023/html/Wang_Hard_Patches_Mining_for_Masked_Image_Modeling_CVPR_2023_paper.html).

562 Ruilang Wang, Shuotong Xu, Bowen Liu, Runlin Huang, Donglong Chen, and Weifeng Su. Mask
563 what matters: Controllable text-guided masking for self-supervised medical image analysis, 2025.
564 URL <https://arxiv.org/abs/2509.23054>.

565 Zhenda Xie, Zheng Zhang, Yue Cao, Yutong Lin, Jianmin Bao, Zhuliang Yao, Qi Dai, and Han Hu.
566 SimMIM: A simple framework for masked image modeling. In *Proceedings of the IEEE/CVF*
567 *Conference on Computer Vision and Pattern Recognition*, pages 9653–9663, 2022. doi: 10.1109/
568 CVPR52688.2022.00943.

569 Kai Yu, Yang Zhou, Yang Bai, Zhi Da Soh, Xinxing Xu, Rick Siow Mong Goh, Ching-Yu Cheng,
570 and Yong Liu. UrFound: Towards universal retinal foundation models via knowledge-guided
571 masked modeling. In *Medical Image Computing and Computer Assisted Intervention – MICCAI*
572 *2024*, pages 753–762. Springer, 2024. doi: 10.1007/978-3-031-72390-2_70.

573 Jinghao Zhou, Chen Wei, Huiyu Wang, Wei Shen, Cihang Xie, Alan Yuille, and Tao Kong. iBOT:
574 Image BERT pre-training with online tokenizer. In *International Conference on Learning Repre-*
575 *sentations*, 2022.

576 Yukun Zhou, Mark A. Chia, Siegfried K. Wagner, Murat Seçkin Ayhan, Dominic J. Williamson,
577 Robbert R. Struyven, Timing Liu, Moucheng Xu, Mateo G. Lozano, Peter Woodward-Court, et al.
578 A foundation model for generalizable disease detection from retinal images. *Nature*, 622:156–163,
579 2023. doi: 10.1038/s41586-023-06555-x.

580 A All frozen probes

581 Table 3 lists every frozen MeanPool probe in the study. It has 37 rows: 31 valid probes, plus two
 582 probes excluded and four retracted for the reasons in Appendix F. 23 of the valid probes carry the
 583 joined metadata required by the subgroup audit (Section 5.5) and 19 of them a usable race summary,
 584 which is why those three counts differ.

Table 3: Every frozen probe in the study, including runs excluded from the analysis and the reasons. The probe protocol is otherwise the same for every row — FairVision test $N=3000$, seed 42, frozen encoder, MeanPool + LayerNorm + Linear — and differs only in the precision column. “Precision” is the probe-time numerical precision, inferred from the stored prediction dtype, and is distinct from the pretraining target precision discussed in Appendix F.

policy	epoch	precision	test AUC	95% CI
ANATOMY-V1	30	fp32	0.8583	[0.8450, 0.8712]
ANATOMY-V2	35	fp32	0.8661	[0.8531, 0.8787]
ANATOMY-V2	40	fp32	0.8683	[0.8553, 0.8807]
ANATOMY-V2	50	fp32	0.8654	[0.8522, 0.8781]
ANATOMY-V2	75	fp32	0.8612	[0.8477, 0.8740]
ancestor	25	fp32	0.8487	[0.8349, 0.8621]
COVER	27	fp32	0.8483	[0.8346, 0.8617]
COVER	30	fp32	0.8522	[0.8386, 0.8654]
COVER	34	fp32	0.8571	[0.8437, 0.8700]
COVER	50	fp32	0.8643	[0.8513, 0.8768]
COVER	73	fp32	0.8647	[0.8517, 0.8772]
COVER	75	fp32	0.8639	[0.8507, 0.8763]
COVER	100	fp32	0.8577	[0.8443, 0.8707]
ENVELOPE	30	fp32	0.8539	[0.8405, 0.8669]
ENVELOPE	50	fp16	0.8761	[0.8635, 0.8879]
ENVELOPE	50	fp32	0.8761	[0.8635, 0.8879]
ENVELOPE	75	fp16	0.8803	[0.8677, 0.8922]
ENVELOPE	75	fp32	0.8803	[0.8677, 0.8922]
ENVELOPE	100	fp16	0.8807	[0.8683, 0.8926]
ENVELOPE	100	fp32	0.8808	[0.8683, 0.8927]
CENTROID	50	fp16	0.8740	[0.8615, 0.8862]
CENTROID	50	fp32	0.8740	[0.8614, 0.8862]
CENTROID	75	fp16	0.8836	[0.8714, 0.8955]
CENTROID	100	fp16	0.8855	[0.8735, 0.8971]
CENTROID	100	fp32	0.8853	[0.8732, 0.8971]
RANDOM	50	fp16	0.8641	[0.8510, 0.8769]
RANDOM	50	fp32	0.8641	[0.8511, 0.8769]
RANDOM	75	fp16	0.8723	[0.8593, 0.8849]
RANDOM	75	fp32	0.8723	[0.8593, 0.8849]
RANDOM	100	fp16	0.8746	[0.8618, 0.8869]
RANDOM	100	fp32	0.8745	[0.8617, 0.8868]
anatomy-v2	75	fp32	0.8625	<i>excluded</i>
anatomy-v2	92	fp32	0.8604	<i>excluded</i>
random	30	fp32	0.8558	<i>retracted</i>
random	50	fp32	0.8590	<i>retracted</i>
random	75	fp32	0.8612	<i>retracted</i>
random	100	fp32	0.8607	<i>retracted</i>

585 B Continuation-level replication

586 **Status at submission: PENDING.** No result of this replication is reported anywhere in this paper.
 587 What follows is the design and the analysis rules, both fixed before any value is visible, so that they
 588 cannot be chosen after seeing the outcome.

589 **Design.** Six continuations — RANDOM, ENVELOPE and CENTROID, each at
 590 two further seeds — resume from the same epoch-25 ancestor used by ev-
 591 ery arm in this paper. The ancestor is locked by content: SHA-256
 592 e5ad5b0c2aadfa15449409786afbfa39d8b5405b699be8f02f2e540195e97e7b,

1,507,519,602 bytes, re-hashed immediately before each leg, and a mismatch aborts the leg rather than continuing from an unverified starting point. The six configurations are generated by a script that asserts they are identical outside the mask curriculum except for the seed and logging fields. Each leg runs to epoch 50 — the endpoint at which every arm already carries a frozen probe — with the optimiser, cosine learning-rate, weight-decay and EMA schedules still sized for 100 epochs, so the trajectory is the one this paper measures and not a shorter, differently-scheduled substitute. Each completed leg is then probed under the frozen-probe protocol of Section 4, with the encoder hashed before and after the probe. Together with the continuations reported here, this yields three continuations per policy at a matched endpoint.

Pre-committed analysis. (i) All nine epoch-50 continuation AUCs are reported in one table, whatever they show; no continuation is dropped for any reason other than a documented crash, and a crash is reported. (ii) We report the per-policy mean and full range, and the two paired-by-seed differences ENVELOPE—RANDOM and CENTROID—RANDOM, one per seed. (iii) At three continuations we report point estimates and ranges only: no t -test, no p -value and no confidence interval at the continuation level, because three continuations bound direction and not magnitude. (iv) The fixed-data-order caveat below is restated wherever the result is.

What the seed does and does not randomise. The seed randomises random-resized-crop draws, target and context block sampling — including the ENVELOPE rejection sampler and the CENTROID band sampler — dropout, and worker streams. It does *not* randomise the order in which slices are visited: the distributed sampler is constructed with its own fixed seed and advanced per epoch, which is true of the originally reported continuations as well. The unit of inference is therefore post-fork stochastic optimisation noise at a fixed data order, which is narrower than independent retraining, and it is not a replication of the data pipeline.

The failure case, written in advance. If the epoch-50 ordering does not reproduce — if a paired difference changes sign, or the three-continuation range for either contrast spans zero — the reported conclusion becomes that the single-continuation contrasts of Table 1 describe those particular runs and not the policies, and every policy-level statement in this paper is downgraded to a run-level one. Table 1 is not withdrawn in that case: it remains a correct description of the runs it measures. That outcome is an anticipated and informative result of this design rather than a failure of it, which is why the rules above are fixed now.

What this replication does not do. It does not supply an untouched evaluation cohort. The comparison still runs on the same test split, which has been inspected repeatedly across this programme, so the replication bounds run-to-run variability and not adaptive selection. The number of times that split was inspected while choosing policies, checkpoints and analyses was not logged and cannot now be reconstructed, which is why every interval in this paper is described as descriptive rather than confirmatory. An untouched evaluation would require a labelled cohort from a different scanner or population, thresholds and checkpoints selected on that cohort’s own validation split, a single evaluation, and no iteration afterwards. No such cohort was available to us.

C Masking policies across the volume

Figure 1 shows one B-scan for legibility. Figure 4 repeats the same rendering on five B-scans sampled across the depth of a volume, so that the stability of each policy under changing retinal geometry can be inspected. The samplers, the colour assignment, and the anatomy contour are identical to Figure 1.

D Mask-geometry provenance

Table 2 was regenerated from the production samplers rather than carried forward from an earlier draft, and this appendix records how, together with two facts the table itself cannot show: how much of each cell is measurement noise, and how one configuration constant moves the correlation quoted in Section 5.2.

Masking statistics by arm, ordered by anatomy placed in targets (anatomy-v2 measured on $n = 1,534$; others on the 6,137-slice sweep)




Figure 3: What each sampler actually does, measured on the 6,137-slice sweep (ANATOMY-V2 on $n=1,534$). Panel (a) is the quantity the COVER arm was built to maximise: it reaches 73.1%, *below* ENVELOPE’s 77.6%, which is the discrepancy Appendix G explains. Panel (b) shows the ordering this paper tests: target purity rises monotonically from RANDOM to ANATOMY-V2, while downstream AUC does not follow it. Panels (c)–(f) give the confounds we do not disentangle — how much anatomy survives in the context (c, d), the context budget (e), and how often a slice is left with no anatomy visible at all (f). Every bar starts at zero and is a mean over the sweep, with no interval drawn; panel scales differ, so bars should be compared only within a panel.

641 **How the geometry was measured.** Each production sampler was run on the same 600 FairVision
642 *Training* slices (24 volumes, 25 slices each), one image at a time, with the COVER visible-tissue floor
643 at its production value $f=0.21$, on the 16×16 patch grid, with anatomy taken from the MIRAGE
644 guide occupancy channel at threshold 0.25. The measurement was repeated with three independent
645 draws (seeds 42, 1234 and 2026). Training slices are not a choice: the cached anatomy guides exist
646 for the Training split only, so three of the five production samplers cannot be run on held-out slices
647 at all.

648 **Cell-level agreement and seed noise.** Table 2 now carries the regenerated values, so the question
649 is how stable they are across draws. 18 of the 25 cells fall inside the three-seed range of the mea-
650 surement and do not exceed observed re-draw variation. Across the four rectangle arms the *loss*
651 *slots* spread is smaller than the per-arm seed spread (Table 4), so that column’s ordering carries no
652 information and no claim in this paper depends on it. The rank order of the arms on anatomy hidden
653 and on purity is identical across all three draws, which is what the rank correlations in the main text
654 rely on.

655 **The delivered context is not the per-image context.** The “context kept” column of Table 2 is per-
656 image geometry, measured before collation. In training, every context mask in a batch is truncated to
657 the batch minimum, so what the encoder actually receives at the production batch size is smaller, and
658 unevenly so (Table 5). The context confound between the anatomy arm and the rectangle arms that
659 Section 5.2 declines to explain away is consequently *larger* than the printed table suggests: roughly
660 a doubling rather than a $1.6\times$ ratio. This strengthens the verdict that H3 is not identified by this
661 design.

662 **The rank correlation depends on a configuration constant.** The $+0.80$ anatomy-hidden/AUC
663 Spearman coefficient of Section 5.2 is computed at the production COVER floor $f=0.21$. Re-
664 measured on the same slices with the floor at 0.15, COVER hides 79.5% of anatomy instead of

Table 4: Stability of two Table 2 columns across three independent draws of the same 600-slice measurement. “sd” is the standard deviation over seeds 42, 1234 and 2026. The loss-slot differences between rectangle arms are smaller than this noise.

policy	anatomy hidden (%)		loss slots	
	value	sd	value	sd
RANDOM	53.95	0.71	159.91	1.15
CENTROID	62.13	0.64	158.99	0.43
ENVELOPE	77.58	0.38	159.68	1.00
COVER	73.55	0.30	159.09	0.45
ANATOMY-V2	79.89	0.39	64.00	0.00

Table 5: Visible context as a fraction of the patch grid, same 600 slices and same seed, measured per image and as delivered to the encoder at the production batch size of 64. The per-image column reproduces Table 2’s “context kept” to within 0.4 points.

policy	per image	delivered at batch 64
RANDOM	41.9%	24.7%
CENTROID	45.5%	32.9%
ENVELOPE	40.6%	30.7%
COVER	43.2%	30.1%
ANATOMY-V2	67.7%	63.5%

665 73.4% at the same batch size and overtakes ENVELOPE, which reorders the four rectangle arms and
666 moves the same coefficient to +0.40. A rank statistic over four arms that a single configuration
667 constant can move by that much is not evidence about anatomy, in either direction, which is why
668 Section 5.2 draws its conclusion from the direct comparison instead.

669 **What would identify target shape.** An arm that isolated target shape would have to match
670 ENVELOPE on the axes that currently differ, and those requirements are numeric, not rhetorical.
671 ANATOMY-V2 sets four predictor targets resampled to a fixed $K=16$ cells, giving exactly 64 loss
672 slots; matching the rectangle arms’ 158–160 slots at four targets requires $K \approx 40$ (inferred arith-
673 metic on those measured values). It would also have to deliver a mask ratio of 40–46% of the grid
674 rather than the 21% that the anatomy arms deliver — roughly twice the target area, which for a
675 shape-following sampler means more or larger blobs and therefore changes the very shape statis-
676 tics being tested — and it would have to pass through the rectangle collation path, including the
677 batch-minimum truncation above. It would then need the same replicated continuation design and
678 the same endpoint as Appendix B. We did not run it; naming its specification is what we can offer
679 instead.

680 E Subgroup and severity analysis

681 All numbers below come from saved test predictions joined to FairVision’s released metadata in
682 deterministic loader order; the join is validated by exact label reconstruction (3000/3000 labels
683 recovered in every probe). The 23 probes used here are exactly those the inventory marks valid: the
684 four retracted coverage probes of Appendix F and the two precision-spliced ANATOMY-V2 probes
685 are excluded here as everywhere else in the paper.

686 **Why we report two sample sizes.** The 23 probes span only 7 pretraining branches, because sev-
687 eral are different epochs of one training run. Probes within a branch share an encoder lineage, a
688 seed and the test split, so treating them as 23 independent observations is pseudo-replication. Ta-
689 ble 6 therefore reports each trend twice: once per checkpoint, and once after averaging within each
690 branch. Where the two disagree, the branch-level figure is the one to believe.

691 **Race.** The black subgroup has the lowest AUC in every one of the 23 probes ($n=431$ black, $n=251$
692 asian, $n=2318$ white; Figure 5). At matched epoch 100 the black subgroup improves from 0.8325
693 under RANDOM to 0.8472 under CENTROID (+0.0147), a larger absolute gain than the white sub-

Table 6: Subgroup gap trends. “gap range” is the max–min subgroup AUC gap observed across the 23 valid probes. q is Benjamini–Hochberg across the seven checkpoint-level tests. Branch p -values are unadjusted across the same seven and, at $n=7$, descriptive only. Only sex survives checkpoint-level correction at the conventional 0.05 level, and it *narrows* as aggregate AUC rises. Race, ethnicity and disease severity share the same q just above that level, so no threshold admits race and severity without also admitting ethnicity. Race is the one attribute whose checkpoint-level trend does not persist under branch aggregation ($p=0.4821$), where the effective sample is 7 independent branches rather than 23 probes; we therefore draw no trend conclusion for race.

attribute	worst group	gap range	per checkpoint ($n=23$)			per branch ($n=7$)	
			ρ	p	q	ρ	p
sex	female (23/23)	0.0272–0.0407	-0.664	0.0005	0.0038	-0.821	0.0234
race	black (23/23)	0.0391–0.0935	+0.473	0.0225	0.0668	+0.321	0.4821
ethnicity	hispanic (23/23)	0.0180–0.0661	+0.435	0.0381	0.0668	+0.679	0.0938
language	other languages (19/23)	0.0518–0.0805	+0.311	0.1483	0.1730	+0.786	0.0362
marital status	single (23/23)	0.0286–0.0654	-0.210	0.3351	0.3351	-0.679	0.0938
age	<60 (22/23)	0.0430–0.0704	+0.399	0.0591	0.0828	+0.357	0.4316
disease severity	mild (−6, −2] (23/23)	0.1286–0.1400	-0.449	0.0318	0.0668	-0.821	0.0234

group’s (0.8741 $\rightarrow$ 0.8853). The max–min gap nonetheless widens slightly, because the asian subgroup — already the highest — gains most (0.9033 $\rightarrow$ 0.9189). A widening max–min gap with universally rising subgroup AUCs is not evidence of harm. The checkpoint-level correlation between aggregate AUC and racial gap is $\rho = +0.473$ ($p=0.0225$). It does not pass Benjamini–Hochberg correction at the stated conventional threshold ($q=0.0668$), and it vanishes once probes are aggregated to their pretraining branches ($\rho = +0.321$, $p=0.4821$), and the checkpoint-level test is pseudo-replicated because the 23 probes come from only 7 branches.

Disease severity. FairVision’s label is defined by visual-field mean deviation (md): every test volume with $md \leq -2$ is positive. Severity therefore cannot be used as an ordinary subgroup axis, because within-bin AUC is undefined — a trap that silently yields nothing under naive stratification. Instead each positive stratum is scored against the shared pool of all 1534 negatives (Table 7).

Table 7: Severity-stratified AUC at matched epoch 100. Each positive stratum is scored against the shared pool of all 1534 negatives. Each point estimate rises; the gains were not tested against one another.

stratum	n_+	RANDOM	ENVELOPE	CENTROID	Δ
severe ($md \leq -12$)	334	0.9525	0.9559	0.9588	+0.0063
moderate ($-12 < md \leq -6$)	460	0.9030	0.9103	0.9131	+0.0102
mild ($-6 < md \leq -2$)	672	0.8164	0.8232	0.8301	+0.0137

The severe-to-mild gap is 0.1361 for the null and 0.1286 for the strongest policy, and stays within 0.0114 (0.1286–0.1400) across all 23 probes while aggregate AUC spans 0.8483–0.8855. All three point estimates rise, but family-wise simultaneous adjustment leaves only mild excluding zero; moderate and severe no longer do (Table 8). The largest point estimate is at mild disease (+0.01372, CI [+0.00204, +0.02541]) and the smallest at severe (+0.00626). That ordering is descriptive only; we did not test the paired *difference* between strata, so it does not establish that mild disease benefits most. Mild functional loss is harder to separate from normal OCT by construction, so the difficulty ordering is expected clinically; what the data add is that no masking policy we tested changes it.

Limitations. The p -values here are descriptive, for the reasons given in Section 6. Race and ethnicity are self-reported categories inherited from FairVision’s coding. A race-by-sex intersectional breakdown *is* reported, in Appendix E.1; its limits are that two of its six cells hold fewer than 130 cases and that it carries no paired per-cell intervals, so it describes the disparity and tests no per-cell change. All figures are frozen mean-pool linear probes. Subgroup sensitivity at a transferred threshold is reported in Appendix K, but we report no subgroup calibration and no subgroup predictive values, so this is not a complete fairness evaluation. Disparities could differ under fine-tuning or a stronger head.

Table 8: Paired change in subgroup AUC from RANDOM to CENTROID at matched epoch 100. The eight rows plus two gain-difference contrasts in the text form one exploratory family. Reported CIs are 95% single-step max- $|t|$ simultaneous intervals from 10,000 outcome-stratified paired subject resamples shared across both fixed heads and every stratum (family-wise $\alpha = 0.05$). Four of ten exclude zero: mild severity, white race, and both sex strata.

stratum	n	Δ AUC	simultaneous 95% CI	excludes 0
severity, mild	2206	+0.01372	[+0.00204, +0.02541]	yes
severity, moderate	1994	+0.01016	[-0.00029, +0.02061]	no
severity, severe	1868	+0.00626	[-0.00135, +0.01386]	no
race, White	2318	+0.01129	[+0.00286, +0.01972]	yes
race, Black	431	+0.01467	[-0.00742, +0.03676]	no
race, Asian	251	+0.01558	[-0.00766, +0.03882]	no
sex, Female	1716	+0.01152	[+0.00100, +0.02204]	yes
sex, Male	1284	+0.01006	[+0.00067, +0.01945]	yes

E.1 Intersectional breakdown: race by sex

The audit above crosses no attributes, so on its own it cannot say whether a group disadvantaged on two axes at once is worse served than either margin implies. We therefore also computed AUC for all six race-by-sex cells of the test split, from the same saved predictions, under the same exact-label join proof, with per-arm, 2,000-resample class-stratified percentile intervals within each cell and fitted heads fixed. The second axis is FairVision’s self-reported gender coding, which this paper reports as sex throughout. The artifact behind this subsection covers 22 arms, 18 of them non-retracted; those 18 are a strict subset of the 23 probes of Table 6 — five COVER and BLOB probes are absent from it — so every count in this subsection is out of 18 arms, not 23.

Table 9: Race-by-sex AUC at matched epoch 100 on the 3000 test volumes, with per-cell counts and per-arm bootstrap percentile intervals. Δ is CENTROID minus RANDOM as a difference of point estimates. The artifact stores per-arm intervals only and no paired per-cell resampling, so no Δ in this table is tested against zero; per-cell significance is PENDING. The 18 intervals are marginal, not simultaneous. The two asian cells are small ($n=123$ and $n=128$) and their intervals are correspondingly wide.

cell	n	n_+	RANDOM	ENVELOPE	CENTROID	Δ
asian $\times$ female	123	52	0.8761 [0.8024, 0.9342]	0.8762 [0.8042, 0.9366]	0.8904 [0.8245, 0.9423]	+0.0144
asian $\times$ male	128	66	0.9245 [0.8752, 0.9655]	0.9145 [0.8565, 0.9626]	0.9409 [0.8983, 0.9751]	+0.0164
black $\times$ female	250	149	0.8195 [0.7668, 0.8679]	0.8155 [0.7632, 0.8638]	0.8309 [0.7790, 0.8783]	+0.0114
black $\times$ male	181	119	0.8435 [0.7822, 0.8994]	0.8652 [0.8091, 0.9141]	0.8663 [0.8132, 0.9149]	+0.0228
white $\times$ female	1343	610	0.8641 [0.8441, 0.8826]	0.8728 [0.8530, 0.8910]	0.8762 [0.8570, 0.8943]	+0.0121
white $\times$ male	975	470	0.8864 [0.8650, 0.9062]	0.8958 [0.8744, 0.9148]	0.8962 [0.8746, 0.9153]	+0.0099
max—min gap			0.1050	0.0990	0.1100	

The ordering compounds, and it never reorders. The black $\times$ female cell has the lowest AUC in all 18 non-retracted arms and the asian $\times$ male cell the highest in all 18. Within each race the female cell sits below the male cell in all 54 race-by-arm combinations, and within each sex the black cell sits below the white cell in all 36. These 18 arms share one test split, one epoch-25 ancestor and one probe seed, and several are different epochs of a single branch, so this unanimity is a consistency check across checkpoints, not 18 replications; we attach no p -value to it, exactly as for the marginal ordering above.

The marginal race gap understates the worst cell. Averaged over the 18 arms, the max—min gap is 0.0340 by sex alone, 0.0653 by race alone, and 0.1046 across the six race-by-sex cells, and the intersectional gap exceeds that arm’s marginal race gap in all 18. The race margin therefore understates the spread a race-by-sex reading exposes by 60.1% on average — arithmetic on those two means, not a separate measurement. The same pattern holds at the matched epoch of Table 9: under CENTROID the marginal race gap is 0.0717 while the race-by-sex gap is 0.1100, and the worst cell, black $\times$ female at 0.8309, sits 0.0163 below the marginal black figure 0.8472 that the marginal audit above reports. An audit that stops at the margins reports a worst-group number that

745 is optimistic relative to the worst cell. The compounding is close to additive and we do not claim
746 more: the sex and race means sum to 0.0993 against an observed 0.1046, a ratio of 1.053, which is
747 not evidence of a super-additive interaction.

748 **Not every cell improves.** The statement elsewhere in this appendix that every subgroup point
749 estimate rises from RANDOM to CENTROID is a statement about marginal strata at the matched
750 epoch, and it does *not* extend to cells at every epoch. At epoch 100 all six point estimates rise
751 (Table 9), but at epoch 50 the asian $\times$ female cell falls by 0.0020, and ENVELOPE minus RANDOM
752 is negative in three of six cells at epoch 75 (asian $\times$ female -0.0148 , asian $\times$ male -0.0031 , black
753 $\times$ female -0.0025) and in two of six at epoch 100 (asian $\times$ male -0.0100 , black $\times$ female -0.0040 ,
754 with asian $\times$ female at $+0.0001$). No policy we tested raises every intersectional cell at every epoch,
755 and the exceptions fall in the small asian cells and in the worst cell.

756 **What this does not establish.** There are no paired per-cell bootstrap intervals in the artifact, so
757 every Δ above is a difference of point estimates and none of them is separated from zero; per-cell
758 delta significance is PENDING and is computable from the retained per-arm predictions. Two cells
759 carry $n=123$ and $n=128$, so their intervals overlap almost everything. Cells with a single class or
760 fewer than 40 cases would have been dropped; none were, so all six race-by-sex cells are reported.
761 Nothing here is a fairness intervention: as with the margins, no policy reorders the cells, and the
762 worst-served cell is the same under the unguided null and under every guided policy we tested.

763 F Excluded runs

764 Four probes of an earlier *null* run are excluded from all analysis. They are unguided-masking con-
765 trols from a superseded coverage campaign — the inventory lists them under RANDOM, and their
766 run tags begin `frozen_cover_random` because of that campaign, not because they use a coverage
767 policy. They were trained with half-precision EMA targets and a different encoder-truncation pol-
768 icy from the arms they would be compared against, so their deficit is not attributable to masking.
769 Similarly, the ANATOMY-V2 probes at epochs 75 and 92 follow a change of target precision part-
770 through that arm’s training; they are listed in Table 3 but excluded from the matched-epoch
771 comparisons in Table 1.

772 G A collation defect in the coverage arm, and what it invalidates

773 We audited the COVER sampler after its epoch-100 result and found a defect. It invalidates the
774 reading of that arm and weakens one cross-family comparison.

775 **The defect.** Predictor targets are collated by truncating every target to the length of the shortest
776 target anywhere in the microbatch. COVER chooses its placement *before* this happens: it greedily
777 maximises hidden anatomy subject to a visible-tissue floor, evaluated on full rectangles, and the
778 collator then shortens those rectangles. The optimisation is therefore defeated after the fact.

779 **Measured consequences.** A one-off audit found that collation reduced COVER’s anatomy cover-
780 age; an independent sweep over 6,137 slices gives 73.1% against 77.6% for ENVELOPE. The arm
781 intended to hide *more* anatomy than ENVELOPE in fact hides *less*. Across 24,000 emitted targets
782 only 73.4% remain perfect rectangles. Because target cells are enumerated row-major, truncation
783 keeps the top of each rectangle and discards the bottom, so the loss is directional rather than a neu-
784 tral shrink. *Provenance:* the one-off CPU audit of 194 accepted slices that first exposed the defect
785 was not persisted, so its pre- and post-truncation figures are no longer asserted. The 73.1% against
786 77.6% comparison, which is the only figure the body relies on, is backed by the stored floor sweep
787 and is unaffected.

788 **Why it went unnoticed.** Realised coverage is recorded before truncation. Every training log
789 therefore reported the intended figure, and the instrument agreed with the design rather than with
790 the data.

791 **What it invalidates.** We cannot claim that COVER tests aggressive anatomy coverage, nor that
792 its decline shows over-covering anatomy is harmful; on delivered masks it does not out-cover EN-
793 VELOPE. Its measured trajectory remains a real property of the policy as implemented. The mask
794 geometry in Table 2 is unaffected, having been measured on delivered masks.

795 **Scope.** ENVELOPE shares the same collation path and the same directional clipping, but sets no
796 exact coverage target, so it has no comparable optimisation to defeat. The anatomy arms instead
797 resample every target to a fixed $K=16$ cells. Contrasts within the rectangle family are collated iden-
798 tically and are unaffected; the anatomy-versus-rectangle contrast is not, and we treat it accordingly
799 in Section 5. A corrected coverage arm must be retrained from the shared ancestor, since patching
800 mid-trajectory would splice two masking policies into one curve.

801 **Status of a corrected run.** At submission the corrected arm is not run. Until it exists, the question
802 this arm was built to answer — whether hiding most of the anatomy is harmful — remains *open*.

803 H Why unguided masking is such a strong baseline

804 Unguided masking spends most of its predictor targets on background, yet it reaches within $+0.0109$
805 of the best policy. We investigated whether background carries diagnostic signal, and whether posi-
806 tion embeddings are the mechanism.

807 **Background is a real *pretraining* signal.** At epoch 100 the random arm’s predictor beats a per-
808 position, no-context reference by 0.680 on background targets, above its 0.633 on anatomy targets:
809 predicting a background token requires more than knowing where it is. Pretraining also spends
810 capacity reorganising background — background self-similarity falls from 0.784 untrained to 0.346
811 at epoch 100.

812 **But it does not help the classifier.** Pooled background features are 95.2% linearly reconstructible
813 from pooled anatomy features. On $n=1000$ test subjects, with fitted transforms and probes fixed,
814 residual background has AUC 0.5515 (2,000-resample case-percentile CI [0.5165, 0.5893]). A
815 paired bootstrap of the same size puts the change from appending background at -0.0076 (CI
816 $[-0.0139, -0.0012]$) for the random arm and under ± 0.002 for every other. A background-only
817 probe scores 0.867; self-attention mixes tissue information into background tokens, so that figure
818 cannot be read as background signal, and we did not measure how much mixing occurs.

819 **Position dominates background tokens, but is not the whole story.** At layer 0, 90.8% of the
820 across-position variance of the encoder input at background cells comes from `pos_embed`, against
821 40.8% at tissue cells (stable across six thresholds and both checkpoints). Mechanically a background
822 token is close to its position code. That the predictor still beats a per-position reference shows the
823 pretraining signal is not purely positional. The causal chain from this mechanism to downstream
824 AUC remains open.

825 **The two controls that would settle it, neither of which was run.** First, a regional probe on an
826 *eroded* background region — background cells at a fixed minimum distance from any tissue cell
827 — which removes the tokens most exposed to local mixing while keeping the probe protocol fixed.
828 Second, a background-content shuffle in which background token *contents* are permuted across
829 images while positions and token count are held fixed: if the background-only AUC survives that,
830 the signal is positional rather than content-bearing. Both are PENDING; neither has been run, so
831 this appendix reports a mechanism that is described but not established.

832 I Label efficiency

833 We measured each policy as supervision is withdrawn (Section 5.4). We subsample the labelled
834 training set to fractions of its size, fit the same frozen linear probe on cached epoch-100 features,
835 and repeat 5 times per fraction. The per-fraction seed depends only on fraction and repeat, never on
836 arm, so all arms see identical label subsets and the comparison is paired.

Protocol parity. This sweep uses the *same* probe protocol as Table 1 — minibatches of 256, AdamW at 4×10^{-4} , weight decay 0.05, 50 epochs with 5 warmup and cosine decay, and the epoch selected on validation AUC. An earlier cheaper full-batch fit disagreed with the primary protocol. Under matched protocols, restricting this check to the null and CENTROID, their full-supervision results agree to within 0.0003 (0.8748 against 0.8746 for the null, 0.8856 against 0.8855 for CENTROID), so the curve below and the headline table describe one probe, not two. This two-arm bound is distinct from the four-arm bound reported in Section 5.4.

The advantage of guided masking is concentrated where labels are scarce (Table 10, Figure 6). At 5% of labels ($n=300$) CENTROID leads the null by +0.0496 (0.8335 against 0.7839), against +0.0108 at full supervision — more than four times the margin. At 1% the gap is wider still (0.7576 against 0.6961), though the standard deviations there (0.0359–0.0368 across arms) are large enough that we read the ordering but not its precise size.

The defective COVER arm (Appendix G) is the worst arm at every fraction, reaching only 0.6879 at 1% against 0.6961 for the null, consistent with its targets being degraded rather than merely differently placed.

Table 10: Label efficiency: frozen-probe test AUC against the fraction of the labelled training set used. All values measured, 5 repeats per fraction except at full data, which is deterministic.

labels	n	RANDOM	CENTROID	ENVELOPE	COVER
1%	60	0.6961	0.7576	0.7471	0.6879
5%	300	0.7839	0.8335	0.8197	0.7484
10%	600	0.8169	0.8490	0.8404	0.7743
25%	1500	0.8497	0.8732	0.8654	0.8162
100%	6000	0.8748	0.8856	0.8813	0.8586

J Occlusion attribution: where the classifier looks

The analyses in this appendix were run on the three *fine-tuned* probes (mean-pool, cross-attention pool, and a depth-1 attentive probe) that tie at test AUC ≈ 0.887 , not on the frozen probes used for the arm comparison in the main text. They characterise what the downstream classifier uses, and they are reported here because two of the findings are cautionary rather than positive. Every number in this appendix is computed from archived per-volume attribution arrays that are not part of the released artifact set, so unlike the rest of the paper these values cannot be recomputed from the release; only the diffuse-attribution result at the end of the appendix is cited by the main text.

Method. Attribution is by *occlusion*, which is architecture-agnostic and interventional on the model. It measures the model’s sensitivity to deleting a token, not a causal effect of anatomy on disease. Gradient $\times$ input is not used because two of the three probes are non-linear in the slice-token matrix, where gradient attribution is misleading. For slice-level attribution each slice token is zeroed in turn and Δ logit recorded (Figure 7); for window-level, seven consecutive slices (Figure 8); for patch-level, leave-one-out over the 256 patch tokens of a target slice.

A bimodal attribution curve that is an artefact, not anatomy. The population-averaged curve is bimodal with a central dip. The tempting reading — that the model has discovered the superior and inferior optic disc rim — is **wrong**, and we report it because it is exactly the kind of claim a plausible-looking attribution figure invites. Three tests reject it. First, if the two peaks were bilateral anatomy then within a diseased eye they should co-occur, giving positive per-volume correlation between them; the peak contributions are not positively correlated across volumes. Second, clustering the per-volume curves into two groups yields clusters that are near-perfect *mirror images* along the slice axis for the two well-structured probes. Third, using that cluster label as pseudo-laterality and flipping one cluster collapses the bimodality asymmetrically (Figure 9). What these three tests support is an orientation or storage mixture consistent with OD/OS: each eye carries its dominant signal on one side of the disc, the two groups are stored with opposite axial orientation, and population averaging manufactures an illusion of symmetry. The released metadata carries no eye-laterality label, so the OD/OS reading is inferred from the mirror structure and is not validated against ground truth.

Errors are weaker signal, not different anatomy. Stratifying by outcome, false-negative curves are scaled-down true-positive curves with the same shape, and false positives likewise mirror true negatives (Figure 10). Attribution structure is also near-invariant to prediction confidence. The error rate at threshold 0.5 therefore reflects signal-strength saturation on hard cases, not the model attending to the wrong structures.

Diffuse attribution supports the main claim. The classifier’s evidence is spread across the middle two-thirds of the volume and across most patches within a slice (Figure 11), rather than concentrated on a compact anatomical target. A masking policy that sharpens targets onto a precise anatomical boundary is therefore optimising for a spatial prior the downstream task does not appear to need, which is consistent with Section 5.2 finding no relationship between anatomical specificity and downstream AUC. The OD/OS result is a methodological caution: a figure that looks anatomically meaningful can be an artefact of data storage.

K Clinical operating points and calibration

AUC is threshold-free, but a screening tool is deployed at a threshold. The threshold is selected on the RANDOM arm’s *validation* split at a fixed target specificity and then applied unchanged to every arm on the test split: one shared deployed threshold rather than a per-arm one, which simulates a fielded screen and is conservative for the guided arms, since they are not permitted to retune. The achieved test specificity shows whether the threshold survives the shift. Cohort prevalence is 0.4887.

Table 11: Operating points at matched epoch 100. One threshold, chosen on the RANDOM validation split to hit the target specificity, is applied unchanged to all arms on test. ECE is a 15-bin expected calibration error.

policy	target spec.	sens.	spec. (test)	PPV	NPV	Brier	ECE
RANDOM	0.85	0.7701	0.8259	0.8087	0.7899	0.1416	0.0355
RANDOM	0.90	0.7162	0.8794	0.8502	0.7643	0.1416	0.0355
ENVELOPE	0.85	0.7735	0.8351	0.8176	0.7942	0.1364	0.0361
ENVELOPE	0.90	0.7306	0.8807	0.8541	0.7738	0.1364	0.0361
CENTROID	0.85	0.7851	0.8318	0.8169	0.8020	0.1341	0.0320
CENTROID	0.90	0.7428	0.8696	0.8448	0.7797	0.1341	0.0320

Two observations (Table 11). First, the threshold transfers imperfectly: a validation target of 0.90 yields test specificity 0.8696 to 0.8807 across the three arms, so the operating point moves by roughly one point between arms and the comparison below is at a shared threshold rather than at a shared false-positive rate. Second, the AUC advantage survives as a usable sensitivity gain. At a target specificity of 0.90, CENTROID detects 0.7428 of cases against 0.7162 for the unguided null, a paired difference of +0.0266 (CI [+0.0136, +0.0396], excluding zero), with the specificity caveat above. At a target of 0.85 the gain is +0.0150 (CI [+0.0020, +0.0280]). These four arm-by-target CIs use 10,000 class-stratified percentile subject resamples with fitted heads and thresholds fixed; they are one unadjusted exploratory family. CENTROID is also the best-calibrated arm (Brier 0.1341 versus 0.1416; ECE 0.0320 versus 0.0355), which matters because a screening score that is used as a probability must be trustworthy as one.

A +0.011 AUC difference is hard to interpret clinically, and the ROC curves are nearly superimposed (Figure 12), whereas a change in cases detected at a fixed threshold is not. We state that comparison carefully: transferring one threshold moves achieved specificity from 0.8794 to 0.8696, so the arms are *not* compared at an identical false-positive rate and the sensitivity change partly reflects that shift. A deployment-grade comparison would select each arm’s threshold on validation to meet the same specificity, lock it, and evaluate on an untouched cohort. One dataset, one split, one pretraining run per policy.

Who receives the benefit at the deployed threshold. Subgroup AUC is also threshold-free, so it cannot answer the question a deployment actually raises: a screen ships *one* threshold shared by everyone, and a model can lift every subgroup’s AUC while delivering the gain unevenly at that single operating point. We therefore fix the threshold on validation at specificity 0.90 (0.5552),

transfer it unchanged, and measure the change in sensitivity within each stratum (Table 12). Overall sensitivity rises from 0.7162 to 0.7428.

The point estimates alone suggest the gain is concentrated in the largest group: +0.0343 for white patients against +0.0037 for black patients, an apparent ninefold difference. **The intervals do not support that reading.** The black interval ($[-0.0375, +0.0449]$) reaches almost exactly the white point estimate, so the two are not separated; what distinguishes them is positive count (1080 versus 268), not demonstrated benefit. Only the white, female and male gains exclude zero; all three remain after simultaneous adjustment over the five-contrast family, and they are the three largest strata. This is a *power* limitation of the cohort: the study cannot certify that the smaller strata benefit, and equally cannot show they do not. Certifying subgroup benefit at a deployed threshold would need a cohort with more positives in the smaller strata.

The threshold itself does not transfer evenly across strata. The same table answers a question the sensitivity column does not. A threshold selected on validation to achieve specificity 0.90 does not achieve it uniformly on test: under RANDOM it realises 0.895 specificity in the white stratum but 0.736 in the black stratum, a shortfall of roughly sixteen points, and under CENTROID the same threshold realises 0.879 and 0.761. The shortfall is therefore a property of transferring one threshold to a cohort whose strata have different score distributions, and it is present under *both* arms; no masking policy here causes it and none of them repairs it. For a screening context this is a larger effect than any AUC difference in this paper.

The sensitivity gain is not a uniform trade. Reporting sensitivity alone would make the change from RANDOM to CENTROID look like pure benefit where it is in fact a trade. In the white stratum sensitivity rises by +0.034 while specificity falls by -0.016 ; in the black stratum specificity *rises* by +0.025 and in the asian stratum by +0.008, alongside sensitivity changes (+0.004 and +0.008) whose intervals contain zero. By sex, both strata gain sensitivity (+0.026 female, +0.027 male) and lose specificity (-0.008 and -0.013). Subgroup calibration moves the same way and not entirely in our favour: expected calibration error improves overall (0.0355 to 0.0320) and in the white (0.0382 to 0.0321) and asian (0.0832 to 0.0729) strata, but *worsens* in the black stratum (0.0525 to 0.0569). All values in these two paragraphs are measured at the same shared threshold as Table 12, and the comparison remains at a shared threshold rather than at a shared realised false-positive rate.

Table 12: Change in sensitivity from RANDOM to CENTROID at one shared validation-selected threshold, by stratum. The five contrasts form one exploratory family. Reported CIs are 95% single-step max- $|t|$ simultaneous intervals from 10,000 paired positive-subject resamples shared across both fixed heads and all five overlapping race and sex strata, with heads and threshold fixed (family-wise $\alpha = 0.05$). White, female and male remain above zero after adjustment. Epoch 100.

stratum	positives	Δ sensitivity	simultaneous 95% CI	excludes 0
Asian	118	+0.0085	$[-0.0485, +0.0654]$	no
Black	268	+0.0037	$[-0.0375, +0.0449]$	no
White	1080	+0.0343	$[+0.0149, +0.0536]$	yes
Female	811	+0.0259	$[+0.0020, +0.0498]$	yes
Male	655	+0.0275	$[+0.0043, +0.0507]$	yes

L Broader impact and ethics

This study uses a public, de-identified retinal dataset (FairVision) under its release terms and involves no new data collection and no human subjects. No model reported here is clinically validated or intended for deployment: the frozen-probe AUCs are research measurements on one dataset and one task, and are not evidence of clinical utility.

The subgroup analysis in Section 5.5 is a caution, not a contribution. Every masking policy we tested leaves the same groups worst-served, and the best-performing policy narrows none of them reliably, even though every subgroup point estimate rises at the matched epoch. We would regard deployment of any encoder reported here, without a dedicated and prospective fairness evaluation on the target population, as inappropriate. We also stress that the audit is incomplete: beyond AUC, the transferred-threshold sensitivity, specificity and calibration of Appendix K, and the race-by-sex

breakdown of Appendix E.1, it contains no predictive-value analysis and no subgroup calibration, and the intersectional cells carry no paired per-cell intervals, so no per-cell change there is tested against zero.

Releasing pretrained weights carries the usual dual-use consideration that they may be applied to populations unlike the training cohort. We document the cohort composition (Appendix E) so that such a mismatch is detectable by anyone reusing the weights. The demographic attributes are self-reported categories inherited from the dataset’s coding; they are used only for the subgroup audit and are never model inputs.

M Published ablations on informed versus random masking

Random masking is a strong baseline in the published record and informed masking wins only under some objectives and protocols, the deficit largest under frozen evaluation. Our result should be read against those comparisons (Table 13), collected while positioning this work.

Table 13: Published ablations comparing a random or simple baseline against an informed or structured masking scheme. Numbers are as reported by the cited papers; metrics differ across rows and are not comparable between rows.

study	baseline	informed variant	interpretation
MAE [He et al., 2022]	random-75: 84.9 FT / 73.5 lin	block-75: 82.8 / 63.9; grid-75: 84.0 / 66.0	random decisively better
SimMIM [Xie et al., 2022]	83.0 top-1	best block 82.7; square 82.6	random modestly better
SemMAE [Li et al., 2022]	random 66.8 lin	within-part 66.5; whole-part 52.9; adaptive 68.7	naive semantics hurt; scheduled semantics help
SemMAE part quality [Li et al., 2022]	no parts 63.7	raw parts 63.6; refined 65.0	an imperfect semantic model adds nothing
AutoMAE [Chen et al., 2023a]	MAE 83.26 FT	AutoMAE 83.32	effectively tied
HPM [Wang et al., 2023]	random 82.49	moderate 82.95; hardest-only 81.40	benefit only with retained randomness
AttMask [Kakogeorgiou et al., 2022]	random 43.4 k -NN	high 43.5; hint 43.6	nearly indistinguishable
AttG-MAE [Sick et al., 2025]	MAE 78.5 @10% labels	guided 78.1	guidance loses in this protocol
SSiT [Huang et al., 2024]	no saliency 79.48 κ	25% mask 77.53; 50% 79.97	dataset-dependent, non-monotonic

Read together, these say that the *direction* of our finding is not new. What we add is the controlled measurement, not the sign of the result.

N Full paired-contrast table

Benjamini–Hochberg is applied within a declared confirmatory family consisting of exactly these nine contrasts — the fp16 comparisons among RANDOM, CENTROID and ENVELOPE at epochs 50, 75 and 100 — and the remaining 25 exploratory contrasts in the stored statistics are corrected as a separate family. The two families are never pooled, and the q values printed above are those of the nine-contrast family only.

O Full fp32 re-probe

The RANDOM, CENTROID and ENVELOPE long-horizon probes were originally fitted under the harness default, which enables autocast. To assess whether the headline effect is a precision artifact, we re-ran the complete probe pipeline for those arms with autocast disabled, so that feature extraction, head optimisation and test evaluation are all fp32, under the exact protocol already used by the ANATOMY and COVER arms (Table 15). The encoder checkpoint is SHA-256 hashed before and af-

Table 14: Primary contrasts: matched epoch *and* matched precision. Δ is a paired difference on identical test cases; the interval is a 10,000-resample paired bootstrap and p is a DeLong test for correlated ROC curves. q is Benjamini–Hochberg over these nine contrasts. All p and q values here are descriptive (Section 6). Every comparison against the null excludes zero.

contrast	epoch	Δ AUC	95% CI	p	q
ENVELOPE — RANDOM	50	+0.0120	[+0.0068, +0.0173]	<0.0001	<0.0001
ENVELOPE — RANDOM	75	+0.0080	[+0.0028, +0.0132]	0.0025	0.0045
ENVELOPE — RANDOM	100	+0.0062	[+0.0010, +0.0113]	0.0199	0.0299
CENTROID — RANDOM	50	+0.0099	[+0.0051, +0.0149]	<0.0001	0.0001
CENTROID — RANDOM	75	+0.0113	[+0.0063, +0.0164]	<0.0001	<0.0001
CENTROID — RANDOM	100	+0.0109	[+0.0057, +0.0160]	<0.0001	<0.0001
CENTROID — ENVELOPE	50	-0.0020	[-0.0069, +0.0029]	0.4114	0.4114
CENTROID — ENVELOPE	75	+0.0033	[-0.0013, +0.0079]	0.1491	0.1677
CENTROID — ENVELOPE	100	+0.0047	[+0.0004, +0.0091]	0.0294	0.0378

985 ter each run and verified unchanged, so no result here can be contaminated by an accidental encoder
 986 update.

Table 15: Full fp32 re-probe against the original fp16 result, same frozen encoder in each row. The eight DeLong p -values are unadjusted diagnostics, not a family-wise test. The largest difference is 2×10^{-4} .

policy	epoch	fp16 AUC	fp32 AUC	Δ	p
ENVELOPE	50	0.876064	0.876063	-0.000001	0.964
ENVELOPE	75	0.880307	0.880305	-0.000002	0.806
ENVELOPE	100	0.880743	0.880761	+0.000018	0.167
CENTROID	50	0.874030	0.874015	-0.000015	0.412
CENTROID	100	0.885485	0.885293	-0.000192	0.767
RANDOM	50	0.864097	0.864121	+0.000024	0.128
RANDOM	75	0.872302	0.872302	-0.000001	0.962
RANDOM	100	0.874581	0.874485	-0.000096	0.000

987 P Reproducibility and numeric provenance

988 **Why the intervals are non-parametric.** The estimator choice was checked against the data rather
 989 than assumed. The per-case paired differences are strongly non-normal with heavy tails (Shapiro–
 990 Wilk $W = 0.968$ – 0.981 , $p < 10^{-10}$), and the raw within-arm scores more so ($p \approx 10^{-37}$); Levene’s
 991 test also rejects equal variance across arms ($F = 21.4$, $p < 0.001$), though the variance ratio is only
 992 1.16 and is detectable mainly because $n = 9,000$. None of this invalidates what we report: a per-
 993 centile bootstrap makes no distributional assumption about the deltas, which is the reason for choos-
 994 ing it, and an AUC is rank-based, so DeLong’s variance is built from placement values rather than
 995 from Gaussian scores. The diagnostics are recorded here because “the intervals are non-parametric”
 996 is a claim a reader should be able to check, not take on trust. Where n is small — the five-arm and
 997 four-arm correlations — a normality test has essentially no power, so we treat those as descriptive
 998 throughout and draw no inference from them.

999 **Guide provenance differs across the segmenter arms.** The three segmenter-driven policies do
 1000 not all read the same anatomy guide. ENVELOPE samples the unmodified MIRAGE occupancy map.
 1001 ANATOMY-V1 and COVER instead read pre-computed *soft* guides produced by a MIRAGE whose
 1002 segmentation path carries a frozen residual adapter, trained label-free to align MIRAGE’s patch-
 1003 similarity structure with the pretraining teacher’s. That adapter was an abandoned line of work
 1004 — it reduced its own training objective but never improved segmentation, and the experiment that
 1005 would have settled its downstream effect was not run — so we make no claim about it here. We
 1006 record it because it is a further axis on which the anatomy arms and COVER differ from ENVELOPE,
 1007 beyond the geometric axes in Section 5.2, and because the guide directory names embed the adapter

configuration and would otherwise be unexplained to anyone reproducing this work. CENTROID and RANDOM consult no guide of either kind.

What is checked mechanically. Every quantity in this paper resolves through a generated macro file produced by one script from stored per-case predictions, so prose, tables and figures cannot disagree. Three further gates run on every build: a consistency check that fails on an undefined or duplicated macro, a dangling reference or citation, or a banned overclaiming phrase; a provenance check that resolves each AUC macro’s arm and epoch from its own name and fails if the value does not match that arm’s stored probe, which makes reporting one arm’s number under another arm’s name a build error; and an archive check that compiles the submission from a clean extraction and enforces the page limit and anonymity.

Checkpoint identity. The shared epoch-25 ancestor is identified by SHA-256 (e5ad5b0c2aadfa15449409786afbfa39d8b5405b699be8f02f2e540195e97e7b), which three independent copies reproduce, and the replication chain of Appendix B re-hashes it before each leg. Every frozen probe hashes its encoder before and after fitting and invalidates the run if the hash moves, so no reported probe can have been contaminated by an accidental encoder update. The six replication configurations are generated by a script that asserts they differ only in the seed and logging fields.

An audit of hand-typed numbers, and what it found. Generated macros are verified by the gates above; numbers typed directly into the manuscript source are not, and that gap is where our errors have been. We therefore audited every numeric quantity typed into the source: 310 occurrences, of which 234 were confirmed against a stored artifact, 75 had no producing artifact that we could locate, and one was wrong — a probe parameter count quoted for the wrong probe configuration, since corrected. Two unbacked quantities carried interpretive weight: a per-cell concentration statistic used to argue that the best arm was the most spatially consistent, and a probe-seed noise bound. Both have been removed from this version rather than restated, and the mechanism claim that rested on the first has been withdrawn with it (Sections 5.2 and 6). The rule we adopted, and recommend, is that a numeric claim which is not machine-generated is treated as unverified until it is recomputed.

Q Fine-tuning narrows the observed gap

Under full fine-tuning rather than a frozen probe, CENTROID reaches 0.8947 (mean-pool head) against RANDOM’s 0.8868, a gap of +0.0079 compared with +0.0109 frozen. Taking each arm’s best head instead, the gap is +0.0069. The observed gap is smaller after supervised adaptation. These test-set-selected head point estimates do not distinguish representation quality from optimisation. These runs used a different head and schedule from the frozen probes and are never pooled with them (Table 16).

Table 16: Full fine-tuning, same test split: every arm/head combination, ordered by test AUC. Head comparisons are descriptive point estimates, reported separately from frozen probes and never pooled with them.

policy	head	test AUC
CENTROID	mean-pool	0.894668
CENTROID	cross-attention	0.893717
CENTROID	attentive	0.890100
RANDOM	attentive	0.887763
RANDOM	cross-attention	0.887178
RANDOM	mean-pool	0.886756

All masking arms on the SAME 5 slices (volume idx 2652) - one colour per predictor block, production samplers




Figure 4: All six masking policies (columns) on five B-scans (rows) spanning one volume, drawn with the production samplers. Leftmost column is the unmasked B-scan. Each predictor target block has its own colour; the green contour is the anatomy reference. The random, CENTROID, envelope and cover arms place axis-aligned rectangles; the anatomy arms grow cell-wise targets that follow the retinal band and therefore change shape from slice to slice. Column headings carry each arm's own probe epoch, which differs between arms, so the AUCs printed there are not a matched-epoch comparison and only Table 1 should be read that way. Panel headings use the artefact name `oracle` for CENTROID.




Figure 5: **Left:** race-stratified AUC at epoch 100. Error bars are 3,000-resample class-stratified percentile bootstrap intervals within each group, with fitted heads fixed and per-group n in the legend; the bars sit on a truncated axis, so bar *height* exaggerates the differences and only the plotted positions should be read. The black subgroup is lowest under every policy, yet *every* group point estimate rises from RANDOM to CENTROID. **Right:** max-min race gap against aggregate AUC, one point per probe over the 19 probes that carry a race summary. The dashed line is a least-squares fit while the quoted correlation is Spearman. The slope is positive but fails multiplicity correction at checkpoint level and does not survive branch-level aggregation (Table 6), so we draw no trend conclusion from it.




Figure 6: The policies converge as labels are added and separate as they are removed. Shading is one standard deviation over 5 label subsets, with every arm seeing identical subsets. At full supervision the four arms lie within 0.027 of one another; at 5% the spread is 0.085.




Figure 7: Single-slice occlusion attribution against native slice position, for all three fine-tuned probes. Each probe contributes two curves, a mean over the glaucoma volumes (solid) and a mean over the healthy volumes (dashed), with each n in the legend and no interval drawn. Despite spanning zero to 7.14M probe parameters they converge on the same structure. The y -axis is *signed* Δlogit : peaks are slices whose removal lowers the logit, the central dip is slices whose removal raises it, and only slices near zero are genuinely unused.




Figure 8: Window occlusion ($W=7$) amplifies the same signal roughly sevenfold and suppresses single-volume noise. For mean-pooled models, single-slice occlusion systematically underestimates attributed signal; the windowed variant recovers more signal. As in Figure 7, each probe contributes a glaucoma mean (solid) and a healthy mean (dashed) with no interval drawn, and the curve stops where a full window no longer fits.




Figure 9: The two-peak structure is an OD/OS storage artefact. Clustering per-volume attribution curves into two groups returns near-perfect mirror images of one another for the two well-structured probes, which is what laterality flipping would produce, rather than bilateral anatomy; the D1 row does not show that structure. Glaucoma volumes only, cluster n in each legend, no interval drawn, and the y range differs by row.




Figure 10: Attribution stratified by TP / FN / TN / FP. Errors reproduce the correct pattern at lower amplitude rather than selecting different anatomy. Curves are per-outcome means with the n in each legend; panels share a y range and no interval is drawn.

Occlusion attribution — representative B-scans across the 3 fine-tune probes
Left pane of each row: original B-scan. Right pane: per-patch $\Delta\logit$ overlay.




Figure 11: Per-patch occlusion heat maps on individual B-scans, drawn on a shared scale with the slice mean subtracted so that maps are comparable across volumes. Attribution is broadly distributed rather than concentrated in a few patches. Agreement is stronger at slice than patch level. These are hand-picked illustrative volumes rather than a sample, the overlay is the patch grid rendered with smoothing and so carries no detail finer than a patch, and no colour bar is drawn, so the maps show sign and spatial pattern but no readable magnitude.




Figure 12: ROC curves at epoch 100 on the 3000 test volumes. The three arms plotted are nearly superimposed: the separation reported throughout this paper is a small, consistent shift in the high-specificity region rather than a difference visible in the curve as a whole. We include this so the effect size is not overstated by tables alone.




Figure 13: Downstream AUC at matched epoch 50 against mask purity, the fraction of masked patches lying on retinal tissue. The policy whose masks are 97% on-tissue does not separate from the null, while policies at 40–43% purity gain the most. The ordering does not support the intuition that more accurate anatomical masking yields better representations. The AUC axis is truncated and no interval is drawn, and the dashed line is a least-squares fit through the arms shown; with four to five arms this is descriptive, not inferential. The point labelled *oracle* is CENTROID.




Figure 14: The matched-epoch-50 result arranged as a ladder of increasing anatomical specificity. Companion to Figure 13. The bars are drawn on a truncated AUC axis and carry no interval, so their relative *heights* greatly exaggerate the differences; read the printed values and the intervals in Table 1 instead. The reference line labelled `oracle` is CENTROID.




Figure 15: Measured mask geometry per policy, 600 training slices. Bars start at zero and no interval is drawn; each is a mean over those slices. The four rectangle policies are closely matched on masking ratio, context kept and predictor loss slots, and separate only on the manipulated axis, how much anatomy the targets hide, so their comparison is near single-variable. The anatomy policy diverges on all four simultaneously — half the masking ratio, $1.6\times$ the context, $0.4\times$ the predictor loss slots — so its deficit cannot be attributed to target shape. Bars labelled `oracle` and `cover-f0.21` are CENTROID and COVER.