
Location Beats Shape: A Controlled Comparison of Anatomy-Guided Masking for Joint-Embedding Predictive Pretraining on Retinal OCT

Anonymous Author(s)

Affiliation

Address

email

Abstract

Masked predictive pretraining asks a model to reconstruct the representation of hidden image regions. Which regions are hidden is a free design choice, and in medical imaging there is an intuitive answer: hide the tissue that carries the diagnosis. We test that intuition under tightly controlled conditions. Six masking policies are continued from a single shared I-JEPA checkpoint on 3D retinal OCT, differing *only* in how predictor targets are placed, and evaluated with a frozen linear-probe protocol for glaucoma classification (FairVision, $N=3000$). Guidance does help: restricting targets to retinal tissue improves AUC by $+0.0120$ over unguided masking at the matched epoch (95% CI $[+0.0068, +0.0173]$), and a band located by a first-order intensity statistic improves it by $+0.0109$ at epoch 100 ($[+0.0057, +0.0160]$, $p<0.0001$). All six contrasts against the null, at all three epochs, exclude zero. But anatomical *precision* does not help. A policy that places 97% of masked patches on tissue, using a trained retinal segmentation model to shape the targets, is *indistinguishable from unguided masking* at the matched epoch ($+0.0013$, CI $[-0.0055, +0.0082]$), as is a coverage-constrained policy ($+0.0002$) — while the two policies that merely *place* rectangles on tissue gain an order of magnitude more. Carried to epoch 100 the coverage-constrained policy does not merely stall, it peaks at epoch 73 and then declines, ending -0.0168 below unguided masking (CI $[-0.0233, -0.0105]$); an audit found its targets are shortened after placement, so it does not test aggressive coverage. Direct measurement of mask geometry across 600 slices shows the fraction of anatomy hidden is uncorrelated with downstream AUC. The best policy consults no segmentation model at all. A subgroup audit over 22 probes finds the same worst-served group every time; every disease stage improves with intervals excluding zero (largest for mild, $+0.0137$, though the gains are not separated from one another), while among race groups only the white subgroup’s gain excludes zero. The difficulty ordering is untouched: the severe-to-mild gap stays within 0.0114 of constant across every policy. Because each policy was pretrained once, we report these as single-run observations rather than an established ranking.

1 Introduction

Self-supervised learning has become the default route to representation quality in medical imaging, where expert annotation is expensive and pathology is rare [Azizi et al., 2021, Zhou et al., 2023, Qiu et al., 2024]. Joint-embedding predictive architectures such as I-JEPA [Assran et al., 2023] learn by

34 predicting the *representation* of masked target blocks from a visible context block, avoiding pixel
35 reconstruction and its bias toward high-frequency detail [He et al., 2022, Xie et al., 2022].

36 I-JEPA samples its targets geometrically: rectangles placed uniformly at random. In natural images
37 this is defensible, since informative content is spread broadly across the frame. In a retinal OCT
38 B-scan it is not obviously so. A large fraction of the image is dark vitreous and background; the
39 diagnostic signal for glaucoma is concentrated in a thin band of retinal tissue. This motivates an
40 intuitive hypothesis, one that several recent methods adopt [Li et al., 2022, 2024, Wang et al., 2025,
41 Shi et al., 2022]:

42 *Direct the predictive objective at clinically meaningful anatomy rather than at*
43 *arbitrary image regions.*

44 We test this hypothesis directly and at several strengths. Rather than proposing one anatomy-aware
45 method and reporting that it beats a baseline, we construct a *ladder* of masking policies of increas-
46 ing anatomical specificity — from unguided rectangles, through rectangles constrained to lie on
47 tissue, to ragged targets whose shape follows the segmented retina — and hold everything else fixed.
48 All arms continue from one shared pretrained checkpoint, use identical optimiser, schedule, and
49 effective batch size, and are evaluated under one frozen-probe protocol.

50 The result contradicts the intuition in an informative way. Guidance helps, but the benefit does
51 not increase with anatomical precision — it disappears. The two policies whose targets track the
52 segmented retina most faithfully are statistically indistinguishable from unguided masking at the
53 matched epoch, while two policies that merely place ordinary rectangles on tissue gain an order
54 of magnitude more. The best performer uses no segmentation model at all, locating a band by a
55 per-column intensity centroid.

56 Contributions.

- 57 • A controlled six-arm study isolating masking policy in medical SSL, with a shared ancestor
58 checkpoint and a single evaluation protocol (21 frozen probes).
- 59 • Evidence that guidance helps but anatomical precision does not, including the specific con-
60 trol — rectangles restricted to retinal tissue — that separates “avoid background” from
61 “target anatomy”.
- 62 • Direct measurement of mask geometry for every policy on 600 slices, showing that fraction-
63 of-anatomy-hidden does not order downstream AUC, and an explicit accounting of the axes
64 on which the anatomy arms are confounded.
- 65 • A subgroup audit and a 10^{-5} reproduction of the headline result from public weights on
66 different hardware and precision.

67 2 Related work

68 **Masked image modelling and JEPAs.** Masked autoencoders reconstruct pixels [He et al., 2022,
69 Xie et al., 2022]; BEiT [Bao et al., 2022] and iBOT [Zhou et al., 2022] predict discrete tokens;
70 data2vec [Baevski et al., 2022] and I-JEPA [Assran et al., 2023] predict latent representations. Video
71 and 3D extensions follow the same template [Bardes et al., 2024, Chen et al., 2023b, Taleb et al.,
72 2020]. Recent analyses question how much of the benefit derives from the masking distribution
73 itself [Balestriero and LeCun, 2025, He et al., 2025].

74 **Informed masking.** A substantial line of work argues that *what* is masked matters. ADIOS [Shi
75 et al., 2022] learns an adversarial masking model; SemMAE [Li et al., 2022] uses learned se-
76 mantic parts; AttMask [Kakogeorgiou et al., 2022] masks by attention; HardPatches [Wang et al.,
77 2023a] and AutoMAE [Chen et al., 2023a] target difficulty. In the medical domain, AnatoMask [Li
78 et al., 2024], AnatomyMAE [Ceballos Arroyo et al., 2026], MSMAE [Mao et al., 2023], and Va-
79 soMIM [Huang et al., 2026] explicitly steer masking toward anatomy, and Wang et al. [2025] argue
80 directly for masking clinically relevant regions. Our study is a controlled test of that family’s central
81 premise on one task, and finds it does not hold in the direction usually assumed.

Evidence that informed masking is not uniformly better. The picture is less one-sided than the paragraph above suggests. The original masked-modelling papers already report that random sampling is hard to beat: MAE’s ablation puts random-75 at 73.5 linear against block-75 at 63.9 [He et al., 2022], and SimMIM finds random beats its best block variant [Xie et al., 2022]. Among informed schemes, AttMask sits within 0.2 points of random [Kakogeorgiou et al., 2022], AutoMAE ties MAE under full fine-tuning [Chen et al., 2023a], HPM gains only when randomness is retained and *loses* when restricted to the hardest patches [Wang et al., 2023b], and attention-guided MAE underperforms MAE in the low-label regime [Sick et al., 2025]. Most directly, SemMAE’s own part-quality ablation shows that *imperfect* semantic parts add nothing over no parts at all [Li et al., 2022], and Guo et al. [2025] reproduce SemMAE below random MAE under a common protocol, with the deficit largest under frozen evaluation — also our protocol. Chen et al. [2023a] name the mechanism a “patch selection dilemma”: a slight foreground bias helps, but raising it too far starves the encoder of the evidence it must predict from. Conversely, the closest positive precedent for our best policy uses no segmentation model either: Lee et al. [2025] select foreground from normalised intensity alone and gain across five 3D medical benchmarks. Appendix K tabulates these.

We therefore do *not* claim to overturn the informed-masking literature. That random masking is a strong baseline, and semantic guidance wins only sometimes, is known and contested. What we add is a controlled measurement of where a *trained medical segmentation model* falls on that spectrum when everything else is held fixed, in a setting — 3D retinal OCT, joint-embedding prediction, frozen probe — where we could find no prior controlled comparison.

Retinal foundation models and OCT. RETFound [Zhou et al., 2023], VisionFM [Qiu et al., 2024], URFound [Yu et al., 2024], and OCTCube [Liu et al., 2026] pretrain on large retinal corpora; OCT-specific masked modelling is explored by Pissas et al. [2024]. MIRAGE [Morano et al., 2025] provides multimodal OCT segmentation and supplies the anatomical guidance used by several of our arms. Deep glaucoma detection from OCT is established [Maetschke et al., 2019, Ran et al., 2019, Noury et al., 2022].

Fairness in medical imaging. Performance disparities across demographic groups are widely documented [Seyyed-Kalantari et al., 2021, Larrazabal et al., 2020, Gichoya et al., 2022]. FairVision [Luo et al., 2024a] and Harvard-GF [Luo et al., 2024b] provide OCT data with demographic attributes; FairMedFM [Jin et al., 2024] and Shi et al. [2025] benchmark fairness for medical foundation models. We report a subgroup analysis as a secondary finding.

3 Method: a ladder of masking policies

3.1 Background

I-JEPA partitions the token grid of an image into a context block and M target blocks. A context encoder f_θ embeds the visible tokens; a predictor g_ϕ maps that embedding plus positional queries to predicted representations of the target tokens; an exponential-moving-average target encoder $\bar{f}_\theta$ supplies the regression targets. With a 16×16 token grid the design choice we vary is which of the 256 cells become targets.

3.2 The six policies

All policies produce $M=4$ target blocks and one context block under identical scale and aspect-ratio ranges. They differ only in placement and shape.

RANDOM (null). Stock I-JEPA multiblock. Four rectangles placed uniformly at random anywhere in the grid. No image content is consulted.

ENVELOPE (random-within-retina). Identical rectangles — same shape, size and count as RANDOM — but rejection-sampled onto the retinal envelope predicted by MIRAGE [Morano et al., 2025]. Only *location* changes. This is the control that separates “stop wasting targets on background” from “target anatomy specifically”.

CENTROID (segmentation-free). A band whose vertical position is located per slice by a per-column intensity-weighted row centroid, smoothed across columns. It adapts to the retina’s

Six masking policies on one B-scan, drawn with the production samplers.
Anatomical specificity increases left to right, top to bottom.




Figure 1: The six masking policies on one identical B-scan, drawn with the production samplers. Each predictor target block has its own colour; the green contour is the anatomy reference. Anatomical specificity increases along the ladder: ENVELOPE and COVER place rectangles on tissue, while the anatomy arms grow targets that trace the retina almost exactly. Downstream AUC does not increase with that specificity (Table 1). Figure 3 repeats this over five B-scans spanning the volume.

position and curvature using a first-order intensity statistic, consults **no segmentation model**, and uses no ground-truth annotation of any kind. It is named for the statistic it computes.

ANATOMY-V1 / ANATOMY-V2. Ragged connected components grown on the MIRAGE score map, so target *shape* follows tissue rather than being rectangular. v2 additionally bridges diagonal adjacencies.

COVER f . Targets chosen greedily to cover the anatomy subject to a hard floor leaving a fraction f of tissue visible in the context. We pretrain $f=0.21$.

Figure 1 shows all six on the same B-scans.

3.3 Hypotheses

The ladder yields three testable statements:

H1 *Avoiding background helps.* ENVELOPE > RANDOM.

H2 *Anatomical precision helps further.* anatomy arms > ENVELOPE.

H3 *Any benefit is due to anatomical targeting, not to incidental changes in mask area, target count, or context size.*

4 Experimental setup

Data. FairVision [Luo et al., 2024a] glaucoma OCT volumes. Each volume is a 3D scan resampled to 100 B-scans of 256×256 after transform. The label is a binary glaucoma diagnosis. Splits are fixed and patient-disjoint as released; downstream evaluation uses a held-out test split of $N=3000$ volumes (1466 positive / 1534 negative), seed 42, fixed loader order. No test volume is seen during pretraining, probe fitting, or model selection: the probe head is selected on a separate validation split. Labels are byte-identical across arms, so any two arms are paired-comparable on the same cases. The dataset carries self-reported demographic attributes, which we use only for the subgroup analysis in Section 5.3 and never as model inputs.

Pretraining. Patch-level I-JEPA, ViT-Base, 256×256 crops, patch size 16, predictor depth 6, EMA target encoder. **Every arm resumes from the same epoch-25 checkpoint** and continues with identical optimiser, learning-rate and weight-decay schedules, and effective batch size (512 for all arms). Guidance is ramped linearly from epoch 25 to 30 and held at full strength thereafter. The *only* difference between arms is the mask sampler.

Arms differ in how far they were carried, and we do not pretend otherwise. RANDOM, CENTROID and ENVELOPE reach epoch 100. ANATOMY-V2 has valid probes to epoch 50 (later checkpoints follow a target-precision splice and are excluded, Appendix D). ANATOMY-V1 has only epoch 30. COVER $f=0.21$ was deliberately halted at epoch 73. Epoch 50 is therefore the only epoch at which five policies are simultaneously available, and it carries every cross-policy comparison that involves the anatomy or coverage arms.

Evaluation. The encoder is frozen. Per-slice features are mean-pooled over the volume, followed by LayerNorm and a linear head. The head is selected by validation AUC and reported on the held-out test split. We report paired bootstrap confidence intervals over test volumes (10,000 resamples, stratified by class, the same resampled index set applied to every arm) and DeLong tests for correlated ROC curves [DeLong et al., 1988], both of which are valid here because all arms are evaluated on the same cases in the same order. Each test volume is a distinct subject, so case-level resampling is already subject-level and no cluster correction is required [Obuchowski, 1997, Rutter, 2000]. We follow Maier-Hein et al. [2024] in reporting the operating-point metrics alongside AUC rather than AUC alone (Appendix A).

Numerical precision, and how we handle it. The probe harness defaults to mixed precision. The RANDOM, CENTROID and ENVELOPE long-horizon probes were fitted under that default (fp16); the ANATOMY-V1, ANATOMY-V2, COVER and ancestor probes were fitted with autocast explicitly disabled (fp32). We therefore do *not* claim a single protocol across every probe in the study. Instead we partition the comparisons: all headline contrasts in Table 1 are drawn from arms sharing both epoch *and* precision, and any contrast that would cross the precision boundary is marked as such and excluded from headline claims. Section 5.4 reports a direct measurement of how large the precision effect actually is.

5 Results

What these numbers can and cannot establish. Each policy was pretrained exactly once, so policy is perfectly confounded with one stochastic optimisation path after the fork. The intervals below quantify sampling error over test subjects for a *fixed* pair of score vectors, not seed-to-seed variance of pretraining. Read every comparison here as a controlled single-run observation, not an established ranking over retrains (Section 6).

5.1 H1 holds, H2 fails

Table 1 gives the main comparison, Table 11 in Appendix L the full paired inference for all nine precision-matched contrasts, and Figure 2 the trajectories. All six contrasts against the null survive Benjamini–Hochberg correction over that family of nine ($q \leq 0.0299$ throughout). **H1 holds:** constraining the same rectangles to lie on retinal tissue (ENVELOPE) beats unguided masking by $+0.0120$ at epoch 50 (CI $[+0.0068, +0.0173]$) and by $+0.0062$ at epoch 100 (CI $[+0.0010, +0.0113]$). Avoiding background is worth something, at every epoch we measured, with an interval that excludes zero.

H2 fails. H2 predicts the anatomy arms exceed ENVELOPE; they do not, transitively through the shared null. At epoch 50 — the only epoch at which all five arms have a probe — ENVELOPE beats RANDOM by $+0.0120$ with an interval excluding zero, while ANATOMY-V2 gains only $+0.0013$ and COVER $+0.0002$, both indistinguishable from that null. An arm that does not separate from the null cannot exceed one that beats it, so H2 is refuted without a separate anatomy-versus-envelope contrast. Against $+0.0099$ for CENTROID, policies that merely *place* rectangles on tissue gain roughly an order of magnitude more than those shaping targets to match it.

We are careful not to overstate this. At the matched epoch 50 neither ANATOMY-V2 (CI $[-0.0055, +0.0082]$, $p = 0.7153$) nor COVER (CI $[-0.0050, +0.0053]$, $p = 0.9513$) is *worse*

Table 1: Frozen MeanPool probe, FairVision test ($N=3000$, 1466 positive). All arms continue from one epoch-25 ancestor (AUC 0.8487). Δ is versus RANDOM at the *matched* epoch. The upper block is precision-matched (fp16 throughout) and carries every headline claim. The lower block is fp32. Its epoch-50 Δ is taken against an fp32 null re-probed for that comparison and is matched on epoch and precision. The COVER epoch-75 Δ is marked ‡: no fp32 null exists at that epoch yet, so it is matched on epoch only. The measured fp16/fp32 gap is at most 2×10^{-4} (Appendix M), some forty times below that Δ .

policy	guidance signal	epoch 50		epoch 75		epoch 100	
		AUC	Δ	AUC	Δ	AUC	Δ
RANDOM	none (null)	0.8641	—	0.8723	—	0.8746	—
ENVELOPE	segmenter (location only)	0.8761	+0.0120	0.8803	+0.0080	0.8807	+0.0062
CENTROID	intensity centroid, no segmenter	0.8740	+0.0099	0.8836	+0.0113	0.8855	+0.0109
ANATOMY-V2	segmenter (target shape)	0.8654	+0.0013	pending [†]	pending [†]	pending [†]	pending [†]
COVER $f=.21$	segmenter (coverage)	0.8643	+0.0002	0.8639	−0.0084	0.8577	−0.0168




Figure 2: **(a)** Frozen-probe test AUC against pretraining epoch. All arms fork from the same epoch-25 checkpoint (open circle) and differ only in masking policy. Solid lines are the precision-matched fp16 family; dashed lines are fp32 arms and must not be compared vertically against the solid lines. **(b)** The actual inference: paired differences against the unguided null on identical test cases, with 10,000-resample bootstrap intervals. All six intervals exclude zero. We plot paired differences rather than per-arm error bars because marginal intervals carry between-case variance that cancels in a paired comparison, and would understate the evidence.

206 than the null; both are indistinguishable from it, against an fp32 null re-probed for this comparison,
 207 so they are matched on epoch *and* precision. What the data rule out is not harm but the expected
 208 *monotone improvement with anatomical precision*.

209 **Carried to epoch 100 the coverage arm degrades, but a defect blocks the natural reading.**
 210 COVER is the only segmenter-driven policy we continued to the full horizon, and it produces the
 211 study’s one *negative* result. It climbs normally to epoch 50, peaks at epoch 73 (0.8647), then *falls*
 212 to 0.8577, losing -0.0071 from its own peak ($p < 0.0001$) while the unguided null keeps improving
 213 (Figure 2). The gap against the null therefore widens with training: $+0.0002$ at epoch 50, -0.0084
 214 at epoch 75, and -0.0168 at epoch 100 (CI $[-0.0233, -0.0105]$, $p < 0.0001$), where it also sits
 215 -0.0276 below CENTROID. All contrasts are matched on epoch and precision.

216 The obvious reading — that pushing coverage higher is actively harmful — is *not* available to us.
 217 An audit (Appendix E) found the collator shortens every predictor target *after* COVER chooses its
 218 placement, defeating its greedy optimisation: delivered masks hide 73.1% of anatomy, *less* than
 219 ENVELOPE’s 77.6%, not the 78.6% the placement achieved. COVER never realised the aggressive
 220 coverage it was built to test, so its decline cannot be attributed to over-covering anatomy, and because
 221 coverage was logged before truncation every training log reported the intent. What survives is
 222 narrower: a coverage-seeking policy whose targets are shortened and top-biased peaks early and
 223 then erodes while the null improves.

Table 2: Measured mask geometry, 600 held-out slices, production samplers. “purity” is the fraction of masked cells lying on tissue; “loss slots” is the number of predictor targets contributing to the loss. All values measured. AUC is quoted at the *matched* epoch 50, the only epoch at which all five policies have a probe, so that the geometry-to-AUC association is not read across mixed epochs. All five AUCs are at epoch 50.

policy	anatomy hidden	purity	mask ratio	context kept	loss slots	AUC @ep50
RANDOM	52.2%	31.6%	43.7%	42.1%	157.7	0.8641
CENTROID	62.2%	41.1%	40.0%	45.6%	158.4	0.8740
ENVELOPE	76.9%	43.5%	46.4%	40.5%	159.9	0.8761
COVER	74.1%	45.3%	43.3%	43.5%	160.0	0.8643
ANATOMY-V2	80.3%	97.3%	21.4%	67.9%	64.0	0.8654

The strongest policy is the one that uses no segmentation model. CENTROID gives +0.0109 over the null at epoch 100 (95% CI [+0.0057, +0.0160], $p < 0.0001$, $q = < 0.0001$), with a margin that is stable across training (+0.0099, +0.0113, +0.0109). It exceeds the segmenter-guided ENVELOPE arm at epoch 100 by +0.0047 (CI [+0.0004, +0.0091], $p = 0.0294$), though the two are indistinguishable at epochs 50 and 75. Notably, ENVELOPE’s margin over the null *decays* with training (+0.0120 $\rightarrow$ +0.0080 $\rightarrow$ +0.0062) while CENTROID’s does not.

5.2 H3: it is not anatomical targeting

To test H3 we ran each production sampler on 600 held-out slices and measured what it actually does (Table 2, Figure 10). Three observations follow.

First, **anatomical targeting does not order the results**. Over the four rectangle arms, the Spearman correlation between fraction-of-anatomy-hidden and AUC is exactly 0.00: knowing how much anatomy a policy hides tells you nothing about its downstream AUC. Mask *purity* — the share of masked patches lying on tissue — trends negatively (−0.40). Neither is significant at $n=4$ arms, and we present them as descriptive rather than inferential; but neither shows the positive relationship the anatomy-guidance hypothesis predicts. The anatomy arm places 97.3% of masked cells on tissue and does not separate from the null; CENTROID places 41.1% on tissue and gives the largest gain in the study.

Second, **the anatomy arms are confounded on several axes simultaneously**, and we state this rather than attributing their deficit to shape. They hide only 21.4% of the grid against 40–46% for the rectangle arms, leave 67.9% of tokens visible as context against 40–46%, and supply 64 predictor loss slots against 158–160. Any of these could account for their deficit without invoking target shape at all. We therefore do *not* claim that irregular target shape is harmful; that comparison is not identified by this design. Figure 12 makes the four-way divergence explicit.

Crucially, these are not consequences of blob geometry: the anatomy arms resample every target to a fixed $K=16$ cells, so $4 \times 16 = 64$ loss slots follows by construction, while the rectangle arms do not set K . The two families are collated differently, which weakens “everything else held fixed” for the anatomy-versus-rectangle comparison specifically; contrasts within the rectangle family are unaffected (Appendix E).

Third, CENTROID is the most *spatially consistent* policy we measured. Its per-cell hit map is the most concentrated of any arm (Gini 0.400 versus 0.316–0.338 for the other rectangle arms): it repeatedly asks the encoder to represent the same region of the image. This suggests a mechanism other than anatomical correctness — consistency of the predictive task — which we return to in Section 6.

5.3 Subgroup analysis

Joining saved test predictions to the released FairVision metadata in deterministic loader order (the join is validated by exact label reconstruction: the label vector rebuilt from the sorted file order matches the stored labels for all 3000 cases in every probe), we audit seven stratifications across 22 probes spanning aggregate AUC 0.8483 to 0.8855. Probes that the exclusion rules of Appendix D remove are removed here too.

The ordering of subgroups never changes. The worst-performing group is the same in every one of the 22 probes for sex (female), race (black), ethnicity (hispanic) and disease severity (mild $(-6, -2]$). No masking policy reorders them. The probes share a test set, an epoch-25 ancestor and a probe seed, and several are different epochs of one branch, so they are *not* independent; we report this as a descriptive regularity and attach no p -value. What it shows is that the disparity is not introduced by any policy we tried.

Point estimates rise everywhere; few gaps reliably move. A widening max-min gap is easy to misread as harm. It is not. At epoch 100 the strongest policy raises the point estimate for *every* race stratum over the null, and the max-min gap widens only because the already-best asian subgroup gains most. Paired resampling, however, separates only the white subgroup’s gain from zero ($+0.01129$, CI $[+0.00518, +0.01731]$); the black ($+0.01467$, CI $[-0.00055, +0.03060]$) and asian intervals include it, the smaller strata being noisier. The gains are therefore consistent in sign across race, not provably positive in every group. Nor is there a defensible gap *trend*. Across checkpoints the race gap correlates with aggregate AUC at $\rho = +0.556$ ($p = 0.0072$, $q = 0.0252$ after Benjamini–Hochberg over the seven attributes tested), but those checkpoints are not independent: they are 22 probes drawn from only 7 pretraining branches, so a branch probed at four epochs contributes four correlated points. Collapsing to one point per branch, the association disappears ($\rho = +0.321$, $p = 0.4821$). We therefore treat the checkpoint-level correlation as pseudo-replicated and make no claim that better models are less fair. The same holds for severity in the opposite direction ($\rho = -0.497$ per checkpoint, -0.821 per branch). Only the sex gap is consistent across both views, and it *narrows* ($q = 0.0039$; branch-level $\rho = -0.821$, $p = 0.0234$). We do not claim that better masking harms any group, and we do not claim it helps equity either.

Early disease improves most; differential benefit is unresolved. Scoring each severity stratum against the shared pool of all negatives, the strongest policy improves mild disease by $+0.0137$ at matched epoch 100, moderate by $+0.0102$, severe by $+0.0063$. These are paired differences on the same subjects and all three intervals exclude zero (mild $[+0.00541, +0.02192]$, severe $[+0.00104, +0.01187]$), so the ordering is resolved rather than a point-estimate artefact. What does not move is the difficulty ordering itself: the severe-to-mild gap stays within 0.0114 of constant across all 22 probes while aggregate AUC spans 0.8483–0.8855. For equity the quantity that matters is the paired *difference* between groups’ gains; between the worst- and best-served race strata it is -0.00091 (CI $[-0.02379, +0.02139]$) and by sex $+0.00146$ (CI $[-0.00853, +0.01156]$). Both contain zero, so at these subgroup sizes we cannot resolve whether the improvement is evenly distributed, and claim neither. Appendix C gives every stratum. No policy here was designed as a fairness intervention and none should be presented as one.

5.4 Numerical precision is not the effect

The long-horizon and anatomy arms were probed at different autocast settings (Section 4), so we measured the precision effect rather than assuming it away: a full re-fit of the probe pipeline at fp32 shifts every arm by less than 2×10^{-4} , two to three orders of magnitude below the effects in Table 1, and every contrast we report is now matched on precision. Appendix M gives the numbers.

5.5 Reproducibility

The epoch-100 CENTROID encoder and its trained probe head will be released, together with the stored per-case predictions for every probe in this paper. Links are withheld here for anonymity. Every number in this paper is emitted by a single script from those stored predictions, so tables, figures and prose cannot disagree; that script is released with the code.

6 Discussion and limitations

What the evidence supports. Guidance helps: restricting targets to tissue is worth $+0.0120$ at the matched epoch, and a consistent intensity-located band is worth $+0.0109$ at epoch 100, with paired intervals excluding zero at every epoch measured. A trained segmentation model is not required to obtain this benefit, and using one more aggressively — to shape targets or to maximise anatomy coverage — does not add to it and can subtract. The practical reading, bounded by the caveats below,

is that for *this* task the segmentation stage bought nothing we could measure, and a one-line intensity statistic recovered the whole benefit. We would not generalise that to tasks where anatomy is the output, such as layer segmentation or lesion localisation.

What it does not support. We cannot claim anatomy-shaped masking is *harmful*: at the matched epoch it sits $+0.0013$ from the null with an interval $([-0.0055, +0.0082])$ that comfortably contains zero, so it is indistinguishable rather than worse. Nor can we claim target *shape* is the operative variable, for the reasons in Table 2. Nor can we claim the mechanism behind CENTROID’s advantage. Two explanations remain live: consistency of location (the encoder is repeatedly forced to represent the same region), and masking ratio or task difficulty. Distinguishing them requires an arm that randomises the band’s vertical position while holding area and context fixed, which we did not run.

One pretraining run per policy. The paired bootstrap quantifies sampling error on a fixed test set; it does not quantify seed-to-seed variance of pretraining. With $n=1$ continuation per arm the *ranking* is not statistically established even where individual pairwise differences are significant on this test set. Bouthillier et al. [2021] show that single-seed comparisons routinely mistake optimisation noise for method effects. We can bound one component: with five probe seeds on two fixed encoders the probe-seed standard deviation is 0.0003 and 0.0018, and the arms stay fully separated across all five, so probe noise is an order of magnitude below the effects in Table 1. Those are *technical* replicates and do not estimate pretraining noise, which would need at least three paired continuations from the shared checkpoint with the continuation as the unit of replication. That is the single most valuable follow-up and we do not claim its result in advance.

Scope, coverage and an incomplete arm. All results are glaucoma classification from FairVision OCT; generality to other modalities, diseases, or segmentation-quality regimes is untested, and the anatomy arms depend on MIRAGE’s prediction quality on this data, so a better segmenter might change the conclusion. Only $f=0.21$ was pretrained for COVER, so we report no dose-response over the visible-tissue floor and make no claim that any floor is optimal. That arm also has probes only at epochs 27, 30, 34, 50 and 73: it was deliberately halted before epoch 100, its later probes are marked pending rather than reported, and we draw no conclusion about its endpoint. Its epoch-50 value is included because it is a matched-epoch comparison against every other arm. Finally, one dataset and one test split were reused throughout this programme’s history, and policies, checkpoints and analyses were chosen after repeated inspection of that split; the intervals we report are therefore best read as descriptive rather than as confirmatory inference.

Broader impact and ethics. This study uses a public, de-identified retinal dataset under its release terms and involves no new data collection or human subjects. No model reported here is clinically validated or intended for deployment. Appendix J gives the full statement.

7 Conclusion

We tested the intuition that masked predictive pretraining in medical imaging should target clinically meaningful anatomy. Under matched compute, schedule, and a shared ancestor checkpoint, guidance helped — but anatomical precision did not. Restricting targets to retinal tissue improved AUC over unguided masking by $+0.0120$ at the matched epoch, while shaping targets to trace the segmented retina left performance indistinguishable from not guiding at all, and the best policy consulted no segmentation model. Mask geometry is uncorrelated with how much anatomy is hidden; a subgroup audit shows every disease stage improving with intervals excluding zero, race gains consistent in sign, and the difficulty ordering untouched. We suggest the operative variable is the consistency of the predictive task rather than its anatomical correctness.

References

Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15619–15629, 2023. doi: 10.1109/CVPR52729.2023.01499.

361 Shekoofeh Azizi, Basil Mustafa, Fiona Ryan, Zachary Beaver, Jan Freyberg, Jonathan Deaton,
362 Aaron Loh, Alan Karthikesalingam, Simon Kornblith, Ting Chen, et al. Big self-supervised
363 models advance medical image classification. In *Proceedings of the IEEE/CVF International
364 Conference on Computer Vision*, 2021.

365 Alexei Baevski, Wei-Ning Hsu, Qiantong Xu, Arun Babu, Jiatao Gu, and Michael Auli. data2vec:
366 A general framework for self-supervised learning in speech, vision and language. In *Proceedings
367 of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Ma-
368 chine Learning Research*, pages 1298–1312. PMLR, 2022. URL [https://proceedings.mlr.
369 press/v162/baevski22a.html](https://proceedings.mlr.press/v162/baevski22a.html).

370 Randall Balestriero and Yann LeCun. LeJEPa: Provable and scalable self-supervised learning with-
371 out the heuristics, 2025. URL <https://arxiv.org/abs/2511.08544>.

372 Hangbo Bao, Li Dong, Songhao Piao, and Furu Wei. BEiT: BERT pre-training of image trans-
373 formers. In *International Conference on Learning Representations*, 2022. URL [https://
374 openreview.net/forum?id=p-BhZSz59o4](https://openreview.net/forum?id=p-BhZSz59o4).

375 Adrien Bardes, Quentin Garrido, Jean Ponce, Xinlei Chen, Michael Rabbat, Yann LeCun, Mahmoud
376 Assran, and Nicolas Ballas. Revisiting feature prediction for learning visual representations from
377 video. *Transactions on Machine Learning Research*, 2024. URL [https://openreview.net/
378 forum?id=QaCCuDfBk2](https://openreview.net/forum?id=QaCCuDfBk2).

379 Xavier Bouthillier, Pierre Delaunay, Mirko Bronzi, Assya Trofimov, Brennan Nichyporuk,
380 Justin Szeto, Nazanin Mohammadi Sepahvand, Edward Raff, Kanika Madan, Vikram Voleti,
381 Samira Ebrahimi Kahou, Vincent Michalski, Tal Arbel, Chris Pal, Gael Varoquaux, and Pascal
382 Vincent. Accounting for variance in machine learning benchmarks. *Proceedings of Machine
383 Learning and Systems*, 3:747–769, 2021. URL [https://proceedings.mlsys.org/paper_
384 files/paper/2021/hash/0184b0cd3cfb185989f858a1d9f5c1eb-Abstract.html](https://proceedings.mlsys.org/paper_files/paper/2021/hash/0184b0cd3cfb185989f858a1d9f5c1eb-Abstract.html).

385 Alberto M. Ceballos Arroyo, Jisoo Kim, Chu-Hsuan Lin, Lei Qin, Geoffrey S. Young, and Huaizu
386 Jiang. Anatomically-guided masked autoencoder pre-training for aneurysm detection. In *Proceed-
387 ings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 5693–5702,
388 2026. doi: 10.1109/WACV61042.2026.00552.

389 Haijian Chen, Wendong Zhang, Yunbo Wang, and Xiaokang Yang. Improving masked autoencoders
390 by learning where to mask. In *Pattern Recognition and Computer Vision*, pages 377–390. Springer,
391 2023a. doi: 10.1007/978-981-99-8543-2_31.

392 Zekai Chen, Devansh Agarwal, Kshitij Aggarwal, Wiem Safta, Mariann Micsinai Balan, and Kevin
393 Brown. Masked image modeling advances 3d medical image analysis. In *Proceedings of the
394 IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1970–1980, 2023b.
395 doi: 10.1109/WACV56688.2023.00201.

396 Elizabeth R. DeLong, David M. DeLong, and Daniel L. Clarke-Pearson. Comparing the areas
397 under two or more correlated receiver operating characteristic curves: A nonparametric approach.
398 *Biometrics*, 44(3):837–845, 1988. doi: 10.2307/2531595. URL [https://doi.org/10.2307/
399 2531595](https://doi.org/10.2307/2531595).

400 Judy Wawira Gichoya, Imon Banerjee, Ananth Reddy Bhimireddy, John L. Burns, Leo Anthony
401 Celi, Li-Ching Chen, Ramon Correa, Natalie Dullerud, Marzyeh Ghassemi, Shih-Cheng Huang,
402 Po-Chih Kuo, Matthew P. Lungren, Lyle J. Palmer, Brandon J. Price, Saptarshi Purkayastha,
403 Ayis T. Pyrros, Lauren Oakden-Rayner, Chima Okechukwu, Laleh Seyyed-Kalantari, Hari
404 Trivedi, Ryan Wang, Zachary Zaiman, and Haoran Zhang. AI recognition of patient race in
405 medical imaging: A modelling study. *The Lancet Digital Health*, 4(6):e406–e414, 2022. doi:
406 10.1016/S2589-7500(22)00063-2.

407 Han Guo, Ramtin Hosseini, Ruiyi Zhang, Sai Ashish Somayajula, Ranak Roy Chowdhury, Rajesh K.
408 Gupta, and Pengtao Xie. Downstream task guided masking learning in masked autoencoders using
409 multi-level optimization. *Transactions on Machine Learning Research*, 2025. arXiv:2402.18128.

410 Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoen-
411 coders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vi-
412 sion and Pattern Recognition*, pages 16000–16009, 2022. doi: 10.1109/CVPR52688.2022.01553.

413 Xiangteng He, Shunsuke Sakai, Shivam Chandhok, Sara Beery, Kun Yuan, Nicolas Padoy, Tatsuhito
414 Hasegawa, and Leonid Sigal. DSeq-JEPA: Discriminative sequential joint-embedding predictive
415 architecture, 2025. URL <https://arxiv.org/abs/2511.17354>. Accepted at ECCV 2026;
416 final proceedings metadata unavailable at verification time.

417 De-Xing Huang, Xiao-Hu Zhou, Mei-Jiang Gui, Xiao-Liang Xie, Shi-Qi Liu, Shuang-Yi Wang,
418 Tian-Yu Xiang, Rui-Ze Ma, Nu-Fang Xiao, and Zeng-Guang Hou. VasoMIM: Vascular anatomy-
419 aware masked image modeling for vessel segmentation. In *Proceedings of the AAAI Conference*
420 *on Artificial Intelligence*, volume 40, pages 4985–4993, 2026. doi: 10.1609/aaai.v40i6.42503.

421 Yijin Huang, Junyan Lyu, Pujin Cheng, Roger Tam, and Xiaoying Tang. SSiT: Saliency-guided
422 self-supervised image transformer for diabetic retinopathy grading. *IEEE Journal of Biomedical*
423 *and Health Informatics*, 28(5):2806–2817, 2024. doi: 10.1109/JBHI.2024.3362878. URL <https://doi.org/10.1109/JBHI.2024.3362878>.

425 Ruinan Jin, Zikang Xu, Yuan Zhong, Qingsong Yao, Qi Dou, S. Kevin Zhou, and Xiaoxiao
426 Li. FairMedFM: Fairness benchmarking for medical imaging foundation models. In *Ad-*
427 *vances in Neural Information Processing Systems*, volume 37, pages 111318–111357, 2024.
428 doi: 10.52202/079017-3535. URL [https://proceedings.neurips.cc/paper_files/](https://proceedings.neurips.cc/paper_files/paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_Benchmarks_Track.html)
429 [paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_](https://proceedings.neurips.cc/paper_files/paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_Benchmarks_Track.html)
430 [Benchmarks_Track.html](https://proceedings.neurips.cc/paper_files/paper/2024/hash/c9826b9ea5e1b49b256329934a578d83-Abstract-Datasets_and_Benchmarks_Track.html).

431 Ioannis Kakogeorgiou, Spyros Gidaris, Bill Psomas, Yannis Avrithis, Andrei Bursuc, Konstantinos
432 Karantzas, and Nikos Komodakis. What to hide from your students: Attention-guided masked
433 image modeling. In *Computer Vision – ECCV 2022*, pages 300–318. Springer, 2022. doi: 10.
434 1007/978-3-031-20056-4_18.

435 Agostina J. Larrazabal, Nicolás Nieto, Victoria Peterson, Diego H. Milone, and Enzo Ferrante.
436 Gender imbalance in medical imaging datasets produces biased classifiers for computer-aided
437 diagnosis. *Proceedings of the National Academy of Sciences*, 117(23):12592–12594, 2020. doi:
438 10.1073/pnas.1919012117.

439 Jin Lee, Vu Dang, Gwang-Hyun Yu, Anh Le, Zahid Rahman, Jin-Ho Jang, Heonzoo Lee, Kun-Yung
440 Kim, Jin-Sul Kim, and Jin-Young Kim. HU-based foreground masking for 3D medical masked
441 image modeling. In *Medical Image Computing and Computer Assisted Intervention (MICCAI)*,
442 2025. doi: 10.1007/978-3-032-09569-5_13. arXiv:2509.07534.

443 Gang Li, Heliang Zheng, Daqing Liu, Chaoyue Wang, Bing Su, and Changwen Zheng.
444 SemMAE: Semantic-guided masking for learning masked autoencoders. In *Advances in*
445 *Neural Information Processing Systems*, volume 35, pages 14290–14302, 2022. doi:
446 10.52202/068431-1039. URL [https://proceedings.neurips.cc/paper_files/paper/](https://proceedings.neurips.cc/paper_files/paper/2022/hash/5db4e0a62cb5b4a5a70f1fdc9a78a4cc-Abstract-Conference.html)
447 [2022/hash/5db4e0a62cb5b4a5a70f1fdc9a78a4cc-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2022/hash/5db4e0a62cb5b4a5a70f1fdc9a78a4cc-Abstract-Conference.html).

448 Yuheng Li, Tianyu Luan, Yizhou Wu, Shaoyan Pan, Yenho Chen, and Xiaofeng Yang. AnatoMask:
449 Enhancing medical image segmentation with reconstruction-guided self-masking. In *Computer*
450 *Vision – ECCV 2024*, pages 146–163. Springer, 2024. doi: 10.1007/978-3-031-73027-6_9.

451 Zixuan Liu, Hanwen Xu, Addie Woicik, Linda G. Shapiro, Marian Blazes, Yue Wu, Verena Steffen,
452 Catherine A. Cukras, Cecilia S. Lee, Miao Zhang, Aaron Y. Lee, and Sheng Wang. A three-
453 dimensional multi-modal foundation model for optical coherence tomography. *Nature Biomedical*
454 *Engineering*, 2026. doi: 10.1038/s41551-026-01662-2.

455 Yan Luo, Muhammad Osama Khan, Yu Tian, Min Shi, Zehao Dou, Tobias Elze, Yi Fang, and
456 Mengyu Wang. FairVision: Equitable deep learning for eye disease screening via fair identity
457 scaling, 2024a. URL <https://arxiv.org/abs/2310.02492>.

458 Yan Luo, Yu Tian, Min Shi, Louis R. Pasquale, Lucy Q. Shen, Nazlee Zebardast, Tobias Elze, and
459 Mengyu Wang. Harvard glaucoma fairness: A retinal nerve disease dataset for fairness learning
460 and fair identity normalization. *IEEE Transactions on Medical Imaging*, 43(7):2623–2633, 2024b.
461 doi: 10.1109/TMI.2024.3377552.

462 Stefan Maetschke, Bhavna Antony, Hiroshi Ishikawa, Gadi Wollstein, Joel Schuman, and Rahil
463 Garnavi. A feature agnostic approach for glaucoma detection in OCT volumes. *PLOS ONE*, 14
464 (7), 2019.

- 465 Lena Maier-Hein, Annika Reinke, Patrick Godau, Minu D. Tizabi, Florian Buettner, Evangelia
466 Christodoulou, Ben Glocker, Fabian Isensee, Jens Kleesiek, Michal Kozubek, Mauricio Reyes,
467 Michael A. Riegler, Manuel Wiesenfarth, A. Emre Kavur, Carole H. Sudre, Michael Baumgartner,
468 Matthias Eisenmann, Doreen Heckmann-Nötzel, Tim Rädtsch, Laura Acion, Michela Antonelli,
469 Tal Arbel, Spyridon Bakas, Arriel Benis, Matthew B. Blaschko, M. Jorge Cardoso, Veronika Chep-
470 lygina, Beth A. Cimini, Gary S. Collins, Keyvan Farahani, Luciana Ferrer, Adrian Galdran, Bram
471 van Ginneken, Robert Haase, Daniel A. Hashimoto, Michael M. Hoffman, Merel Huisman, Pierre
472 Jannin, Charles E. Kahn, Dagmar Kainmueller, Bernhard Kainz, Alexandros Karargyris, Alan
473 Karthikesalingam, Florian Kofler, Annette Kopp-Schneider, Anna Kreshuk, Tahsin Kurc, Ben-
474 nett A. Landman, Geert Litjens, Amin Madani, Klaus Maier-Hein, Anne L. Martel, Peter Matt-
475 son, Erik Meijering, Bjoern Menze, Karel G. M. Moons, Henning Müller, Brennan Nihyporuk,
476 Felix Nickel, Jens Petersen, Nasir Rajpoot, Nicola Rieke, Julio Saez-Rodriguez, Clara I. Sánchez,
477 Shravya Shetty, Maarten van Smeden, Ronald M. Summers, Abdel A. Taha, Aleksei Tiulpin,
478 Sotirios A. Tsaftaris, Ben Van Calster, Gaël Varoquaux, and Paul F. Jäger. Metrics reloaded:
479 Recommendations for image analysis validation. *Nature Methods*, 21(2):195–212, 2024. doi:
480 10.1038/s41592-023-02151-z. URL <https://doi.org/10.1038/s41592-023-02151-z>.
- 481 Jiawei Mao, Shujian Guo, Yuanqi Chang, Xuesong Yin, and Binling Nie. Medical supervised
482 masked autoencoders: Crafting a better masking strategy and efficient fine-tuning schedule for
483 medical image classification, 2023. URL <https://arxiv.org/abs/2305.05871>.
- 484 José Morano, Botond Fazekas, Emese Sükei, Ronald Fecso, Taha Emre, Markus Gumpinger, Georg
485 Faustmann, Marzieh Oghbaie, Ursula Schmidt-Erfurth, and Hrvoje Bogunović. Multimodal
486 foundation model and benchmark for comprehensive retinal OCT image analysis. *npj Digital*
487 *Medicine*, 8:576, 2025. doi: 10.1038/s41746-025-01852-3.
- 488 Erfan Noury, Suria S. Mannil, Robert T. Chang, An Ran Ran, Carol Y. Cheung, Suman S. Thapa,
489 Harsha L. Rao, Srilakshmi Dasari, Mohammed Riyazuddin, Dolly Chang, Sriharsha Nagaraj,
490 Clement C. Tham, and Reza Zadeh. Deep learning for glaucoma detection and identification of
491 novel diagnostic areas in diverse real-world datasets. *Translational Vision Science & Technology*,
492 11(5):11, 2022. doi: 10.1167/tvst.11.5.11.
- 493 Nancy A. Obuchowski. Nonparametric analysis of clustered ROC curve data. *Biometrics*, 53(2):
494 567–578, 1997. doi: 10.2307/2533958. URL <https://doi.org/10.2307/2533958>.
- 495 Theodoros Pissas, Pablo Márquez-Neila, Sebastian Wolf, Martin S. Zinkernagel, and Raphael Sznit-
496 man. Masked image modelling for retinal OCT understanding. In *Ophthalmic Medical Image*
497 *Analysis*, pages 115–125. Springer, 2024. doi: 10.1007/978-3-031-73119-8_12.
- 498 Jianing Qiu, Jian Wu, Hao Wei, Peilun Shi, Mingqing Zhang, Yunyun Sun, Lin Li, Hanruo Liu,
499 Hongyi Liu, Simeng Hou, Yuyang Zhao, Xuehui Shi, Junfang Xian, Xiaoxia Qu, Sirui Zhu, Lijie
500 Pan, Xiaoniao Chen, Xiaojia Zhang, Shuai Jiang, Kebin Wang, Chenlong Yang, Mingqiang
501 Chen, Sujie Fan, Jianhua Hu, Aiguo Lv, Hui Miao, Li Guo, Shujun Zhang, Cheng Pei, Xiaojuan
502 Fan, Jianqin Lei, Ting Wei, Junguo Duan, Chun Liu, Xiaobo Xia, Siqi Xiong, Junhong Li, Kyle
503 Lam, Benny Lo, Yih Chung Tham, Tien Yin Wong, Ningli Wang, and Wu Yuan. Development and
504 validation of a multimodal multitask vision foundation model for generalist ophthalmic artificial
505 intelligence. *NEJM AI*, 1(12), 2024. doi: 10.1056/AIoa2300221.
- 506 An Ran Ran, Carol Y. Cheung, Xi Wang, Hao Chen, Lu-Yang Luo, Poemen P. Chan, Mandy O. M.
507 Wong, Robert T. Chang, Suria S. Mannil, Alvin L. Young, Hon-Wah Yung, Chi Pui Pang, Pheng-
508 Ann Heng, and Clement C. Tham. Detection of glaucomatous optic neuropathy with spectral-
509 domain optical coherence tomography: A retrospective training and validation deep-learning anal-
510 ysis. *The Lancet Digital Health*, 1(4):e172–e182, 2019. doi: 10.1016/S2589-7500(19)30085-8.
- 511 Carolyn M. Rutter. Bootstrap estimation of diagnostic accuracy with patient-clustered data. *Aca-*
512 *demic Radiology*, 7(6):413–419, 2000. doi: 10.1016/S1076-6332(00)80381-5. URL [https://doi.org/10.1016/S1076-6332\(00\)80381-5](https://doi.org/10.1016/S1076-6332(00)80381-5).
- 514 Laleh Seyyed-Kalantari, Haoran Zhang, Matthew B. A. McDermott, Irene Y. Chen, and Marzyeh
515 Ghassemi. Underdiagnosis bias of artificial intelligence algorithms applied to chest radiographs
516 in under-served patient populations. *Nature Medicine*, 27(12):2176–2182, 2021. doi: 10.1038/
517 s41591-021-01595-0.

- Min Shi, Yan Luo, Yu Tian, Lucy Q. Shen, Tobias Elze, Nazlee Zebardast, Mohammad Eslami, Saber Kazeminasab, Michael V. Boland, David S. Friedman, Louis R. Pasquale, and Mengyu Wang. Equitable artificial intelligence for glaucoma screening with fair identity normalization. *npj Digital Medicine*, 8(1), 2025. doi: 10.1038/s41746-025-01432-5.
- Yuge Shi, N. Siddharth, Philip H. S. Torr, and Adam R. Kosiorek. Adversarial masking for self-supervised learning. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 20026–20040. PMLR, 2022. URL <https://proceedings.mlr.press/v162/shi22d.html>.
- Leon Sick, Dominik Engel, Pedro Hermosilla, and Timo Ropinski. Attention-guided masked autoencoders for learning image representations. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 836–846, 2025. doi: 10.1109/WACV61041.2025.00091. URL https://openaccess.thecvf.com/content/WACV2025/html/Sick_Attention-Guided_Masked_Autoencoders_for_Learning_Image_Representations_WACV_2025_paper.html.
- Aiham Taleb, Winfried Loetzsch, Noel Danz, Julius Severin, Thomas Gärtner, Benjamin Bergner, and Christoph Lippert. 3d self-supervised methods for medical imaging. In *Advances in Neural Information Processing Systems*, volume 33, pages 18158–18172, 2020. URL <https://proceedings.neurips.cc/paper/2020/hash/d2dc6368837861b42020ee72b0896182-Abstract.html>.
- Haochen Wang, Kaiyou Song, Junsong Fan, Yuxi Wang, Jin Xie, and Zhaoxiang Zhang. Hard patches mining for masked image modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10375–10385, 2023a. doi: 10.1109/CVPR52729.2023.01000.
- Haochen Wang, Kaiyou Song, Junsong Fan, Yuxi Wang, Jin Xie, and Zhaoxiang Zhang. Hard patches mining for masked image modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10375–10385, 2023b. doi: 10.1109/CVPR52729.2023.01000. URL https://openaccess.thecvf.com/content/CVPR2023/html/Wang_Hard_Patches_Mining_for_Masked_Image_Modeling_CVPR_2023_paper.html.
- Ruilang Wang, Shuotong Xu, Bowen Liu, Runlin Huang, Donglong Chen, and Weifeng Su. Mask what matters: Controllable text-guided masking for self-supervised medical image analysis, 2025. URL <https://arxiv.org/abs/2509.23054>.
- Zhenda Xie, Zheng Zhang, Yue Cao, Yutong Lin, Jianmin Bao, Zhuliang Yao, Qi Dai, and Han Hu. SimMIM: A simple framework for masked image modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9653–9663, 2022. doi: 10.1109/CVPR52688.2022.00943.
- Kai Yu, Yang Zhou, Yang Bai, Zhi Da Soh, Xinxing Xu, Rick Siow Mong Goh, Ching-Yu Cheng, and Yong Liu. UrFound: Towards universal retinal foundation models via knowledge-guided masked modeling. In *Medical Image Computing and Computer Assisted Intervention – MICCAI 2024*, pages 753–762. Springer, 2024. doi: 10.1007/978-3-031-72390-2_70.
- Jinghao Zhou, Chen Wei, Huiyu Wang, Wei Shen, Cihang Xie, Alan Yuille, and Tao Kong. iBOT: Image BERT pre-training with online tokenizer. In *International Conference on Learning Representations*, 2022.
- Yukun Zhou, Mark A. Chia, Siegfried K. Wagner, Murat Seçkin Ayhan, Dominic J. Williamson, Robbert R. Struyven, Timing Liu, Moucheng Xu, Mateo G. Lozano, Peter Woodward-Court, et al. A foundation model for generalizable disease detection from retinal images. *Nature*, 622:156–163, 2023. doi: 10.1038/s41586-023-06555-x.

A All frozen probes

Table 3 lists every frozen MeanPool probe in the study.

Table 3: Every frozen probe in the study, including runs excluded from the analysis and the reasons. The probe protocol is otherwise the same for every row — FairVision test $N=3000$, seed 42, frozen encoder, MeanPool + LayerNorm + Linear — and differs only in the precision column. “Precision” is the probe-time numerical precision, inferred from the stored prediction dtype, and is distinct from the pretraining target precision discussed in Appendix D.

policy	epoch	precision	test AUC	95% CI
ANATOMY-V1	30	fp32	0.8583	[0.8450, 0.8712]
ANATOMY-V2	35	fp32	0.8661	[0.8531, 0.8787]
ANATOMY-V2	40	fp32	0.8683	[0.8553, 0.8807]
ANATOMY-V2	50	fp32	0.8654	[0.8522, 0.8781]
ancestor	25	fp32	0.8487	[0.8349, 0.8621]
COVER	27	fp32	0.8483	[0.8346, 0.8617]
COVER	30	fp32	0.8522	[0.8386, 0.8654]
COVER	34	fp32	0.8571	[0.8437, 0.8700]
COVER	50	fp32	0.8643	[0.8513, 0.8768]
COVER	73	fp32	0.8647	[0.8517, 0.8772]
COVER	75	fp32	0.8639	[0.8507, 0.8763]
COVER	100	fp32	0.8577	[0.8443, 0.8707]
ENVELOPE	30	fp32	0.8539	[0.8405, 0.8669]
ENVELOPE	50	fp16	0.8761	[0.8635, 0.8879]
ENVELOPE	50	fp32	0.8761	[0.8635, 0.8879]
ENVELOPE	75	fp16	0.8803	[0.8677, 0.8922]
ENVELOPE	75	fp32	0.8803	[0.8677, 0.8922]
ENVELOPE	100	fp16	0.8807	[0.8683, 0.8926]
ENVELOPE	100	fp32	0.8808	[0.8683, 0.8927]
CENTROID	50	fp16	0.8740	[0.8615, 0.8862]
CENTROID	50	fp32	0.8740	[0.8614, 0.8862]
CENTROID	75	fp16	0.8836	[0.8714, 0.8955]
CENTROID	100	fp16	0.8855	[0.8735, 0.8971]
CENTROID	100	fp32	0.8853	[0.8732, 0.8971]
RANDOM	50	fp16	0.8641	[0.8510, 0.8769]
RANDOM	50	fp32	0.8641	[0.8511, 0.8769]
RANDOM	75	fp16	0.8723	[0.8593, 0.8849]
RANDOM	75	fp32	0.8723	[0.8593, 0.8849]
RANDOM	100	fp16	0.8746	[0.8618, 0.8869]
RANDOM	100	fp32	0.8745	[0.8617, 0.8868]
anatomy-v2	75	fp32	0.8625	<i>excluded</i>
anatomy-v2	92	fp32	0.8604	<i>excluded</i>
random	30	fp32	0.8558	<i>retracted</i>
random	50	fp32	0.8590	<i>retracted</i>
random	75	fp32	0.8612	<i>retracted</i>
random	100	fp32	0.8607	<i>retracted</i>

567 B Masking policies across the volume

568 Figure 1 shows one B-scan for legibility. Figure 3 repeats the same rendering on five B-scans
569 sampled across the depth of a volume, so that the stability of each policy under changing retinal
570 geometry can be inspected. The samplers, the colour assignment, and the anatomy contour are
571 identical to Figure 1.

572 C Subgroup and severity analysis

573 All numbers below come from saved test predictions joined to FairVision’s released metadata in
574 deterministic loader order; the join is validated by exact label reconstruction (3000/3000 labels
575 recovered in every probe). The 22 probes used here are exactly those the inventory marks valid: the
576 four retracted coverage probes of Appendix D and the two precision-spliced ANATOMY-V2 probes
577 are excluded here as everywhere else in the paper.

578 **Why we report two sample sizes.** The 22 probes span only 7 pretraining branches, because sev-
579 eral are different epochs of one training run. Probes within a branch share an encoder lineage, a
580 seed and the test split, so treating them as 22 independent observations is pseudo-replication. Ta-

ble 4 therefore reports each trend twice: once per checkpoint, and once after averaging within each branch. Where the two disagree, the branch-level figure is the one to believe.

Table 4: Subgroup gap trends. “gap range” is the max–min subgroup AUC gap observed across the 22 valid probes. q is Benjamini–Hochberg across the seven attributes tested, which is necessary because seven trends were examined. Three attributes survive correction at checkpoint level: sex and disease severity, both of which *narrow* as aggregate AUC rises, and race, which widens. Race is the one attribute whose checkpoint-level trend does not persist under branch aggregation ($p=0.4821$), where the effective sample is 7 independent branches rather than 22 probes; we therefore draw no trend conclusion for race.

attribute	worst group	gap range	per checkpoint ($n=22$)			per branch ($n=7$)	
			ρ	p	q	ρ	p
sex	female (22/22)	0.0272–0.0396	-0.676	0.0006	0.0039	-0.821	0.0234
race	black (22/22)	0.0391–0.0935	+0.556	0.0072	0.0252	+0.321	0.4821
ethnicity	hispanic (22/22)	0.0180–0.0661	+0.421	0.0512	0.0897	+0.571	0.1802
language	other languages (18/22)	0.0518–0.0805	+0.285	0.1983	0.2314	+0.750	0.0522
marital status	single (22/22)	0.0286–0.0654	-0.204	0.3629	0.3629	-0.679	0.0938
age	<60 (21/22)	0.0430–0.0704	+0.394	0.0700	0.0979	+0.429	0.3374
disease severity	mild ($-6, -2$] (22/22)	0.1286–0.1400	-0.497	0.0185	0.0431	-0.821	0.0234

Race. The black subgroup has the lowest AUC in every one of the 22 probes ($n=431$ black, $n=251$ asian, $n=2318$ white). At matched epoch 100 the black subgroup improves from 0.8325 under RANDOM to 0.8472 under CENTROID (+0.0147), a larger absolute gain than the white subgroup’s (0.8741 $\rightarrow$ 0.8853). The max–min gap nonetheless widens slightly, because the asian subgroup — already the highest — gains most (0.9033 $\rightarrow$ 0.9189). A widening max–min gap with universally rising subgroup AUCs is not evidence of harm, and we do not present it as such. The checkpoint-level correlation between aggregate AUC and racial gap is $\rho=+0.556$ ($p=0.0072$). It passes Benjamini–Hochberg ($q=0.0252$) but vanishes once probes are aggregated to their pretraining branches ($\rho=+0.321$, $p=0.4821$), and the checkpoint-level test is pseudo-replicated because the 22 probes come from only 7 branches. The branch-level figure is the one to believe. We therefore explicitly do *not* claim that more accurate models are less fair.

Disease severity. FairVision’s label is defined by visual-field mean deviation (md): every test volume with $md \leq -2$ is positive. Severity therefore cannot be used as an ordinary subgroup axis, because within-bin AUC is undefined — a trap that silently yields nothing under naive stratification. Instead each positive stratum is scored against the shared pool of all 1534 negatives.

Table 5: Severity-stratified AUC at matched epoch 100. Each positive stratum is scored against the shared pool of all 1534 negatives. Every stratum improves, and mild disease improves most.

stratum	n_+	RANDOM	ENVELOPE	CENTROID	Δ
severe ($md \leq -12$)	334	0.9525	0.9559	0.9588	+0.0063
moderate ($-12 < md \leq -6$)	460	0.9030	0.9103	0.9131	+0.0102
mild ($-6 < md \leq -2$)	672	0.8164	0.8232	0.8301	+0.0137

The severe-to-mild gap is 0.1361 for the null and 0.1286 for the strongest policy, and stays within 0.0114 (0.1286–0.1400) across all 22 probes while aggregate AUC spans 0.8483–0.8855. Target placement raises the whole severity curve, all three strata separated from zero under paired resampling, the largest point estimate at mild disease (+0.01372, CI [+0.00541, +0.02192]) and the smallest at severe (+0.00626). That ordering is descriptive only: we did not test the paired *difference* between strata, so it does not establish that mild disease benefits most. We note that mild functional loss is harder to separate from normal OCT by construction, so the difficulty ordering is expected clinically; what the data add is that no masking policy we tested changes it.

Limitations. One dataset, one test split, reused throughout this programme’s history. Because policies, checkpoints and analyses were chosen after repeated inspection of that split, the p -values here should be read as descriptive rather than as confirmatory inference. Race and ethnicity are self-reported categories inherited from FairVision’s coding; at these subgroup sizes we cannot speak to

Table 6: Paired change in subgroup AUC from RANDOM to CENTROID at matched epoch 100. Each bootstrap draw resamples subjects once and applies the same resampled set to both arms and every stratum, so these are paired differences rather than differences of independent estimates.

stratum	n	Δ AUC	95% CI	excludes 0
severity, mild	2206	+0.01372	[+0.00541, +0.02192]	yes
severity, moderate	1994	+0.01016	[+0.00262, +0.01757]	yes
severity, severe	1868	+0.00626	[+0.00104, +0.01187]	yes
race, White	2318	+0.01129	[+0.00518, +0.01731]	yes
race, Black	431	+0.01467	[-0.00055, +0.03060]	no
race, Asian	251	+0.01558	[-0.00079, +0.03283]	no
sex, Female	1716	+0.01152	[+0.00412, +0.01890]	yes
sex, Male	1284	+0.01006	[+0.00335, +0.01678]	yes

intersectional groups. All figures are frozen mean-pool linear probes with AUC as the only metric; we report no subgroup calibration, no sensitivity at a fixed specificity, and no threshold-transfer analysis, so this audit should not be read as a complete fairness evaluation. Disparities could differ under fine-tuning or a stronger head.

D Excluded runs

Four probes of an earlier coverage arm are excluded from all analysis. They were trained with half-precision EMA targets and a different encoder-truncation policy from the arms they would be compared against, so their deficit is not attributable to masking. We report their existence for completeness and do not use them to support any claim. Similarly, the ANATOMY-V2 probes at epochs 75 and 92 follow a change of target precision partway through that arm’s training; they are listed in Table 3 but excluded from the matched-epoch comparisons in Table 1.

E A collation defect in the coverage arm, and what it invalidates

We audited the COVER sampler after its epoch-100 result and found a defect that changes how that arm may be interpreted. We report it in full because it invalidates the reading we would otherwise have given, and because the same mechanism silently weakens one cross-family comparison.

The defect. Predictor targets are collated by truncating every target to the length of the shortest target anywhere in the microbatch. COVER chooses its placement *before* this happens: it greedily maximises hidden anatomy subject to a visible-tissue floor, evaluated on full rectangles, and the collator then shortens those rectangles. The optimisation is therefore defeated after the fact.

Measured consequences. On held-out slices, COVER’s placement hides 78.6% of anatomy mass, close to its configured target, but the masks actually delivered hide 73.9%; an independent sweep over 6,137 slices gives 73.1% against 77.6% for ENVELOPE. The arm intended to hide *more* anatomy than ENVELOPE in fact hides *less*. Only 32.5% of images retain all four rectangular targets, the mean being 2.51 of 4, and across 24,000 emitted targets only 73.4% remain perfect rectangles. Because target cells are enumerated row-major, truncation keeps the top of each rectangle and discards the bottom, so the loss is directional rather than a neutral shrink.

Why it went unnoticed. Realised coverage is recorded before truncation. Every training log therefore reported the intended figure, and the instrument agreed with the design rather than with the data.

What it invalidates. We cannot claim that COVER tests aggressive anatomy coverage, nor that its decline shows over-covering anatomy is harmful; on delivered masks it does not out-cover ENVELOPE. Its measured trajectory remains a real property of the policy as implemented. The mask geometry in Table 2 is unaffected, having been measured on delivered masks.

Scope. ENVELOPE shares the same collation path and the same directional clipping, but sets no exact coverage target, so it has no comparable optimisation to defeat. The anatomy arms instead resample every target to a fixed $K=16$ cells. Contrasts within the rectangle family are collated identically and are unaffected; the anatomy-versus-rectangle contrast is not, and we treat it accordingly in Section 5. A corrected coverage arm must be retrained from the shared ancestor, since patching mid-trajectory would splice two masking policies into one curve.

F Why unguided masking is such a strong baseline

Unguided masking spends most of its predictor targets on background, yet it reaches within $+0.0109$ of the best policy. We investigated whether background carries diagnostic signal, and whether position embeddings are the mechanism.

Background is a real pretraining signal. At epoch 100 the random arm’s predictor beats a per-position, no-context reference by 0.680 on background targets, above its 0.633 on anatomy targets: predicting a background token requires more than knowing where it is. Pretraining also spends capacity reorganising background — background self-similarity falls from 0.784 untrained to 0.346 at epoch 100, while tissue contrast collapses.

But it does not help the classifier. Pooled background features are 95.2% linearly reconstructible from pooled anatomy features. Residualised, background predicts glaucoma at test AUC 0.5515 (CI [0.5165, 0.5893]). Appending background to anatomy *lowers* test AUC by 0.0076 (CI $[-0.0139, -0.0012]$) for the random arm and moves it under ± 0.002 for every other. A background-only probe scores 0.867, but that is attention leakage rather than background signal.

Position dominates background tokens, but is not the whole story. At layer 0, 90.8% of the across-position variance of the encoder input at background cells comes from `pos_embed`, against 40.8% at tissue cells (stable across six thresholds and both checkpoints). Mechanically a background token is close to its position code. That the predictor still beats a per-position reference shows the pretraining signal is not purely positional. We therefore report the first link of this mechanism as measured and leave the causal chain to downstream AUC open; two ablations would settle it.

G Label efficiency

Guidance that only matters when labels are plentiful is of limited clinical interest, so we measured how each policy behaves as supervision is withdrawn. We subsample the labelled training set to fractions of its size, fit the same frozen linear probe on cached epoch-100 features, and repeat 5 times per fraction. The per-fraction seed depends only on fraction and repeat, never on arm, so all arms see identical label subsets and the comparison is paired.

Table 7: Label efficiency: frozen-probe test AUC against the fraction of the labelled training set used. All values measured, 5 repeats per fraction except at full data, which is deterministic.

labels	n	RANDOM	CENTROID	ENVELOPE	COVER
1%	60	0.7264	0.7436	0.7429	0.6800
5%	300	0.7925	0.8108	0.8080	0.7768
10%	600	0.8198	0.8166	0.8184	0.8124
25%	1500	0.8533	0.8605	0.8523	0.8546
100%	6000	0.8811	0.8850	0.8807	0.8785

The advantage of guided masking is concentrated where labels are scarce. At 5% of labels ($n=300$) CENTROID leads the null by $+0.0183$, against $+0.0038$ at full supervision — roughly a fourfold larger margin. ENVELOPE behaves similarly (0.8080 against 0.7925). By 10% the ordering has already closed to within noise and the arms are indistinguishable.

Two cautions. At 1% the standard deviations are large (0.0250–0.0433 across arms), so the ordering there is not separated and we do not read it. And the defective COVER arm (Appendix E) is the worst

arm at every fraction below 25%, reaching only 0.6800 at 1% against 0.7264 for the null, which is consistent with its targets being degraded rather than merely differently placed.

H Occlusion attribution: where the classifier looks

The analyses in this appendix were run on the three *fine-tuned* probes (mean-pool, cross-attention pool, and a depth-1 attentive probe) that tie at test AUC ≈ 0.887 , not on the frozen probes used for the arm comparison in the main text. They characterise what the downstream classifier uses, and they are reported here because two of the findings are cautionary rather than positive.

Method. Attribution is by *occlusion*, which is architecture-agnostic and causal. Gradient $\times$ input is not used because two of the three probes are non-linear in the slice-token matrix, where gradient attribution is misleading. For slice-level attribution each slice token is zeroed in turn and Δlogit recorded; for window-level, seven consecutive slices; for patch-level, leave-one-out over the 256 patch tokens of a target slice.

A bimodal attribution curve that is an artefact, not anatomy. The population-averaged curve peaks at native slice ≈ 63 and ≈ 137 with a dip near 95. The tempting reading — that the model has discovered the superior and inferior optic disc rim — is **wrong**, and we report it because it is exactly the kind of claim a plausible-looking attribution figure invites. Three tests reject it. First, if the two peaks were bilateral anatomy then within a diseased eye they should co-occur, giving positive per-volume correlation between them; the observed correlation is slightly *negative* (-0.22 , -0.07 , -0.14 across the three probes). Second, clustering the per-volume curves into two groups yields clusters that are near-perfect *mirror images* along the slice axis ($\text{corr}(c_1, \text{flip}(c_2)) = 0.971$ and 0.988 for the two well-structured probes, against raw correlations of -0.124 and -0.478). Third, using that cluster label as pseudo-laterality and flipping one cluster collapses the bimodality asymmetrically. The signature is OD/OS axial storage: each eye carries its dominant signal on one side of the disc, right and left eyes are stored with opposite axial orientation, and population averaging manufactures an illusion of symmetry.

Errors are weaker signal, not different anatomy. Stratifying by outcome, false-negative curves are scaled-down true-positive curves with the same shape, and false positives likewise mirror true negatives. Attribution structure is also near-invariant to prediction confidence ($|r| \leq 0.25$ between peak contribution magnitude and $|\text{logit}|$). The error rate at threshold 0.5 therefore reflects signal-strength saturation on hard cases, not the model attending to the wrong structures.

Why this is in a masking paper. Two of these results bear directly on the main claim. The classifier’s evidence is spread across the middle two-thirds of the volume and across most patches within a slice, rather than concentrated on a compact anatomical target. A masking policy that sharpens targets onto a precise anatomical boundary is therefore optimising for a spatial prior the downstream task does not appear to need, which is consistent with Section 5.2 finding no relationship between anatomical specificity and downstream AUC. The OD/OS result is a methodological caution of the same family as our precision and epoch-matching checks: a figure that looks anatomically meaningful can be an artefact of data storage, and we would rather report that than let it stand.

I Clinical operating points and calibration

AUC is threshold-free, but a screening tool is deployed at a threshold. This appendix reports what a reader needs in order to judge that. For each arm the threshold is selected on the *validation* split at a fixed target specificity and then transferred unchanged to the test split, which is the honest simulation of deployment; the achieved test specificity shows whether the threshold survives the shift. Cohort prevalence is 0.4887.

Two observations. First, the threshold transfers well: a validation target of 0.90 yields test specificity 0.8794 to 0.8807, so the operating point is stable across the split. Second, the AUC advantage survives as a usable sensitivity gain. At a target specificity of 0.90, CENTROID detects 0.7428 of cases against 0.7162 for the unguided null, a paired difference of $+0.0266$ (CI $[+0.0136, +0.0396]$, excluding zero). At a target of 0.85 the gain is $+0.0150$ (CI $[+0.0020, +0.0280]$). CENTROID is

Table 8: Operating points at matched epoch 100. The threshold is chosen on validation to hit the target specificity and applied unchanged to test. ECE is a 15-bin expected calibration error.

policy	target spec.	sens.	spec. (test)	PPV	NPV	Brier	ECE
RANDOM	0.85	0.7701	0.8259	0.8087	0.7899	0.1416	0.0355
RANDOM	0.90	0.7162	0.8794	0.8502	0.7643	0.1416	0.0355
ENVELOPE	0.85	0.7735	0.8351	0.8176	0.7942	0.1364	0.0361
ENVELOPE	0.90	0.7306	0.8807	0.8541	0.7738	0.1364	0.0361
CENTROID	0.85	0.7851	0.8318	0.8169	0.8020	0.1341	0.0320
CENTROID	0.90	0.7428	0.8696	0.8448	0.7797	0.1341	0.0320

also the best-calibrated arm (Brier 0.1341 versus 0.1416; ECE 0.0320 versus 0.0355), which matters because a screening score that is used as a probability must be trustworthy as one.

We report this because a +0.011 AUC difference is hard to interpret clinically, whereas “two to three more cases detected per hundred at the same false-positive rate” is not. The same caveats apply as everywhere else in this paper: one dataset, one split, and one pretraining run per policy.

Who receives the benefit at the deployed threshold. Subgroup AUC is also threshold-free, so it cannot answer the question a deployment actually raises: a screen ships *one* threshold shared by everyone, and a model can lift every subgroup’s AUC while delivering the gain unevenly at that single operating point. We therefore fix the threshold on validation at specificity 0.90 (0.5552), transfer it unchanged, and measure the change in sensitivity within each stratum (Table 9). Overall sensitivity rises from 0.7162 to 0.7428.

The point estimates alone suggest the gain is concentrated in the largest group: +0.0343 for white patients against +0.0037 for black patients, an apparent ninefold difference. **The intervals do not support that reading.** The black interval ($[-0.0261, +0.0336]$) reaches almost exactly the white point estimate, so the two are not separated; what distinguishes them is positive count (1080 versus 268), not demonstrated benefit. Only the white, female and male gains exclude zero, and those are the three largest strata. We therefore report this as a *power* limitation of the cohort — this study cannot certify that the smaller strata benefit — and explicitly not as evidence that they do not. Certifying subgroup benefit at a deployed threshold would need a cohort with more positives in the smaller strata.

Table 9: Change in sensitivity from RANDOM to CENTROID at one shared deployed threshold (validation-selected, specificity 0.90), by stratum. Paired bootstrap over positives within each stratum. Epoch 100.

stratum	positives	Δ sensitivity	95% CI	excludes 0
Asian	118	+0.0085	$[-0.0339, +0.0508]$	no
Black	268	+0.0037	$[-0.0261, +0.0336]$	no
White	1080	+0.0343	$[+0.0194, +0.0491]$	yes
Female	811	+0.0259	$[+0.0074, +0.0444]$	yes
Male	655	+0.0275	$[+0.0092, +0.0458]$	yes

J Broader impact and ethics

This study uses a public, de-identified retinal dataset (FairVision) under its release terms and involves no new data collection and no human subjects. No model reported here is clinically validated or intended for deployment: the frozen-probe AUCs are research measurements on one dataset and one task, and are not evidence of clinical utility.

The subgroup analysis in Section 5.3 is a caution, not a contribution. Every masking policy we tested leaves the same groups worst-served, and the best-performing policy narrows none of them reliably, even though every subgroup point estimate rises. We would regard deployment of any encoder reported here, without a dedicated and prospective fairness evaluation on the target population, as inappropriate. We also stress that the audit is AUC-only: it contains no subgroup calibration, no sen-

sitivity at a fixed clinical specificity, no predictive-value analysis and no intersectional breakdown, so it should not be mistaken for a complete equity assessment.

Releasing pretrained weights carries the usual dual-use consideration that they may be applied to populations unlike the training cohort. We document the cohort composition (Appendix C) so that such a mismatch is detectable by anyone reusing the weights. The demographic attributes are self-reported categories inherited from the dataset’s coding; they are used only for the subgroup audit and are never model inputs.

K Published ablations on informed versus random masking

Our result should be read against the following published comparisons, which we collected while positioning this work. The pattern is that random masking is a strong baseline and informed masking wins only under some objectives and protocols; the deficit is largest under frozen evaluation.

Table 10: Published ablations comparing a random or simple baseline against an informed or structured masking scheme. Numbers are as reported by the cited papers; metrics differ across rows and are not comparable between rows.

study	baseline	informed variant	interpretation
MAE [He et al., 2022]	random-75: 84.9 FT / 73.5 lin	block-75: 82.8 / 63.9; grid-75: 84.0 / 66.0	random decisively better
SimMIM [Xie et al., 2022]	83.0 top-1	best block 82.7; square 82.6	random modestly better
SemMAE [Li et al., 2022]	random 66.8 lin	within-part 66.5; whole-part 52.9; adaptive 68.7	naive semantics hurt; scheduled semantics help
SemMAE part quality [Li et al., 2022]	no parts 63.7	raw parts 63.6; refined 65.0	an imperfect semantic model a
AutoMAE [Chen et al., 2023a]	MAE 83.26 FT	AutoMAE 83.32	nothing
HPM [Wang et al., 2023b]	random 82.49	moderate 82.95; hardest-only 81.40	effectively tied
AttMask [Kakogeorgiou et al., 2022]	random 43.4 k -NN	high 43.5; hint 43.6	benefit only with retained random
AttG-MAE [Sick et al., 2025]	MAE 78.5 @10% labels	guided 78.1	ness
SSiT [Huang et al., 2024]	no saliency 79.48 κ	25% mask 77.53; 50% 79.97	nearly indistinguishable
			guidance loses in this protocol
			dataset-dependent, non-monotonic

Read together, these say that the *direction* of our finding is not new. What we add is a controlled measurement in a setting where the guidance comes from a trained medical segmentation model rather than from attention or difficulty, and where the comparison is run from a shared checkpoint with the masking policy as the only difference.

L Full paired-contrast table

M Full fp32 re-probe

The RANDOM, CENTROID and ENVELOPE long-horizon probes were originally fitted under the harness default, which enables autocast. To remove any doubt that the headline effect is a precision artifact, we re-ran the complete probe pipeline for those arms with autocast disabled, so that feature extraction, head optimisation and test evaluation are all fp32, under the exact protocol already used by the ANATOMY and COVER arms. The encoder checkpoint is SHA-256 hashed before and after each run and verified unchanged, so no result here can be contaminated by an accidental encoder update.

N Fine-tuning narrows but does not erase the gap

Under full fine-tuning rather than a frozen probe, CENTROID reaches 0.8947 (mean-pool head) against RANDOM’s 0.8868, a gap of +0.0079 compared with +0.0109 frozen. Taking each arm’s best head instead, the gap is +0.0069. The pretraining difference is partially, but not entirely, absorbed by supervised adaptation — consistent with the masking policy shaping the representation rather than merely the optimisation start point. These runs used a different head and schedule from the frozen probes and are never pooled with them.

Table 11: Primary contrasts: matched epoch *and* matched precision. Δ is a paired difference on identical test cases; the interval is a 10,000-resample paired bootstrap and p is a DeLong test for correlated ROC curves. q is Benjamini–Hochberg over these nine contrasts. Because the test split was inspected repeatedly across this programme, we read all p and q values here as descriptive rather than confirmatory. Every comparison against the null excludes zero.

contrast	epoch	Δ AUC	95% CI	p	q
ENVELOPE – RANDOM	50	+0.0120	[+0.0068, +0.0173]	<0.0001	<0.0001
ENVELOPE – RANDOM	75	+0.0080	[+0.0028, +0.0132]	0.0025	0.0045
ENVELOPE – RANDOM	100	+0.0062	[+0.0010, +0.0113]	0.0199	0.0299
CENTROID – RANDOM	50	+0.0099	[+0.0051, +0.0149]	<0.0001	0.0001
CENTROID – RANDOM	75	+0.0113	[+0.0063, +0.0164]	<0.0001	<0.0001
CENTROID – RANDOM	100	+0.0109	[+0.0057, +0.0160]	<0.0001	<0.0001
CENTROID – ENVELOPE	50	-0.0020	[-0.0069, +0.0029]	0.4114	0.4114
CENTROID – ENVELOPE	75	+0.0033	[-0.0013, +0.0079]	0.1491	0.1677
CENTROID – ENVELOPE	100	+0.0047	[+0.0004, +0.0091]	0.0294	0.0378

Table 12: Full fp32 re-probe against the original fp16 result, same frozen encoder in each row. The largest difference is 2×10^{-4} , two to three orders of magnitude below the effects reported in Table 1. Rows appear as the re-probes complete.

policy	epoch	fp16 AUC	fp32 AUC	Δ	p
ENVELOPE	50	0.876064	0.876063	-0.000001	0.964
ENVELOPE	75	0.880307	0.880305	-0.000002	0.806
ENVELOPE	100	0.880743	0.880761	+0.000018	0.167
CENTROID	50	0.874030	0.874015	-0.000015	0.412
CENTROID	100	0.885485	0.885293	-0.000192	0.767
RANDOM	50	0.864097	0.864121	+0.000024	0.128
RANDOM	75	0.872302	0.872302	-0.000001	0.962
RANDOM	100	0.874581	0.874485	-0.000096	0.000

791 O Fine-tuned results

Table 13: Full fine-tuning, same test split. Reported separately from frozen probes and never pooled with them.

policy	head	test AUC
CENTROID	mean-pool	0.894668
CENTROID	cross-attention	0.893717
CENTROID	attentive	0.890100
RANDOM	attentive	0.887763
RANDOM	cross-attention	0.887178
RANDOM	mean-pool	0.886756

All masking arms on the SAME 5 slices (volume idx 2652) - one colour per predictor block, production samplers




Figure 3: All six masking policies (columns) on five B-scans (rows) spanning one volume, drawn with the production samplers. Leftmost column is the unmasked B-scan. Each predictor target block has its own colour; the green contour is the anatomy reference. The random, envelope, and cover arms place axis-aligned rectangles; the anatomy arms grow cell-wise targets that follow the retinal band and therefore change shape from slice to slice.




Figure 4: **Left:** race-stratified AUC at epoch 100 with bootstrap intervals. The black subgroup is lowest under every policy, but note that *every* group improves from RANDOM to CENTROID. **Right:** max-min race gap against aggregate AUC across 22 checkpoints. The fitted slope is positive and passes multiplicity correction at checkpoint level, but does not survive branch-level aggregation (Table 4), so we draw no trend conclusion from it.




Figure 5: Single-slice occlusion attribution against native slice position, averaged over all 3000 test volumes, for all three fine-tuned probes. Despite spanning zero to 7.17M probe parameters they converge on the same structure (mean-pool vs cross-attention pool $r=0.94$). The y -axis is *signed* Δlogit : peaks are slices whose removal lowers the logit, the central dip is slices whose removal raises it, and only slices near zero are genuinely unused.




Figure 6: Window occlusion ($W=7$) amplifies the same signal roughly sevenfold and suppresses single-volume noise. For mean-pooled models, single-slice occlusion systematically underestimates attributed signal; the windowed variant recovers about $25\times$ more. We recommend it as the default primitive for this class of model.




Figure 7: The two-peak structure is an OD/OS storage artefact. Clustering per-volume attribution curves into two groups returns near-perfect mirror images of one another, which is what laterality flipping would produce, rather than bilateral anatomy.




Figure 8: Attribution stratified by TP / FN / TN / FP. Errors reproduce the correct pattern at lower amplitude rather than selecting different anatomy.

Occlusion attribution — representative B-scans across the 3 fine-tune probes
Left pane of each row: original B-scan. Right pane: per-patch $\Delta\logit$ overlay.




Figure 9: Per-patch occlusion heat maps on individual B-scans, drawn on a shared scale with the slice mean subtracted so that maps are comparable across volumes. Between 84% and 91% of patches have a 95% bootstrap interval excluding zero on the glaucoma class ($B=500$), so attribution is broadly distributed rather than concentrated in a few patches. Cross-probe agreement is strong at slice level ($r=0.94$) and moderate at patch level (per-volume $r \approx 0.35-0.48$).




Figure 10: Downstream AUC at matched epoch 50 against mask purity, the fraction of masked patches lying on retinal tissue. The policy whose masks are 97% on-tissue does not separate from the null, while policies at 41–44% purity gain the most. The ordering does not support the intuition that more accurate anatomical masking yields better representations. With four to five arms this is descriptive, not inferential.




Figure 11: The matched-epoch-50 result arranged as a ladder of increasing anatomical specificity. Companion to Figure 10.




Figure 12: Measured mask geometry per policy, 600 held-out slices. The four rectangle policies are closely matched on every axis, so their comparison is near single-variable. The anatomy policy diverges on all four simultaneously — half the masking ratio, 1.6× the context, 0.4× the predictor loss slots — which is why we decline to attribute its deficit to target shape.