

# *Part F*

## CHAPTER 3

### Architecture and Organization



1

These slides are provided with permission from the copyright for CS2208 use only. The slides must not be reproduced or provided to anyone outside the class.

All downloaded copies of the slides are for personal use only.

Students must destroy these copies within 30 days after receiving the course's final assessment.

# ARM Assembly Instructions Summary

ADC{cond}{S} {Rd,}Rn,Op2	Add with carry	$Rd \leftarrow Rn + Op2 + \text{Carry}$
ADD{cond}{S} {Rd,}Rn,Op2	Add	$Rd \leftarrow Rn + Op2$
MLA{cond}{S} Rd, Rm,Rs,Rn	Multiply Accumulate	$Rd \leftarrow (Rm \times Rs) + Rn$
MUL{cond}{S} Rd, Rm,Rs	Multiply	$Rd \leftarrow Rm \times Rs$
MOV{cond}{S} Rd,Op2	Move register or constant	$Rd \leftarrow Op2$
NEG{cond}{S} Rd,Rn	Negate the value in a register	$Rd \leftarrow -Rn$
RSB{cond}{S} {Rd,}Rn,Op2	Reverse Subtract	$Rd \leftarrow Op2 - Rn$
RSC{cond}{S} {Rd,}Rn,Op2	Reverse Subtract with Carry	$Rd \leftarrow Op2 - Rn - 1 + \text{Carry}$
SBC{cond}{S} {Rd,}Rn,Op2	Subtract with Carry	$Rd \leftarrow Rn - Op2 - 1 + \text{Carry}$
SUB{cond}{S} {Rd,}Rn,Op2	Subtract	$Rd \leftarrow Rn - Op2$

## ARM Assembly Instructions Summary

AND{cond}{S} {Rd,}Rn,Op2	AND	$Rd \leftarrow Rn \text{ AND } Op2$
BIC{cond}{S} {Rd,}Rn,Op2	Bit Clear	$Rd \leftarrow Rn \text{ AND NOT } Op2$
ORR{cond}{S} {Rd,}Rn,Op2	OR	$Rd \leftarrow Rn \text{ OR } Op2$
EOR{cond}{S} {Rd,}Rn,Op2	Exclusive OR	$Rd \leftarrow Rn \oplus Op2$
MVN{cond}{S} Rd,Op2	Move not	$Rd \leftarrow 0xFFFFFFFF \oplus Op2$

## ARM Assembly Instructions Summary

CMN{cond} Rn,Op2	Compare Negative	CPSR flags $\leftarrow$ Rn + Op2
CMP{cond} Rn,Op2	Compare	CPSR flags $\leftarrow$ Rn - Op2
TEQ{cond} Rn,Op2	Test bitwise equality	CPSR flags $\leftarrow$ Rn $\oplus$ Op2
TST{cond} Rn,Op2	Test bits	CPSR flags $\leftarrow$ Rn <i>AND</i> Op

# ARM Assembly Instructions Summary

B{cond} address	Branch	$R15 \leftarrow \text{address}$
BL{cond} address	Branch with Link	$R14 \leftarrow R15, R15 \leftarrow \text{address}$

# ARM Assembly Instructions Summary

ADR{cond}Rd,label	Load address	$Rd \leftarrow$ The address of the label
STR{cond}{B} Rd,address	Store register to memory	$[address] \leftarrow Rd$
LDR{cond}{B} Rd,address	Load register from memory	$Rd \leftarrow [address]$
LDR{cond} Rd,=expr	Load a 32-bit immediate value	$Rd \leftarrow expr$
LDR{cond} Rd,=label	Load a 32-bit address	$Rd \leftarrow$ The address of the label

# ARM Assembly Instructions Summary

LDM{cond}{IA|IB|DA|DB}{cond} Rn{!},reglist

Load Multiple registers/Stack pop

LDM{cond}{FD|FA|ED|EA}{cond} Rn{!},reglist

Load Multiple registers/Stack pop

STM{cond}{IA|IB|DA|DB}{cond} Rn{!},reglist

Store Multiple registers/Stack push

STM{cond}{FD|FA|ED|EA}{cond} Rn{!},reglist

Store Multiple registers/Stack push

# ARM Assembly Instructions Summary

ADC{cond}{S} {Rd},Rn,Op2	Add with carry	$Rd \leftarrow Rn + Op2 + \text{Carry}$
ADD{cond}{S} {Rd},Rn,Op2	Add	$Rd \leftarrow Rn + Op2$
AND{cond}{S} {Rd},Rn,Op2	AND	$Rd \leftarrow Rn \text{ AND } Op2$
ADR{cond}Rd,label	Load address	$Rd \leftarrow \text{The address of the label}$
B{cond} address	Branch	$R15 \leftarrow \text{address}$
BIC{cond}{S} {Rd},Rn,Op2	Bit Clear	$Rd \leftarrow Rn \text{ AND NOT } Op2$
BL{cond} address	Branch with Link	$R14 \leftarrow R15, R15 \leftarrow \text{address}$
CMN{cond} Rn,Op2	Compare Negative	CPSR flags $\leftarrow Rn + Op2$
CMP{cond} Rn,Op2	Compare	CPSR flags $\leftarrow Rn - Op2$
EOR{cond}{S} {Rd},Rn,Op2	Exclusive OR	$Rd \leftarrow Rn \oplus Op2$
LDM{cond}{IA IB DA DB}{cond} Rn{!},reglist	Load Multiple registers/Stack pop	Load Multiple registers/Stack pop
LDM{cond}{FD FA ED EA}{cond} Rn{!},reglist	Load Multiple registers/Stack pop	Load Multiple registers/Stack pop
LDR{cond}{B} Rd,address	Load register from memory	$Rd \leftarrow [\text{address}]$
LDR{cond} Rd,=expr	Load a 32-bit immediate value	$Rd \leftarrow \text{expr}$
LDR{cond} Rd,=label	Load a 32-bit address	$Rd \leftarrow \text{The address of the label}$
MLA{cond}{S} Rd, Rm,Rs,Rn	Multiply Accumulate	$Rd \leftarrow (Rm \times Rs) + Rn$
MOV{cond}{S} Rd,Op2	Move register or constant	$Rd \leftarrow Op2$
MUL{cond}{S} Rd, Rm,Rs	Multiply	$Rd \leftarrow Rm \times Rs$
MVN{cond}{S} Rd,Op2	Move not	$Rd \leftarrow 0xFFFFFFFF \oplus Op2$
NEG{cond}{S} Rd,Rn	Negate the value in a register	$Rd \leftarrow -Rn$
NOP	No operation	No operation
ORR{cond}{S} {Rd},Rn,Op2	OR	$Rd \leftarrow Rn \text{ OR } Op2$
RSB{cond}{S} {Rd},Rn,Op2	Reverse Subtract	$Rd \leftarrow Op2 - Rn$
RSC{cond}{S} {Rd},Rn,Op2	Reverse Subtract with Carry	$Rd \leftarrow Op2 - Rn - 1 + \text{Carry}$
SBC{cond}{S} {Rd},Rn,Op2	Subtract with Carry	$Rd \leftarrow Rn - Op2 - 1 + \text{Carry}$
STM{cond}{IA IB DA DB}{cond} Rn{!},reglist	Store Multiple registers/Stack push	Store Multiple registers/Stack push
STM{cond}{FD FA ED EA}{cond} Rn{!},reglist	Store Multiple registers/Stack push	Store Multiple registers/Stack push
STR{cond}{B} Rd,address	Store register to memory	$[\text{address}] \leftarrow Rd$
SUB{cond}{S} {Rd},Rn,Op2	Subtract	$Rd \leftarrow Rn - Op2$
TEQ{cond} Rn,Op2	Test bitwise equality	CPSR flags $\leftarrow Rn \oplus Op2$
TST{cond} Rn,Op2	Test bits	CPSR flags $\leftarrow Rn \text{ AND } Op2$

{S} → Update condition flags if S present

{cond} → (to be omitted for unconditional execution)

Refer to the table below for the meaning of the {cond} field.




# ARM Assembly Instructions Summary

## Meaning of {condition} field


Encoding	Mnemonic	Branch on Flag Status	Execute on Condition
0000	EQ	Z set	Equal (i.e., zero)
0001	NE	Z clear	Not equal (i.e., not zero)
0010	CS	C set	Unsigned higher or same
0011	CC	C clear	Unsigned lower
0100	MI	N set	Negative
0101	PL	N clear	Positive or zero
0110	VS	V set	Overflow
0111	VC	V clear	No overflow
1000	HI	C set and Z clear	Unsigned higher
1001	LS	C clear or Z set	Unsigned lower or same
1010	GE	N set and V set, or N clear and V clear	Greater or equal
1011	LT	N set and V clear, or N clear and V set	Less than
1100	GT	Z clear and N set and V set, or Z clear and N clear and V clear	Greater than
1101	LE	Z set, or N set and V clear, or N clear and V set	Less than or equal
1110	AL		Always (default)
1111	NV		Never (reserved)

# Instruction Encoding Formats


**FIGURE 3.26** Encoding the ARM's data processing instructions



**FIGURE 3.39** Format of ARM's load and store instructions




**FIGURE 3.41** Encoding ARM's branch and branch-with-link instructions



## Shift type

00 = logical left  
01 = logical right  
10 = arithmetic right  
11 = rotate right

**FIGURE 3.58** Encoding ARM's block move instructions



## Conversion Tables

$2^0 = 1$
$2^1 = 2$
$2^2 = 4$
$2^3 = 8$
$2^4 = 16$
$2^5 = 32$
$2^6 = 64$
$2^7 = 128$
$2^8 = 256$
$2^9 = 512$
$2^{10} = 1024$ (Kilo)
$2^{11} = 2048$
$2^{12} = 4096$
$2^{13} = 8192$
$2^{14} = 16384$
$2^{15} = 32768$
$2^{16} = 65536$
$2^{17} = 131072$
$2^{18} = 262144$
$2^{19} = 524288$
$2^{20} = 1048576$ (Mega)

$(0)_{16} = (0)_{10} = (0000)_2$
$(1)_{16} = (1)_{10} = (0001)_2$
$(2)_{16} = (2)_{10} = (0010)_2$
$(3)_{16} = (3)_{10} = (0011)_2$
$(4)_{16} = (4)_{10} = (0100)_2$
$(5)_{16} = (5)_{10} = (0101)_2$
$(6)_{16} = (6)_{10} = (0110)_2$
$(7)_{16} = (7)_{10} = (0111)_2$
$(8)_{16} = (8)_{10} = (1000)_2$
$(9)_{16} = (9)_{10} = (1001)_2$
$(A)_{16} = (10)_{10} = (1010)_2$
$(B)_{16} = (11)_{10} = (1011)_2$
$(C)_{16} = (12)_{10} = (1100)_2$
$(D)_{16} = (13)_{10} = (1101)_2$
$(E)_{16} = (14)_{10} = (1110)_2$
$(F)_{16} = (15)_{10} = (1111)_2$

ASCII Table	
'0' →	0x30
'1' →	0x31
'2' →	0x32
...	
'8' →	0x38
'9' →	0x39
...	
'A' →	0x41
'B' →	0x42
'C' →	0x43
'D' →	0x44
'E' →	0x45
'F' →	0x46
...	
'X' →	0x58
'Y' →	0x59
'Z' →	0x5A
...	
'a' →	0x61
'b' →	0x62
'c' →	0x63
'd' →	0x64
'e' →	0x65
'f' →	0x66
...	
'x' →	0x78
'y' →	0x79
'z' →	0x7A