Part 2

CHAPTER 4

Computer Organization and Architecture



CENGAGE Learning

Calling a Subroutine Step-by-Step

- To call a subroutine, the following steps need to be performed:
  - ***Parameters*** need to be *passed* from the caller to the subroutine.
    This can be performed via the stack.
  - The ***address*** of the instruction immediately after the calling instruction needs to be *saved in a safe place* ***BEFORE*** branching to the subroutine.
    This can be performed by using BL instruction or via the stack, or both.
  - *Inside the subroutine*, we need to:
    - Push the values of all registers to be used inside the subroutine, as well as the FP (R11) and LR (R14).
    - Make the FP (R11) point to the base of the frame by copying the value of the SP (R13) to the FP (R11).
    - Create a space inside the stack for local variables.
    - Perform the subroutine instructions.
      The addresses of parameters and local variables are calculated relative to the value of the FP (R11).
    - *At the end of the subroutine*, deallocate all created local variables.
    - Pop all pushed registers but use PC (R15) instead of LR (R14).
  - *At the caller program*, all pushed parameters need to be popped.

Passing Parameters via the Stack

- You can pass a parameter to a subroutine
  - ***by value***
  - *by reference*

- When passed ***by value***, the subroutine receives a **copy** of the parameter.
  - Passing a parameter by value causes the *parameter to be cloned* and the *cloned version of the parameter* to be used by the subroutine.
  - If the parameter is modified by the subroutine, the new value does not affect the value of the parameter elsewhere in the program.

- When passed *by reference*, the subroutine receives a **pointer**, (i.e., an **address**) to the parameter.
  - *There is only one copy of the parameter,* and the subroutine can access this value because it knows the address of the parameter.
  - If the subroutine modifies the parameter, it modifies the original value.

You need to re-map the memory to make the stack space read/write enabled (Debug/Memory Map).
The other option is to use a .ini file
You may want to review tutorial 7, slides 93-106.

Passing Parameters via the Stack

- The subroutine `swap(int a, int b)` *intends* to exchange two values.
- Let's examine how parameters are passed to this subroutine.

```
void swap(int a, int b)   /* swaps the value of a and b */
{   int temp;
    temp = a;             /* copy a      to temp      */
    a    = b              /* copy b      to a,    and */
    b    = temp;          /* copy temp to b           */
}

void main(void)
{   int x = 2, y = 3;
    swap (x, y);          /* swap a and b */
}
```

Passing Parameters via the Stack

```
        AREA SwapVal, CODE, READONLY

        ENTRY
        ADR   sp,STACK          ;set up stack pointer
        MOV   fp,#0xFFFFFFFF    ;set up dummy fp for tracing
        B      main             ;jump to the function main

        SPACE 0x20
STACK   DCD 0
```



You need to re-do it yourself using the other stack types.

```
;       void swap (int a, int b)
;       Parameter a    is at [fp]+4
;       Parameter b    is at [fp]+8
;       Variable  temp is at [fp]-4
```

Passing Parameters via the Stack



You need to re-do it yourself using the other stack types.

```
;       {
swap    SUB   sp,sp,#4      ;Create stack frame: decrement sp
        STR   fp,[sp]        ;push the frame pointer onto the stack
        MOV   fp,sp          ;frame pointer points at the frame base
;       int temp;
        SUB   sp,sp,#4       ;move sp up 4 bytes for temp
;       temp = a;
        LDR   r0,[fp,#4]     ;get parameter a from the stack
        STR   r0,[fp,#-4]    ;copy a to temp onto the stack frame
;       a    = b;
        LDR   r0,[fp,#8]     ;get parameter b from the stack
        STR   r0,[fp,#4]     ;copy b to a
;       b    = temp;
        LDR   r0,[fp,#-4]    ;get temp from the stack frame
        STR   r0,[fp,#8]     ;copy temp to b
;       }
                             ;Collapse stack frame created for swap
        MOV   sp,fp          ;restore the stack pointer
        LDR   fp,[sp]        ;restore old frame pointer from stack
        ADD   sp,sp,#4       ;move stack pointer down 4 bytes
        MOV   pc,lr          ;return by loading LR into PC
```

Passing Parameters via the Stack

```
;     void main(void)
;     {
main                        ;Create stack frame in main for x, y
      SUB   sp,sp,#4        ;move the stack pointer up
      STR   fp,[sp]         ;push the frame pointer onto the stack
      MOV   fp,sp           ;frame pointer points at the frame base
;     int x = 2, y = 3;
      SUB   sp,sp,#8        ;move sp up 8 bytes for 2 integers
      MOV   r0,#2           ;x = 2
      STR   r0,[fp,#-4]     ;put x in stack frame
      MOV   r0,#3           ;y = 3
      STR   r0,[fp,#-8]     ;put y in stack frame
;     swap(x, y);
      LDR   r0,[fp,#-8]     ;get y from stack frame
      STR   r0,[sp,#-4]!    ;push y on stack
      LDR   r0,[fp,#-4]     ;get x from stack frame
      STR   r0,[sp,#-4]!    ;push x on stack
      BL    swap            ;call swap, save return address in LR
      ADD   sp,sp,#8        ;Clean the stack from the parameters
;     }
      MOV   sp,fp           ;restore the stack pointer
      LDR   fp,[sp]         ;restore old frame pointer from stack
      ADD   sp,sp,#4        ;move stack pointer down 4 bytes
Loop  B     Loop            ;Stop
      END
```

Bold is not correct in page 244

Passing Parameters via the Stack

- This code swaps the variables inside the stack frame
- When the return is made, the stack frame will be collapsed, and the effect of the swap will be lost.
- The variables in the calling environment are not affected.

Passing Parameters via the Stack

FIGURE 4.8 Passing values to a subroutine by value



(a) State of the stack in main after creating stack frame with:

```
SUB sp,sp,#4
STR fp,[sp]
MOV fp,sp
SUB sp,sp,#8
```

The location of the addresses relative to the FP needs to be shifted down one cell. It is not correct in page 245

FP not SP. Not correct in page 245

Same thing

The values of parameters are not correct in page 245



The values of parameters *x* and *y* are pushed on the stack

(b) The stack in main after putting two parameters in the stack frame with:

```
MOV r0,#2
STR r0,[fp,#-4]
MOV r0,#3
STR r0,[fp,#-8]
```

Then pushing two parameters on the stack

```
LDR r0,[fp,#-8]
STR r0,[sp,#-4]!
LDR r0,[fp,#-4]
STR r0,[sp,#-4]!
```



Addresses relative to the current value of FP

Addresses relative to the previous value of FP

(c) The stack after the creation of a stack frame in `swap`. The new stack frame is four bytes deep and holds the variable temp. The frame is created by:

```
SUB sp,sp,#4
STR fp,[sp]
MOV fp,sp
SUB sp,sp,#4
```



(d) The stack after executing the body of swap. Note that all data is referenced to FP.

```
LDR r0,[fp,#4]
STR r0,[fp,#-4]
LDR r0,[fp,#8]
STR r0,[fp,#4]
LDR r0,[fp,#-4]
STR r0,[fp,#8]
```

Passing Parameters via the Stack

- In the next example, we pass parameters by reference

```
void swap(int *a, int *b)   /* A function to swap two parameters
                               in calling program       */
{ int temp;                 /* copy *a     to temp      */
  temp = *a;                /* copy *b     to *a,   and */
  *a   = *b;                /* copy temp to  *b         */
  *b   = temp;
}

void main(void)
{ int x = 2, y = 3;
  swap(&x, &y);             /* call swap and pass
                               addresses of parameters  */
}
```

Passing Parameters via the Stack

```
        AREA SwapVal, CODE, READONLY

        ENTRY
        ADR   sp, STACK          ;set up stack pointer
        MOV   fp,#0xFFFFFFFF     ;set up dummy fp for tracing
        B     main               ;jump to main function

        SPACE 0x20
STACK   DCD 0

  ;    void swap (int *a, int *b)
  ;    Parameter *a   is at [fp]+4
  ;    Parameter *b   is at [fp]+8
  ;    Variable  temp is at [fp]-4
```

Passing Parameters via the Stack

```
;       {
swap    SUB   sp,sp,#4      ;Create stack frame: decrement sp
        STR   fp,[sp]        ;push the frame pointer onto the stack
        MOV   fp,sp          ;frame pointer points at the base
;       int temp;
        SUB   sp,sp,#4       ;move sp up 4 bytes for temp
;       temp = *a;
        LDR   r1,[fp,#4]     ;get address of parameter a
        LDR   r2,[r1]        ;get value of parameter a (i.e., *a)
        STR   r2,[fp,#-4]    ;store *a in temp in stack frame
;       *a = *b;
        LDR   r0,[fp,#8]     ;get address of parameter b
        LDR   r3,[r0]        ;get value of parameter b (i.e., *b)
        STR   r3,[r1]        ;store *b in *a
;       *b = temp;
        LDR   r3,[fp,#-4]     ;get temp
        STR   r3,[r0]         ;store temp in *b
;       }
                             ;Collapse stack frame created for swap
        MOV   sp,fp          ;restore the stack pointer
        LDR   fp,[sp]        ;restore old frame pointer from stack
        ADD   sp,sp,#4       ;move stack pointer down 4 bytes
        MOV   pc,lr          ;return by loading LR into PC
```

Missing the * in page 247

Passing Parameters via the Stack

```
;     void main(void)
;     {
main                        ;Create stack frame in main for x, y
      SUB   sp,sp,#4        ;move the stack pointer up
      STR   fp,[sp].        ;push the frame pointer onto the stack
      MOV   fp,sp           ;the frame pointer points at the base;
;     int x = 2, y = 3;
      SUB   sp,sp,#8        ;move sp up 8 bytes for 2 integers
      MOV   r0,#2           ;x = 2
      STR   r0,[fp,#-4]     ;put x in stack frame
      MOV   r0,#3           ;y = 3
      STR   r0,[fp,#-8]     ;put y in stack frame
;     swap(&x, &y);
      SUB   r0,fp,#8        ;get  address of y in stack frame
      STR   r0,[sp,#-4]!    ;push address of y on stack
      SUB   r0,fp,#4        ;get  address of x in stack frame
      STR   r0,[sp,#-4]!    ;push address of x on stack
      BL    swap            ;call swap, save return address in LR
      ADD   sp,sp,#8        ;Clean the stack from the parameters
;     }
      MOV   sp,fp           ;restore the stack pointer
      LDR   fp,[sp]         ;restore old frame pointer from stack
      ADD   sp,sp,#4        ;move stack pointer down 4 bytes
Loop  B     Loop            ;Stop
      END
```

Bold is not correct in page 244

Passing Parameters via the Stack

- In the function main, the addresses of the *parameters are pushed onto the stack* by means of the following instructions:

```
SUB   r0,fp,#8       ;get  address of y in stack frame
STR   r0,[sp,#-4]!   ;push address of y on stack
SUB   r0,fp,#4       ;get  address of x in stack frame
STR   r0,[sp,#-4]!   ;push address of x on stack
```

- In the function swap, the addresses of *parameters are read from the stack* by means of

```
;     temp = *a;
      LDR   r1,[fp,#4]   ;get address of parameter a
      LDR   r2,[r1]      ;get value of parameter a (i.e., *a)
      STR   r2,[fp,#-4]  ;store *a in temp in stack frame
;     *a = *b;
      LDR   r0,[fp,#8]   ;get address of parameter b
      LDR   r3,[r0]      ;get value of parameter b (i.e., *b)
      STR   r3,[r1]      ;store *b in *a
;     *b = temp;
      LDR   r3,[fp,#-4]  ;get temp
      STR   r3,[r0]      ;store temp in *b
```

Passing Parameters via the Stack

FIGURE 4.9 Passing values to a subroutine by reference



(a) State of the stack after

```
SUB sp,sp,#4
STR fp,[sp]
MOV fp,sp
SUB sp,sp,#8
MOV r0,#2
STR r0,[fp,#-4]
MOV r0,#3
STR r0,[fp,#-8]
```

in function main



(b) State of the stack after pushing parameter addresses by

```
SUB r0,fp,#8
STR r0,[sp,#-4]!
SUB r0,fp,#4
STR r0,[sp,#-4]!
```



(c) State of the stack after subroutine call and stack frame created by

```
SUB sp,sp,#4
STR fp,[sp]
MOV fp,sp
SUB sp,sp,#4
```

Addresses with respect to new FP

–4
+0
+4
+8

Local variables

parameters

The swap function should not have a ***direct*** access to x and y

The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism

The function calculates the addresses of the ***local variables*** relative to the current FP value.

call by value
vs
call by reference

The function calculates the addresses of the ***parameters*** and the ***returning value*** relative to the current FP value.

At the beginning of the function

FD stack



current SP

current FP

What will happen if the function called itself? i.e., recursion

The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism



The Traditional Call/Return Mechanism